

FCC Radio TEST Report

FCC ID: VGUZWM2

This report concerns (check one): Class I Change

Issued Date: Oct. 12, 2007

Report No.: 0708043

Equipment: Wireless Messenger 2

Model Name: Z2

Applicant: Zipit Wireless, Inc.

Address: 200 North Main St. Greenville, SC 29601

Tested by:

Neutron Engineering Inc. EMC Laboratory

Data of Test:

Aug. 11, 2007 ~ Sep. 26, 2007

Testing Engineer

(Jeff Yang)

Technical Manager

(Stoven Lu

Authorized Signatory

(Andy Chiu)

NEUTRON ENGINEERING INC.

No. 132-1, Lane 329, Sec. 2, Palain Rd., Shijr City, Taipei, Taiwan TEL: (02) 2646-5426 FAX: (02) 2646-6815









Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Report No.: NEI-FCCP-1-0708043 Page 2 of 78



Table of Contents	Page
1 . CERTIFICATION	5
2 . SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3 . GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	9
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	9
3.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM	
3.5 DESCRIPTION OF SUPPORT UNITS	11
4 . EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS 4.1.2 MEASUREMENT INSTRUMENTS LIST	12 12
4.1.3 TEST PROCEDURE	13
4.1.4 DEVIATION FROM TEST STANDARD 4.1.5 TEST SETUP	13 13
4.1.7 TEST RESULTS	14
4.2 RADIATED EMISSION MEASUREMENT	16
4.2.1 RADIATED EMISSION LIMITS	16 17
4.2.2 MEASUREMENT INSTRUMENTS LIST 4.2.3 TEST PROCEDURE	17
4.2.4 DEVIATION FROM TEST STANDARD	18
4.2.5 TEST SETUP 4.2.6 EUT OPERATING CONDITIONS	19 19
4.2.7 TEST RESULTS (Between 30 – 1000 MHz)	20
4.2.8 TEST RESULTS (Above 1000 MHz)	24
4.2.9 TEST RESULTS (Restricted Bands Requirements)	48
5 . BANDWIDTH TEST	56
5.1 APPLIED PROCEDURES / LIMIT 5.1.1 MEASUREMENT INSTRUMENTS LIST	56 56
5.1.2 TEST PROCEDURE	56
5.1.3 DEVIATION FROM STANDARD	56 56
5.1.4 TEST SETUP 5.1.5 EUT OPERATION CONDITIONS	56 56
5.1.6 TEST RESULTS	57

Report No.: NEI-FCCP-1-0708043 Page 3 of 78



Table of Contents	Page
6 . PEAK OUTPUT POWER TEST 6.1 APPLIED PROCEDURES / LIMIT 6.1.1 MEASUREMENT INSTRUMENTS LIST 6.1.2 TEST PROCEDURE 6.1.3 DEVIATION FROM STANDARD 6.1.4 TEST SETUP 6.1.5 EUT OPERATION CONDITIONS 6.1.6 TEST RESULTS	61 61 61 61 61 61 62
7 . ANTENNA CONDUCTED SPURIOUS EMISSION 7.1 APPLIED PROCEDURES / LIMIT 7.1.1 MEASUREMENT INSTRUMENTS LIST 7.1.2 TEST PROCEDURE 7.1.3 DEVIATION FROM STANDARD 7.1.4 TEST SETUP 7.1.5 EUT OPERATION CONDITIONS 7.1.6 TEST RESULTS	63 63 63 63 63 64 65
8 . POWER SPECTRAL DENSITY TEST 8.1 APPLIED PROCEDURES / LIMIT 8.1.1 MEASUREMENT INSTRUMENTS LIST 8.1.2 TEST PROCEDURE 8.1.3 DEVIATION FROM STANDARD 8.1.4 TEST SETUP 8.1.5 EUT OPERATION CONDITIONS 8.1.6 TEST RESULTS	69 69 69 69 69 69 70
9 . RF EXPOSURE TEST 9.1 Applied procedures / limit 9.1.1 MEASUREMENT INSTRUMENTS LIST 9.1.2 MPE CALCULATION METHOD 9.1.3 DEVIATION FROM STANDARD 9.1.4 TEST SETUP 9.1.5 EUT OPERATION CONDITIONS 9.1.6 TEST RESULTS	74 74 74 74 75 75 75 76

Report No.: NEI-FCCP-1-0708043 Page 4 of 78



1. CERTIFICATION

Equipment: Wireless Messenger 2

Trade Name : Zipit Model Name : Z2

Applicant: Zipit Wireless,Inc. (Certificate and Report Holder)

Data of Test: Aug. 11, 2007 ~ Sep. 26, 2007 Test Item: ENGINEERING SAMPLE

Standards: FCC Part15, Subpart C(15.247)/ ANCI C63.4: 2003

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-0708043) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Report No.: NEI-FCCP-1-0708043 Page 5 of 78



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C					
Standard Section	Test Item	Judgment	Remark		
15.207	Conducted Emission	PASS			
15.247 (c)	Antenna conducted Spurious Emission	PASS			
15.247 (a)(2)	6dB Bandwidth	PASS			
15.247 (b)	Peak Output Power	PASS			
15.247 (c)	Radiated Spurious Emission	PASS			
15.247 (d)	Power Spectral Density	PASS			
15.203	Antenna Requirement	PASS			
1.1307 1.1310 2.1091 2.1093	RF Exposure Compliance	PASS			

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

Report No.: NEI-FCCP-1-0708043 Page 6 of 78



2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **C01/OS02** at the location of No.132-1, Lane 329, Sec. 2, Palain Road, Shijr City, Taipei, Taiwan. Neurtron's test firm number is: 95335.

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % $^{\circ}$

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
C01	ANSI	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	NOTE
OS-01	ANSI	30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	Н	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	Н	3.94	
OS-02	ANSI	30MHz ~ 200MHz	V	2.48	
		30MHz ~ 200MHz	Н	2.16	
		200MHz ~ 1,000MHz	V	2.50	
		200MHz ~ 1,000MHz	Н	2.66	_

Report No.: NEI-FCCP-1-0708043 Page 7 of 78



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless Messenger 2			
Trade Name	Zipit			
Model Name	Z2			
OEM Brand/Model No.	N/A			
Model Difference	N/A			
	The EUT is a Wireless M	lessenger 2.		
	Operation Frequency:	2412~2462 MHz		
	Product Class:	Class 1		
	Receiver Class:	Class 3		
	Modulation Type:	DSSS & OFDM		
	Bit Rate of Transmitter	802.11b:11/5.5/2/1Mbps		
		802.11g:		
Product Description		54/48/36/24/18/12/9/6 Mbps		
Froduct Description	Number Of Channel	11 CH, Please see Note 2.		
	Antenna Designation:	Please see Note 3.		
	Antenna Gain(Peak)			
	Output Power:	11B:16.83dBm,11G:14.59dBm		
		n, features, or specification exhibited		
	in User's Manual, the EU			
		More details of EUT technical		
	specification, please refer to the User's Manual.			
Channel List	Please refer to the Note 2.			
Power Source	DC Voltage supplied from AC/DC adapter.			
Power Rating	I/P 100-240VAC~ 50/60Hz, 0.3A O/P 5V, 1.2A			
Connecting I/O Port(s)	Please refer to the User'	s Manual		

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

	Channel List						
Channel	Channel Frequency (MHz) Channel Frequency (MHz) Channel Frequency (MHz) Channel (MHz)						
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	WIESON	G9851B002-022	Dipole Antenna	U.FL	2.72

Report No.: NEI-FCCP-1-0708043 Page 8 of 78



3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX CH01 (With Jump)
Mode 2	TX CH01(W/O Jump)

The worst emission was found in Mode 1. The final test was executed under test mode with highest emission and recorded in the report individually.

For Conducted Test			
Final Test Mode Description			
Mode 1	TX CH06		

For Radiated Test			
Final Test Mode	Description		
Mode 1	TX CH01		
Mode 2	TX CH06		
Mode 3	TX CH11		

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

Test Software Version	Class C Test		
Frequency (MHz)	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b DSSS	15	15	15
IEEE 802.11g OFDM	15	15	15

Report No.: NEI-FCCP-1-0708043 Page 9 of 78



3.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



C-1 Power Line

C-2 Audio Cable

C-3 Docket Cable

Report No.: NEI-FCCP-1-0708043 Page 10 of 78



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	Wireless Messenger 2	Zipit	Z2	VGUZWM2	N/A	EUT
E-2	Earphone	N/A	DT-602MV	N/A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.8M	
C-2	NO	NO	1.8M	
C-3	NO	YES	0.1M	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length_"</code> column.

Report No.: NEI-FCCP-1-0708043 Page 11 of 78



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
TREQUENCT (MITZ)	Quasi-peak	Average	Quasi-peak	Average	Stariuaru
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	Rolf Heine	NNB-2/16Z	98053	Dec. 27, 2007
2	4L-V-LISN	Rolf Heine	NNB-4/63TL	02/10040	Apr. 08, 2008
3	Pulse Limiter	Electro-Metrics	EM-7600	112644	Nov. 28, 2007
4	50Ω Terminator	N/A	N/A	N/A	May.13, 2009
5	Test Cable	N/A	C01	N/A	Nov. 28, 2007
6	EMI Test Receiver	R&S	ESCI	100082	Mar. 08, 2008

Remark: "N/A" denotes No Model No., Serial No. or No Calibration specified.

The following table is the setting of the receiver

Receiver Parameters	Setting		
Attenuation	10 dB		
Start Frequency	0.15 MHz		
Stop Frequency	30 MHz		
IF Bandwidth	9 kHz		

Report No.: NEI-FCCP-1-0708043 Page 12 of 78




4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

Report No.: NEI-FCCP-1-0708043 Page 13 of 78




4.1.7 TEST RESULTS

EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure:	1009 hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX CH06		

Freq.	Terminal	Measured(dBuV)		Limits(dBuV)		Margin	Note
(MHz)	L/N	QP-Mode	AV-Mode	QP-Mode	AV-Mode	(dB)	NOLE
0.17	Line	46.65	*	64.81	54.81	-18.16	(QP)
0.23	Line	42.62	*	62.41	52.41	-19.79	(QP)
0.29	Line	40.46	*	60.54	50.54	-20.08	(QP)
0.37	Line	41.39	*	58.49	48.49	-17.10	(QP)
0.40	Line	39.45	*	57.91	47.91	-18.46	(QP)
22.55	Line	36.60	*	60.00	50.00	-23.40	(QP)

Remark

- (1) All readings are QP Mode value unless otherwise stated AVG in column of Note ... If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform In this case, a " * " marked in AVG Mode column of Interference Voltage Measured •
- (2) Measuring frequency range from 150KHz to 30MHz ${\scriptstyle \circ}$




Report No.: NEI-FCCP-1-0708043 Page 14 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure:	1009 hPa	Test Power :	AC 120V/60Hz
Test Mode :	TX CH06		

Freq.	Terminal	Measured(dBuV)		Limits(dBuV)		Margin	Note
(MHz)	L/N	QP-Mode	AV-Mode	QP-Mode	AV-Mode	(dB)	NOIC
0.17	Neutral	45.27	*	64.84	54.84	-19.57	(QP)
0.23	Neutral	41.37	*	62.53	52.53	-21.16	(QP)
0.29	Neutral	40.46	*	60.50	50.50	-20.04	(QP)
0.38	Neutral	40.64	*	58.49	48.49	-17.85	(QP)
0.40	Neutral	38.73	*	57.88	47.88	-19.15	(QP)
22.55	Neutral	38.43	*	60.00	50.00	-21.57	(QP)

- (1) All readings are QP Mode value unless otherwise stated AVG in column of Note ... If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform In this case, a " * " marked in AVG Mode column of Interference Voltage Measured In the Normal Republic Norma
- (2) Measuring frequency range from 150KHz to 30MHz •



Report No.: NEI-FCCP-1-0708043 Page 15 of 78



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBu	V/m) (at 3m)	Class B (dBuV/m) (at 3m)		
	PEAK	AVERAGE	PEAK	AVERAGE	
Above 1000	80	60	74	54	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Report No.: NEI-FCCP-1-0708043 Page 16 of 78



4.2.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Log-Bicon Antenna	Schwarzbeck	VULB 9161	4022	Jun. 13, 2008
2	Test Cable	N/A	10M_OS01	N/A	Nov. 28, 2007
3	Test Cable	N/A	OS01-1/-2	N/A	Nov. 28, 2007
4	Pre-Amplifier	Anritsu	MH648A(OS02)	M10061	Nov. 28, 2007
5	Pre-Amplifier	Agilent	8449B	3008A01714	May,14, 2008
6	Spectrum Analyzer	R&S	FSP_40	100129	Aug,16, 2008
7	Test Receiver	MEB	SMV41	130	Jun. 21, 2008
8	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-546	Jun. 03, 2008
9	Antenna Mast	Chance Most	CMTB-1.5	N/A	N/A
10	Turn Table	Chance Most	CMTB-1.5	N/A	N/A
11	Loop Ant	EMCO	6502	00042960	Jan. 13, 2008
12	Horn Antenna	EMCO	3115	9120D-325	Aug. 19, 2008
13	Microwave Pre_amplifier	Agilent	8449B	3008A01714	May. 14, 2008
14	Microflex Cable	United Microwave	57793	1m	May. 13, 2008
15	Microflex Cable	United Microwave	A30A30-5006	10M	Jul. 24, 2008

Remark: "N/A" denotes No Model Name / Serial No. and No Calibration specified.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	100KHz / 100KHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

Report No.: NEI-FCCP-1-0708043 Page 17 of 78



4.2.3 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


4.2.4 DEVIATION FROM TEST STANDARD
No deviation

Report No.: NEI-FCCP-1-0708043 Page 18 of 78




4.2.5 TEST SETUP

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



4.2.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **4.1.6** Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-0708043 Page 19 of 78




4.2.7 TEST RESULTS (Between 30 – 1000 MHz)

EUT:	Multimedia Networking Device	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57%
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX CH06		

Freq.	Ant.	Reading(RA)	Corr.Factor(CF)	Measured(FS)	Limits(QP)	Margin	Note
(MHz)	H/V	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Note
113.42	V	52.78	-22.18	30.60	43.50	-12.9	
437.40	V	54.49	-18.77	35.72	46.00	-10.28	
838.98	V	47.04	-13.87	33.17	46.00	-12.83	
918.52	V	47.87	-10.70	37.17	46.00	-8.83	
957.32	V	52.43	-10.89	41.54	46.00	-4.46	
996.12	V	54.13	-11.65	42.48	54.00	-11.52	

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz $^{\circ}$
- (2) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (3) Measuring frequency range from 30MHz to 1000MHz •
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table $^{\circ}$




Report No.: NEI-FCCP-1-0708043 Page 20 of 78



EUT:	Multimedia Networking Device	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure:	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX CH06		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
761.38	Η	50.35	-11.44	38.91	46.00	- 7.09	
838.98	Η	48.28	-12.04	36.24	46.00	- 9.76	
877.78	Η	48.61	-12.07	36.54	46.00	- 9.46	
918.52	Η	50.22	-13.75	36.47	46.00	- 9.53	
957.32	Η	48.49	-6.54	41.95	46.00	- 4.05	
996.12	Н	55.77	-10.60	45.17	54.00	- 8.83	

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz $^{\circ}$
- (2) All readings are Peak unless otherwise stated QP in column of $^{\mathbb{F}}$ Note $_{\mathbb{F}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{\circ}$
- (3) Measuring frequency range from 30MHz to 1000MHz •
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table ${}^{\circ}$




Report No.: NEI-FCCP-1-0708043 Page 21 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature:	34 ℃	Relative Humidity:	54%
Pressure:	1003 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX		

Freq.	Ant.	Reading(RA)	Corr.Factor(CF)	Measured(FS)	Limits(QP)	Margin	Note
(MHz)	H/V	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	NOIC
111.48	V	44.30	-6.27	38.03	43.50	-5.47	
319.06	V	35.05	-2.99	32.06	46.00	-13.94	
468.44	V	38.00	0.56	38.56	46.00	-7.44	
483.96	V	38.34	0.89	39.23	46.00	-6.77	
800.18	V	31.55	6.74	38.29	46.00	-7.71	
838.98	V	27.24	7.25	34.49	46.00	-11.51	

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz
- (2) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (3) Measuring frequency range from 30MHz to 1000MHz •
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table ${}^{\circ}$




Report No.: NEI-FCCP-1-0708043 Page 22 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	34 ℃	Relative Humidity:	54 %
Pressure:	1003 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX		

Freq.	Ant.	Reading(RA)	Corr.Factor(CF)	Measured(FS)	Limits(QP)	Margin	Note
(MHz)	H/V	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Note
274.44	Τ	39.70	-4.36	35.34	46.00	- 10.66	
289.96	Η	41.18	-3.84	37.34	46.00	- 8.66	
468.44	Н	34.14	0.56	34.70	46.00	- 11.30	
761.38	Η	33.73	6.08	39.81	46.00	- 6.19	
800.18	Η	34.56	6.74	41.30	46.00	- 4.70	
838.98	Н	33.85	7.25	41.10	46.00	- 4.90	

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz $^{\circ}$
- (2) All readings are Peak unless otherwise stated QP in column of $^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{\circ}$
- (3) Measuring frequency range from 30MHz to 1000MHz •
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table ${}^{\circ}$



Report No.: NEI-FCCP-1-0708043 Page 23 of 78



4.2.8 TEST RESULTS (Above 1000 MHz)

EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11B mode CH01		

Freq.	Ant.Pol.	Rea	ding	Ant./CF	A	ct.	Lir	mit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2389.20	V	26.41	15.75	31.77	58.18	47.52	74.00	54.00	Y/E
2412.80	V	74.04	70.22	31.88	105.92	102.10			Y/F
1032.00	V	61.16	59.95	-10.73	50.46	49.45	74.00	54.00	Y/H
1072.00	V	57.68	56.31	-7.95	49.73	48.36	74.00	54.00	Y/H


Remark:

- (1) All readings are Peak unless otherwise stated QP in column of $^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:

"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 24 of 78





Report No.: NEI-FCCP-1-0708043 Page 25 of 78




EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature:	26 ℃	Relative Humidity:	57 %
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11B mode CH01		

Freq.	Ant.Pol.	Rea	ding	Ant./CF	A	ct.	Lir	mit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2412.80	Н	60.78	56.89	31.88	92.66	88.77			Y/F
2390.00	Н	22.81	11.06	31.77	54.58	42.83	74.00	54.00	Y/E
1032.00	Н	59.32	58.41	-10.26	48.76	48.15	74.00	54.00	Y/H

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 26 of 78





Report No.: NEI-FCCP-1-0708043 Page 27 of 78




EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11B mode CH06		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2436.20	٧	72.60	69.32	31.99	104.59	101.31			Y/F
1033.32	V	60.92	60.06	-10.30	50.62	49.80	74.00	54.00	Y/E

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 28 of 78





Report No.: NEI-FCCP-1-0708043 Page 29 of 78




EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11B mode CH06		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2436.20	Н	56.99	53.10	31.99	88.98	85.09			Y/F
1032.00	Н	59.26	58.36	-10.47	48.79	48.09	74.00	54.00	Y/E

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 30 of 78





Report No.: NEI-FCCP-1-0708043 Page 31 of 78




EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11B mode CH11		

Freq.	Ant.Pol.	Rea	ding	Ant./CF	A	ct.	Lir	nit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2461.00	V	72.14	69.80	32.11	104.25	101.92			Y/F
2483.50	V	20.74	11.15	32.22	52.96	43.37	74.00	54.00	Y/E
1033.32	V	60.88	59.98	-10.30	50.58	49.72	74.00	54.00	Y/E

- (1) All readings are Peak unless otherwise stated QP in column of $^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 32 of 78





Report No.: NEI-FCCP-1-0708043 Page 33 of 78




EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11B mode CH11		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2462.80	Н	57.25	53.40	32.12	89.37	85.52			Y/F
2483.50	Н	21.11	11.01	32.22	53.33	43.23	74.00	54.00	Y/E
1032.00	Н	59.43	58.65	-10.47	48.96	48.38	74.00	54.00	Y/E

- (1) All readings are Peak unless otherwise stated QP in column of $^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 34 of 78





Report No.: NEI-FCCP-1-0708043 Page 35 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure:	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11G mode CH01		


Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	V	38.73	20.68	31.77	70.50	52.45	74.00	54.00	Y/E
2417.00	٧	73.56	64.11	31.90	105.46	96.01			Y/F
1032.00	V	61.62	60.40	-8.11	53.51	52.29	74.00	54.00	Y/H

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:

"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 36 of 78





Report No.: NEI-FCCP-1-0708043 Page 37 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure:	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11G mode CH01		


Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2414.80	Н	64.51	54.97	31.89	96.40	86.86			Y/F
2389.00	Н	24.42	11.87	31.77	56.19	43.64	74.00	54.00	Y/E
1032.56	Н	59.38	58.76	-8.11	51.27	50.65	74.00	54.00	Y/H

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 38 of 78





Report No.: NEI-FCCP-1-0708043 Page 39 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11G mode CH06		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2432.00	V	71.61	62.22	31.97	103.58	94.19			Y/F
1032.00	V	61.35	60.60	-8.11	53.24	52.49	74.00	54.00	Y/H

Remark:


- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:

"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 40 of 78

Page 41 of 78





Report No.: NEI-FCCP-1-0708043



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11G mode CH06		


Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2432.00	Н	59.53	50.19	31.97	91.50	82.16			Y/F
1032.00	Н	59.44	58.56	-8.11	51.33	50.45	74.00	54.00	Y/H

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 42 of 78





Report No.: NEI-FCCP-1-0708043 Page 43 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature:	26 ℃	Relative Humidity:	57 %
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11G mode CH11		


Fred	٦.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
			Peak	AV		Peak	AV	Peak	AV	Note
(MH	z)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2469.	20	٧	68.18	58.73	32.15	100.33	90.88			Y/F
2483.	50	V	32.88	17.19	32.22	65.10	49.41	74.00	54.00	Y/E
1032.	00	V	61.52	60.70	-8.11	53.41	52.59	74.00	54.00	Y/H

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 44 of 78





Report No.: NEI-FCCP-1-0708043 Page 45 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure:	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX 11G mode CH11		


Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2455.20	Н	59.19	49.33	32.08	91.28	81.41			Y/F
2483.50	Н	22.99	11.33	32.22	55.21	43.55	74.00	54.00	Y/E
1032.48	Н	59.75	58.62	-8.11	51.64	50.51	74.00	54.00	Y/H

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 46 of 78





Report No.: NEI-FCCP-1-0708043 Page 47 of 78



4.2.9 TEST RESULTS (Restricted Bands Requirements)

EUT:	Wireless Messenger 2	Model Name :	Z2				
Temperature :	26 ℃	Relative Humidity:	57 %				
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz				
Test Mode :	11B mode CH 01/11(Vertical)						
Note:	The emission of the carrier radi (Peak and AV) as following: 1. The transmitter was then cor to transmit at the lowest char measured at 2310-2390 MH: 2. The transmitter was configur transmit at the highest chanr measured at 2483.5-2500 M	nfigured with the wor nnel (CH01). Then th z. red with the worst ca nel (CH11). Then the	st case antenna and setup ne field strength was se antenna and setup to				

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2389.20	V	26.41	15.75	31.77	58.18	47.52	74.00	54.00	CH01
2483.50	V	20.74	11.15	32.22	52.96	43.37	74.00	54.00	CH11

Remark:

- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = 200 ms
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (3) EUT Orthogonal Axes:

"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand


Report No.: NEI-FCCP-1-0708043 Page 48 of 78


2512.000 MHz



20.0

2412.000





2462.000

Report No.: NEI-FCCP-1-0708043 Page 49 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure:	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	11B mode CH 01/11 (Horizonta	ıl)	
Note:	The emission of the carrier radi (Peak and AV) as following: 1. The transmitter was then cor to transmit at the lowest char measured at 2310-2390 MH: 2. The transmitter was configur transmit at the highest chanr measured at 2483.5-2500 M	nfigured with the wor nnel (CH01). Then the z. red with the worst can nel (CH11). Then the	st case antenna and setup ne field strength was se antenna and setup to

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	Н	22.81	11.06	31.77	54.58	42.83	74.00	54.00	CH01
2483.50	Н	21.11	11.01	32.22	53.33	43.23	74.00	54.00	CH11


Remark:


- (1) Spectrum Setting : 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = 200 ms
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (3) EUT Orthogonal Axes:

"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand

Report No.: NEI-FCCP-1-0708043 Page 50 of 78







Report No.: NEI-FCCP-1-0708043 Page 51 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2		
Temperature:	26 ℃	Relative Humidity:	57 %		
Pressure:	1009 hPa	Test Voltage :	AC 120V/60Hz		
Test Mode :	11G mode CH 01/11 (Vertical)				
Note:	The emission of the carrier rad (Peak and AV) as following: 1. The transmitter was then conto transmit at the lowest chameasured at 2310-2390 MH. 2. The transmitter was configur transmit at the highest chanmeasured at 2483.5-2500 MH.	nfigured with the wor nnel (CH01). Then th z. red with the worst can nel (CH11). Then the	st case antenna and setup ne field strength was se antenna and setup to		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	V	38.73	20.68	31.77	70.50	52.45	74.00	54.00	CH01
2483.50	V	32.88	17.19	32.22	65.10	49.41	74.00	54.00	CH11

Remark:


- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = 200 ms
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (3) EUT Orthogonal Axes:

"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand


Report No.: NEI-FCCP-1-0708043 Page 52 of 78







11G mode CH 11 (Restricted Bands Requirements, Vertical)



Report No.: NEI-FCCP-1-0708043 Page 53 of 78



EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	26 ℃	Relative Humidity:	57 %
Pressure :	1009 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	11G mode CH 01/11(Horizonta	l)	
Note:	 The emission of the carrier rad (Peak and AV) as following: 1. The transmitter was then conto transmit at the lowest chameasured at 2310-2390 MH: 2. The transmitter was configur transmit at the highest chanrameasured at 2483.5-2500 M 	nfigured with the wor nnel (CH01). Then th z. red with the worst can nel (CH11). Then the	st case antenna and setup ne field strength was se antenna and setup to

Freq.	Ant.Pol.	Reading		Ant./CF	A	ct.	Lir	mit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	Н	24.42	11.87	31.77	56.19	43.64	74.00	54.00	CH01
2483.50	Η	22.99	11.33	32.22	55.21	43.55	74.00	54.00	CH11

Remark:


- (1) Spectrum Setting: 30MHz 1000MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 25GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = 200 ms
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (3) EUT Orthogonal Axes:

"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand


Report No.: NEI-FCCP-1-0708043 Page 54 of 78







11G mode CH 11 (Restricted Bands Requirements, Horizontal)



Report No.: NEI-FCCP-1-0708043 Page 55 of 78



5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C						
Section	Test Item	Limit	Frequency Range (MHz)	Result		
15.247 (a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS		

5.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP_40	100129	Aug,16, 2008

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

5.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = 20 ms.

5.1.3 DEVIATION FROM STANDARD

No deviation.

5.1.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER

5.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


Report No.: NEI-FCCP-1-0708043 Page 56 of 78



5.1.6 TEST RESULTS


EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature : 27 °C		Relative Humidity:	58 %
Pressure :	1004 hPa	Test Power :	AC 120V/60Hz
Test Mode :	802.11b/CH01, CH06, CH11		


Test Channel	Frequency (MHz)	Bandwidth (MHz)	99% Occupied BW (MHz)	LIMIT (MHz)
CH01	2412	10.04	14.28	>=500KHz
CH06	2437	10.08	14.00	>=500KHz
CH11	2462	10.08	13.88	>=500KHz



Report No.: NEI-FCCP-1-0708043 Page 57 of 78








Report No.: NEI-FCCP-1-0708043 Page 58 of 78




EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature:	27 ℃	Relative Humidity:	58 %
Pressure:	1004 hPa	Test Power :	AC 120V/60Hz
Test Mode :	802.11g/CH01, CH06, CH11		


Test Channel	Frequency (MHz)	Bandwidth (MHz)	99% Occupied BW (MHz)	LIMIT (MHz)
CH01	2412	16.56	16.64	>=500KHz
CH06	2437	16.36	16.52	>=500KHz
CH11	2462	16.56	16.52	>=500KHz



Report No.: NEI-FCCP-1-0708043 Page 59 of 78







Report No.: NEI-FCCP-1-0708043 Page 60 of 78



6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(1)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	Anritsu	ML2487A	6K00004714	Feb. 04, 2008
2	Power Meter Sensor	Anritsu	MA2491A	34138	Feb. 04, 2008

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

6.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 3MHz, VBW= 3MHz, Sweep time = 20 ms.

6.1.3 DEVIATION FROM STANDARD

No deviation.

6.1.4 TEST SETUP



6.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-0708043 Page 61 of 78



6.1.6 TEST RESULTS

EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	27 ℃	Relative Humidity:	58 %
Pressure :	1004 hPa	Test Power :	AC 120V/60Hz
Test Mode :	802.11b/CH01, CH06, CH11		

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH01	2412	16.83	30	1
CH06	2437	16.52	30	1
CH11	2462	16.57	30	1

EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature:	27 ℃	Relative Humidity:	58 %
Pressure:	1004 hPa	Test Power :	AC 120V/60Hz
Test Mode :	802.11g/CH01, CH06, CH11		

Test Channel	Frequency	Peak Output Power	LIMIT	LIMIT
icst orialino	(MHz)	(dBm)	(dBm)	(W)
CH01	2412	14.59	30	1
CH06	2437	13.81	30	1
CH11	2462	13.08	30	1

Report No.: NEI-FCCP-1-0708043 Page 62 of 78



7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a)limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

7.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP_40	100129	Aug,16, 2008

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	100 KHz /100 KHz for Peak

7.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.

7.1.3 DEVIATION FROM STANDARD

No deviation.

7.1.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER

Report No.: NEI-FCCP-1-0708043 Page 63 of 78



7.1.5 EUT OPERATION CONDITIONS The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-0708043 Page 64 of 78



7.1.6 TEST RESULTS

EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	27 ℃	Relative Humidity:	58 %
Pressure :	1004 hPa	Test Power :	AC 120V/60Hz
Test Mode :	11B mode CH01, CH11		


Channel of Worst Data: CH01					
The max. radio frequency power in any 100kHz bandwidth outside the frequency band bandwidth within the frequency band.					
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)		
2384.6 -46.62 2484.1 -47.12					
	Pocult				


Result

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.

Report No.: NEI-FCCP-1-0708043 Page 65 of 78







Report No.: NEI-FCCP-1-0708043 Page 66 of 78




EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	27 ℃	Relative Humidity:	58 %
Pressure :	1004 hPa	Test Power :	AC 120V/60Hz
Test Mode :	11G mode CH01, CH11		


Channel of Worst Data: CH01				
The max. radio frequency power in any 100kHz bandwidth outside the frequency band bandwidth within the frequency band.				
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)	
2389.96 -35.83 2484.1 -41.54				
Result				

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.

Report No.: NEI-FCCP-1-0708043 Page 67 of 78







Report No.: NEI-FCCP-1-0708043 Page 68 of 78



8. POWER SPECTRAL DENSITY TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C					
Section	Test Item	Limit	Frequency Range (MHz)	Result	
15.247 (d)	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS	

8.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP_40	100129	Aug,16, 2008

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

8.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=3KHz, VBW=30 KHz, Sweep time = 500s.

8.1.3 DEVIATION FROM STANDARD

No deviation.

8.1.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER

8.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


Report No.: NEI-FCCP-1-0708043 Page 69 of 78



8.1.6 TEST RESULTS


EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	27 ℃	Relative Humidity:	58 %
Pressure :	1004 hPa	Test Power :	AC 120V/60Hz
Test Mode :	11B mode CH01, CH06, CH11		


Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH01	2412	-16.62	8
CH06	2437	-17.75	8
CH11	2462	-18.67	8



Report No.: NEI-FCCP-1-0708043 Page 70 of 78








Report No.: NEI-FCCP-1-0708043 Page 71 of 78




EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	27 ℃	Relative Humidity:	58 %
Pressure :	1004 hPa	Test Power :	AC 120V/60Hz
Test Mode :	11G mode CH01, CH06, CH11		


Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH01	2412	-13.00	8
CH06	2437	-14.95	8
CH11	2462	-14.16	8



Report No.: NEI-FCCP-1-0708043 Page 72 of 78







Report No.: NEI-FCCP-1-0708043 Page 73 of 78



9. RF EXPOSURE TEST

9.1 Applied procedures / limit

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ², H ²or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	9
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz; *Plane-wave equivalent power density

9.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP_40	100129	Aug,16, 2008

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

9.1.2 MPE CALCULATION METHOD

E (V/m)
$$=\frac{\sqrt{30 \times P \times G}}{d}$$
 Power Density: Pd (W/m²) $=\frac{E^2}{377}$

 $\mathbf{E} = \text{Electric field (V/m)}$

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

Report No.: NEI-FCCP-1-0708043 Page 74 of 78



9.1.3 DEVIATION FROM STANDARD

No deviation.

9.1.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER

9.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-0708043 Page 75 of 78



9.1.6 TEST RESULTS

EUT:	Wireless Messenger 2	Model Name :	Z2	
Temperature :	27 ℃	Relative Humidity:	58 %	
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz	
Test Mode : 11B mode CH01, CH06, CH11				

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.72	1.8707	16.83	48.1948	0.017945	1	Complies
2.72	1.8707	16.52	44.8745	0.016709	1	Complies
2.72	1.8707	16.57	45.3942	0.016902	1	Complies

EUT:	Wireless Messenger 2	Model Name :	Z2
Temperature :	27 ℃	Relative Humidity:	58 %
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	11G mode CH01, CH06, CH11		


Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.72	1.8707	14.59	28.7740	0.010714	1	Complies
2.72	1.8707	13.81	24.0436	0.008953	1	Complies
2.72	1.8707	13.08	20.3236	0.007567	1	Complies

Report No.: NEI-FCCP-1-0708043 Page 76 of 78



10. EUT TEST PHOTO

Conducted Measurement Photos





Report No.: NEI-FCCP-1-0708043 Page 77 of 78



Radiated Measurement Photos





Report No.: NEI-FCCP-1-0708043 Page 78 of 78