

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
UNINTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 18 REQUIREMENT**

for

CFLs

M/N: GYT3S09/L-27, GYT3S13/L-27, GYT3S13/L-50

FCC ID: VGZ3S09-13

Trade Name: Not Applicable

Report No.: SHEE080331259301-09

Issue Date: Sept. 24, 2008

Prepared for

**JIANGXI ELEGANT LIGHTING CO LTD
No. 713, Xihou St., Guixi, Jiangxi, China
TEL: 86-701-377 1030
FAX: 86-701-379 4699**

Prepared by

**CENTRE TESTING INTERNATIONAL CO., LTD.
1F., BUILDING C, HONGWEI INDUSTRIAL ZONE,
BAOAN 70 DISTRICT, SHENZHEN, CHINA
TEL: 86-755-3368 3365
FAX: 86-755-3368 3365**

**This report shall not be reproduced, except in full, without the written approval of
CENTRE TESTING INTERNATIONAL**

TABLE OF CONTENTS

1. General Information	3
2. Product Information.....	4
3. Test Methodology.....	4
4. Test Facility	4
5. Special Accessories	4
6. Equipment Modifications.....	4
7. Test Condition	5
7.1 Test Configuration	5
7.2 Test Procedure	5
7.3 EUT operation	5
7.4 Peripherals / Support Equipment Used	5
7.5 Limit	6
8. Summary of Test Results.....	6
9. Conducted Emissions Test.....	7
9.1 Measurement Procedure	7
9.2 Test Set-up (Block Diagram of Configuration)	7
9.3 Measurement Equipment Used	7
9.4 Measurement Results	7
10. Radiated Emission Test.....	11
10.1 Measurement Procedure	11
10.2 Test Set-up (Block Diagram of Configuration)	11
10.3 Measurement Equipment Used	12
10.4 Measurement Results	12
11. Measurement Uncertainty.....	16
APPENDIX 1 PHOTOGRAPHS OF TEST SETUP.....	17
APPENDIX 2 EXTERNAL PHOTOGRAPHS OF EUT.....	18
APPENDIX 3 INTERNAL PHOTOGRAPHS OF EUT	错误！未定义书签。

1. General Information

Applicant: JIANGXI ELEGANT LIGHTING CO LTD
No. 713, Xihou St., Guixi, Jiangxi, China

Manufacturer: JIANGXI ELEGANT LIGHTING CO LTD
No. 713, Xihou St., Guixi, Jiangxi, China

Trade Name: Not Applicable

Product Name : CFLs

M/N: GYT3S09/L-27, GYT3S13/L-27, GYT3S13/L-50

Report No.: SHEE080331259301-09


Date of Test: Apr. 01, 2008 to Aug. 31, 2008

We hereby certify that:

The above equipment was tested by Centre Testing International (CTI), The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 18.


The test results of this report relate only to the tested sample identified in this report.

Prepared by :




Lily Yan

Inspected by :



Christy Chen

Approved by:



Jacky Guo
General Manager

Date : _____

Oct. 30, 2008



2. Product Information

Product name: CFLs
Model name: GYT3S09/L-27, GYT3S13/L-27, GYT3S13/L-50
Trade name: Not Applicable
Technical data: Input voltage: AC 120V/60Hz
GYT3S09/L-27:T3 Spiral lamp 9W,
GYT3S13/L-27, GYT3S13/L-50:T3 Spiral lamp 13W
Model difference: All the models are identical in schematic, PCB layout and appearance except the rated power.
The tested models in the report are GYT3S09/L-27, GYT3S13/L-27.
Function: Lighting

3. Test Methodology

Both conducted and radiated tests were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at a distance 3 meters from the antenna to EUT.

4. Test Facility

The 3m Semi-Anechoic chamber test site and conducted measurement facility used to collect the radiated data is located on the address:

1F., Building C, Hongwei Industrial Zone 70 District., Baoan, Shenzhen, Guangdong, China.

The Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003 requirements. The test site Registration Number: 614926

5. Special Accessories

Not available for this EUT intended for grant.

6. Equipment Modifications

Not available for this EUT intended for grant.

7. Test Condition

7.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the EUT and the supported equipments were installed to meet FCC requirement and operated in a manner which tends to maximize its emission level in a typical application.

7.2 Test Procedure

Conducted Emissions:

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

Radiated Emissions:

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2003.

7.3 EUT operation

EUT was tested according to the following operation modes provided by the specifications given by the manufacturer, and reported the worst emissions.

7.4 Peripherals / Support Equipment Used

Following peripheral devices and interface cables were connected during the measurement:

Type of Peripheral Equipment Used: None

Type of Cables Used: None

7.5 Limit

Conducted Emission:

According to section 18.307(c) Conducted Emission Limits is as following:

Frequency (MHz)	Maximum RF Line Voltage
	Q.P.(dBuV)
0.45-2.51	48
2.51-3.0	69.5
3.0-30	48

Radiated Emission:

According to section 18.305(c) Radiated Emission Limits is as following:

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m Q.P.)
30-88	3	40.0
88-216	3	43.5
216-1000	3	46.0

Remark:

1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

8. Summary of Test Results


FCC Rules	Description Of Test	Result
§18.307(c)	Conducted Emission	Compliant
§18.305(c)	Radiated Emission	Compliant

9. Conducted Emissions Test

9.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane, connected to the LISN, and worked normally during the whole test.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. If the EUT emission level was less -6dB to the Q.P. limit in Peak mode, then the emission signal was re-checked using Q.P. detector.
4. Repeat above procedures until all frequencies measured were completed.

9.2 Test Set-up (Block Diagram of Configuration)



9.3 Measurement Equipment Used

Equipment Type	Manufacturer	Model Number	Serial Number	Last Calibration	Calibration Due
Receiver	R&S	ESCI	100435	01/29/2008	01/28/2009
LISN	ETS	3816	00060336	06/07/2008	06/06/2009

9.4 Measurement Results

Limit : FCC Part 18 Conduction
EUT : CFLs
M/N : GYT3S09/L-27
Mode : Normal

Power : AC 120V/60HZ
Temperature : 24°C
Humidity : 53%
Tested by : Lily Yan

(The chart below shows the highest readings taken from the final data)

FCC Conducted Emission Test Result													
Frequency (MHz)	Reading Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limits (dBuV)		Margin		Result (P/F)	Remarks (L/N)
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Q.P.	Avg.	Q.P.	Avg.		
0.4700	14.69	--	--	21.61	36.30	--	--	48.00	--	<-10	--	P	L
0.5340	12.69	--	--	21.56	34.25	--	--	48.00	--	<-10	--	P	L
0.5820	11.90	--	--	21.54	33.44	--	--	48.00	--	<-10	--	P	L
0.7060	13.04	11.20	--	21.53	34.57	32.73	--	48.00	--	-15.27	--	P	L
0.8340	12.92	--	--	21.55	34.47	--	--	48.00	--	<-10	--	P	L
1.1380	13.07	--	--	21.46	34.53	--	--	48.00	--	<-10	--	P	L
0.4500	12.99	--	--	21.62	34.61	--	--	48.00	--	<-10	--	P	N
0.5860	13.30	--	--	21.54	34.84	--	--	48.00	--	<-10	--	P	N
0.7020	12.82	--	--	21.53	34.35	--	--	48.00	--	<-10	--	P	N
0.7780	13.09	--	--	21.54	34.63	--	--	48.00	--	<-10	--	P	N
1.1180	10.22	--	--	21.47	31.69	--	--	48.00	--	<-10	--	P	N
25.4580	7.31	--	--	22.44	29.75	--	--	48.00	--	<-10	--	P	N

Limit : FCC Part 18 Conduction
EUT : CFLs
M/N : GYT3S13/L-27
Mode : Normal

Power : AC 120V/60HZ
Temperature : 24°C
Humidity : 53%
Tested by : Lily Yan


(The chart below shows the highest readings taken from the final data)

Frequency (MHz)	Reading Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limits (dBuV)		Margin		Result (P/F)	Remarks (L/N)
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Q.P.	Avg.	Q.P.	Avg.		
0.4620	14.23	10.86	--	21.61	35.84	32.47	--	48.00	--	-15.53	--	P	L
0.5780	16.31	14.74	--	21.54	37.85	36.28	--	48.00	--	-11.72	--	P	L
0.6419	16.01	14.11	--	21.53	37.54	35.64	--	48.00	--	-12.36	--	P	L
0.7700	14.59	11.37	--	21.54	36.13	32.91	--	48.00	--	-15.09	--	P	L
0.9620	14.04	9.14	--	21.55	35.59	30.69	--	48.00	--	-17.31	--	P	L
1.0859	15.66	10.95	--	21.49	37.15	32.44	--	48.00	--	-15.56	--	P	L
0.4740	16.95	14.14	--	21.60	38.55	35.74	--	48.00	--	-12.26	--	P	N
0.5340	18.32	15.97	--	21.56	39.88	37.53	--	48.00	--	-10.47	--	P	N
0.6300	15.44	8.33	--	21.53	36.97	29.86	--	48.00	--	-18.14	--	P	N
0.7220	15.37	12.92	--	21.53	36.90	34.45	--	48.00	--	-13.55	--	P	N
0.8700	16.58	12.88	--	21.57	38.15	34.45	--	48.00	--	-13.55	--	P	N
1.2579	17.17	11.55	--	21.38	38.55	32.93	--	48.00	--	-15.07	--	P	N


Freq.
 Reading level
 Factor
 Emission level
 Limit
 Margin

= Emission frequency in MHz
 = Uncorrected Analyzer/Receiver reading
 = Cable loss + insertion loss
 = Reading level + Factor
 = Limit stated in standard
 = Reading in reference to limit


Graph of Conducted Emissions:
L: (normal Mode for GYT3S09/L-27)




N: (normal Mode for GYT3S09/L-27)



L: (normal Mode for GYT3S13/L-27)



N: (normal Mode for GYT3S13/L-27)




10. Radiated Emission Test

10.1 Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane, and worked normally during the whole test.
2. Maximum procedure was performed on the twelve highest emissions to ensure EUT compliance.
3. If the EUT emission level was less -6dB to the Q.P. limit in Peak mode, then the emission signal was re-checked using Q.P. detector.
4. Repeat above procedures until all frequencies measured were completed.

10.2 Test Set-up (Block Diagram of Configuration)

A. Radiated Emission Test Set-Up, Frequency below 1000MHz



B. Radiated Emission Test Set-Up, Frequency above 1000MHz



10.3 Measurement Equipment Used

Equipment Type	Manufacturer	Model Number	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	E4443A	MY46185649	06/29/2008	06/28/2009
Biconilog Antenna	ETS	3142C	920250	05/30/2008	05/29/2009
ETS Horn Antenna	ETS	3117	57410	05/30/2008	05/29/2009
Multi device Controller	ETS	2090	00057230	06/07/2008	06/06/2009

10.4 Measurement Results

Limit : FCC Part 18 Radiation
EUT : CFLs
M/N : GYT3S09/L-27
Mode : Normal

Power : AC 120V/60Hz
Temperature : 26°C
Humidity : 60%
Tested by : Lily Yan

(The chart below shows the highest readings taken from the final data)

FCC Radiated Emission Test Result													
Frequency (MHz)	Reading Level (dBuv)			Correct Factor (dB)	Measurement (dBuV/m)			Limit (dBuV/m)		Margin (dB)		Result (P/F)	Remarks (H/V)
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Q.P.	Avg.	Q.P.	Avg.		
30.0000	7.46	--	--	17.63	25.09	--	--	40.00	--	<-10	--	P	H
102.7500	8.24	--	--	10.24	18.48	--	--	43.50	--	<-10	--	P	H
251.4833	8.51	--	--	14.18	22.69	--	--	46.00	--	<-10	--	P	H
358.1833	9.04	--	--	17.75	26.79	--	--	46.00	--	<-10	--	P	H
518.2333	9.23	--	--	20.57	29.80	--	--	46.00	--	<-10	--	P	H
650.8000	9.32	--	--	23.34	32.66	--	--	46.00	--	<-10	--	P	H
30.0000	8.88	--	--	17.63	26.51	--	--	40.00	--	<-10	--	P	V
59.1000	18.88	15.37	--	8.42	27.30	23.79	--	40.00	--	-16.21	--	P	V
114.0667	15.58	11.96	--	9.53	25.11	21.49	--	40.00	--	-18.51	--	P	V
298.3667	8.29	--	--	15.76	24.05	--	--	43.50	--	<-10	--	P	V
477.8167	9.35	--	--	20.08	29.43	--	--	46.00	--	<-10	--	P	V
553.8000	9.10	--	--	21.46	30.56	--	--	46.00	--	<-10	--	P	V

Limit : FCC Part 18 Radiation
EUT : CFLs
M/N : GYT3S13/L-27
Mode : Normal

Power : AC 120V/60Hz
Temperature : 26°C
Humidity : 60%
Tested by : Lily Yan


(The chart below shows the highest readings taken from the final data)

FCC Radiated Emission Test Result													
Frequency (MHz)	Reading Level (dBuv)			Correct Factor (dB)	Measurement (dBuV/m)			Limit (dBuV/m)		Margin (dB)		Result (P/F)	Remarks (H/V)
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Q.P.	Avg.	Q.P.	Avg.		
30.0000	8.03	--	--	17.63	25.66	--	--	40.00	--	<-10	--	P	H
107.5999	8.53	--	--	9.92	18.45	--	--	43.50	--	<-10	--	P	H
152.8667	9.11	--	--	10.74	19.85	--	--	46.00	--	<-10	--	P	H
419.6166	9.15	--	--	18.50	27.65	--	--	46.00	--	<-10	--	P	H
623.3166	9.50	--	--	23.19	32.69	--	--	46.00	--	<-10	--	P	H
820.5499	10.05	--	--	25.48	35.53	--	--	46.00	--	<-10	--	P	H
31.6167	10.73	--	--	16.67	27.40	--	--	40.00	--	<-10	--	P	V
104.3667	12.62	--	--	10.13	22.75	--	--	40.00	--	<-10	--	P	V
396.9833	9.07	--	--	18.35	27.42	--	--	40.00	--	<-10	--	P	V
587.7500	9.20	--	--	21.82	31.02	--	--	43.50	--	<-10	--	P	V
760.7333	9.49	--	--	24.76	34.25	--	--	46.00	--	<-10	--	P	V
922.4000	9.41	5.09	--	26.88	36.29	31.97	--	46.00	--	-14.03	--	P	V


Freq. = Emission frequency in MHz
 Raw Data (dBuV/m) = Uncorrected Analyzer / Receiver reading
 Corr. Factor (dB) = Correction factors of antenna factor and cable loss
 Emiss. Leve = Raw reading converted to dBuV/m and CF added
 Limit dBuV/m = Limit stated in standard
 Margin dB = Reading in reference to limit
 PK = Peak Reading
 QP = Quasi-peak

Graph of Radiated Emissions:


H:(Antenna) (normal mode for GYT3S09/L-27)




V:(Antenna) (normal mode for GYT3S09/L-27)



H:(Antenna) (normal mode for GYT3S13/L-27)



V:(Antenna) (normal mode for GYT3S13/L-27)



11. Measurement Uncertainty

Conduction Uncertainty : $\pm 2.8\text{dB}$


Radiation Uncertainty : $\pm 3.4\text{dB}$

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST



APPENDIX 2 EXTERNAL PHOTOGRAPHS OF EUT



Whole View of EUT (GYT3S09/L)



Whole View of EUT (GYT3S13/L)-1



Whole View of EUT (GYT3S13/L)-2

----End of the report----