

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
UNINTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 18 REQUIREMENT**

for

CFLs

M/N: GYT3S18/L-27, GYT3S18/L-50, GYT3S20/L-27, GYT3S20/L-50

GYT3S23/L-27, GYT3S23/L-50, GYT3S26/L-27

FCC ID: VGZ3S18-26

Trade Name: Not Applicable

Report No.: SHEE080331259301-10

Issue Date: Sept. 24, 2008

Prepared for

**JIANGXI ELEGANT LIGHTING CO LTD
No. 713, Xihou St., Guixi, Jiangxi, China
TEL: 86-701-377 1030
FAX: 86-701-379 4699**

Prepared by

**CENTRE TESTING INTERNATIONAL CO., LTD.
1F., BUILDING C, HONGWEI INDUSTRIAL ZONE,
BAOAN 70 DISTRICT, SHENZHEN, CHINA
TEL: 86-755-3368 3365
FAX: 86-755-3368 3365**

**This report shall not be reproduced, except in full, without the written approval of
CENTRE TESTING INTERNATIONAL**

TABLE OF CONTENTS

1. General Information	3
2. Product Information	4
3. Test Methodology.....	4
4. Test Facility	4
5. Special Accessories.....	4
6. Equipment Modifications.....	4
7. Test Condition	5
7.1 Test Configuration.....	5
7.2 Test Procedure	5
7.3 EUT operation	5
7.4 Peripherals / Support Equipment Used	5
7.5 Limit	6
8. Summary of Test Results	6
9. Conducted Emissions Test	7
9.1 Measurement Procedure.....	7
9.2 Test Set-up (Block Diagram of Configuration).....	7
9.3 Measurement Equipment Used	7
9.4 Measurement Results	7
10. Radiated Emission Test.....	11
10.1 Measurement Procedure.....	11
10.2 Test Set-up (Block Diagram of Configuration).....	11
10.3 Measurement Equipment Used	11
10.4 Measurement Results.....	11
11. Measurement Uncertainty	15
APPENDIX 1 PHOTOGRAPHS OF TEST SETUP	16
APPENDIX 2 EXTERNAL PHOTOGRAPHS OF EUT.....	17

1. General Information

Applicant: JIANGXI ELEGANT LIGHTING CO LTD
No. 713, Xihou St., Guixi, Jiangxi, China

Manufacturer: JIANGXI ELEGANT LIGHTING CO LTD
No. 713, Xihou St., Guixi, Jiangxi, China

Trade Name: Not Applicable

Product Name : CFLs

M/N: GYT3S18/L-27, GYT3S18/L-50, GYT3S20/L-27,
GYT3S20/L-50, GYT3S23/L-27, GYT3S23/L-50,
GYT3S26/L-27

Report No.: SHEE080331259301-10


Date of Test: Apr. 01, 2008 to Aug. 31, 2008

We hereby certify that:


The above equipment was tested by Centre Testing International (CTI), The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 18.

The test results of this report relate only to the tested sample identified in this report.


Prepared by :


Lily Yan

Inspected by :


Christy Chen

Approved by:


Jacky Guo
General Manager

Date :

Oct. 30, 2008



2. Product Information

Product name:	CFLs
Model name:	GYT3S18/L-27, GYT3S18/L-50, GYT3S20/L-27, GYT3S20/L-50, GYT3S23/L-27, GYT3S23/L-50, GYT3S26/L-27
Trade name:	Not Applicable
Technical data:	Input voltage: AC 120V/50Hz GYT3S18/L-27, GYT3S18/L-50: T3 Spiral lamp 18W GYT3S20/L-27, GYT3S20/L-50: T3 Spiral lamp 20W GYT3S23/L-27, GYT3S23/L-50: T3 Spiral lamp 23W GYT3S26/L-27: T3 Spiral lamp 26W
Model difference:	All the models are identical in schematic, PCB layout and appearance except the rated power. The tested models in the report are GYT3S18/L-27, GYT3S26/L-27.
Function:	Lighting

3. Test Methodology

Both conducted and radiated tests were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at a distance 3 meters from the antenna to EUT.

4. Test Facility

The 3m Semi-Anechoic chamber test site and conducted measurement facility used to collect the radiated data is located on the address:

1F., Building C, Hongwei Industrial Zone 70 District., Baoan, Shenzhen, Guangdong, China.

The Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003 requirements. The test site Registration Number: 614926

5. Special Accessories

Not available for this EUT intended for grant.

6. Equipment Modifications

Not available for this EUT intended for grant.

7. Test Condition

7.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the EUT and the supported equipments were installed to meet FCC requirement and operated in a manner which tends to maximize its emission level in a typical application.

7.2 Test Procedure

Conducted Emissions:

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

Radiated Emissions:

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2003.

7.3 EUT operation

EUT was tested according to the following operation modes provided by the specifications given by the manufacturer, and reported the worst emissions.

7.4 Peripherals / Support Equipment Used

Following peripheral devices and interface cables were connected during the measurement:

Type of Peripheral Equipment Used: None

Type of Cables Used: None

7.5 Limit

Conducted Emission:

According to section 18.307(c) Conducted Emission Limits is as following:

Frequency (MHz)	Maximum RF Line Voltage
	Q.P.(dBuV)
0.45-2.51	48
2.51-3.0	69.5
3.0-30	48

Radiated Emission:

According to section 18.305(c) Radiated Emission Limits is as following:

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m Q.P.)
30-88	3	40.0
88-216	3	43.5
216-1000	3	46.0

Remark:

1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

8. Summary of Test Results


FCC Rules	Description Of Test	Result
§18.307(c)	Conducted Emission	Compliant
§18.305(c)	Radiated Emission	Compliant

9. Conducted Emissions Test

9.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane, connected to the LISN, and worked normally during the whole test.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. If the EUT emission level was less -6dB to the Q.P. limit in Peak mode, then the emission signal was re-checked using Q.P. detector.
4. Repeat above procedures until all frequencies measured were completed.

9.2 Test Set-up (Block Diagram of Configuration)



9.3 Measurement Equipment Used

Equipment Type	Manufacturer	Model Number	Serial Number	Last Calibration	Calibration Due
Receiver	R&S	ESCI	100435	01/29/2008	01/28/2009
LISN	ETS	3816	00060336	06/07/2008	06/06/2009

9.4 Measurement Results

Limit : FCC Part 18 Conduction
EUT : CFLs
M/N : See belows
Mode : Normal

Power : AC 120V/60HZ
Temperature : 24°C
Humidity : 53%
Tested by : Lily Yan

(The chart below shows the highest readings taken from the final data)

M/N : GYT3S18/L-27

Frequency (MHz)	Reading Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limits (dBuV)		Margin		Result (P/F)	Remarks (L/N)
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Q.P.	Avg.	Q.P.	Avg.		
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Peak	Q.P.	Peak	Q.P.		
0.5060	15.27	13.27	--	21.58	36.85	34.85	--	48.00	--	-13.15	--	P	L
0.5299	16.83	15.29	--	21.56	38.39	36.85	--	48.00	--	-11.15	--	P	L
0.6419	15.69	7.61	--	21.53	37.22	29.14	--	48.00	--	-18.86	--	P	L
0.8059	14.63	11.02	--	21.54	36.17	32.56	--	48.00	--	-15.44	--	P	L
0.9620	13.98	9.44	--	21.55	35.53	30.99	--	48.00	--	-17.01	--	P	L
1.1300	13.76	6.66	--	21.46	35.22	28.12	--	48.00	--	-19.88	--	P	L
0.5740	15.68	10.90	--	21.54	37.22	32.44	--	48.00	--	-15.56	--	P	N
0.6300	15.69	12.64	--	21.53	37.22	34.17	--	48.00	--	-13.83	--	P	N
0.7820	15.59	11.62	--	21.54	37.13	33.16	--	48.00	--	-14.84	--	P	N
1.2140	16.47	6.37	--	21.41	37.88	27.78	--	48.00	--	-20.22	--	P	N
1.4500	14.47	7.12	--	21.27	35.74	28.39	--	48.00	--	-19.61	--	P	N
1.6060	14.40	8.67	--	21.17	35.57	29.84	--	48.00	--	-18.16	--	P	N


M/N : GYT3S26/L-27

Frequency (MHz)	Reading Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limits (dBuV)		Margin		Result (P/F)	Remarks (L/N)
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Q.P.	Avg.	Q.P.	Avg.		
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Peak	Q.P.	Peak	Q.P.		
0.4820	18.88	16.49	--	21.60	40.48	38.09	--	48.00	--	-9.91	--	P	L
0.5300	22.36	14.25	--	21.56	43.92	35.81	--	48.00	--	-12.19	--	P	L
0.9840	25.71	14.69	--	21.55	47.26	36.24	--	48.00	--	-11.76	--	P	L
1.0660	24.12	12.97	--	21.50	45.62	34.47	--	48.00	--	-13.53	--	P	L
1.2760	24.60	10.06	--	21.37	45.97	31.43	--	48.00	--	-16.57	--	P	L
1.3280	25.37	10.08	--	21.34	46.71	31.42	--	48.00	--	-16.58	--	P	L
0.4660	17.21	16.10	--	21.61	38.82	37.71	--	48.00	--	-10.29	--	P	N
0.5620	19.78	16.44	--	21.55	41.33	37.99	--	48.00	--	-10.01	--	P	N
0.7260	19.54	17.55	--	21.53	41.07	39.08	--	48.00	--	-8.92	--	P	N
0.8900	18.30	16.05	--	21.58	39.88	37.63	--	48.00	--	-10.37	--	P	N
1.1700	19.76	10.94	--	21.44	41.20	32.38	--	48.00	--	-15.62	--	P	N
1.2140	22.14	12.28	--	21.41	43.55	33.69	--	48.00	--	-14.31	--	P	N


Freq.
 Reading level
 Factor
 Emission level
 Limit
 Margin

= Emission frequency in MHz
 = Uncorrected Analyzer/Receiver reading
 = Cable loss + insertion loss
 = Reading level + Factor
 = Limit stated in standard
 = Reading in reference to limit


Graph of Conducted Emissions:
L: (normal Mode for GYT3S18/L-27)




N: (normal Mode for GYT3S18/L-27)



L: (normal Mode for GYT3S26/L-27)



N: (normal Mode for GYT3S26/L-27)




10. Radiated Emission Test

10.1 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane, and worked normally during the whole test.
2. Maximum procedure was performed on the twelve highest emissions to ensure EUT compliance.
3. If the EUT emission level was less -6dB to the Q.P. limit in Peak mode, then the emission signal was re-checked using Q.P. detector.
4. Repeat above procedures until all frequencies measured were completed.

10.2 Test Set-up (Block Diagram of Configuration)

Radiated Emission Test Set-Up, Frequency below 1000MHz



10.3 Measurement Equipment Used

Equipment Type	Manufacturer	Model Number	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	E4443A	MY46185649	06/29/2008	06/28/2009
Biconilog Antenna	ETS	3142C	920250	05/30/2008	05/29/2009
ETS Horn Antenna	ETS	3117	57410	05/30/2008	05/29/2009
Multi device Controller	ETS	2090	00057230	06/07/2008	06/06/2009

10.4 Measurement Results

Limit : FCC Part 18 Radiation
EUT : CFLs
M/N : See belows
Mode : Normal

Power : AC 120V/60Hz
Temperature : 26°C
Humidity : 60%
Tested by : Lily Yan

(The chart below shows the highest readings taken from the final data)

M/N : GYT3S18/L-27

Frequency (MHz)	Reading Level (dBuV)			Correct Factor (dB)	Measurement (dBuV/m)			Limit (dBuV/m)		Margin (dB)		Result (P/F)	Remarks (H/V)
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Q.P.	Avg.	Q.P.	Avg.		
	30.0000	7.46	--	--	17.63	25.09	--	40.00	--	<-10	--	P	H
102.7500	8.24	--	--	10.24	18.48	--	--	43.50	--	<-10	--	P	H
251.4833	8.51	--	--	14.18	22.69	--	--	46.00	--	<-10	--	P	H
358.1833	9.04	--	--	17.75	26.79	--	--	46.00	--	<-10	--	P	H
518.2333	9.23	--	--	20.57	29.80	--	--	46.00	--	<-10	--	P	H
650.8000	9.32	--	--	23.34	32.66	--	--	46.00	--	<-10	--	P	H
30.0000	8.88	--	--	17.63	26.51	--	--	40.00	--	<-10	--	P	V
59.1000	18.88	15.37	--	8.42	27.30	23.79	--	40.00	--	-16.21	--	P	V
114.0667	15.58	11.96	--	9.53	25.11	21.49	--	40.00	--	-18.51	--	P	V
298.3667	8.29	--	--	15.76	24.05	--	--	43.50	--	<-10	--	P	V
477.8167	9.35	--	--	20.08	29.43	--	--	46.00	--	<-10	--	P	V
553.8000	9.10	--	--	21.46	30.56	--	--	46.00	--	<-10	--	P	V

M/N : GYT3S26/L-27

Frequency (MHz)	Reading Level (dBuV)			Correct Factor (dB)	Measurement (dBuV/m)			Limit (dBuV/m)		Margin (dB)		Result (P/F)	Remarks (H/V)
	Peak	Q.P.	Avg.		Peak	Q.P.	Avg.	Q.P.	Avg.	Q.P.	Avg.		
	30.0000	8.23	7.39	--	17.63	25.86	25.02	--	40.00	--	-14.98	--	P
97.9000	9.22	--	--	10.33	19.55	--	--	43.50	--	<-10	--	P	H
251.4833	10.01	--	--	14.18	24.19	--	--	46.00	--	<-10	--	P	H
333.9332	9.67	--	--	17.12	26.79	--	--	46.00	--	<-10	--	P	H
594.2166	10.38	--	--	22.01	32.39	--	--	46.00	--	<-10	--	P	H
776.8999	9.91	--	--	24.90	34.81	--	--	46.00	--	<-10	--	P	H
31.6167	12.75	10.59	--	16.67	29.42	27.26	--	40.00	--	-12.74	--	P	V
59.1000	20.85	--	--	8.42	29.27	--	--	40.00	--	<-10	--	P	V
160.9500	9.16	--	--	11.27	20.43	--	--	40.00	--	<-10	--	P	V
287.0500	9.79	--	--	15.30	25.09	--	--	43.50	--	<-10	--	P	V
616.8500	10.09	--	--	22.91	33.00	--	--	46.00	--	<-10	--	P	V
846.4167	10.10	--	--	25.61	35.71	--	--	46.00	--	<-10	--	P	V

Freq. = Emission frequency in MHz
 Raw Data (dBuV/m) = Uncorrected Analyzer / Receiver reading
 Corr. Factor (dB) = Correction factors of antenna factor and cable loss
 Emiss. Leve = Raw reading converted to dBuV/m and CF added
 Limit dBuV/m = Limit stated in standard
 Margin dB = Reading in reference to limit
 PK = Peak Reading
 QP = Quasi-peak

Graph of Radiated Emissions:

H:(Antenna) (normal mode for GYT3S18/L-27)


File :0407

Data :#18

Date: 2004/01/04


Time: 23:42:54

76.9 dBuV/m




V:(Antenna) (normal mode for GYT3S18/L-27)


76.9 dBuV/m



H:(Antenna) (normal mode for GYT3S26/L-27)



V:(Antenna) (normal mode for GYT3S26/L-27)



11. Measurement Uncertainty

Conduction Uncertainty : $\pm 2.7\text{dB}$


Radiation Uncertainty : $\pm 3.8\text{dB}$

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST



APPENDIX 2 EXTERNAL PHOTOGRAPHS OF EUT



Whole View of EUT- GYT3S18/L-27 & GYT3S18/L-50



Whole View of EUT- GYT3S20/L-27 & GYT3S20/L-50



Whole View of EUT- GYT3S23/L-27 & GYT3S23/L-50



Whole View of EUT- GYT3S26/L-27

----End of the report----