



# FCC Test Report (TR-0908-015-02)

**Applicant**: GOLDEN REGENT ELECTRONICS INDUSTRIAL LTD

Address : SUN ON TOWN.KUNG LOK INDUSTRIAL VILLAGE..

SHENZHEN.GUANGDONG, CHINA

**Manufacturer** : GOLDEN REGENT ELECTRONICS INDUSTRIAL LTD

Address : SUN ON TOWN.KUNG LOK INDUSTRIAL VILLAGE..

SHENZHEN.GUANGDONG, CHINA

**Product Name** : Reader

**Trademark**: None

**Model(s)** : RDR 7(GNG-A741-02)

**Standard(s)** : FCC Part 15 Subpart C

**Test Result** : Pass

**Date of Test** : Nov 11, 2009 to Feb 04, 2010

**Report issued Dated**: Feb 04, 2010

The report shall not be reproduced except in full, without the written approval of the TDK EMC Center.

The results in this report apply only to the sample(s) tested. The production units are required to conform to the initial sample as received when the units are placed in the market.

Responsible :

Engineer

Approved by :

Technical Technical

nenix Zhang / manager CHAN king-chui

Date : 2010.02.04 Date : 2010.02.04





#### **Table of Contents**

Description	Page
1. Description of the Test Site	3
1.1 Test Site Location:	3
1.2 Site Registration	3
1.3 Test Scope	3
2. Description of the Tested Samples	4
2.1 Customer Information	4
2.2 Identification of EUT	4
2.3 Spec of EUT	4
2.4 Test Standards List	4
3. Test Specifications	5
3.1 Standard(s) Used	5
3.2 Deviations from the Test Specification	5
4. Test Result	6
4.1 Antenna Requirement	6
4.2 Conducted Emission (mains)	7
4.3 Maximum Peak Output Power	8
4.4 Band Edges Emission	10
4.5 6dB BANDWIDTH	17
4.6 Power Spectral Density	19
4.7 Spurious Radiated Emission	21
5. FCC ID Label	30
5. Test Setup	31
5.1 Ancillary and Accessory Equipment Used	31
5.2 Photographs of the Test Configuration	
5.3 Photographs of the EUT	
6. Equipment List	37
7. Test Uncertainty	38
8. Appendix	38
8.1 Confirmation of Compliance within the Limits	38





## 1. Description of the Test Site

#### 1.1 Test Site Location:

Laboratory : TDK South China EMC Center

SAE Technologies Development (Dongguan) Co.,

Ltd. Changan Branch

Address : Zhenan Hi-tech Industrial Park, Dongguang City,

Guangdong Province, China

Phone no. : (86)-769-8564-4678 Fax no. : (86)-769-8564-4499 Email : emc@cn.tdk.com

#### 1.2 Site Registration

VCCI (September, 2008) : Reg. No. R-2205, C-2392

FCC site registration (July, 2008) : Reg. No. 732901 IC registration : Reg. No. 7993

EMCC (September, 2008) : Reg. No. NAR/tl-060330

#### 1.3 Test Scope

EMC and RF testing according to national / international standards





## 2. Description of the Tested Samples

#### 2.1 Customer Information

Customer : GOLDEN REGENT ELECTRONICS INDUSTRIAL LTD Address : SUN ON TOWN.KUNG LOK INDUSTRIAL VILLAGE..

SHENZHEN.GUANGDONG, CHINA

Phone no. : 0086-755-29667713

Fax no. : 0086-755-29667044

#### 2.2 Identification of EUT

Trademark : None

Model(s) No. : Reader

Serial No. : R-1098S50011A

#### 2.3 Spec of EUT

Description of EUT : This product is a RFID reader, which has a 13.56MHz

module to read a passive tag. It also has a 2.4GHz module to

communicate with GSC(Gas Station Communicator). In this report, only 2.4GHz part was tested and recorded.

Description of Antenna : fixed permanent antenna, 3dBi gain for 13.56MHz

3dBi gain for 2.4GHz

Power Supply : Internal battery 3.6V DC

Operation Frequency: 13.56MHz and 2450 MHz

Number of Channels : 2

Bandwidth : 0.4MHz at 13.56MHz and 64MHz at 2450MHz

Type of Modulation : ASK for 13.56MHz

CSS for 2450MHz

#### 2.4 Test Standards List

FCC Part 15 (2008)

American national standard for methods of measurement of radio noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40GHz.





## 3. Test Specifications

## 3.1 Standard(s) Used

FCC Rules	Description Of Test	Result
15.203/15.247(b)	Antenna Requirement	Pass
15.207	Conducted Emission	N/A
15.247(b)(3)	Maximum Peak Output Power	Pass
15.247(d)	Band Edges Emission	Pass
15.247(a)(2)	6 dB Bandwidth	Pass
15.247(e)	Power Spectral Density	Pass
15.247(d)	Spurious Radiated Emission	Pass

## 3.2 Deviations from the Test Specification

N/A

Report No.: TR-0908-015-02



#### 4. Test Result

#### 4.1 Antenna Requirement

## 4.1.1 Standard Applicable Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna James or electrical connector is prohibited.

Section 15.247(b):

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 4.1.2 Antenna Connected Construction

The antenna connector is designed with permanent attachment and no consideration of replacement.

Transmitter antenna of directional gain is 3dBi.



#### **4.2 Conducted Emission (mains)**


#### 4.2.1 Test Summary

Test Room : Shielded Room
Power Source : AC 120V / 60Hz
Standards: : FCC Part15 B : 2008

EUT Type : Table Top

EUT configuration : EUT's highest possible emission level

#### 4.2.2 Block diagram of test setup



#### 4.2.3 Measurement method

The EUT along with its peripherals were placed on a 1.0m (W) x 1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4m space from a vertical reference plane. The EUT was connected to power mains through a Artificial Mains Network(AMN), which provided 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.

The excess power cable between the EUT and the AMN was bundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

#### 4.2.4. Result

N/A

Because the power of EUT is internal battery, this test item is not applicable.




#### 4.3 Maximum Peak Output Power

4.3.1 Applicable Standard

According to Section 15.247(b)(3), for systems using digital modulation in 2400-2483.5MHz: 1 Watt.

#### 4.3.2 Block diagram of test setup



**Connection method:** The shield cable was connected with EUT and Spectrum which have  $50\Omega Z_C$ . The connector of EUT side is original by manufacturer. The connector of Spectrum side is N type.

#### 4.3.3 Measurement method

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in above figure without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3. Set the spectrum analyzer as Center= 2.44 GHz, RBW=10 MHz, VBW=10 MHz, Span=100MHz.
- 4. Set Detector to Peak, Trace to Max Hold and Sweep Time is auto.
- 5. Hold on 30s, find out the max value on the screen of Spectrum.
- 6. Repeat above procedures until all frequencies measured were complete.




#### 4.3.4. Result

Temperature ( ): 22~23	EUT: Reader
Humidity (%RH ): 50~54	M/N: RDR 7(GNG-A741-02)
Barometric Pressure (mbar): 950~1000	Operation Condition: 2.4GHz Tx Mode
Test data: Feb 04, 2010	Test engineer: Phenix

Frequency	Output Power	Limits	Margin	
(MHz)	(dBm)	(dBm)	(dB)	
2436.69	5.03	30	24.97	

#### Test Plot:



Report No.: TR-0908-015-02




#### 4.4 Band Edges Emission

#### 4.4.1 Applicable Standard

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions that fall in the restricted bands, as defined in Section 15.205, must also comply with the radiated emission limits specified in Section 15.209.

#### 4.4.2 Block diagram of test setup



Connection method: The shield cable was connected with EUT and Spectrum which have  $50\Omega~Z_C$ . The connector of EUT side is original by manufacturer. The connector of Spectrum side is N type.

#### 4.4.3 Measurement method

- 1. The transmitter is set to the lowest channel.
- 2. The transmitter output was connected to the spectrum analyzer via a cable and cable loss is used as the offset of the spectrum analyzer.
- 3. Set both RBW and VBW of spectrum analyzer to 100KHz with convenient frequency span including 50MHz bandwidth from lower band edge. Then detector set to peak and max hold this trace.
- 4. The lowest band edges emission was measured and recorded.
- 5. The transmitter set to the highest channel and repeated  $2\sim4$ .





## 4.4.4. Result


#### **Conducted:**

Temperature ( ) : 22~23	EUT: Reader
Humidity (%RH ): 50~54	M/N: RDR 7(GNG-A741-02)
Barometric Pressure ( mbar ): 950~1000	Operation Condition: 2.4G Tx Mode
Test data: Dec 02, 2009 & Feb 02, 2010	Test engineer: Phenix


Frequency (MHz)	Read Delta (dB)	Limits (dB)	Margin (dB)
2400	-34.52	-20	14.52
2399.75	-27.39	-20	7.39
2394.75	-32.53	-20	12.53
2483.5	-36.83	-20	16.83
2485.25	-27.46	-20	7.46
2491.25	-26.95	-20	6.95



#### **Channel LOW:**



#### **Channel HIG:**





2.35G

#### **Radiated:**

2009-12-02 17:44:06

## RADIATED EMISSION


Date: 2009-12-02 17:43:21

Company Name Golden Document No.

Model Name RDR 7(GNG-A741-02) Power Supply internal battery
Product Name Reader Temp/Humi 27/55RH%
Test Condition TX 2.4G testing Operator Phenix

Memo :

LIMIT : FCC Part15 C transmitter spurious above1G(peak) FCC Part15 C transmitter spurious above1G(average)







2009-12-02 17:44:06

## **RADIATED EMISSION**

Date: 2009-12-02 17:43:21

Company Name Model Name Product Name Test Condition Golden RDR 7(GNG-A741-02) Reader TX 2.4G testing Document No. Power Supply Temp/Humi Operator

internal battery 27/55RH% Phenix

Memo

LIMIT : FCC Part15 C transmitter spurious above1G(peak) FCC Part15 C transmitter spurious above1G(average)

No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE	REMARK
	[MHz]	[dBuV]	FACTO [dB]	[dB]	[dB]	[dBuV/m][d	dBuV/m]	[dB]	[cm]	[deg]	
	- Horizontal -										
2 3 4 5 6 7 8	2373.050 2383.070 2392.090 2394.290 2399.100 2400.000 2373.051 2383.073	51.9 51.4 50.1 53.5 54.5 36.5 56.2 55.7	31.5 31.5 31.4 31.4 31.4 31.5 31.5	5.5 5.5 5.5 5.5 5.5 5.5 5.5 5.5	39.5 39.5 39.5 39.5 39.5 39.5 39.5	49.4 48.9 47.5 50.9 51.9 33.9 53.7 53.2	54.0 54.0 54.0 54.0 54.0 54.0 74.0	4.6 5.1 6.5 3.1 2.1 20.1 20.3 20.8	300 300 300 300 300 300 300 300	287 291 287 299 287 287 287 291	AV AV AV AV PK PK
11 12	2392.092 2394.297 2399.108 2400.110 - Vertical	56.5 56.8 60.0 63.1	31.4 31.4 31.4 31.4	5.5 5.5 5.5 5.5	39.5 39.5 39.5 39.5	53.9 54.2 57.4 60.5	74.0 74.0 74.0 74.0	20.1 19.8 16.6 13.5	300 300 300 300	287 299 287 287	PK PK PK PK
14 15 16 17 18 19 20 21 22 23	2383.130 2392.090 2394.290 2396.100 2399.300 2400.000 2383.273 2392.092 2394.297 2396.101 2399.308 2400.110	51.3 52.5 51.7 51.7 54.4 30.2 55.4 56.4 56.5 55.8 58.1 61.7	31.5 31.4 31.4 31.4 31.4 31.5 31.4 31.4 31.4 31.4 31.4	5.5 5.5 5.5 5.5 5.5 5.5 5.5 5.5 5.5 5.5	39.5 39.5 39.5 39.5 39.5 39.5 39.5 39.5	48.8 49.9 49.1 51.8 27.6 52.9 53.8 53.9 53.2 55.5 59.1	54.0 54.0 54.0 54.0 54.0 74.0 74.0 74.0 74.0 74.0 74.0	5.2 4.1 4.9 4.9 2.2 26.4 21.1 20.2 20.1 20.8 18.5 14.9	200 200 200 200 200 200 200 200 200 200	146 68 121 84 72 20 146 68 121 84 72 20	AV AV AV AV AV PK PK PK PK PK






2009-12-08 19:06:45

## RADIATED EMISSION

Date: 2009-12-08 19:06:33







2009-12-08 19:06:45

## **RADIATED EMISSION**

Date: 2009-12-08 19:06:33

Company Name Model Name Product Name Test Condition Golden RDR 7(GNG-A741-02) Reader TX 2.4G testing Document No. Power Supply Temp/Humi Operator

internal battery 27/55RH% Phenix

Memo

LIMIT : FCC Part15 C transmitter spurious above1G(peak) FCC Part15 C transmitter spurious above1G(average)

No	. FREQ	READING			GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE	REMARK
	[MHz]	[dBuV]	FACTO [dB]	(dB)	[dB]	[dBuV/m][	dBuV/m]	[dB]	[cm]	[deg]	
0	Horizontal	<u> 25.535</u> 6)									
1 2 3 4 5 6	2483,500 2485,142 2491,138 2483,339 2485,343 2491,356	24.6 54.4 55.0 55.8 54.9 55.7	31.2 31.2 31.2 31.2 31.2 31.2	5.6 5.6 5.6 5.6 5.6 5.6	39.4 39.4 39.4 39.4 39.4 39.4	22.0 51.8 52.4 53.2 52.3 53.1	54.0 54.0 54.0 74.0 74.0 74.0	32.0 2.2 1.6 20.8 21.7 20.9	100 100 100 100 100 100	105 101 101 105 101 101	AV AV QP QP QP
	Vertical										
7	2483.500	25.0	31.2	5.6	39.4	22.4	54.0	31.6	100	39	AV
8	2485.127	55.1	31.2	5.6	39.4	52.5	54.0	1.5	100	39	AV
9	2489.144	55.2	31.2	5.6	39.4	52.6	54.0	1.4	100	39	ΑV
10	2491.137	55.5	31.2	5.6	39.4	52.9	54.0	1.1	100	43	AV
11	2483.339	59.8	31.2	5.6	39.4	57.2	74.0	16.8	100	39	QP
12	2485.343	58.1	31.2	5.6	39.4	55.5	74.0	18.5	100	39	QP
13	2489.352	57.4	31.2	5.6	39.4	54.8	74.0	19.2	100	39	QP
14	2491.356	58.2	31.2	5.6	39.4	55.6	74.0	18.4	100	43	QP




## 4.5 6dB BANDWIDTH

#### 4.5.1 Applicable Standard

According to section 15.247(a)(2), for digital modulation technique, the minimum 6dB bandwidth shall be at least 500kHz.

#### 4.5.2 Block diagram of test setup



Connection method: The shield cable was connected with EUT and Spectrum which have  $50\Omega Z_C$ . The connector of EUT side is original by manufacturer. The connector of Spectrum side is N type.

#### 4.5.3 Measurement method

- 1. The transmitter output was connected to the spectrum analyzer through a shielded cable.
- 2. Set the spectrum analyzer as RBW=100 kHz, VBW=300 kHz, Span=110MHz, Sweep=auto.
- 3. Set Detector to Peak, Trace to Max Hold and Sweep Time is auto.
- 4. Mark the peak frequency and -6dB(upper and lower) frequency.
- 5. Repeat above 1-4 points for the middle and highest channel of the EUT.




#### 4.5.4. Result

Temperature ( ) : 22~23	EUT: Reader
Humidity (%RH ): 50~54	M/N: RDR 7(GNG-A741-02)
Barometric Pressure (mbar): 950~1000	Operation Condition: 2.4G Tx Mode
Test data: Dec 02, 2009	Test engineer: Phenix

Frequency	6dB Bandwidth	Limits
(MHz)	(MHz)	(MHz)
2445	62.975	> 0.5

#### **Test Plot:**



Report No.: TR-0908-015-02




#### **4.6 Power Spectral Density**

#### 4.6.1 Applicable Standard

According to section 15.247(d), for digital modulation technique, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.6.2 Block diagram of test setup



Connection method: The shield cable was connected with EUT and Spectrum which have  $50\Omega$  Z<sub>C</sub>. The connector of EUT side is original by manufacturer. The connector of Spectrum side is N type.

#### 4.6.3 Measurement method

- 1. The transmitter output was connected to the spectrum analyzer through a shielded cable.
- 2. Set the spectrum analyzer as RBW=3 kHz, VBW=10 kHz, Span=300 kHz, Sweep=100s.
- 3. Set Detector to Peak, Trace to Max Hold.
- 4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The plot of result is show on the screen of spectrum analyzer.
- 5. Repeat above 1-4 points for the middle and highest channel of the EUT.




#### 4.6.4. Result

Temperature ( ): 22~23	EUT: Reader
Humidity (%RH ): 50~54	M/N: RDR 7(GNG-A741-02)
Barometric Pressure ( mbar ): 950~1000	Operation Condition: 2.4G Tx Mode
Test data: Dec 02, 2009	Test engineer: Phenix

Frequency	Power Spectral Density	Limits	Margin
(MHz)	(MHz)	(dBm)	(dB)
2416	-17.59	8	25.59

#### **Test Plot:**





#### 4.7 Spurious Radiated Emission

## 4.7.1 Applicable Standard

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions that fall in the restricted bands, as defined in Section 15.205, must also comply with the radiated emission limits specified in Section 15.209.

#### 4.7.2 Block diagram of test setup

#### Radiated Measurement Setup:




Figure 1: Frequencies measured below 1 GHz configuration





Figure 2: Frequencies measured above 1 GHz configuration



#### Conducted Measurement Setup:



**Connection method:** The shield cable was connected with EUT and Spectrum which have  $50\Omega~Z_C$ . The connector of EUT side is original by manufacturer. The connector of Spectrum side is N type.

#### 4.7.3 Measurement method

#### **Radiated Measurement**

- 1. Configure the EUT according to ANSI C63.4.
- 2. The EUT was placed on the top of the turntable 0.8 meter above ground.
- 3. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 4. Power on the EUT and all the supporting units.
- 5. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 6. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.
- 7. For each suspected emission, the antenna tower was scanned (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 8. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.





#### **Conducted Measurement**

- 1. For emission above 1GHz, conducted measurement method is used.
- 2. The transmitter is set to the lowest channel.
- 3. The transmitter output was connected to the spectrum analyzer via a cable and cable loss is used as the offset of the spectrum analyzer.
- 4. Set RBW to 100 KHz and VBW to 300 KHz, Then detector set to peak and max hold this trace.
- 5. The lowest band edges emission was measured and recorded.
- 6. The transmitter set to the highest channel and repeated  $2\sim4$ .



#### 4.7.4. Result

#### **PASS**

#### Radiated:

#### **Below 30MHz:**

No further spurious emissions found between lowest internal used or generated frequency and 30 MHz.

#### 30M-1GHz:

2009-11-11 15:18:34

## RADIATED EMISSION

Date: 2009-11-11 15:18:25

 Trade Name
 : GOLDEN
 Document No.
 :


 Model Name
 : RDR 7(GNG-A741-02)
 Power Supply
 : Internal Battery

 Product Name
 : Reader
 Temp/Humi
 : 27/55RH%

 Test Condition
 : TX ON 2.4GHz
 Operator
 : Phenix

Memo :

LIMIT: FCC Part15 Class B(3m)/USA







2009-11-11 15:18:34

## **RADIATED EMISSION**

Date: 2009-11-11 15:18:25

Trade Name Model Name Product Name Test Condition GOLDEN RDR 7(GNG-A741-02) Reader TX ON 2.4GHz Document No. Power Supply Temp/Humi Operator

: Internal Battery : 27/55RH% : Phenix

Memo

LIMIT : FCC Part15 Class B(3m)/USA

No.	FREQ	READING PEAK	ANT FACTOR		GAIN	RESULT	LIMIT	MARGIN	ANTENN	A TABLE
	[MHz]	[dBuV]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m	] [dB]	[cm]	[DEG]
H	Horizontal									
1 2 3 4 5	175.792 189.399 203.006 298.257 325.471 434.328	47.8	12.3 12.9 13.3 13.5 14.9 17.2	7.9 7.9 8.0 8.6 8.7 9.2	31.5 31.5 31.5 31.3 31.3 31.3	38.4 37.1 39.6 40.1 39.6 43.3	43.5 43.5 43.5 46 46 46	5.1 6.4 3.9 5.9 6.4 2.7	200 200 200 100 100 100	191 191 12 199 335 150
V	ertical									
7 8 9	203.006 325.471 467.374	40.9 40.5 30.9	13.3 14.9 18.1	8.0 8.7 9.5	31.5 31.3 31.3	30.7 32.8 27.2	43.5 46 46	12.8 13.2 18.8	200	278 357 172



#### **Above 1GHz:**

2009-12-02 18:19:52


## **RADIATED EMISSION**

Date: 2009-12-02 18:19:35

Frequency[Hz]

Memo :

LIMIT : FCC Part15 C transmitter spurious above1G(peak) FCC Part15 C transmitter spurious above1G(average)







2009-12-02 18:19:52

## **RADIATED EMISSION**

Date: 2009-12-02 18:19:35

 Company Name
 : Golden
 Document No.
 : Model Name
 : RDR 7(GNG-A741-02)
 Power Supply
 : internal battery

 Product Name
 : Reader
 Temp/Humi
 : 27/55RH%

 Test Condition
 : TX 2.4G testing
 Operator
 : Phenix

Memo :


LIMIT : FCC Part15 C transmitter spurious above1G(peak) FCC Part15 C transmitter spurious above1G(average)


No.	FREQ	READING PEAK F	ANT ACTOR	LOSS	GAIN	RESULT	LIMIT I	MARGIN	ANTENN	A TABLE
	[MHz]	[dBuV]		[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
H	orizontal									
1 2 3 4	3002.010 6987.996 18000.00 18000.00	34.6 0 24.0	32.3 41.0 49.8 49.8	6.2 9.6 15.6 15.6		33.8 46.0 49.2 49.2	74 74 74 74	40.2 28.0 24.8 24.8	400 100 200 200	31 358 150 150
V	ertical									
5 6 7 8	2731.469 6591.201 6951.923 17743.48	35.3 34.8	31.7 40.2 40.9 47.5	6.0 9.3 9.6 15.6	39.3 39.6 39.3 40.3	32.9 45.2 46.0 48.4	74 74 74 74	41.1 28.8 28.0 25.6	300 200 300 100	59 126 2 14

No further spurious emissions found between 18GHz and 25GHz.




#### **Conducted:**











#### 5. FCC ID Label





## 5. Test Setup

## **5.1** Ancillary and Accessory Equipment Used

Connect to GSC, for control EUT:

No.	Description	Quantity	
1.	PC	DELL, M/N:540, S/N: 124XK2X	1
2.	Monitor	DELL, M/N:E157FPc, S/N:CN-OFJ061-64180-69A-06CS	1
3.	Keyboard	DELL, M/N:L100, S/N: CN0RH6566589006860007J	1
4.	Mouse	HP, M/N:M-SBF96	1



## **5.2** Photographs of the Test Configuration

## 5.2.1 Radiated emission

Below 1GHz:



#### Above 1GHz:





## 5.3 Photographs of the EUT




Enclosure of EUT




Enclosure of EUT





PCB of EUT



PCB of EUT





Photo of Battery



Photo of Battery







Connectors





## 6. Equipment List

No.	Equipment	Manufacturer	Model	Serial No.	Calibration
1	Precision Biconical	TDK Co.	PBA-2030	090500	<b>Date</b> 2009-09-18
	Antenna	1212 00.	12112000		2007 07 10
2	Precision Log	TDK Co.	PLP-3003	061001	2009-09-18
	Periodic Antenna				
3	Hybrid Log	TDK	HLP-3003C	130174	2009-09-18
	Periodic Antenna				
4	Horn antenna	TDK	HRN-0118	130186	2009-04-07
5	Attenuator 6 dB	Agilent	8491B	MY39260147	2009-09-18
6	Preamplifier	TDK Sonoma	310	242803	2009-04-07
7	Preamplifier	ELENA	EAU-3718	A070701	2009-04-07
			GXA		
8	EMI Receiver	Rohde &	ESIB26	100234	2009-04-07
		Schwarz			
9	EMI Receiver	Rohde &	ESCS30	100350	2009-04-07
		Schwarz			
10	Spectrum Analyzer	Agilent	E4403B	MY44210199	2009-04-07
11	Art. Mains Network	EMCO	3816/2	00044921	2009-04-07
12	Transient	Agilent	11947A	3107A03736	2009-04-07
	Limiter(10 dB)				
13	Personal Computer	HP	DX2000MT	MXD4250FZM	N/A
14	Personal Computer	НР	DX2000MT	MXD4130B2N	N/A
15	Semi-Anechoic	TDK Co.	N/A	N/A	2009-04-07
	Chamber				
16	Shielded Room	TDK Co.	N/A	N/A	N/A
17	Loop Antenna	EMCO	6502	9107-2440	2009-04-07





#### 7. Test Uncertainty

Test	Range Confidence		Calculated	
		Level	Uncertainty	
Radiated emission(3m)	30-1000MHz	95%	4.3dB	
Conducted emission	0.15-30MHz	95%	3.3dB	

## 8. Appendix

## **8.1** Confirmation of Compliance within the Limits

8.1.1 Method of calculating measurement result

**Radiated Emission** 

For example the point of 203.006MHz, vertical, Page 25.

	Reading	+	Antenna factor		Cable loss	-	Gain	=	Result
Example	40.9	+	13.3	+	8.0	_	31.5	=	30.7