



# RF EXPOSURE REPORT

**REPORT NO.:** SA960202L05

**MODEL NO.:** LBT324A

**SERIES NO.:** BTH01

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Liyuh Technology Ltd.

**ADDRESS:** 7F, No. 13, Alley 23, Lane 796, Jhong Sino E. Rd.,  
Taipei R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB ADDRESS:** No. 47, 14<sup>th</sup> Ling, Chia Pau Tsuen, Lin Kou Hsiang  
244, Taipei Hsien, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2<sup>nd</sup> Rd., Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	-1.460	0.714
EIRP Power	-4.120	0.387

**\*Note:** The antenna is chip antenna with -2.66dBi gain.

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 0.714mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold