FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : PND

Model No. : 21MAX

Brand Name : NAVIGON

Filing Type : New Application

Applicant . NAVIGON AG . Berliner Platz 11 D-97080 Würzburg Germany

FCC ID : VIL-21MAX

Manufacturer . Compal Communications (Nanjing) Co., Ltd.

No.68-2, Suyuan Road, Export Processing Zone (South

Area). Nanjing China Post:211100

Received Date : Jan. 30, 2008 Final Test Date : Feb. 04, 2008

Statement

Test result included is only for the Bluetooth part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.4-2003 and 47 CFR FCC Part 15 Subpart C.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



SPORTON International Inc.

6F, No. 106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

Table of Contents

1.	SUMI	MARY OF THE TEST RESULT	2
2.	GENE	ERAL INFORMATION	3
	2.1.	Product Details	
	2.2.	Navigation device	3
	2.3.	Table for Filed Antenna	3
	2.4.	Table for Carrier Frequencies	3
	2.5.	Table for Test Modes	4
	2.6.	Table for Testing Locations	4
	2.7.	Table for Supporting Units	4
	2.8.	Table for Parameters of Test Software Setting	5
	2.9.	EUT Operation during Test	5
	2.10.	Test Configurations	6
3.	TEST	RESULT	8
	3.1.	AC Power Line Conducted Emissions Measurement	8
	3.2.	Maximum Peak Output Power Measurement	12
	3.3.	Hopping Channel Separation Measurement	14
	3.4.	Number of Hopping Frequency Measurement	19
	3.5.	Dwell Time Measurement	21
	3.6.	Radiated Emissions Measurement	28
	3.7.	Band Edge Emissions Measurement	40
	3.8.	Antenna Requirements	43
4.	LIST	OF MEASURING EQUIPMENTS	44
5.	TEST	LOCATION	46
6.	TAF (CERTIFICATE OF ACCREDITATION	47
ΑI	PPEN	DIX A. TEST PHOTOS	. A1 ~ A6
ΔΙ	PPFNI	DIX B. PHOTOGRAPHS OF FUT	R1 ~ R20

TEL: 886-2-2696-2468 FAX: 886-2-2696-2255 Issued Date : Feb. 28, 2008 FCC ID : VIL-21MAX

History of This Test Report

Original Issue Date: Feb. 28, 2008

Report No.: FR813018

No additional attachment.

Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

SPORTON International Inc. Page No. : ii of ii



Report No.: FR813018

CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment

: PND

Model No.

: 21MAX

Applicant

: NAVIGON AG

Berliner Platz 11 D-97080 Würzburg Germany

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jan. 30, 2008 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

FCC ID

1. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C						
Part	Part Rule Section Description of Test		Result	Under Limit		
3.1	15.207	AC Power Line Conducted Emissions	Complies	9.38 dB		
3.2	15.247(b)(1)	Maximum Peak Conducted Output Power	Complies	27.94 dB		
3.3	3.3 15.247(a)(1) Hopping Channel Separation		Complies	-		
3.4	15.247(b)(1) Number of Hopping Frequency		Complies	-		
3.5	3.5 15.247(a)(1) Dwell Time		Complies	-		
3.6	3.6 15.247(d) Radiated Emissions		Complies	1.02 dB		
3.7	15.247(d)	Band Edge Emissions	Complies	9.40 dB		
3.8	3.8 15.203 Antenna Requirements		Complies	-		

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Hopping Channel Separation	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

 SPORTON International Inc.
 Page No.
 : 2 of 47

 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

2. GENERAL INFORMATION

2.1. Product Details

EUT is a PND with Bluetooth radio function. The part number is 21001125. Only the radio detail of Bluetooth is shown in the table below. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Power Type	From Battery or Car charger
Modulation	FHSS (GFSK)
Data Rate (Mbps)	1
Frequency Range	2400 ~ 2483.5MHz
Channel Number	79
Channel Band Width (99%)	0.894 MHz
Conducted Output Power	2.06 dBm

2.2. Navigation device

- SD-card containing software and navigation maps
- Installation instructions
- CD with manuals (PDF)

2.3. Table for Filed Antenna

Ant.	Antenna Type	Connector	Gain (dBi)
1	Printed Antenna	Fixed on board	0.19

2.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency
	0	2402 MHz
	1	2403 MHz
	:	:
	38	2440 MHz
2400~2483.5MHz	39	2441 MHz
	40	2442 MHz
	:	:
	77	2479 MHz
	78	2480 MHz

 SPORTON International Inc.
 Page No.
 : 3 of 47

 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

2.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Conducted Emissions	Data Link Mode	1 Mbps	Hopping 0~78	1
Max. Conducted Output Power	GFSK	1 Mbps	0/39/78	NA
Hopping Channel Separation	GFSK	1 Mbps	0~1/39~40/77~78	NA
Number of Hopping Frequency	GFSK	1 Mbps	0~78	NA
Dwell Time	DH1/DH3/DH5	1 Mbps	0/39/78	NA
Radiated Emissions Below 1GHz	GFSK	1 Mbps	39	1
Radiated Emissions Above 1GHz	GFSK	1 Mbps	0/39/78	1
Band Edge Emissions	GFSK	1 Mbps	0/78	1

2.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4086B-1	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4086B-1	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

2.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
(PS2) Keyboard	BTC	9110	DoC
Mouse	Microsoft	1004	DoC
Printer	EPSON	LQ300+	DoC
Modem	ACEEX	DM-1414	IFAXDM1414
Monitor	Sony	G520	DoC
PC	HP	DC7700	DoC
Notebook	DELL	D400	DoC
DC Power Supply	G.W	GPC-6030D	DoC
Car Charger (Provide by Customer)	JESS-LINK	HH-12B	DoC

 SPORTON International Inc.
 Page No. : 4 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

2.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of Bluetooth

Test Software Version	CMU200		
Frequency	2402 MHz	2441 MHz	2480 MHz
Power Parameters	0	0	0

2.9. EUT Operation during Test

<Conduction>

Two executive programs, EMCTEST.EXE & Winthrax under WIN XP, then PC sends messages to the internal Hard Disk, and the Hard Disk reads and writes the message.

The PC sends "H" messages to the monitor, and the monitor displays "H" patterns on the screen.

The PC sends "H" messages to the printer, then the printer prints them on the paper.

The PC sends "H" messages to the modem

<Radiation>

An executive program, EMCTEST.EXE under WIN XP, then NB sends messages to the internal Hard Disk, and the Hard Disk reads and writes the message.

The NB sends "H"messages to the panel, and the panel displays "H "patterns on the screen.

The NB sends "H" messages to the modem

<RF>

Executed "CMU200" to keep transmitting signals at fixed frequency.

 SPORTON International Inc.
 Page No.
 : 5 of 47


 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

2.10. Test Configurations

2.10.1. Radiation Emissions Test Configuration

For radiated emissions 9kHz~1GHz




 SPORTON International Inc.
 Page No.
 : 6 of 47

 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

For radiated emissions above 1GHz



 SPORTON International Inc.
 Page No. : 7 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3. TEST RESULT

3.1. AC Power Line Conducted Emissions Measurement

3.1.1. Limit

For a Low-power Radio-frequency device which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

3.1.3. Test Procedures

- Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far
 from the conducting wall of the shielding room and at least 80 centimeters from any other grounded
 conducting surface.
- 2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
- 4. The frequency range from 150 KHz to 30 MHz was searched.
- 5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.


6. The measurement has to be done between each power line and ground at the power terminal.

 SPORTON International Inc.
 Page No.
 : 8 of 47

 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

3.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5. Test Deviation

There is no deviation with the original standard.

 SPORTON International Inc.
 Page No.
 : 9 of 47

 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008


 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

3.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

3.1.7. Results of AC Power Line Conducted Emissions Measurement

Test date	Feb. 04, 2008	Test Site No.	CO04-HY
Temperature	25	Humidity	55%
Test Engineer	Chris Lin	Phase	Line
Configuration	Data Link Mode		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	ф	dBuV	dBuV	dB	dB	
1	0.1758420	49.96	-14.72	64.68	49.72	0.10	0.14	QP
2	@0.1758420	45.30	-9.38	54.68	45.06	0.10	0.14	Average
3	0.2353310	41.08	-21.18	62.26	40.70	0.10	0.28	QP
4	0.2353310	36.39	-15.87	52.26	36.01	0.10	0.28	Average
5	0.4711010	34.20	-22.29	56.49	33.42	0.10	0.68	QP
6	0.4711010	27.53	-18.96	46.49	26.75	0.10	0.68	Average
7	1.870	37.47	-18.53	56.00	36.94	0.10	0.43	QP
8	1.870	32.76	-13.24	46.00	32.23	0.10	0.43	Average
9	3.801	28.25	-17.75	46.00	27.82	0.10	0.33	Average
10	3.801	39.89	-16.11	56.00	39.46	0.10	0.33	QP
11	15.150	32.93	-27.07	60.00	32.21	0.58	0.14	QP
12	15.150	26.76	-23.24	50.00	26.04	0.58	0.14	Average

 SPORTON International Inc.
 Page No. : 10 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

Test date	Feb. 04, 2008	Test Site No.	CO04-HY
Temperature	25	Humidity	55%
Test Engineer	Chris	Phase	Neutral
Configuration	Data Link Mode		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	- dB	dBuV	dBuV	dB	dB	0
1	0.1767760	49.74	-14.90	64.64	49.50	0.10	0.14	QP
2	0.1767760	44.68	-9.96	54.64	44.44	0.10	0.14	Average
3	0.2353310	44.34	-17.92	62.26	43.96	0.10	0.28	QP
4	0.2353310	36.74	-15.52	52.26	36.36	0.10	0.28	Average
5	0.3520120	38.76	-20.15	58.91	38.04	0.10	0.62	QP
6	0.3520120	32.39	-16.52	48.91	31.67	0.10	0.62	Average
7	1.113	35.70	-20.30	56.00	35.16	0.10	0.44	QP
8	1.113	31.53	-14.47	46.00	30.99	0.10	0.44	Average
9	1.876	35.79	-10.21	46.00	35.26	0.10	0.43	Average
10	1.876	39.23	-16.77	56.00	38.70	0.10	0.43	QP
11	3.814	40.52	-15.48	56.00	40.00	0.19	0.33	QP
12	3.814	27.32	-18.68	46.00	26.80	0.19	0.33	Average

Note:

Level = Read Level + LISN Factor + Cable Loss.

 SPORTON International Inc.
 Page No. : 11 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.2. Maximum Peak Output Power Measurement

3.2.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	NRV-Z32 (model 04)

3.2.3. Test Procedures

- 1. The transmitter output (antenna port) was connected to the power meter.
- 2. Turn on the EUT and power meter and then record the peak power value.
- 3. Repeat above procedures on all channels needed to be tested.

3.2.4. Test Setup Layout



3.2.5. Test Deviation

There is no deviation with the original standard.

3.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

 SPORTON International Inc.
 Page No. : 12 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.2.7. Test Result of Maximum Peak Output Power

Test date	Jan. 31, 2008	Test Site No.	TH01-HY
Temperature	28	Humidity	58%
Test Engineer	Nan	Configurations	GFSK

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
0	2402 MHz	2.06	30.00	Complies
39	2441 MHz	1.98	30.00	Complies
78	2480 MHz	1.85	30.00	Complies

 SPORTON International Inc.
 Page No. : 13 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.3. Hopping Channel Separation Measurement

3.3.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.3.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.3.3. Test Procedures

- 1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- 2. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- 3. The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised for channel separation measurement.

3.3.4. Test Setup Layout



3.3.5. Test Deviation

There is no deviation with the original standard.

 SPORTON International Inc.
 Page No. : 14 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.3.7. Test Result of Hopping Channel Separation

Test date	Jan. 31, 2008	Test Site No.	TH01-HY
Temperature	28	Humidity	58%
Test Engineer	Nan	Configurations	GFSK

Frequency	Ch. Separation (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Result
2402 MHz	1.002	0.936	0.894	Complies
2441 MHz	1.002	0.936	0.888	Complies
2480 MHz	1.002	0.936	0.888	Complies


Ch. Separation Limits: >20dB bandwidth

 SPORTON International Inc.
 Page No. : 15 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008


 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

20 dB Bandwidth Plot on Channel 0 / 2402 MHz



Date: 31.JAN.2008 09:51:46

20 dB Bandwidth Plot on Channel 39 / 2441 MHz




Date: 31.JAN.2008 09:52:56

 SPORTON International Inc.
 Page No. : 16 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008


 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

20 dB Bandwidth Plot on Channel 78 / 2480 MHz



Date: 31.JAN.2008 09:54:43

Channel Separation Plot on Channel 0~1 / 2402 MHz ~ 2403 MHz




Date: 31.JAN.2008 10:15:40

 SPORTON International Inc.
 Page No. : 17 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008


 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

Channel Separation Plot on Channel 39~40 / 2441 MHz ~ 2442 MHz



Date: 31.JAN.2008 10:16:36

Channel Separation Plot on Channel 77~78 / 2479 MHz ~ 2480 MHz



Date: 31.JAN.2008 10:17:16

 SPORTON International Inc.
 Page No.
 : 18 of 47

 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

3.4. Number of Hopping Frequency Measurement

3.4.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.

3.4.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.4.3. Test Procedures

- 1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- 2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were utilised.
- 3. Observe frequency hopping in 2400MHz~2483.5MHz, there are at least 75 non-overlapping channels.

3.4.4. Test Setup Layout



 SPORTON International Inc.
 Page No. : 19 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.4.5. Test Deviation

There is no deviation with the original standard.

3.4.6. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

3.4.7. Test Result of Number of Hopping Frequency

Test date	Jan. 31, 2008	Test Site No.	TH01-HY
Temperature	28	Humidity	58%
Test Engineer	Nan	Configurations	GFSK

Modulation	Channel	Frequency	Hopping Ch.	Min. Limit	Test Result
Туре	No.	(MHz)	(Channels)	(Channels)	iest Result
GFSK	0 ~ 78	2402 ~ 2480	79	75	Complies

Number of Hopping Channel Plot on Channel 0~78 / 2402 MHz ~ 2480 MHz



Date: 31.JAN.2008 10:22:47

 SPORTON International Inc.
 Page No. : 20 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.5. Dwell Time Measurement

3.5.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.5.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	0 MHz
RB	1000 kHz
VB	1000 kHz
Detector	Peak
Trace	Single Trigger

3.5.3. Test Procedures


- 1. The transmitter output (antenna port) was connected to the spectrum analyser
- 2. Set RBW of spectrum analyzer to 1000kHz and VBW to 1000kHz.
- 3. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- 4. Sweep Time is more than once pulse time.
- 5. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- 6. Measure the maximum time duration of one single pulse.
- 7. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- 8. Measure the maximum time duration of one single pulse.
- 9. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds
- 10. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
- 11. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds.

 SPORTON International Inc.
 Page No. : 21 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.5.4. Test Setup Layout



3.5.5. Test Deviation

There is no deviation with the original standard.

3.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.5.7. Test Result of Dwell Time

Test date	Jan. 31, 2008	Test Site No.	TH01-HY	
Temperature	28	Humidity	58%	
Test Engineer	Nan	Configurations	DH1, DH3, DH5	


Data Packet	Frequency	Pulse Duration	Dwell Time	Limits	Test Result
Data Facket	Frequency	(ms)	(s)	(s)	rest Result
DH5	2402 MHz	3.1400	0.3349	0.4000	Complies
DH3	2402 MHz	1.9000	0.3040	0.4000	Complies
DH1	2402 MHz	0.6200	0.1984	0.4000	Complies
DH5	2441 MHz	3.0800	0.3285	0.4000	Complies
DH3	2441 MHz	1.8400	0.2944	0.4000	Complies
DH1	2441 MHz	0.6200	0.1984	0.4000	Complies
DH5	2480 MHz	3.0800	0.3285	0.4000	Complies
DH3	2480 MHz	1.8600	0.2976	0.4000	Complies
DH1	2480 MHz	0.6000	0.1920	0.4000	Complies

 SPORTON International Inc.
 Page No. : 22 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008


 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

DH5 Dwell Time Plot on Channel 0 / 2402 MHz



Date: 31.JAN.2008 10:00:39

DH3 Dwell Time Plot on Channel 0 / 2402 MHz




Date: 31.JAN.2008 10:00:04

 SPORTON International Inc.
 Page No.
 : 23 of 47

 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008


 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

DH1 Dwell Time Plot on Channel 0 / 2402 MHz



Date: 31.JAN.2008 09:59:29

DH5 Dwell Time Plot on Channel 39 / 2441 MHz




Date: 31.JAN.2008 10:03:02

 SPORTON International Inc.
 Page No. : 24 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008


 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

DH3 Dwell Time Plot on Channel 39 / 2441 MHz



Date: 31.JAN.2008 10:02:15

DH1 Dwell Time Plot on Channel 39 / 2441 MHz




Date: 31.JAN.2008 10:01:13

 SPORTON International Inc.
 Page No. : 25 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008


 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

DH5 Dwell Time Plot on Channel 78 / 2480 MHz



Date: 31.JAN.2008 10:05:15

DH3 Dwell Time Plot on Channel 78 / 2480 MHz




Date: 31.JAN.2008 10:04:42

 SPORTON International Inc.
 Page No. : 26 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

DH1 Dwell Time Plot on Channel 78 / 2480 MHz



Date: 31.JAN.2008 10:04:10

 SPORTON International Inc.
 Page No. : 27 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.6. Radiated Emissions Measurement

3.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance		
(MHz)	(micorvolts/meter)	(meters)		
0.009~0.490	2400/F(KHz)	300		
0.490~1.705	24000/F(KHz)	30		
1.705~30.0	30	30		
30~88	100	3		
88~216	150	3		
216~960	200	3		
Above 960	500	3		

3.6.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1000KHz / 1000KHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

 SPORTON International Inc.
 Page No.
 : 28 of 47

 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

3.6.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.

- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.


 SPORTON International Inc.
 Page No. : 29 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008


 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.6.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade form 3m to 1m.

Distance extrapolation factor = 20 log (specific distance [3m] / test distance [1m]) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.6.5. Test Deviation

There is no deviation with the original standard.

3.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

 SPORTON International Inc.
 Page No. : 30 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.6.7. Results of Radiated Emissions (9kHz~30MHz)

Test date	Feb. 04, 2008	Test Site No.	03CH03-HY
Temperature	20	Humidity	57%
Test Engineer	Eddie		

Freq.	Level	Over Limit	Limit Line	Remark
(MHz)	(dBuV)	(dB)	(dBuV)	
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

 SPORTON International Inc.
 Page No. : 31 of 47


 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.6.8. Results of Radiated Emissions (30MHz~1GHz)

Test date	Feb. 04, 2008	Test Site No.	03CH03-HY	
Temperature	20	Humidity	57%	
Test Engineer	Eddie Lan	Configurations	Channel 39	

Horizontal




			Over	Limit	Readi	Antenna	Cable	Preamp	
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Remark
	MHz	dBuV/m	фВ	dBuV/m	dBuV	dB/m	dB	dB	-
1	132.820	22.69	-20.81	43.50	35.56	12.10	2.96	27.93	Peak
2	191.990	28.27	-15.23	43.50	43.63	9.29	3.31	27.96	Peak
3	218.180	32.05	-13.95	46.00	47.64	9.20	3.45	28.23	Peak
4	377.260	30.28	-15.72	46.00	39.11	15.70	4.33	28.86	Peak
5	801.150	32.96	-13.04	46.00	36.36	20.75	5.69	29.84	Peak
6	960.230	41.11	-12.89	54.00	43.02	21.24	6.42	29.57	Peak

 SPORTON International Inc.
 Page No. : 32 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

Vertical



	Freq	I Level		A THE ASSESSMENT OF		Antenna Factor dB/m		Factor	
	МН	z dBuV/m			dBuV				
1	132.82	0 24.94	-18.56	43.50	37.81	12.10	2.96	27.93	Peak
2 3	198.78	0 31.60	-11.90	43.50	46.55	9.61	3.54	28.09	Peak
3	237.58	0 24.70	-21.30	46.00	37.97	11.32	3.61	28.20	Peak
4	474.26	0 34.51	-11.49	46.00	41.66	17.74	4.55	29.45	Peak
4 5 @	493.66	0 34.84	-11.16	46.00	41.60	18.05	4.38	29.18	Peak
6	960.23	0 32.48	-21.52	54.00	34.39	21.24	6.42	29.57	Peak

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

 SPORTON International Inc.
 Page No. : 33 of 47


 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.6.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Test date	Feb. 04, 2008	Test Site No.	03CH03-HY
Temperature	20	Humidity	57%
Test Engineer	Eddie Lan	Configurations	Channel 0

Horizontal




	Freq	Level	Over Limit			Antenna Factor			Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	e l
1	4800.000	42.70	-11.30	54.00	40.93	33.02	1.49	32.74	Peak
2 @	7210.000	48.16	-5.84	54.00	41.33	35.70	4.08	32.95	Peak
3 @	9608.000	52.85	-1.15	54.00	42.52	38.31	5.42	33.40	Peak

 SPORTON International Inc.
 Page No. : 34 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

Vertical



			Over	Limit	Readi	Antenna	Cable	Preamp	
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	-
10	4808.000	43.24	-10.76	54.00	41.58	33.02	1.38	32.74	Peak
2 @	7206.000	48.16	-5.84	54.00	41.32	35.70	4.08	32.94	Peak
3 @	9604.000	52.62	-1.38	54.00	42.29	38.31	5.42	33.40	Peak


 SPORTON International Inc.
 Page No. : 35 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

Test date	Feb. 04, 2008	Test Site No.	03CH03-HY
Temperature	20	Humidity	57%
Test Engineer	Eddie Lan	Configurations	Channel 39

Horizontal




Freq	Level							Remark
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	=
4882.000	42.61	-11.39	54.00	41.01	33.16	1.17	32.73	Peak
7319.000	48.73	-5.27	54.00	41.45	35.99	4.26	32.97	Peak
9768.000	52.34	-1.66	54.00	41.47	38.65	5.62	33.40	PEAK
	MHz 4882.000 7319.000	MHz dBuV/m 4882.000 42.61 7319.000 48.73	Freq Level Limit MHz dBuV/m dB 4882.000 42.61 -11.39 7319.000 48.73 -5.27	### Hevel Limit Line MHz dBuV/m dB dBuV/m	### Freq Level Limit Line Level MHz dBuV/m dB dBuV/m dBuV	### Freq Level Limit Line Level Factor MHz dBuV/m dB dBuV/m dBuV dB/m	Freq Level Limit Line Level Factor Loss MHz dBuV/m dB dBuV/m dBuV dB/m dB 4882.000 42.61 -11.39 54.00 41.01 33.16 1.17 7319.000 48.73 -5.27 54.00 41.45 35.99 4.26	4882.000 42.61 -11.39 54.00 41.01 33.16 1.17 32.73

 SPORTON International Inc.
 Page No. : 36 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

Vertical



			Over	Limit	Readi	Antenna	Cable	Preamp	
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	-
1 @	4886.000	43.25	-10.75	54.00	41.61	33.19	1.17	32.73	Peak
2 @	7324.000	48.07	-5.93	54.00	40.79	35.99	4.26	32.97	Peak
3 @	9764.000	51.63	-2.37	54.00	40.75	38.65	5.62	33.40	Peak


 SPORTON International Inc.
 Page No. : 37 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

Test date	Feb. 04, 2008	Test Site No.	03CH03-HY
Temperature	20	Humidity	57%
Test Engineer	Eddie Lan	Configurations	Channel 78

Horizontal




		Freq	Level	Over Limit			Antenna Factor			Remark
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	e	4960.000	43.53	-10.47	54.00	41.95	33.33	0.96	32.71	Peak
2	e	7440.000	49.25	-4.75	54.00	41.52	36.28	4.44	32.99	Peak
3	e	9916.000	52.93	-1.07	54.00	41.58	38.93	5.82	33.40	Peak

 SPORTON International Inc.
 Page No. : 38 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX





		Freq	Level	Over Limit	Limit Line		Antenna Factor			Remark
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	e	4960.000	43.10	-10.90	54.00	41.52	33.33	0.96	32.71	Peak
2	e	7440.000	48.86	-5.14	54.00	41.14	36.28	4.44	32.99	Peak
3	0	9924.000	52.98	-1.02	54.00	41.59	38.96	5.82	33.40	Peak

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

 SPORTON International Inc.
 Page No. : 39 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.7. Band Edge Emissions Measurement

3.7.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.7.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

3.7.3. Test Procedures

- 1. The test procedure is the same as section 3.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
- 2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

3.7.4. Test Setup Layout

This test setup layout is the same as that shown in section 3.6.4.

3.7.5. Test Deviation

There is no deviation with the original standard.

3.7.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

 SPORTON International Inc.
 Page No.
 : 40 of 47

 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

3.7.7. Test Result of Band Edge Emissions

Test date	Feb. 04, 2008	Test Site No.	03CH03-HY
Temperature	20	Humidity	57%
Test Engineer	Eddie Lan	Configurations	Channel 0, 78

Channel 0

		Freq	Level	Over Limit		ReadAntenna Level Factor			Preamp Factor	Remark
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	O <u>-</u>
1		2311.140	55.43	-18.57	74.00	25.12	28.12	2.19	0.00	Peak
2	a	2401 770	80 87			50 35	28 29	2 23	0 00	Peak
1	0	2390.000	43.07	-10.93	54.00	12.55	28.29	2.23	0.00	Average
2	0	2401.770	65.45			34.93	28.29	2.23	0.00	Average

Item 2 is the fundamental frequency Ch00 2402MHz.

Channel 78

		Level	Over Limit		ReadAntenna		Cable	Preamp	
	Freq				Level	Factor	Loss	Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dВ	dB	2
1 @	2480.050	82.33			51.59	28.47	2.27	0.00	Peak
2	2483.500	55.26	-18.74	74.00	24.52	28.47	2.27	0.00	Peak
10	2480.050	66.72			35.98	28.47	2.27	0.00	Average
2 @	2483.500	44.60	-9.40	54.00	13.86	28.47	2.27	0.00	Average

Item 1 is the fundamental frequency Ch78 2480MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


 SPORTON International Inc.
 Page No. : 41 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX


For Emission not in Restricted Band

Low Band Edge Plot on Channel 0 / 2402 MHz



Date: 31.JAN.2008 09:56:30

High Band Edge Plot on Channel 78 / 2480 MHz



Date: 31.JAN.2008 09:57:33

 SPORTON International Inc.
 Page No. : 42 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

3.8. Antenna Requirements

3.8.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

3.8.2. Antenna Connector Construction

Please refer to section 2.3 in this test report, antenna connector complied with the requirements.

 SPORTON International Inc.
 Page No. : 43 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

4. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100359	9kHz – 2.75GHz	Mar. 01, 2007	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2007	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2007	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2007	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz –30MHz	May 09, 2007	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
Isolation Transformer	Erika Fiedler OHG	D-65396 Walluf	58	45MHz-2.15GHz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2007	Radiation (03CH03-HY)
	COLLAFENED	COA0224A	10667		lon 14 2000	Radiation
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan 14 2008	(03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jun. 07, 2007	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100305	9 kHz - 40 GHz	Sep. 27, 2007	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 21, 2007	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 04, 2007	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.18.2008	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Dec. 17, 2007	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 27, 2007	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 03, 2007	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2007	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2007	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2007	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 14, 2007	Conducted (TH01-HY)

 SPORTON International Inc.
 Page No. : 44 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 07, 2007	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 04, 2007*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

 SPORTON International Inc.
 Page No. : 45 of 47

 TEL: 886-2-2696-2468
 Issued Date : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID : VIL-21MAX

5. TEST LOCATION

 SPORTON International Inc.
 Page No.
 : 46 of 47

 TEL: 886-2-2696-2468
 Issued Date
 : Feb. 28, 2008

 FAX: 886-2-2696-2255
 FCC ID
 : VIL-21MAX

6. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-070110

財團法人全國認證基金會 Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.

EMC & Wireless Communications Laboratory

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria

: ISO/IEC 17025:2005

Accreditation Number

: 1190

Originally Accredited

December 15, 2003

Effective Period

January 10, 2007 to January 09, 2010

Accredited Scope

: Testing Field, see described in the Appendix

Accreditation Program for Designated Testing Laboratory

Specific Accreditation

Program

for Commodities Inspection

Accreditation Program for Telecommunication Equipment

Testing Laboratory

President, Taiwan Accreditation Foundation

Date ! January 10, 2007

P1, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix,

SPORTON International Inc. Page No. : 47 of 47 TEL: 886-2-2696-2468 Issued Date : Feb. 28, 2008 FAX: 886-2-2696-2255 FCC ID : VIL-21MAX



Annex Declaration for Bluetooth Device acc to Part 15.247



1 Output power and channel separation of a Bluetooth device in the different operating modes:

The different operating modes (data-mode, acquisition-mode) of a Bluetooth device has no influence on the output power and the channel spacing. There is only one transmitter which is driven by identical input parameters concerning these two parameters.

Only a different hopping sequence will be used. For this reason the check of these RF parameters in one op-mode is sufficient.

2 Frequency range of a Bluetooth device:

Hereby we declare that the maximum frequency of this device is: 2402 – 2480 MHz. This is according to the Bluetooth Core Specification (+ critical errata) for devices which will be operated in the USA.

This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/04-E). Other frequency ranges (e.g. for Spain, France, Japan) which are allowed according the Core Specification are not supported by this device.

3 Co-ordination of the hopping sequence in data mode to avoid simultaneous occupancy by multiple transmitters:

Bluetooth units which want to communicate with other units must be organised in a structure called piconet. This piconet consist of max. 8 Bluetooth units. One unit is the master the other seven are the slaves. The master co-ordinates frequency occupation in this piconet for all units. As the master hop sequence is derived from its BD address which is unique for each Bluetooth device, additional masters intending to establish new piconets will always use different hop sequences.

4 Example of a hopping sequence in data mode:

Example of a 79 hopping sequence in data mode: 40, 21, 44, 23, 42, 53, 46, 55, 48, 33, 52, 35, 50, 65, 54, 67, 56, 37, 60, 39, 58, 69, 62, 71, 64, 25, 68, 27, 66, 57, 70, 59, 72, 29, 76, 31, 74, 61, 78, 63, 01, 41, 05, 43, 03, 73, 07, 75, 09, 45, 13, 47, 11, 77, 15, 00, 64, 49, 66, 53, 68, 02, 70, 06, 01, 51, 03, 55, 05, 04



5 Equally average use of frequencies in data mode and behaviour for short transmissions:

The generation of the hopping sequence in connection mode depends essentially on two input values:

- 1. LAP/UAP of the master of the connection
- 2. Internal master clock

The LAP (lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24 MSB's of the 48 BD_ADDRESS.

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For synchronisation with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5 μ s. The clock has a cycle of about one day (23h30). In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire

LAP (24 bits), 4 LSB's (4 bits) (Input 1) and the 27 MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR- operations) are performed to generate the sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behaviour: The first connection between the two devices is established, a hopping sequence was generated. For transmitting the wanted data the complete hopping sequence was not used. The connection ended.

The second connection will be established. A new hopping sequence is generated. Due to the fact that the Bluetooth clock has a different value, because the period between the two transmission is longer (and it cannot be shorter) than the minimum resolution of the clock (312.5 μ s). The hopping sequence will always differ from the first one.

6 Receiver input bandwidth and behaviour for repeated single or multiple packets:

The input bandwidth of the receiver is 1 MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence (see chapter 5). The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master.

Additionally the type of connection (e.g. single or multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.



7 Dwell time in data mode

The dwell time of 0.3797s within a 30 second period in data mode is independent from the packet type (packet length). The calculation for a 30 second period is a follows:

Dwell time = time slot length * hop rate / number of hopping channels *30s

Example for a DH1 packet (with a maximum length of one time slot) Dwell time = $625 \mu s$ * 1600 1/s / 79 * 30s = 0.3797s (in a 30s period)

For multislot packet the hopping is reduced according to the length of the packet. Example for a DH5 packet (with a maximum length of five time slots)

Dwell time = $5 * 625 \mu s$ * 1600 * 1/5 * 1/s / 79 * 30s = 0.3797s (in a 30s period). This is according the Bluetooth Core Specification V 1.0B (+ critical errata) for all Bluetooth devices. Therefor all Bluetooth devices **comply** with the FCC dwell time requirement in data mode. This was checked during the Bluetooth Qualification tests. The Dwell time in hybrid mode is measured and stated in the test report.

8 Channel Separation in hybrid mode

The nominal channel spacing of the Bluetooth system is 1Mhz independent of the operating mode.

The maximum "initial carrier frequency tolerance" which is allowed for Bluetooth is fcenter = 75 kHz.

This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/07-E) for three frequencies (2402, 2441, 2480 MHz).

Additionally an example for the channel separation is given in the test report

9 Derivation and examples for a hopping sequence in hybrid mode

For the generation of the inquiry and page hop sequences the same procedures as described for the data mode are used (see chapter 5), but this time with different input vectors:

- For the inquiry hop sequence, a predefined fixed address is always used. This results in the same 32 frequencies used by all devices doing an inquiry but every time with a different start frequency and phase in this sequence.
- For the page hop sequence, the device address of the paged unit is used as input vector. This results in the use of a subset of 32 frequencies which is specific for that initial state of the connection establishment between the two units. A page to different devices would result in a different subset of 32 frequencies.

So it is ensured that also in hybrid mode the frequency use equally averaged.

Example of a hopping sequence in inquiry mode: 48, 50, 09, 13, 52, 54,41, 45, 56, 58, 11, 15, 60, 62, 43, 47, 00, 02, 64, 68, 04, 06, 17, 21, 08, 10, 66, 70, 12, 14, 19, 23



Example of a hopping sequence in paging mode: 08, 57, 68, 70, 51, 02, 42, 40, 04, 61, 44, 46, 63, 14, 50, 48, 16, 65, 52, 54, 67, 18, 58, 56, 20, 53, 60, 62, 55, 06, 66, 64

10 Receiver input bandwidth and synchronisation in hybrid mode:

The receiver input bandwidth is the same as in the data mode (1 MHz). When two Bluetooth devices establish contact for the first time, one device sends an inquiry access code, the other device is scanning for this inquiry access code. If two devices have been connected previously and want to start a new transmission, a similar procedure takes place. The only difference is, instead of the inquiry access code, an special access code, derived from the BD_ADDRESS of the paged device will be, will be sent by the master of this connection.

Due to the fact that both units have been connected before (in the inquiry procedure) the paging unit has timing and frequency information about the page scan of the paged unit. For this reason the time to establish the connection is reduced considerable.

11 Spread rate / data rate of the direct sequence signal

The Spread rate / Data rate in inquiry and paging mode can be defined via the access code. The access code is the only criterion for the system to check if there is a valid transmission or not. If you regard the presence of a valid access code as one bit of information, and compare it with the length of the access code of 68 bits, the Spread rate

/ Data rate will be 68/1.

12 Spurious emission in hybrid mode

The dwell time in hybrid mode is shorter than in data mode. For this reason the spurious emissions average level in data mode is worst case. The spurious emissions peak level is the same for both modes.

13 Peak power spectral density measurement

Since the transmitter is only active for some milliseconds on one channel you would get a result with many interruptions if using a sweep time of e.g. 1s as stated in the FCC rules. Therefore a fast sweep in maxhold function is used instead and the EUT is activated several times until the measurement curve has stabilized.