

RF Exposure Exemption Report

Safran Electronics & Defence Beacons SAS
Model: ULTIMA-DT-05

In accordance with FCC CFR 47 Pt 1.1307

Prepared for: Safran Electronics & Defense Beacon SAS
4 Rue Pierre Fauchard
ZI Des Cinq Chemins
CS 10028
Le Hirgoat
Guidel
56520
France



Add value.
Inspire trust.

COMMERCIAL-IN-CONFIDENCE

FCC ID: VIQ-ULTIMADT

Document 75958513-03 Issue: 01

SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Matthew Russell	Chief Engineer	Authorised Signatory	20 June 2023

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

FCC Accreditation
90987 Octagon House, Fareham Test Laboratory

EXECUTIVE SUMMARY

The wireless devices described within this report are compliant with the exemption criteria related to human exposure to electromagnetic fields laid out in FCC CFR Title 47 Part 1.1307.



DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2023 TÜV SÜD. This report relates only to the actual item/items tested.

ACCREDITATION

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

TÜV SÜD
is a trading name of TÜV SÜD Ltd
Registered in Scotland at East Kilbride,
Glasgow G75 0QF, United Kingdom
Registered number: SC215164

TÜV SÜD Ltd is a
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100
Fax: +44 (0) 1489 558101
www.tuvsud.com/en

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire PO15 5RL
United Kingdom



Contents

- 1 Report Summary2**
- 1.1 Report Modification Record.....2
- 1.2 Introduction.....2
- 1.3 Brief Summary of Results3
- 1.4 Product Information4
- 2 Assessment Details5**
- 2.1 Single RF Source options for determination of exemption.....5
- 2.2 Multiple RF Sources options for determination of exemption.6
- 2.3 Individual Antenna Port Exposure Results.....7



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	20-June-2023

Table 1

1.2 Introduction

Applicant	Safran Electronics & Defence Beacons SAS
Manufacturer	Safran Electronics & Defence Beacons SAS
Model Number(s)	ULTIMA-DT-05
Hardware Version(s)	S1865601-01
Software Version(s)	YLS1820A
Specification/Issue/Date	FCC 47 CFR Part 1.1307: 2021
Order Number	55317
Date	02 May 2023
Related Document(s)	• KDB 447498 D04 v01



1.3 Brief Summary of Results

The wireless devices described within this report are compliant with the exemption criteria related to human exposure to electromagnetic fields laid out in FCC CFR Title 47 Part 1.1307.

The calculations shown in this report were made in accordance with the procedures specified in the applied test specification(s).



1.4 Product Information

1.4.1 Technical Description

Emergency locator beacon with automatic distress tracking functionality.

1.4.2 Transmitter Description

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	Frequency Band (MHz)	Minimum Frequency (MHz)	Output Power (dBm)	Duty Cycle (%)
406 MHz	403.5 – 408.5	403.5	39	9.4
121.5 MHz	120.6 – 122.4	120.6	26	37

Table 2 – Transmitter Description

Note: Transmitter power includes upper bounds of uncertainty therefore maximum values are used.

1.4.3 Antenna Description

The following antennas are supported by the equipment under test.

Radio Access Technology	Antenna Model	Gain (dBi)	Antenna length (cm)	Minimum Separation Distance (cm)
406 MHz	Dayton Granger Tri-frequency Antenna (406/121.5/GNSS) - ELT10-903	6	20.9	100
121.5 MHz	Dayton Granger Tri-frequency Antenna (406/121.5/GNSS) - ELT10-903	-2.5	20.9	100

Table 3 – Antenna description

In the case of more than one type of antenna being supported by the equipment, the calculation is based on the maximum of the antenna gains. If other antennas can be used that have greater gains, the minimum separation distances will need to be recalculated.

Note: Antenna gain includes upper bounds of uncertainty therefore maximum values are used.

1.4.4 Equipment Configuration

No simultaneous transmission is supported



2 Assessment Details

2.1 Single RF Source options for determination of exemption.

Option	Reference	RF Exposure Test Exemptions for Single Source												
A (1-mW Test Exemption)	FCC 1.1307(b)(3)(i)(A)	The available maximum time averaged power is no more than 1 mW, regardless of separation distance.												
B (SAR-Based Exemption)	FCC 1.1307(b)(3)(i)(B)	The available maximum timeaveraged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by: $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ Where $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ and $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ <i>d</i> = the separation distance (cm);												
C (MPE-Based Exemption)	FCC 1.1307(b)(3)(i)(C)	Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least λ/2π, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of λ/4 or if the antenna gain is less than that of a half-wave dipole (1.64 linear value). TABLE 1 TO § 1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION <table><tr><th>RF Source frequency (MHz)</th><th>Threshold ERP (watts)</th></tr><tr><td>0.3–1.34</td><td>1,920 R².</td></tr><tr><td>1.34–30</td><td>3,450 R²/f².</td></tr><tr><td>30–300</td><td>3.83 R².</td></tr><tr><td>300–1,500</td><td>0.0128 R²f.</td></tr><tr><td>1,500–100,000</td><td>19.2R².</td></tr></table>	RF Source frequency (MHz)	Threshold ERP (watts)	0.3–1.34	1,920 R ² .	1.34–30	3,450 R ² /f ² .	30–300	3.83 R ² .	300–1,500	0.0128 R ² f.	1,500–100,000	19.2R ² .
RF Source frequency (MHz)	Threshold ERP (watts)													
0.3–1.34	1,920 R ² .													
1.34–30	3,450 R ² /f ² .													
30–300	3.83 R ² .													
300–1,500	0.0128 R ² f.													
1,500–100,000	19.2R ² .													



2.2 Multiple RF Sources options for determination of exemption.

Option	Reference	
A 1-mW Test Exemption for Multiple Sources	FCC 1.1307(b)(3)(ii)(A)	The available maximum time averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).
B Simultaneous Transmission with both SAR-based and MPE- Based Test Exemptions	FCC 1.1307(b)(3)(ii)(B)	in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation. $\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$



2.3 Individual Antenna Port Exposure Results

2.3.1 Single Source Calculation of Exposure at Specified Separation Distance FCC 1.1307(b)(3)(i)(C) 'Option C' (MPE Based Exemption)

RAT	Frequency (MHz)	Conducted Power Output (mW)	Duty Cycle %	Time Average Conducted Power Output (mW)	Antenna Gain Ratio	Maximum Power (EIRP) mW	Maximum Power (ERP) mW	Minimum separation distance for MPE evaluation $\lambda/2 \pi$ mm	Actual Distance (mm)	Threshold ERP (mW)	1.1307(b)(3)(i)(C) Exemption (Yes/No) (300 kHz to 100 GHz)
406 MHz	403.5	7943.28	9.4	746.668	3.981	2972.487	1812.49	118.3	1000	5165	Yes
121.5 MHz	120.6	398.11	37	147.301	0.562	82.827	50.50	395.9	1000	3830	Yes

Table 4 –Transmitter Result

The calculations show that the individual transmitters comply with FCC 1.1307(b)(3)(i)(C) MPE-based exception at a minimum distance of 100 cm.