



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15C TEST REPORT

For

Voxx Accessories Corp.

3502 Woodview Trace, suite 220, Indianapolis, Indiana 46268 United States

FCC ID: VIXRCQ500

Report Type: Original Report	Product Type: Wireless charging alarm clock
Test Engineer:	Winnie Yang <i>Winnie Yang</i>
Report Number:	RXM200527050-00B
Report Date:	2020-06-11
Reviewed By:	Oscar Ye EMC Manager <i>Oscar Ye</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
FCC §1.1310 & §2.1091–MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	9
APPLICABLE STANDARD	9
EUT SETUP	10
RESULT	10
TEST DATA	11
FCC §15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
FACTOR & OVER LIMIT CALCULATION.....	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC §15.209 & §15.205 - SPURIOUS EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST RESULTS SUMMARY	18
TEST DATA	18

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Voxx Accessories Corp.
Tested Model	RCQ500
Series Model	S718, S5014, S7012
Model Difference	Model names
Product Type	Wireless charging alarm clock
Power Supply	DC 5.0V charging by adapter
RF Function	WPT
Operating Band/Frequency	110-205 kHz
Modulation Type	ASK
Antenna Type	Loop antenna
Antenna Gain	0 dBi

Adapter Information:

Model: HX12H-0502000-AU-001

Input: AC100-240 V 50/60Hz 0.5A Max

Output: 5.0V, 2.0A

**All measurement and test data in this report was gathered from production sample serial number: 20200527050.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2020-05-27)*

Objective

This report is prepared on behalf of *Voxx Accessories Corp.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communications Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207 and 15.209 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
Radiated emission	9kHz~30MHz	3.19dB
	30MHz~1GHz	6.11dB
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user)

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

No Exercise Software was used.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Apple	Mobile phone	ML7J2CH/A	F4HR2B0TGRYD

External I/O Cable


Cable Description	Length (m)	From Port	To
Power Cable	1.0	Adapter	AC Source

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions (Below & Above 30MHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 & §1.1310&§2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209	Spurious Emissions	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test receiver	ESCI	100195	2019-12-14	2020-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	PASSIVE LOOP	6512	108100	2019-04-25	2022-04-24
Sonoma Instrument	Pre-amplifier	310N	185700	2019-08-14	2020-08-13
Rohde & Schwarz	Auto Test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2019-07-11	2020-07-10
Rohde & Schwarz	LISN	ENV216	3560655016	2019-11-30	2020-11-29
Audix	Test Software	e3	V9	/	/
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2019-08-10	2020-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14
RF Exposure					
Narda	E-Field Tester	NARD-EA5091	/	2019-11-19	2021-11-18
Narda	B Field Meter	NBM-550	B-1130	2019-11-19	2021-11-18
ETS-LINDGREN	Isotropic Electric Field Probe	HI-6005	00200234	2018-05-22	2021-05-21

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091–MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

FCC & 1.1310& §2.1091

According to the item 5.2 of KDB 680106 D01 RF Exposure Wireless Charging Apps v03: Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF evaluation.


- a) Power transfer frequency is less than 1 MHz.
- b) Output power from each primary coil is less than or equal to 15 watts.
- c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
- d) Client device is placed directly in contact with the transmitter.
- e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
- f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Limits for Maximum Permissible Exposure (MPE)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

EUT Setup



Result

a) Power transfer frequency is less than 1 MHz.

Yes, the device operates in the frequency 110 kHz-205 kHz.

b) Output power from each primary coil is less than or equal to 15 watts.

Yes, the maximum output power of the primary coil is $10W < 15W$.

c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils..

Yes, the transfer system including a charging system with only single primary coils is to detect and allow only between individual of coils.

d) Client device is inserted in or placed directly in contact with the transmitter.

Yes, client device is placed directly in contact with the transmitter.

e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

Yes, this is a mobile device.

f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

The EUT H-field Strength levels at 15cm surrounding the device and 20 cm above the top surface are less than 50% the MPE limit.

Test Data**Environmental Conditions**

Temperature:	24.3 °C
Relative Humidity:	49 %
ATM Pressure:	101.2 kPa

The testing was performed by Winnie Yang on 2020-06-05.

H-Filed Strength

Frequency Range (kHz)	Position A (A/m)	Position B (A/m)	Position C (A/m)	Position D (A/m)	Position E (A/m)	Limit Test (A/m)	50%Limit (A/m)
110-205	0.056	0.087	0.072	0.069	0.216	1.63	0.815

E-Filed Strength

Frequency Range (kHz)	Position A (V/m)	Position B (V/m)	Position C (V/m)	Position D (V/m)	Position E (V/m)	Limit Test (V/m)	50%Limit (V/m)
110-205	1.727	1.685	1.614	1.796	1.801	614	307

Note:

1. According with KDB 680106 D01 RF Exposure Wireless Charging Apps v03, Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614V/m and 1.63 A/m.

2: The distance for position A, B, C, D are 15cm, the distance for position E is 20cm.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Antenna Connector Construction

The EUT has a Loop antenna and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 30 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The Corrected Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of 7dB means the emission is 7 dB above the limit. The equation for over limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Winnie Yang on 2020-06-02.

EUT operation mode: charging and communication

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.155	9.40	19.82	29.22	55.74	-26.52	Average
2	0.155	24.00	19.82	43.82	65.74	-21.92	QP
3	0.589	10.00	19.75	29.75	46.00	-16.25	Average
4	0.589	17.60	19.75	37.35	56.00	-18.65	QP
5	0.857	3.01	19.71	22.72	46.00	-23.28	Average
6	0.857	11.21	19.71	30.92	56.00	-25.08	QP
7	1.255	3.40	19.82	23.22	46.00	-22.78	Average
8	1.255	11.40	19.82	31.22	56.00	-24.78	QP
9	2.358	1.31	19.56	20.87	46.00	-25.13	Average
10	2.358	9.31	19.56	28.87	56.00	-27.13	QP
11	19.950	6.99	19.96	26.95	50.00	-23.05	Average
12	19.950	18.09	19.96	38.05	60.00	-21.95	QP

AC 120V/60 Hz, Neutral

	Freq	Read		Limit	Over	
	MHz	Level	Factor	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.153	7.00	19.82	26.82	55.82	-29.00 Average
2	0.153	20.70	19.82	40.52	65.82	-25.30 QP
3	0.576	2.10	19.75	21.85	46.00	-24.15 Average
4	0.576	14.90	19.75	34.65	56.00	-21.35 QP
5	1.043	4.10	19.82	23.92	46.00	-22.08 Average
6	1.043	14.30	19.82	34.12	56.00	-21.88 QP
7	2.321	1.10	19.59	20.69	46.00	-25.31 Average
8	2.321	9.50	19.59	29.09	56.00	-26.91 QP
9	4.549	2.09	19.49	21.58	46.00	-24.42 Average
10	4.549	11.69	19.49	31.18	56.00	-24.82 QP
11	20.162	6.30	19.95	26.25	50.00	-23.75 Average
12	20.162	16.30	19.95	36.25	60.00	-23.75 QP

Note:


- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

FCC §15.209 & §15.205 - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.209; §15.205;

EUT Setup



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.

EMI Test Receiver Setup

The system was investigated from 9 kHz to 1 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
9 kHz – 150 kHz	200 Hz	1 kHz	QP/Average
150 kHz – 30MHz	9kHz	30kHz	QP/Average
30 MHz – 1000 MHz	120 kHz	300 kHz	QP

Note: For the frequency bands 9-90 kHz and 110-490 kHz, the test was based on average detector.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V/m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205 and 15.209.


Test Data

Environmental Conditions


Temperature:	25.1 °C
Relative Humidity:	52 %
ATM Pressure:	101.3 kPa

The testing was performed by Winnie Yang on 2020-06-03.

EUT operation mode: charging and communication

9 kHz-30 MHz:*(Pre-scan in the X,Y and Z axes of orientation, the worst case in Z-axis of orientation was recorded)***9kHz-150kHz (PK)**

Date: 3.JUN.2020 14:58:07

150kHz-30MHz (PK)

Date: 3.JUN.2020 15:01:15

9 kHz-490 kHz:

Indicated		PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.209		
Frequency (kHz)	Corrected Amplitude (dB μ V/m) @3m			Limit (dB μ V/m) @3m	Limit (dB μ V/m) @300m	Margin (dB)
15.10096	55.15	PK	53.12	124.03	44.03	68.88
61.87500	57.34	PK	43.95	111.77	31.77	54.43
119.26923	93.99	PK	50.47	106.24	26.24	12.25
136.21635	69.90	PK	50.71	104.92	24.92	35.02
341.34615	70.52	PK	27.46	96.94	16.94	26.42


490 kHz-30 MHz:

Indicated		PK/QP/Ave.	Corrected Factor (dB/m)	FCC Part 15.209		
Frequency (kHz)	Corrected Amplitude (dB μ V/m) @3m			Limit (dB μ V/m) @3m	Limit (dB μ V/m) @300m	Margin (dB)
580.52885	61.03	PK	22.09	72.33	32.33	11.30
819.71153	54.72	PK	19.36	69.33	29.33	14.61
3976.92308	40.43	PK	18.82	69.54	29.54	29.11

Note: The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.

Note:

- 1) Factor (dB) = Antenna Factor (dB/m) + Cable Loss (dB) + Amplifier Gain (dB)
- 2) Over Limit (dB) = Read level (dB μ V) + Factor (dB) - Limit (dB μ V)

30MHz-1GHz

Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
43.76	38.25	100	V	141	-13.3	40.00	1.75
48.81	32.78	100	V	330	-16.7	40.00	7.22
59.50	39.02	100	V	162	-17.9	40.00	0.98
117.61	29.46	100	V	202	-11.6	43.50	14.04
131.96	31.15	100	V	245	-11.7	43.50	12.35
214.82	27.47	200	V	172	-12.3	43.50	16.03

***** END OF REPORT *****