

FCC Test Report

Report No.: RF161103C32

FCC ID: VIYHRM1016

Test Model: HRM1016

Received Date: Nov. 03, 2016

Test Date: Nov. 09 ~ Nov. 15, 2016

Issued Date: Nov. 29, 2016

Applicant: Hosiden Corporation

Address: 4-33, Kitakyuhoji 1-chome, Yao-City, Osaka 581-0071 Japan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

| | |
|--|----|
| Release Control Record | 4 |
| 1 Certificate of Conformity | 5 |
| 2 Summary of Test Results | 6 |
| 2.1 Measurement Uncertainty | 6 |
| 2.2 Modification Record | 6 |
| 3 General Information | 7 |
| 3.1 General Description of EUT | 7 |
| 3.2 Description of Test Modes | 7 |
| 3.2.1 Test Mode Applicability and Tested Channel Detail..... | 8 |
| 3.3 Description of Support Units | 10 |
| 3.3.1 Configuration of System under Test | 10 |
| 3.4 General Description of Applied Standards | 10 |
| 4 Test Types and Results | 11 |
| 4.1 Radiated Emission and Bandedge Measurement..... | 11 |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement | 11 |
| 4.1.2 Test Instruments | 12 |
| 4.1.3 Test Procedures..... | 13 |
| 4.1.4 Deviation from Test Standard | 13 |
| 4.1.5 Test Set Up | 14 |
| 4.1.6 EUT Operating Conditions..... | 15 |
| 4.1.7 Test Results | 16 |
| 4.2 Conducted Emission Measurement..... | 23 |
| 4.2.1 Limits of Conducted Emission Measurement | 23 |
| 4.2.2 Test Instruments | 23 |
| 4.2.3 Test Procedures..... | 24 |
| 4.2.4 Deviation from Test Standard | 24 |
| 4.2.5 Test Setup..... | 24 |
| 4.2.6 EUT Operating Conditions..... | 24 |
| 4.2.7 Test Results | 25 |
| 4.3 Number of Hopping Frequency Used | 27 |
| 4.3.1 Limits of Hopping Frequency Used Measurement | 27 |
| 4.3.2 Test Setup..... | 27 |
| 4.3.3 Test Instruments | 27 |
| 4.3.4 Test Procedure | 27 |
| 4.3.5 Deviation from Test Standard | 27 |
| 4.3.6 Test Results | 27 |
| 4.4 Dwell Time on Each Channel | 29 |
| 4.4.1 Limits of Dwell Time on Each Channel Measurement..... | 29 |
| 4.4.2 Test Setup..... | 29 |
| 4.4.3 Test Instruments | 29 |
| 4.4.4 Test Procedures..... | 29 |
| 4.4.5 Deviation from Test Standard | 29 |
| 4.4.6 Test Results | 30 |
| 4.5 Channel Bandwidth | 32 |
| 4.5.1 Limits of Channel Bandwidth Measurement..... | 32 |
| 4.5.2 Test Setup..... | 32 |
| 4.5.3 Test Instruments | 32 |
| 4.5.4 Test Procedure | 32 |
| 4.5.5 Deviation from Test Standard | 32 |
| 4.5.6 EUT Operating Condition | 32 |
| 4.5.7 Test Results | 33 |
| 4.6 Hopping Channel Separation | 34 |
| 4.6.1 Limits of Hopping Channel Separation Measurement..... | 34 |

| | |
|---|-----------|
| 4.6.2 Test Setup..... | 34 |
| 4.6.3 Test Instruments | 34 |
| 4.6.4 Test Procedure | 34 |
| 4.6.5 Deviation from Test Standard | 34 |
| 4.6.6 Test Results | 35 |
| 4.7 Maximum Output Power..... | 36 |
| 4.7.1 Limits of Maximum Output Power Measurement | 36 |
| 4.7.2 Test Setup..... | 36 |
| 4.7.3 Test Instruments | 36 |
| 4.7.4 Test Procedure | 36 |
| 4.7.5 Deviation from Test Standard | 36 |
| 4.7.6 EUT Operating Condition | 36 |
| 4.7.7 Test Results | 37 |
| 4.8 Conducted Out of Band Emission Measurement..... | 38 |
| 4.8.1 Limits Of Conducted Out Of Band Emission Measurement..... | 38 |
| 4.8.2 Test Instruments | 38 |
| 4.8.3 Test Procedure | 38 |
| 4.8.4 Deviation from Test Standard | 38 |
| 4.8.5 EUT Operating Condition | 38 |
| 4.8.6 Test Results | 38 |
| 5 Pictures of Test Arrangements..... | 41 |
| Appendix – Information on the Testing Laboratories | 42 |

Release Control Record

| Issue No. | Description | Date Issued |
|-------------|-------------------|---------------|
| RF161103C32 | Original release. | Nov. 29, 2016 |

1 Certificate of Conformity

Product: Bluetooth Module

Brand: Hosiden

Test Model: HRM1016

Sample Status: Engineering sample

Applicant: Hosiden Corporation

Test Date: Nov. 09 ~ Nov. 15, 2016

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , **Date:** Nov. 29, 2016
Polly Chien / Specialist

Approved by : , **Date:** Nov. 29, 2016
Ken Liu / Senior Manager

2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.247) | | | |
|--|---|--------|--|
| FCC Clause | Test Item | Result | Remarks |
| 15.207 | AC Power Conducted Emission | Pass | Meet the requirement of limit. Minimum passing margin is -14.81dB at 0.47813 MHz. |
| 15.247(a)(1) (iii) | Number of Hopping Frequency Used | Pass | Meet the requirement of limit. |
| 15.247(a)(1) (iii) | Dwell Time on Each Channel | Pass | Meet the requirement of limit. |
| 15.247(a)(1) | 1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System | Pass | Meet the requirement of limit. |
| 15.247(b) | Maximum Peak Output Power | Pass | Meet the requirement of limit. |
| 15.205 / 15.209 / 15.247(d) | Radiated Emissions and Band Edge Measurement | Pass | Meet the requirement of limit. Minimum passing margin is -3.0dB at 76.56MHz. |
| 15.247(d) | Antenna Port Emission | Pass | Meet the requirement of limit. |
| 15.203 | Antenna Requirement | Pass | No antenna connector is used. |

Note: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement | Frequency | Expanded Uncertainty (k=2) (±) |
|------------------------------------|------------------|--------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz | 2.44 dB |
| Radiated Emissions up to 1 GHz | 30MHz ~ 200MHz | 3.86 dB |
| | 200MHz ~ 1000MHz | 3.87 dB |
| Radiated Emissions above 1 GHz | 1GHz ~ 18GHz | 2.29 dB |
| | 18GHz ~ 40GHz | 2.29 dB |

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

| | |
|-----------------------|--------------------------------|
| Product | Bluetooth Module |
| Brand | Hosiden |
| Test Model | HRM1016 |
| Status of EUT | Engineering sample |
| Power Supply Rating | 3.7Vdc from host equipment |
| Modulation Type | GFSK, $\pi/4$ -DQPSK, 8DPSK |
| Modulation Technology | FHSS |
| Transfer Rate | 1/2/3Mbps |
| Operating Frequency | 2402 ~ 2480MHz |
| Number of Channel | 79 |
| Output Power | 4.188mW |
| Antenna Type | PCB antenna with -1.50dBi gain |
| Antenna Connector | NA |
| Accessory Device | NA |
| Data Cable Supplied | NA |

3.2 Description of Test Modes

79 channels are provided to this EUT:

| Channel | Freq. (MHz) |
|---------|-------------|---------|-------------|---------|-------------|---------|-------------|
| 0 | 2402 | 20 | 2422 | 40 | 2442 | 60 | 2462 |
| 1 | 2403 | 21 | 2423 | 41 | 2443 | 61 | 2463 |
| 2 | 2404 | 22 | 2424 | 42 | 2444 | 62 | 2464 |
| 3 | 2405 | 23 | 2425 | 43 | 2445 | 63 | 2465 |
| 4 | 2406 | 24 | 2426 | 44 | 2446 | 64 | 2466 |
| 5 | 2407 | 25 | 2427 | 45 | 2447 | 65 | 2467 |
| 6 | 2408 | 26 | 2428 | 46 | 2448 | 66 | 2468 |
| 7 | 2409 | 27 | 2429 | 47 | 2449 | 67 | 2469 |
| 8 | 2410 | 28 | 2430 | 48 | 2450 | 68 | 2470 |
| 9 | 2411 | 29 | 2431 | 49 | 2451 | 69 | 2471 |
| 10 | 2412 | 30 | 2432 | 50 | 2452 | 70 | 2472 |
| 11 | 2413 | 31 | 2433 | 51 | 2453 | 71 | 2473 |
| 12 | 2414 | 32 | 2434 | 52 | 2454 | 72 | 2474 |
| 13 | 2415 | 33 | 2435 | 53 | 2455 | 73 | 2475 |
| 14 | 2416 | 34 | 2436 | 54 | 2456 | 74 | 2476 |
| 15 | 2417 | 35 | 2437 | 55 | 2457 | 75 | 2477 |
| 16 | 2418 | 36 | 2438 | 56 | 2458 | 76 | 2478 |
| 17 | 2419 | 37 | 2439 | 57 | 2459 | 77 | 2479 |
| 18 | 2420 | 38 | 2440 | 58 | 2460 | 78 | 2480 |
| 19 | 2421 | 39 | 2441 | 59 | 2461 | | |

3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT CONFIGURE MODE | APPLICABLE TO | | | | DESCRIPTION |
|--------------------------|---------------|-----------|-----|------|-------------|
| | RE \geq 1G | RE $<$ 1G | PLC | APCM | |
| - | ✓ | ✓ | ✓ | ✓ | - |

Where RE \geq 1G: Radiated Emission above 1GHz & Bandedge Measurement

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

Radiated Emission Test (Above 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | PACKET TYPE |
|-----------------------|----------------------|----------------|--------------------------|-----------------|-------------|
| - | 0 to 78 | 0, 39, 78 | FHSS | GFSK | DH5 |
| | 0 to 78 | 0, 39, 78 | FHSS | 8DPSK | DH5 |

Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | PACKET TYPE |
|-----------------------|----------------------|----------------|--------------------------|-----------------|-------------|
| - | 0 to 78 | 39 | FHSS | GFSK | DH5 |

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | PACKET TYPE |
|-----------------------|----------------------|----------------|--------------------------|-----------------|-------------|
| - | 0 to 78 | 39 | FHSS | GFSK | DH5 |

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | PACKET TYPE |
|--------------------|-------------------|----------------|-----------------------|-----------------|-------------|
| - | 0 to 78 | 0, 39, 78 | FHSS | GFSK | DH5 |
| | 0 to 78 | 0, 39, 78 | FHSS | 8DPSK | DH5 |

Test Condition:

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | INPUT POWER (System) | TESTED BY |
|---------------|--------------------------|----------------------|------------|
| RE \geq 1G | 20deg. C, 66%RH | 120Vac, 60Hz | James Yang |
| RE<1G | 20deg. C, 66%RH | 120Vac, 60Hz | James Yang |
| PLC | 20deg. C, 66%RH | 120Vac, 60Hz | James Yang |
| APCM | 25deg. C, 60%RH | 120Vac, 60Hz | Ted Chang |

3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


| ID | Product | Brand | Model No. | Serial No. | FCC ID | Remarks |
|----|-------------------------------|---------|------------------|------------|------------------|--------------------|
| A. | PC | DELL | OptiPlex 9010 DT | HR465W1 | FCC DoC Approved | - |
| B. | Conversion JIG | CSR | 1324 | NA | NA | Provided by client |
| C. | DC Power Supply | Topward | 33010D | 807748 | NA | - |
| D. | Evaluation Board for HRM 1016 | Hosiden | HRM1033 | NA | NA | Provided by client |

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A was placed under the test table.

| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks |
|----|--------------|------|------------|--------------------|--------------|---------|
| 1. | LAN cable | 1 | 3 | N | 0 | - |
| 2. | Power cable | 1 | 1 | N | 0 | - |
| 3. | Power cable | 1 | 1 | N | 0 | - |

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

FCC Public Notice DA 00-705

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).
 The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_{uV/m}) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

| Description & Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Due |
|--------------------------------------|------------------------------|--------------------------------|---------------|---------------|
| Test Receiver ROHDE & SCHWARZ | ESIB7 | 100187 | Apr. 18, 2016 | Apr. 17, 2017 |
| Spectrum Analyzer ROHDE & SCHWARZ | FSP40 | 100040 | Aug. 16, 2016 | Aug. 15, 2017 |
| BILOG Antenna SCHWARZBECK | VULB9168 | 9168-171 | Jan. 07, 2016 | Jan. 06, 2017 |
| HORN Antenna SCHWARZBECK | 9120D | 209 | Jan. 20, 2016 | Jan. 19, 2017 |
| HORN Antenna SCHWARZBECK | BBHA 9170 | BBHA9170241 | Jan. 18, 2016 | Jan. 17, 2017 |
| Loop Antenna | EM-6879 | 269 | Aug. 11, 2016 | Aug. 10, 2017 |
| Preamplifier Agilent | 8447D | 2944A10738 | Aug. 22, 2016 | Aug. 21, 2017 |
| Preamplifier Agilent | 8449B | 3008A01964 | Aug. 22, 2016 | Aug. 21, 2017 |
| RF signal cable HUBER+SUHNER | SUCOFLEX 104 | Cable-CH3-03 (214378) | Aug. 22, 2016 | Aug. 21, 2017 |
| RF signal cable HUBER+SUHNER | SUCOFLEX 106 | Cable-CH3-03 (309224+12738) | Aug. 22, 2016 | Aug. 21, 2017 |
| Software BV ADT | ADT_Radiated_ V7.6.15.9.4 | NA | NA | NA |
| Antenna Tower inn-co GmbH | MA 4000 | 013303 | NA | NA |
| Antenna Tower Controller BV ADT | AT100 | AT93021702 | NA | NA |
| Turn Table BV ADT | TT100 | TT93021702 | NA | NA |
| Turn Table Controller BV ADT | SC100 | SC93021702 | NA | NA |
| Turn Table Controller BV ADT | SC100 | SC93021705 | NA | NA |
| High Speed Peak Power Meter | ML2495A | 0824011 | Jul. 09, 2016 | Jul. 08, 2017 |
| Power Sensor | MA2411B | 0738171 | Jul. 09, 2016 | Jul. 08, 2017 |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 3.
 3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 988962.
 5. The IC Site Registration No. is IC 7450F-3.

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Set Up


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- The EUT connected with Conversion JIG & PC and placed on the testing table.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1GHz Data:

GFSK

| | | | |
|-----------------|--------------|----------------------|--------------|
| CHANNEL | TX Channel 0 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 2390.00 | 53.4 PK | 74.0 | -20.6 | 1.38 H | 75 | 22.50 | 30.90 |
| 2 | 2390.00 | 42.7 AV | 54.0 | -11.3 | 1.38 H | 75 | 11.80 | 30.90 |
| 3 | #2400.00 | 44.4 PK | 73.4 | -29.0 | 1.35 H | 70 | 47.70 | -3.30 |
| 4 | #2400.00 | 14.3 AV | 44.3 | -29.0 | 1.35 H | 70 | 17.60 | -3.30 |
| 5 | *2402.00 | 93.4 PK | | | 1.35 H | 70 | 62.40 | 31.00 |
| 6 | *2402.00 | 63.3 AV | | | 1.35 H | 70 | 32.30 | 31.00 |
| 7 | 4804.00 | 48.0 PK | 74.0 | -26.0 | 1.40 H | 151 | 43.60 | 4.40 |
| 8 | 4804.00 | 17.9 AV | 54.0 | -36.1 | 1.40 H | 151 | 13.50 | 4.40 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 2390.00 | 53.4 PK | 74.0 | -20.6 | 3.20 V | 314 | 22.50 | 30.90 |
| 2 | 2390.00 | 42.7 AV | 54.0 | -11.3 | 3.20 V | 314 | 11.80 | 30.90 |
| 3 | #2400.00 | 42.2 PK | 73.2 | -31.0 | 3.23 V | 305 | 45.50 | -3.30 |
| 4 | #2400.00 | 12.1 AV | 43.1 | -31.0 | 3.23 V | 305 | 15.40 | -3.30 |
| 5 | *2402.00 | 93.2 PK | | | 3.23 V | 305 | 62.20 | 31.00 |
| 6 | *2402.00 | 63.1 AV | | | 3.23 V | 305 | 32.10 | 31.00 |
| 7 | 4804.00 | 48.6 PK | 74.0 | -25.4 | 2.92 V | 313 | 44.20 | 4.40 |
| 8 | 4804.00 | 18.5 AV | 54.0 | -35.5 | 2.92 V | 313 | 14.10 | 4.40 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.
7. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
8. Average value = peak reading + $20\log(\text{duty cycle})$.

| | | | |
|-----------------|---------------|----------------------|--------------|
| CHANNEL | TX Channel 39 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2441.00 | 96.5 PK | | | 1.39 H | 77 | 65.30 | 31.20 |
| 2 | *2441.00 | 66.4 AV | | | 1.39 H | 77 | 35.20 | 31.20 |
| 3 | 4882.00 | 48.7 PK | 74.0 | -25.3 | 1.35 H | 152 | 44.20 | 4.50 |
| 4 | 4882.00 | 18.6 AV | 54.0 | -35.4 | 1.35 H | 152 | 14.10 | 4.50 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2441.00 | 91.6 PK | | | 2.84 V | 310 | 60.40 | 31.20 |
| 2 | *2441.00 | 61.5 AV | | | 2.84 V | 310 | 30.30 | 31.20 |
| 3 | 4882.00 | 48.7 PK | 74.0 | -25.3 | 2.76 V | 324 | 44.20 | 4.50 |
| 4 | 4882.00 | 18.6 AV | 54.0 | -35.4 | 2.76 V | 324 | 14.10 | 4.50 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. "#": The radiated frequency is out of the restricted band.
7. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
8. Average value = peak reading + $20\log(\text{duty cycle})$.

| | | | |
|-----------------|---------------|----------------------|--------------|
| CHANNEL | TX Channel 78 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2480.00 | 96.8 PK | | | 1.58 H | 76 | 65.50 | 31.30 |
| 2 | *2480.00 | 66.7 AV | | | 1.58 H | 76 | 35.40 | 31.30 |
| 3 | 2483.50 | 41.6 PK | 74.0 | -32.4 | 1.58 H | 76 | 44.60 | -3.00 |
| 4 | 2483.50 | 11.5 AV | 54.0 | -42.5 | 1.58 H | 76 | 14.50 | -3.00 |
| 5 | 4960.00 | 48.0 PK | 74.0 | -26.0 | 1.50 H | 357 | 43.30 | 4.70 |
| 6 | 4960.00 | 17.9 AV | 54.0 | -36.1 | 1.50 H | 357 | 13.20 | 4.70 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2480.00 | 92.5 PK | | | 2.97 V | 333 | 61.20 | 31.30 |
| 2 | *2480.00 | 62.4 AV | | | 2.97 V | 333 | 31.10 | 31.30 |
| 3 | 2483.50 | 42.0 PK | 74.0 | -32.0 | 2.97 V | 333 | 45.00 | -3.00 |
| 4 | 2483.50 | 11.9 AV | 54.0 | -42.1 | 2.97 V | 333 | 14.90 | -3.00 |
| 5 | 4960.00 | 49.5 PK | 74.0 | -24.5 | 3.01 V | 322 | 44.80 | 4.70 |
| 6 | 4960.00 | 19.4 AV | 54.0 | -34.6 | 3.01 V | 322 | 14.70 | 4.70 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.
7. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
8. Average value = peak reading + $20\log(\text{duty cycle})$.

8DPSK

| | | | |
|-----------------|--------------|----------------------|--------------|
| CHANNEL | TX Channel 0 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 2390.00 | 54.2 PK | 74.0 | -19.8 | 2.51 H | 53 | 23.30 | 30.90 |
| 2 | 2390.00 | 42.9 AV | 54.0 | -11.1 | 2.51 H | 53 | 12.00 | 30.90 |
| 3 | #2400.00 | 43.8 PK | 73.6 | -29.8 | 2.49 H | 46 | 47.10 | -3.30 |
| 4 | #2400.00 | 13.7 AV | 43.5 | -29.8 | 2.49 H | 46 | 17.00 | -3.30 |
| 5 | *2402.00 | 93.6 PK | | | 2.49 H | 46 | 62.60 | 31.00 |
| 6 | *2402.00 | 63.5 AV | | | 2.49 H | 46 | 32.50 | 31.00 |
| 7 | 4804.00 | 48.0 PK | 74.0 | -26.0 | 2.52 H | 70 | 43.60 | 4.40 |
| 8 | 4804.00 | 17.9 AV | 54.0 | -36.1 | 2.52 H | 70 | 13.50 | 4.40 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 2390.00 | 56.3 PK | 74.0 | -17.7 | 3.52 V | 295 | 25.40 | 30.90 |
| 2 | 2390.00 | 42.9 AV | 54.0 | -11.1 | 3.52 V | 295 | 12.00 | 30.90 |
| 3 | #2400.00 | 46.4 PK | 75.9 | -29.5 | 3.59 V | 286 | 49.70 | -3.30 |
| 4 | #2400.00 | 16.3 AV | 45.8 | -29.5 | 3.59 V | 286 | 19.60 | -3.30 |
| 5 | *2402.00 | 95.9 PK | | | 3.59 V | 286 | 64.90 | 31.00 |
| 6 | *2402.00 | 65.8 AV | | | 3.59 V | 286 | 34.80 | 31.00 |
| 7 | 4804.00 | 48.8 PK | 74.0 | -25.2 | 3.00 V | 315 | 44.40 | 4.40 |
| 8 | 4804.00 | 18.7 AV | 54.0 | -35.3 | 3.00 V | 315 | 14.30 | 4.40 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.
7. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
8. Average value = peak reading + 20log(duty cycle).

| | | | |
|-----------------|---------------|-------------------|---------------------------|
| CHANNEL | TX Channel 39 | DETECTOR FUNCTION | Peak (PK) Average (AV) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2441.00 | 96.4 PK | | | 2.44 H | 72 | 65.20 | 31.20 |
| 2 | *2441.00 | 66.2 AV | | | 2.44 H | 72 | 35.00 | 31.20 |
| 3 | 4882.00 | 48.4 PK | 74.0 | -25.6 | 2.12 H | 29 | 43.90 | 4.50 |
| 4 | 4882.00 | 18.3 AV | 54.0 | -35.7 | 2.12 H | 29 | 13.80 | 4.50 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2441.00 | 96.3 PK | | | 3.55 V | 301 | 65.10 | 31.20 |
| 2 | *2441.00 | 66.2 AV | | | 3.55 V | 301 | 35.00 | 31.20 |
| 3 | 4882.00 | 48.7 PK | 74.0 | -25.3 | 3.56 V | 288 | 44.20 | 4.50 |
| 4 | 4882.00 | 18.6 AV | 54.0 | -35.4 | 3.56 V | 288 | 14.10 | 4.50 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. "#": The radiated frequency is out of the restricted band.
7. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
8. Average value = peak reading + $20\log(\text{duty cycle})$.

| | | | |
|-----------------|---------------|----------------------|--------------|
| CHANNEL | TX Channel 78 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2480.00 | 97.4 PK | | | 1.86 H | 79 | 66.10 | 31.30 |
| 2 | *2480.00 | 67.3 AV | | | 1.86 H | 79 | 36.00 | 31.30 |
| 3 | 2483.50 | 42.0 PK | 74.0 | -32.0 | 1.86 H | 79 | 45.00 | -3.00 |
| 4 | 2483.50 | 11.9 AV | 54.0 | -42.1 | 1.86 H | 79 | 14.90 | -3.00 |
| 5 | 4960.00 | 50.1 PK | 74.0 | -23.9 | 2.52 H | 27 | 45.40 | 4.70 |
| 6 | 4960.00 | 20.0 AV | 54.0 | -34.0 | 2.52 H | 27 | 15.30 | 4.70 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | *2480.00 | 92.8 PK | | | 2.86 V | 338 | 61.50 | 31.30 |
| 2 | *2480.00 | 62.8 AV | | | 2.86 V | 338 | 31.50 | 31.30 |
| 3 | 2483.50 | 41.2 PK | 74.0 | -32.8 | 2.86 V | 338 | 44.20 | -3.00 |
| 4 | 2483.50 | 11.1 AV | 54.0 | -42.9 | 2.86 V | 338 | 14.10 | -3.00 |
| 5 | 4960.00 | 50.3 PK | 74.0 | -23.7 | 3.18 V | 323 | 45.60 | 4.70 |
| 6 | 4960.00 | 20.2 AV | 54.0 | -33.8 | 3.18 V | 323 | 15.50 | 4.70 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.
7. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
8. Average value = peak reading + $20\log(\text{duty cycle})$.

Below 1GHz worst-case data:

GFSK

| | | | |
|-----------------|---------------|----------------------|-----------------|
| CHANNEL | TX Channel 39 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 33.79 | 30.0 QP | 40.0 | -10.0 | 2.00 H | 158 | 45.70 | -15.70 |
| 2 | 119.34 | 39.0 QP | 43.5 | -4.5 | 1.49 H | 42 | 55.40 | -16.40 |
| 3 | 175.72 | 29.8 QP | 43.5 | -13.7 | 1.00 H | 289 | 44.40 | -14.60 |
| 4 | 385.70 | 31.6 QP | 46.0 | -14.4 | 1.00 H | 243 | 42.00 | -10.40 |
| 5 | 486.81 | 30.5 QP | 46.0 | -15.5 | 2.00 H | 194 | 38.70 | -8.20 |
| 6 | 764.84 | 30.5 QP | 46.0 | -15.5 | 1.00 H | 189 | 32.30 | -1.80 |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | |
| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1 | 33.04 | 32.1 QP | 40.0 | -7.9 | 1.00 V | 276 | 48.10 | -16.00 |
| 2 | 76.56 | 37.0 QP | 40.0 | -3.0 | 1.00 V | 158 | 54.90 | -17.90 |
| 3 | 105.73 | 35.7 QP | 43.5 | -7.8 | 1.49 V | 39 | 53.60 | -17.90 |
| 4 | 201.00 | 27.5 QP | 43.5 | -16.0 | 2.00 V | 91 | 44.00 | -16.50 |
| 5 | 395.43 | 32.6 QP | 46.0 | -13.4 | 1.00 V | 171 | 42.70 | -10.10 |
| 6 | 722.07 | 29.2 QP | 46.0 | -16.8 | 2.00 V | 6 | 32.30 | -3.10 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) | |
|-----------------|------------------------|---------|
| | Quasi-peak | Average |
| 0.15 - 0.5 | 66 - 56 | 56 - 46 |
| 0.50 - 5.0 | 56 | 46 |
| 5.0 - 30.0 | 60 | 50 |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

| Description & Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Due |
|---|--------------------------|----------------|---------------|---------------|
| Test Receiver ROHDE & SCHWARZ | ESCS30 | 100289 | Dec. 23, 2015 | Dec. 22, 2016 |
| RF signal cable (with 10dB PAD) Woken | 5D-FB | Cable-cond2-01 | Dec. 26, 2015 | Dec. 25, 2016 |
| LISN/AMN ROHDE & SCHWARZ (EUT) | ESH2-Z5 | 100100 | Jan. 11, 2016 | Jan. 10, 2017 |
| LISN/AMN ROHDE & SCHWARZ (Peripheral) | ESH3-Z5 | 100312 | Jul. 26, 2016 | Jul. 25, 2017 |
| Software ADT | BV ADT_Cond_ V7.3.7.3 | NA | NA | NA |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.

3. The VCCI Site Registration No. is C-2047.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

| Phase | Line (L) | | Detector Function | | Quasi-Peak (QP) / Average (AV) | |
|-------|----------|--|-------------------|--|--------------------------------|--|
|-------|----------|--|-------------------|--|--------------------------------|--|

| No | Freq. [MHz] | Corr. Factor (dB) | Reading Value [dB (uV)] | | Emission Level [dB (uV)] | | Limit [dB (uV)] | | Margin (dB) | |
|----|----------------|-------------------------|----------------------------|--------------|-----------------------------|--------------|--------------------|--------------|----------------|---------------|
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| | 0.19297 | 10.15 | 28.76 | 19.95 | 38.91 | 30.10 | 63.91 | 53.91 | -25.00 | -23.81 |
| 2 | 0.35703 | 10.18 | 30.25 | 23.10 | 40.43 | 33.28 | 58.80 | 48.80 | -18.37 | -15.52 |
| 3 | 0.47813 | 10.19 | 30.33 | 21.37 | 40.52 | 31.56 | 56.37 | 46.37 | -15.85 | -14.81 |
| 4 | 1.71484 | 10.26 | 21.98 | 19.33 | 32.24 | 29.59 | 56.00 | 46.00 | -23.76 | -16.41 |
| 5 | 6.35156 | 10.40 | 19.24 | 7.27 | 29.64 | 17.67 | 60.00 | 50.00 | -30.36 | -32.33 |
| 6 | 15.25000 | 10.53 | 19.43 | 7.40 | 29.96 | 17.93 | 60.00 | 50.00 | -30.04 | -32.07 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




| Phase | Neutral (N) | | Detector Function | | Quasi-Peak (QP) / Average (AV) | |
|-------|-------------|--|-------------------|--|--------------------------------|--|
|-------|-------------|--|-------------------|--|--------------------------------|--|

| No | Freq. [MHz] | Corr. Factor (dB) | Reading Value [dB (uV)] | | Emission Level [dB (uV)] | | Limit [dB (uV)] | | Margin (dB) | |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| | | | | | | | | | | |
| 1 | 0.16562 | 10.14 | 36.87 | 11.86 | 47.01 | 22.00 | 65.18 | 55.18 | -18.17 | -33.18 |
| 2 | 0.21641 | 10.16 | 36.97 | 19.13 | 47.13 | 29.29 | 62.96 | 52.96 | -15.83 | -23.67 |
| 3 | 0.52500 | 10.19 | 29.83 | 19.10 | 40.02 | 29.29 | 56.00 | 46.00 | -15.98 | -16.71 |
| 4 | 0.94297 | 10.21 | 26.71 | 10.40 | 36.92 | 20.61 | 56.00 | 46.00 | -19.08 | -25.39 |
| 5 | 6.42969 | 10.46 | 19.69 | 4.30 | 30.15 | 14.76 | 60.00 | 50.00 | -29.85 | -35.24 |
| 6 | 15.22266 | 10.66 | 21.43 | 1.04 | 32.09 | 11.70 | 60.00 | 50.00 | -27.91 | -38.30 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure


- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 Test Results

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency to be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 Test Results

GFSK

| Mode | Number of transmission in a 31.6 (79Hopping*0.4) | Length of transmission time (msec) | Result (msec) | Limit (msec) |
|------|--|------------------------------------|---------------|--------------|
| DH1 | 50 (times / 5 sec) * 6.32 = 316.00 times | 0.456 | 144.10 | 400 |
| DH3 | 25 (times / 5 sec) * 6.32 = 158.00 times | 1.750 | 276.50 | 400 |
| DH5 | 17 (times / 5 sec) * 6.32 = 107.44 times | 3.000 | 322.32 | 400 |

Note: Test plots of the transmitting time slot are shown as below.




8DPSK


| Mode | Number of transmission in a 31.6 (79Hopping*0.4) | Length of transmission time (msec) | Result (msec) | Limit (msec) |
|------|--|------------------------------------|---------------|--------------|
| DH1 | 51 (times / 5 sec) * 6.32 = 322.32 times | 0.456 | 146.98 | 400 |
| DH3 | 26 (times / 5 sec) * 6.32 = 164.32 times | 1.760 | 289.20 | 400 |
| DH5 | 17 (times / 5 sec) * 6.32 = 107.44 times | 2.970 | 319.10 | 400 |

Note: Test plots of the transmitting time slot are shown as below.


DH1




BUREAU
VERITAS




DH3




BUREAU
VERITAS



DH5



BUREAU
VERITAS



4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard


No deviation.

4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) | |
|---------|-----------------|----------------------|-------|
| | | GFSK | 8DPSK |
| 0 | 2402 | 0.88 | 1.21 |
| 39 | 2441 | 0.88 | 1.21 |
| 78 | 2480 | 0.88 | 1.21 |



4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- c. By using the MaxHold function record the separation of two adjacent channels.
- d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.


4.6.5 Deviation from Test Standard

No deviation.

4.6.6 Test Results

| Channel | Frequency (MHz) | Adjacent Channel Separation (MHz) | | 20dB Bandwidth (MHz) | | Minimum Limit (MHz) | | Pass / Fail |
|---------|-----------------|-----------------------------------|-------|----------------------|-------|---------------------|-------|-------------|
| | | GFSK | 8DPSK | GFSK | 8DPSK | GFSK | 8DPSK | |
| 0 | 2402 | 1.00 | 1.00 | 0.88 | 1.21 | 0.59 | 0.81 | Pass |
| 39 | 2441 | 1.00 | 1.00 | 0.88 | 1.21 | 0.59 | 0.81 | Pass |
| 78 | 2480 | 1.00 | 1.00 | 0.88 | 1.21 | 0.59 | 0.81 | Pass |

Note: The minimum limit is two-third 20dB bandwidth.



4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

4.7.5 Deviation from Test Standard


No deviation.

4.7.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

| Channel | Frequency (MHz) | Output Power (mW) | | Output Power (dBm) | | Power Limit (mW) | Pass / Fail |
|---------|-----------------|-------------------|-------|--------------------|-------|------------------|-------------|
| | | GFSK | 8DPSK | GFSK | 8DPSK | | |
| 0 | 2402 | 3.020 | 2.594 | 4.80 | 4.14 | 125 | Pass |
| 39 | 2441 | 4.188 | 3.467 | 6.22 | 5.40 | 125 | Pass |
| 78 | 2480 | 4.018 | 3.311 | 6.04 | 5.20 | 125 | Pass |



4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits Of Conducted Out Of Band Emission Measurement

Below –20dB of the highest emission level of operating band (in 100kHz RBW).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation from Test Standard

No deviation.

4.8.5 EUT Operating Condition


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 Test Results


The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK


Hopping disabled_Low Channel




Hopping disabled_High Channel



Hopping enabled_Low Channel





Hopping enabled_High Channel





8DPSK



Hopping disabled_Low Channel





Hopping disabled_High Channel



Hopping enabled_Low Channel



Hopping enabled_High Channel



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---