

# FCC Test Report

## Part 15 subpart C

### Client Information:

Applicant: Plastoform Industries Ltd.

Applicant add.: Rm. 902-4 Seapower Center 73 Lei Muk Road, Kwai Chung

### Product Information:

EUT Name: Big Blue Party Chrome

Model No.: AR106A4BK

Brand Name: BROOKSTONE

FCC ID: VL5-AR106A4BK

Standards: FCC PART 15 Subpart C: 2016 section 15.247

### Prepared By:

**Dongguan Yaxu (AiT) Technology Limited**

Add. : No.22, Jinqianling Third Street, Jitigang, Huangjiang,  
Dongguan, Guangdong, China

Date of Receipt: Sep. 23, 2016

Date of Test: Sep. 23~ Oct. 25, 2016

Date of Issue: Oct. 26, 2016

Test Result: Pass

This device described above has been tested by Dongguan Yaxu(AiT) Technology Limited, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

\*This test report must not be used by the client to claim product endorsement by any agency of the U.S. government.

Reviewed by: Seal-Chan

Approved by: Jerry

# 1 Contents

	Page
COVER PAGE	
<b>1 CONTENTS</b>	<b>2</b>
<b>2 VERSION</b>	<b>3</b>
<b>3 TEST SUMMARY</b>	<b>4</b>
3.1 COMPLIANCE WITH FCC PART 15 SUBPART C	4
3.2 MEASUREMENT UNCERTAINTY	5
3.3 TEST LOCATION	5
<b>4 TEST FACILITY</b>	<b>6</b>
4.1 DEVIATION FROM STANDARD	6
4.2 ABNORMALITIES FROM STANDARD CONDITIONS	6
<b>5 GENERAL INFORMATION</b>	<b>7</b>
5.1 GENERAL DESCRIPTION OF EUT	7
5.2 EUT PERIPHERAL LIST	9
5.3 TEST PERIPHERAL LIST	9
<b>6 EQUIPMENTS LIST FOR ALL TEST ITEMS</b>	<b>10</b>
<b>7 TEST RESULT</b>	<b>11</b>
7.1 DESCRIPTION OF TEST CONDITIONS	11
7.2 ANTENNA REQUIREMENT	12
7.3 CONDUCTION EMISSIONS MEASUREMENT	13
7.4 RADIATED EMISSIONS MEASUREMENT	17
7.5 6 dB BANDWIDTH	45
7.6 6 dB BANDWIDTH	45
7.7 MAXIMUM PEAK OUTPUT POWER	52
7.8 PEAK POWER SPECTRAL DENSITY	54
7.9 BAND EDGES REQUIREMENT	62
7.10 CONDUCTED SPURIOUS EMISSIONS	67
<b>8 PHOTOGRAPHS</b>	<b>86</b>
8.1 RADIATED SPURIOUS EMISSION TEST SETUP	86
8.2 CONDUCTED EMISSION TEST SETUP	87

## 2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00	--	Oct. 27, 2016	--	--

### 3 Test Summary

#### 3.1 Compliance with FCC Part 15 subpart C

TEST	TEST REQUIREMENT	TEST METHOD	RESULT
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	PASS
Radiated Spurious Emission 30 MHz to 25 GHz)	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.4, 6.5 and 6.6	PASS
6 dB Bandwidth	FCC PART 15 C section 15.247 (a)(2)	ANSI C63.10: Clause 6.9.1	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(3)	FCC/KDB-558074 D01 v03r05 Clause 9.1.2	PASS
Peak Power Spectral Density	FCC PART 15 C section 15.247(e)	ANSI C63.10: Clause 6.11.2.3	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	FCC/KDB-558074 D01 v03r05 Clause 13.3.1	PASS
Conducted Spurious Emission (30MHz to 25GHz)	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.7	PASS

**Remark:**

N/A: not applicable. Refer to the relative section for the details.

EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2013 in the whole report.

## 3.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, the following measurements uncertainty Levels have estimated based on standards, the maximum value of the uncertainty as below:

No.	Item	Uncertainty
1	Conducted Emission Test	1.20dB
2	Radiated Emission Test	3.30dB

## 3.3 Test Location

All tests were performed at:

Dongguan Yaxu (AiT) Technology Limited  
No.22, Jinqianling Third Street, Jitigang, Huangjiang, Dongguan, Guangdong, China  
Tel.: +86.769.82020499 Fax.: +86.769.82020495

## 4 Test Facility

**The test facility is recognized, certified or accredited by the following organizations:**

**.CNAS- Registration No: L6177**

Dongguan Yaxu (AiT) technology Limited is accredited to ISO/IEC 17025:2005 general Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the competence of testing and calibration laboratories) on Apr. 18, 2013

**.FCC- Registration No: 248337**

The 3m Semi-Anechoic Chamber, 3m/10m Open Area Test Site and Shielding Room of Dongguan Yaxu (AiT) Technology Limited have been registered by Federal Communications Commission (FCC) on Aug.29, 2014.

**.Industry Canada(IC)-Registration No: 6819A**

The 3m Semi-Anechoic Chamber and 3m/10m Open Area Test Site of Dongguan Yaxu (AiT) Technology Limited have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing on Oct. 01, 2014.

### 4.1 Deviation from standard

None

### 4.2 Abnormalities from standard conditions

None

## 5 General Information

### 5.1 General Description of EUT

Manufacturer:	Brookstone Inc.
Manufacturer Address:	One Innovation Way, Merrimack, New Hampshire, 03054 United States
EUT Name:	Big Blue Party Chrome
Model No.:	AR106A4BK
Brand Name:	BROOKSTONE
Derivative model No.:	N/A
Operation frequency:	2412 MHz to 2462 MHz for 802.11b/g/n(HT20)
Number of Channels:	11 Channels for 802.11b/g/n(HT20)
Modulation Technology:	802.11b: CCK/QPSK/BPSK 802.11g/n: BPSK/QPSK/16QAM/64QAM
Transmit Data Rate:	802.11b :1/2/5.5/11 Mbps 802.11g :6/9/12/18/24/36/48/54 Mbps 802.11n(HT20): 7.2/14.4/21.7/28.9/43.3/57.8/65/72.2 Mbps
Channel Separation:	5 MHz
Antenna Type and Gain:	Integral antenna maximum 2.21dBi
H/W No.:	E09-02160-01
S/W No.:	1.0
Power Supply Range:	Input: AC 100-240v 50/60Hz 1.5A, Output: DC18V 3.5A or DC11.1V from battery.
Power Cord:	1.2 m x 2 wires unscreened DC cable 1.5 m x 2 wires unscreened AC cable
Note:	
	1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

**EUT channels and frequencies list:**

1. Test frequencies are lowest channel: 2412 MHz, middle channel: 2437 MHz and highest channel: 2462 MHz for 802.11b/g/n(HT20)

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

## 5.2 EUT Peripheral List

No .	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	N/A	N/A	N/A	N/A	N/A	N/A

## 5.3 Test Peripheral List

No .	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	N/A	N/A	N/A	N/A	N/A	N/A

## 6 Equipments List for All Test Items

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	SIGNAL ANALYZER	R&S	FSV40	101470	2016.06.29	2017.06.29
2	EMI Measuring Receiver	R&S	ESR	101660	2016.06.29	2017.06.29
3	Low Noise Pre Amplifier	Tsj	MLA-10K01-B01-27	1205323	2016.06.29	2017.06.29
4	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2016.06.29	2017.06.29
5	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9160	9160-3206	2016.06.29	2017.06.29
6	Broadband Horn Antenna	SCHWARZBECK	BBHA9120D	452	2016.06.29	2017.06.29
7	SHF-EHF Horn	SCHWARZBECK	BBHA9170	BBHA9170367	2016.06.29	2017.06.29
8	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.06.29	2017.06.29
9	EMI Test Receiver	R&S	ESCI	100124	2016.06.29	2017.06.29
10	LISN	Kyoritsu	KNW-242	8-837-4	2016.06.29	2017.06.29
11	LISN	Kyoritsu	KNW-407	8-1789-3	2016.06.29	2017.06.29
12	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2016.06.29	2017.06.29
13	Loop Antenna	ARA	PLA-1030/B	1029	2016.06.29	2017.06.29
14	Radiated Cable 1# (30MHz-1GHz)	FUJIKURA	5D-2W	01	2016.06.29	2017.06.29
15	Radiated Cable 2# (1GHz -25GHz)	FUJIKURA	10D2W	02	2016.06.29	2017.06.29
16	Conducted Cable 1#(9KHz-30MHz)	FUJIKURA	1D-2W	01	2016.06.29	2017.06.29
17	SMA Antenna connector	Dosin	Dosin-SMA	N/A	N/A	N/A
18	Power Meter	Anritsu	ML2495A	N/A	2016.06.29	2017.06.29
19	Power sensor	Anritsu	MA2411B	N/A	2016.06.29	2017.06.29

Note: The SMA antenna connector is soldered on the PCB board in order to perform conducted tests and this SMA antenna connector is listed in the equipment list.

## 7 Test Result

### 7.1 Description of Test conditions

(1) EUT was tested in normal configuration (Please See following Block diagram)

1. Block diagram of EUT configuration(TX Mode)



Note: 1. The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

2. Using the software Putty to control the fixed transmitting power (tx power:15) frequency and other test mode. After finishing the test setting, the notebook and the transform board will be removed during measurements.

(2) E.U.T. test conditions:

15.31(e): For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part.

(3) Test frequencies:

According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and. If required reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

(4) Frequency range of radiated measurements:

According to the 15.33, the test range will be up to the tenth harmonic of the highest fundamental frequency.

(5) Pre-test the EUT in all transmitting mode at the lowest, middle and highest channel with different data rate and conducted to determine the worst-case mode, only the worst-case results are recorded in this report.

## 7.2 Antenna Requirement


### 7.2.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### 7.2.2 EUT Antenna

The antenna is Integral antenna and no consideration of replacement. Antenna gain is maximum 2.21dBi from 2.4GHz to 2.5GHz.



Note: 1. 1/2 Represent the value of antenna1/2, The worst data is Antenna 1, only shown Antenna 1Plot.  
2. Antenna 1 and Antenna 2 can not transmit simultaneously.

## 7.3 Conduction Emissions Measurement

**Test Requirement:** FCC Part 15 C section 15.207  
**Test Method:** ANSI C63.10: Clause 6.2  
**Frequency Range:** 150 kHz to 30 MHz  
**Detector:** Peak for pre-scan (9kHz Resolution Bandwidth)

### Test Limit

#### Limits for conducted disturbance at the mains ports


Frequency Range (MHz)	Quasi-peak (dBuV)	Average (dBuV)
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

**EUT Operation:** Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.  
Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

### Test procedure

1. The mains terminal disturbance voltage test was conducted in a shielded room.
2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a  $50\Omega/50\mu\text{H} + 5\Omega$  linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.


**Test setup**

### 7.3.1 Test results

EUT:	Big Blue Party Chrome	Model Name. :	AR106A4BK
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date :	2016-09-27
Test Mode:	TX:11Mbps 802.11b 2.412 GHz (worst-case)	Phase :	Line
<b>Test Voltage :</b>	DC 18V from Adapter, AC 120V/60Hz for Adapter		

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor(dB)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Over (dB)	Detector
0.1539	38.19	11.84	50.03	65.78	-15.75	Quasi-Peak
0.1620	22.48	11.68	34.16	55.36	-21.20	Average
0.4300	27.74	10.09	37.83	57.25	-19.42	Quasi-Peak
0.4340	23.86	10.09	33.95	47.18	-13.23	Average
4.4940	26.26	10.08	36.34	56.00	-19.66	Quasi-Peak
4.4940	24.54	10.08	34.62	46.00	-11.38	Average


Remark: Factor = LISN factor + Cable Loss + Pulse limiter factor.



EUT:	Big Blue Party Chrome	Model Name. :	AR106A4BK
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date :	2016-09-27
Test Mode:	TX:11Mbps 802.11b 2.412 GHz (worst-case)	Phase :	Neutral
<b>Test Voltage :</b>	DC 18V from Adapter, AC 120V/60Hz for Adapter		

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor(dB)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Over (dB)	Detector
0.1620	39.02	11.68	50.70	65.36	-14.66	Quasi-Peak
0.1620	29.51	11.68	41.19	55.36	-14.17	Average
0.6419	26.13	9.99	36.12	56.00	-19.88	Quasi-Peak
0.6419	21.48	9.99	31.47	46.00	-14.53	Average
3.5300	25.44	10.04	35.48	56.00	-20.52	Quasi-Peak
3.5300	23.30	10.04	33.34	46.00	-12.66	Average

Remark: Factor = LISN factor + Cable Loss + Pulse limiter factor.




## 7.4 Radiated Emissions Measurement


Test Requirement:	FCC Part 15 C section 15.247  (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that Contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.
Test Method:	ANSI C63.10: Clause 6.4, 6.5 and 6.6
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.
Detector:	For PK value:  RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz  VBW $\geq$ RBW  Sweep = auto  Detector function = peak  Trace = max hold  For AV value:  RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz  VBW = 10Hz  Sweep = auto  Detector function = peak  Trace = max hold
15.209 Limit:	40.0 dB $\mu$ V/m between 30MHz & 88MHz 43.5 dB $\mu$ V/m between 88MHz & 216MHz 46.0 dB $\mu$ V/m between 216MHz & 960MHz 54.0 dB $\mu$ V/m above 960MHz

**Test Configuration:**


1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:



## 3) 1 GHz to 40 GHz emissions:



**Test procedure:**

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.

The receiver was scanned from 30MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

From 30MHz to 1GHz, read the Quasi-Peak field strength of the emissions with receiver QP detector RBW=120KHz.

Above 1GHz, read the Peak field strength and Average field strength.

Read the Peak field strength through RBW=1MHz, VBW=3MHz in spectrum analyzer setting;

Read the Average field strength through RBW=1MHz, VBW=10Hz in spectrum analyzer setting;

For measurement at frequency above 1GHz

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

While maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the average field strength reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit.

## 7.4.1 Test Result

### 7.4.1.1 Radiated Emissions Test Data Below 30MHz

EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1005 hPa	Relative Humidity:	60%
Test Mode :	TX	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frequency Range	9KHz to 30MHz
RBW/VBW	9KHz~150KHz/RB 200Hz for QP, 150KHz~30MHz/RB 9KHz for QP		

No emission found between lowest internal used/generated frequencies to 30MHz.

### 7.4.1.2 TEST RESULTS (Between 30 – 1000 MHz)


EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX:1Mbps 802.11b 2.412 GHz (worst-case)	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frenqucy Range	30MHz to 1GHz
RBW/VBW	100KHz / 300KHz for spectrum, RBW=120KHz for receiver.		

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

**Vertical:**

Peak scan

Level (dB $\mu$ V/m)




Quasi-peak measurement

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dB $\mu$ V	dB	dB $\mu$ V/m	dB	Detector
1		80.0806	45.63	-19.09	26.54	40.00	-13.46 QP
2		108.2667	41.14	-13.46	27.68	43.50	-15.82 QP
3		137.4202	45.76	-14.80	30.96	43.50	-12.54 QP
4	*	171.9946	51.88	-15.41	36.47	43.50	-7.03 QP
5		193.7728	52.35	-16.22	36.13	43.50	-7.37 QP
6		238.3102	47.50	-14.23	33.27	46.00	-12.73 QP

**Horizontal:**

Peak scan

 Level (dB $\mu$ V/m)

**Quasi-peak measurement**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dB	Detector
1		79.8003	37.93	-18.81	19.12	40.00	-20.88 QP
2		134.5592	34.91	-14.74	20.17	43.50	-23.33 QP
3		163.7550	35.98	-14.65	21.33	43.50	-22.17 QP
4		187.0958	39.05	-13.17	25.88	43.50	-17.62 QP
5		242.5253	39.93	-14.02	25.91	46.00	-20.09 QP
6	*	724.2611	31.53	-0.46	31.07	46.00	-14.93 QP

### 7.4.1.3 TEST RESULTS (ABOVE 1000 MHZ)

#### 7.4.1.4 802.11b mode with 1Mbps data rate

EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX Channel 1 (2.412 GHz)	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	54.39	5.08	59.47	74.00	-14.53	PEAK
4824.000	42.64	5.08	47.72	54.00	-6.28	AVERAGE
7236.000	43.51	7.16	50.67	74.00	-23.33	PEAK
7236.000	32.34	7.16	39.50	54.00	-14.50	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	56.37	5.08	61.45	74.00	-12.55	PEAK
4824.000	44.60	5.08	49.68	54.00	-4.32	AVERAGE
7236.000	45.85	7.16	53.01	74.00	-20.99	PEAK
7236.000	33.17	7.16	40.33	54.00	-13.67	AVERAGE

EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX Channel 6 (2.437 GHz)	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

## 1~25 GHz Harmonics &amp; Spurious Emissions. Peak &amp; Average Measurement

## (a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	53.10	5.13	58.23	74.00	-15.77	PEAK
4874.000	42.44	5.13	47.57	54.00	-6.43	AVERAGE
7311.000	43.82	7.49	51.31	74.00	-22.69	PEAK
7311.000	31.49	7.49	38.98	54.00	-15.02	AVERAGE

## (b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	54.36	5.13	59.49	74.00	-14.51	PEAK
4874.000	43.59	5.13	48.72	54.00	-5.28	AVERAGE
7311.000	44.72	7.49	52.21	74.00	-21.79	PEAK
7311.000	33.94	7.49	41.43	54.00	-12.57	AVERAGE

EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX Channel 11 (2.462 GHz)	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

## 1~25 GHz Harmonics &amp; Spurious Emissions. Peak &amp; Average Measurement

## (a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	52.65	5.18	57.83	74.00	-16.17	PEAK
4924.000	41.43	5.18	46.61	54.00	-7.39	AVERAGE
7386.000	43.26	7.82	51.08	74.00	-22.92	PEAK
7386.000	32.72	7.82	40.54	54.00	-13.46	AVERAGE

## (b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	54.69	5.18	59.87	74.00	-14.13	PEAK
4924.000	41.33	5.18	46.51	54.00	-7.49	AVERAGE
7386.000	45.80	7.82	53.62	74.00	-20.38	PEAK
7386.000	33.61	7.82	41.43	54.00	-12.57	AVERAGE

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.

As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

#### 7.4.1.5 802.11g mode with 6Mbps data rate

EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX Channel 1 (2.412 GHz)	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	52.37	5.08	57.45	74.00	-16.55	PEAK
4824.000	41.60	5.08	46.68	54.00	-7.32	AVERAGE
7236.000	44.32	7.16	51.48	74.00	-22.52	PEAK
7236.000	33.51	7.16	40.67	54.00	-13.33	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	55.70	5.08	60.78	74.00	-13.22	PEAK
4824.000	43.12	5.08	48.20	54.00	-5.80	AVERAGE
7236.000	45.92	7.16	53.08	74.00	-20.92	PEAK
7236.000	34.04	7.16	41.20	54.00	-12.80	AVERAGE

EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX Channel 6 (2.437GHz)	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

## 1~25 GHz Harmonics &amp; Spurious Emissions. Peak &amp; Average Measurement

## (a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	52.42	5.13	57.55	74.00	-16.45	PEAK
4874.000	40.90	5.13	46.03	54.00	-7.97	AVERAGE
7311.000	43.24	7.49	50.73	74.00	-23.27	PEAK
7311.000	31.28	7.49	38.77	54.00	-15.23	AVERAGE

## (b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	53.72	5.13	58.85	74.00	-15.15	PEAK
4874.000	42.50	5.13	47.63	54.00	-6.37	AVERAGE
7311.000	45.69	7.49	53.18	74.00	-20.82	PEAK
7311.000	32.84	7.49	40.33	54.00	-13.67	AVERAGE

EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX Channel 11 (2.462 GHz)	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

## 1~25 GHz Harmonics &amp; Spurious Emissions. Peak &amp; Average Measurement

## (a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	52.73	5.18	57.91	74.00	-16.09	PEAK
4924.000	41.56	5.18	46.74	54.00	-7.26	AVERAGE
7386.000	42.98	7.82	50.80	74.00	-23.20	PEAK
7386.000	31.20	7.82	39.02	54.00	-14.98	AVERAGE

## (b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	53.34	5.18	58.52	74.00	-15.48	PEAK
4924.000	42.70	5.18	47.88	54.00	-6.12	AVERAGE
7386.000	46.58	7.82	54.40	74.00	-19.60	PEAK
7386.000	35.91	7.82	43.73	54.00	-10.27	AVERAGE

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor -Preamplifier Factor.

No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

#### 7.4.1.6 802.11n(HT20) mode with 7.2Mbps data rate

EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX Channel 1 (2.412 GHz)	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	53.26	5.08	58.34	74.00	-15.66	PEAK
4824.000	40.94	5.08	46.02	54.00	-7.98	AVERAGE
7236.000	43.14	7.16	50.30	74.00	-23.70	PEAK
7236.000	32.69	7.16	39.85	54.00	-14.15	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	55.26	5.08	60.34	74.00	-13.66	PEAK
4824.000	42.35	5.08	47.43	54.00	-6.57	AVERAGE
7236.000	45.18	7.16	52.34	74.00	-21.66	PEAK
7236.000	34.72	7.16	41.88	54.00	-12.12	AVERAGE

EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX Channel 6 (2.437 GHz)	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

## 1~25 GHz Harmonics &amp; Spurious Emissions. Peak &amp; Average Measurement

## (a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	52.11	5.13	57.24	74.00	-16.76	PEAK
4874.000	41.73	5.13	46.86	54.00	-7.14	AVERAGE
7311.000	44.86	7.49	52.35	74.00	-21.65	PEAK
7311.000	32.97	7.49	40.46	54.00	-13.54	AVERAGE

## (b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	55.98	5.13	61.11	74.00	-12.89	PEAK
4874.000	43.86	5.13	48.99	54.00	-5.01	AVERAGE
7311.000	45.51	7.49	53.00	74.00	-21.00	PEAK
7311.000	33.70	7.49	41.19	54.00	-12.81	AVERAGE

EUT:	Big Blue Party Chrome	Model Name :	AR106A4BK
Temperature:	25 °C	Test Data	2016-09-27
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX Channel 11 (2.462 GHz)	Test Voltage :	DC 18V from Adapter, AC 120V/60Hz for Adapter
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

## 1~25 GHz Harmonics &amp; Spurious Emissions. Peak &amp; Average Measurement

## (a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	53.16	5.18	58.34	74.00	-15.66	PEAK
4924.000	42.80	5.18	47.98	54.00	-6.02	AVERAGE
7386.000	43.64	7.82	51.46	74.00	-22.54	PEAK
7386.000	32.39	7.82	40.21	54.00	-13.79	AVERAGE

## (b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	55.43	5.18	60.61	74.00	-13.39	PEAK
4924.000	44.82	5.18	50.00	54.00	-4.00	AVERAGE
7386.000	45.18	7.82	53.00	74.00	-21.00	PEAK
7386.000	34.69	7.82	42.51	54.00	-11.49	AVERAGE

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.

As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

Remark:

- 1) For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonics of the highest fundamental frequency. And above the third harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 3<sup>rd</sup> harmonic.
- 2) As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3) The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

**Test result: The unit does meet the FCC requirements.**

### 7.4.2 Radiated Emissions which fall in the restricted bands

Test Requirement: FCC Part 15 C section 15.247  
(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Method: ANSI C63.10: Clause 6.4, 6.5 and 6.6

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test site: Measurement Distance: 3m (Semi-Anechoic Chamber)

Limit: 40.0 dB $\mu$ V/m between 30MHz & 88MHz;  
43.5 dB $\mu$ V/m between 88MHz & 216MHz;  
46.0 dB $\mu$ V/m between 216MHz & 960MHz;  
54.0 dB $\mu$ V/m above 960MHz.

Detector: For PK value:  
RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz  
VBW  $\geq$  RBW  
Sweep = auto  
Detector function = peak  
Trace = max hold  
For AV value:  
RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz  
VBW = 10Hz  
Sweep = auto  
Detector function = peak  
Trace = max hold

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

**Test Result:**

Note: 1/2 Represent the value of antenna1/2, The worst data is Antenna 1, only shown Antenna 1 Plot.

**7.4.2.1 802.11b mode with 1Mbps data rate**

Test at Channel 1 (2.412 GHz) in transmitting status

**Peak Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	52.73	27.93	4.74	35.09	50.31	74.00	Vertical
2390.000	54.69	27.63	4.96	35.05	52.23	74.00	V
2483.500	53.82	27.55	4.9	34.99	51.28	74.00	V
2500.000	53.51	27.55	5.00	34.98	51.08	74.00	V
2310.000	54.24	27.93	4.74	35.09	51.82	74.00	Horizontal
2390.000	53.77	27.63	4.96	35.05	51.31	74.00	H
2483.500	52.94	27.55	4.9	34.99	50.40	74.00	H
2500.000	53.12	27.55	5.00	34.98	50.69	74.00	H

**Average Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	42.65	27.93	4.74	35.09	40.23	54.00	Vertical
2390.000	43.10	27.63	4.96	35.05	40.64	54.00	V
2483.500	42.26	27.55	4.9	34.99	39.72	54.00	V
2500.000	43.85	27.55	5.00	34.98	41.42	54.00	V
2310.000	42.76	27.93	4.74	35.09	40.34	54.00	Horizontal
2390.000	44.54	27.63	4.96	35.05	42.08	54.00	H
2483.500	43.31	27.55	4.9	34.99	40.77	54.00	H
2500.000	42.60	27.55	5.00	34.98	40.17	54.00	H

Test at Channel 6 (2.437 GHz) in transmitting status

**Peak Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna actors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	53.94	27.93	4.74	35.09	51.52	74.00	Vertical
2390.000	55.28	27.63	4.96	35.05	52.82	74.00	V
2483.500	53.60	27.55	4.90	34.99	51.06	74.00	V
2500.000	54.72	27.55	5.00	34.98	52.29	74.00	V
2310.000	54.29	27.93	4.74	35.09	51.87	74.00	Horizontal
2390.000	53.33	27.63	4.96	35.05	50.87	74.00	H
2483.500	52.64	27.55	4.90	34.99	50.10	74.00	H
2500.000	53.78	27.55	5.00	34.98	51.35	74.00	H

**Average Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	42.67	27.93	4.74	35.09	40.25	54.00	Vertical
2390.000	43.95	27.63	4.96	35.05	41.49	54.00	V
2483.500	43.10	27.55	4.90	34.99	40.56	54.00	V
2500.000	42.76	27.93	4.74	35.09	40.34	54.00	V
2310.000	43.85	27.93	4.74	35.09	41.43	54.00	Horizontal
2390.000	42.64	27.63	4.96	35.05	40.18	54.00	H
2483.500	43.01	27.55	4.90	34.99	40.47	54.00	H
2500.000	43.96	27.93	4.74	35.09	41.54	54.00	H

Test at Channel 11 (2.462 GHz) in transmitting status

**Peak Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	55.84	27.93	4.74	35.09	53.42	74.00	Vertical
2390.000	53.67	27.63	4.96	35.05	51.21	74.00	V
2483.500	54.29	27.55	4.90	34.99	51.75	74.00	V
2500.000	54.42	27.93	4.74	35.09	52.00	74.00	V
2310.000	53.31	27.93	4.74	35.09	50.89	74.00	Horizontal
2390.000	54.53	27.63	4.96	35.05	52.07	74.00	H
2483.500	52.82	27.55	4.90	34.99	50.28	74.00	H
2500.000	54.15	27.93	4.74	35.09	51.73	74.00	H

**Average Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	42.96	27.93	4.74	35.09	40.54	54.00	Vertical
2390.000	43.11	27.63	4.96	35.05	40.65	54.00	V
2483.500	44.68	27.55	4.90	34.99	42.14	54.00	V
2500.000	43.27	27.93	4.74	35.09	40.85	54.00	V
2310.000	43.46	27.93	4.74	35.09	41.04	54.00	Horizontal
2390.000	45.59	27.63	4.96	35.05	43.13	54.00	H
2483.500	42.73	27.55	4.90	34.99	40.19	54.00	H
2500.000	43.06	27.93	4.74	35.09	40.64	54.00	H

### 7.4.2.2 802.11g mode with 6Mbps data rate

Test at Channel 1 (2.412 GHz) in transmitting status

#### Peak Measurement:

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	53.21	27.93	4.74	35.09	50.79	74.00	Vertical
2390.000	54.54	27.63	4.96	35.05	52.08	74.00	V
2483.500	53.75	27.55	4.90	34.99	51.21	74.00	V
2500.000	52.43	27.55	5.00	34.98	50.00	74.00	V
2310.000	53.16	27.93	4.74	35.09	50.74	74.00	Horizontal
2390.000	52.92	27.63	4.96	35.05	50.46	74.00	H
2483.500	54.37	27.55	4.90	34.99	51.83	74.00	H
2500.000	53.47	27.55	5.00	34.98	51.04	74.00	H

#### Average Measurement:

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	43.51	27.93	4.74	35.09	41.09	54.00	Vertical
2390.000	42.84	27.63	4.96	35.05	40.38	54.00	V
2483.500	43.23	27.55	4.90	34.99	40.69	54.00	V
2500.000	42.75	27.55	5.00	34.98	40.32	54.00	V
2310.000	43.24	27.93	4.74	35.09	40.82	54.00	Horizontal
2390.000	42.17	27.63	4.96	35.05	39.71	54.00	H
2483.500	42.68	27.55	4.90	34.99	40.14	54.00	H
2500.000	43.90	27.55	5.00	34.98	41.47	54.00	H

Test at Channel 6 (2.437 GHz) in transmitting status

**Peak Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	53.13	27.93	4.74	35.09	50.71	74.00	Vertical
2390.000	52.69	27.63	4.96	35.05	50.23	74.00	V
2483.500	54.85	27.55	4.90	34.99	52.31	74.00	V
2500.000	53.08	27.55	5.00	34.98	50.65	74.00	V
2310.000	52.76	27.93	4.74	35.09	50.34	74.00	Horizontal
2390.000	53.92	27.63	4.96	35.05	51.46	74.00	H
2483.500	54.65	27.55	4.90	34.99	52.11	74.00	H
2500.000	53.62	27.55	5.00	34.98	51.19	74.00	H

**Average Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	43.95	27.93	4.74	35.09	41.53	54.00	Vertical
2390.000	42.57	27.63	4.96	35.05	40.11	54.00	V
2483.500	43.16	27.55	4.90	34.99	40.62	54.00	V
2500.000	44.95	27.55	5.00	34.98	42.52	54.00	V
2310.000	45.61	27.93	4.74	35.09	43.19	54.00	Horizontal
2390.000	43.44	27.63	4.96	35.05	40.98	54.00	H
2483.500	45.78	27.55	4.90	34.99	43.24	54.00	H
2500.000	44.16	27.55	5.00	34.98	41.73	54.00	H

Test at Channel 11 (2.462 GHz) in transmitting status

**Peak Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	54.87	27.93	4.74	35.09	52.45	74.00	Vertical
2390.000	52.29	27.63	4.96	35.05	49.83	74.00	V
2483.500	53.66	27.55	4.90	34.99	51.12	74.00	V
2500.000	53.51	27.55	5.00	34.98	51.08	74.00	V
2310.000	54.82	27.93	4.74	35.09	52.40	74.00	Horizontal
2390.000	53.86	27.63	4.96	35.05	51.40	74.00	H
2483.500	54.17	27.55	4.90	34.99	51.63	74.00	H
2500.000	53.50	27.55	5.00	34.98	51.07	74.00	H

**Average Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	42.27	27.93	4.74	35.09	39.85	54.00	Vertical
2390.000	43.54	27.63	4.96	35.05	41.08	54.00	V
2483.500	42.38	27.55	4.90	34.99	39.84	54.00	V
2500.000	43.62	27.55	5.00	34.98	41.19	54.00	V
2310.000	44.80	27.93	4.74	35.09	42.38	54.00	Horizontal
2390.000	43.91	27.63	4.96	35.05	41.45	54.00	H
2483.500	43.45	27.55	4.90	34.99	40.91	54.00	H
2500.000	42.19	27.55	5.00	34.98	39.76	54.00	H

### 7.4.2.3 802.11n(HT20) mode with 7.2Mbps data rate

Test at Channel 1 (2.412 GHz) in transmitting status

#### Peak Measurement:

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	58.83	27.93	4.74	35.09	56.41	74.00	Vertical
2390.000	61.26	27.63	4.96	35.05	58.80	74.00	V
2483.500	60.75	27.55	4.90	34.99	58.21	74.00	V
2500.000	59.94	27.55	5.00	34.98	57.51	74.00	V
2310.000	58.28	27.93	4.74	35.09	55.86	74.00	Horizontal
2390.000	58.72	27.63	4.96	35.05	56.26	74.00	H
2483.500	59.35	27.55	4.90	34.99	56.81	74.00	H
2500.000	59.61	27.55	5.00	34.98	57.18	74.00	H

#### Average Measurement:

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	48.54	27.93	4.74	35.09	46.12	54.00	Vertical
2390.000	51.38	27.63	4.96	35.05	48.92	54.00	V
2483.500	49.39	27.55	4.90	34.99	46.85	54.00	V
2500.000	48.80	27.55	5.00	34.98	46.37	54.00	V
2310.000	51.74	27.93	4.74	35.09	49.32	54.00	Horizontal
2390.000	49.62	27.63	4.96	35.05	47.16	54.00	H
2483.500	50.70	27.55	4.90	34.99	48.16	54.00	H
2500.000	49.24	27.55	5.00	34.98	46.81	54.00	H

Test at Channel 6 (2.437 GHz) in transmitting status

**Peak Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	59.15	27.93	4.74	35.09	56.73	74.00	Vertical
2390.000	58.92	27.63	4.96	35.05	56.46	74.00	V
2483.500	57.43	27.55	4.90	34.99	54.89	74.00	V
2500.000	59.13	27.55	5.00	34.98	56.70	74.00	V
2310.000	58.56	27.93	4.74	35.09	56.14	74.00	Horizontal
2390.000	57.64	27.63	4.96	35.05	55.18	74.00	H
2483.500	57.22	27.55	4.90	34.99	54.68	74.00	H
2500.000	59.68	27.55	5.00	34.98	57.25	74.00	H

**Average Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	45.10	27.93	4.74	35.09	42.68	54.00	Vertical
2390.000	44.98	27.63	4.96	35.05	42.52	54.00	V
2483.500	45.16	27.55	4.90	34.99	42.62	54.00	V
2500.000	44.28	27.55	5.00	34.98	41.85	54.00	V
2310.000	45.32	27.93	4.74	35.09	42.90	54.00	Horizontal
2390.000	44.75	27.63	4.96	35.05	42.29	54.00	H
2483.500	43.91	27.55	4.90	34.99	41.37	54.00	H
2500.000	42.27	27.55	5.00	34.98	39.84	54.00	H

Test at Channel 11 (2.462 GHz) in transmitting status

**Peak Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	53.91	27.93	4.74	35.09	51.49	74.00	Vertical
2390.000	52.65	27.63	4.96	35.05	50.19	74.00	V
2483.500	54.87	27.55	4.90	34.99	52.33	74.00	V
2500.000	53.22	27.55	5.00	34.98	50.79	74.00	V
2310.000	53.45	27.93	4.74	35.09	51.03	74.00	Horizontal
2390.000	52.63	27.63	4.96	35.05	50.17	74.00	H
2483.500	53.83	27.55	4.90	34.99	51.29	74.00	H
2500.000	52.74	27.55	5.00	34.98	50.31	74.00	H

**Average Measurement:**

Frequency (MHz)	Reading Level (dB $\mu$ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
2310.000	42.14	27.93	4.74	35.09	39.72	54.00	Vertical
2390.000	43.30	27.63	4.96	35.05	40.84	54.00	V
2483.500	41.24	27.55	4.90	34.99	38.70	54.00	V
2500.000	40.76	27.55	5.00	34.98	38.33	54.00	V
2310.000	39.35	27.93	4.74	35.09	36.93	54.00	Horizontal
2390.000	41.77	27.63	4.96	35.05	39.31	54.00	H
2483.500	43.15	27.55	4.90	34.99	40.61	54.00	H
2500.000	42.43	27.55	5.00	34.98	40.00	54.00	H

## 7.5 6 dB Bandwidth

## 7.6 6 dB Bandwidth

Test Requirement:

FCC Part 15 C section 15.247

(a)(2)Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.


Test Method:

FCC/KDB-558074 D01v03r05

Test Status:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


Note:1/2 Represent the value of antenna1/2,The worst data is Antenna 1,only shown Antenna 1Plot.

Channel No.	Frequency (MHz)	Mode	Data Rate	Measured 6dB bandwidth (MHz)	Limit	Result
1	2412	802.11b	1 Mbps	10.01	≥500KHz	Pass
6	2437		1 Mbps	10.04		Pass
11	2462		1 Mbps	10.48		Pass
1	2412	802.11g	6 Mbps	10.19	≥500KHz	Pass
6	2437		6 Mbps	11.22		Pass
11	2462		6 Mbps	10.43		Pass
1	2412	802.11n (HT20)	7.2 Mbps	11.37	≥500KHz	Pass
6	2437		7.2 Mbps	12.15		Pass
11	2462		7.2 Mbps	11.82		Pass


**Test result: The unit does meet the FCC requirements.**

**Result plot as follows:**
**802.11b mode with 1Mbps data rate**


Channel 1: 2.412GHz:




Channel 6: 2.437GHz:




Channel 11: 2.462GHz:


**802.11g mode with 6Mbps data rate**


Channel 1: 2.412GHz:



Channel 6: 2.437GHz:




Channel 11: 2.462GHz:




**802.11n(HT20) mode with 7.2Mbps data rate**


Channel 1: 2.412GHz:



Channel 6: 2.437GHz:



Channel 11: 2.462GHz:



## 7.7 Maximum Peak Output Power

Test Requirement:

FCC Part 15 C section 15.247

(b)(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b) (1), (b) (2), and (b) (3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


Test Method:

FCC/KDB-558074 D01 v03r05 9.2.3 Measurement using an RF average power meter

Test Status:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss =0.5dB) from the antenna port to the power meter.
2. Measurement using an RF average power meter.
3. Report the worse case.

**Test result:**

Test Mode	Frequency (MHz)	Peak Output Power (/dBm)	Limit (dBm)	Result
802.11b (2.412GHz-2.462GHz) Data rate 1Mbps	2412	13.13	30.00	Pass
	2437	13.19	30.00	Pass
	2462	13.55	30.00	Pass
802.11g (2.412GHz-2.462GHz) Data rate 6Mbps	2412	16.35	30.00	Pass
	2437	16.27	30.00	Pass
	2462	16.52	30.00	Pass
802.11n20 (2.412GHz-2.462GHz) Data rate 7.2Mbps	2412	15.89	30.00	Pass
	2437	15.73	30.00	Pass
	2462	15.25	30.00	Pass

**Remark:** Level = Read Level + Cable Loss.

The unit does meet the FCC requirements.

## 7.8 Peak Power Spectral Density

Test Requirement:

FCC Part 15 C section 15.247

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


Test Method:

ANSI C63.10: Clause 6.11.2.3

Test Status:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (cable loss =2.5dB) from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer:
  - a) Set CENTER FREQUENCY = Frequency from Power Spectral Density Test Matrix (see 6.10.2)
  - b) Set SPAN = 20 MHz (For devices with a nominal 40 MHz BW, 50 MHz span will be needed)
  - c) Set REFERENCE LEVEL = 20 dBm
  - d) Set ATTENUATION = 0 dB (add internal attenuation, if necessary)
  - e) Set SWEEP TIME = Coupled
  - f) Set RBW = 3 kHz
  - g) Set VBW = 10 kHz
  - h) Set DETECTOR = Peak
  - i) Set MKR = Center Frequency
  - j) Set TRACE = CLEAR WRITE

Place the radio in continuous transmit mode. Set the TRACE to MAX HOLD, and after the trace stabilizes, the TRACE to VIEW. Set the marker on the peak of the signal and then adjust the center frequency of the spectrum analyzer to the marker frequency.

After viewing the EUT waveform on the spectrum analyzer, perform the following spectrum analyzer functions to capture the trace:

Set SPAN = 300 kHz  
Set SWEEP TIME = 100 s  
Set TRACE = MAX HOLD  
Set MKR = PEAK SEARCH

3. Measure the Power Spectral Density of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse case.

Note:1/2 Represent the value of antenna1/2,The worst data is Antenna 1,only shown Antenna 1Plot.

Channel No.	Frequency (MHz)	Mode	Data Rate	Measured Peak Power Spectral Density (dBm/3KHz)	Limit	Result
1	2412	802.11b	1 Mbps	-12.31	8dBm/3KHz	Pass
6	2437		1 Mbps	-12.76		Pass
11	2462		1 Mbps	-12.76		Pass
1	2412	802.11g	6 Mbps	-10.24	8dBm/3KHz	Pass
6	2437		6 Mbps	-10.11		Pass
11	2462		6 Mbps	-10.70		Pass
1	2412	802.11n (HT20)	7.2 Mbps	-15.63		Pass
6	2437		7.2 Mbps	-15.12		Pass
11	2462		7.2 Mbps	-16.54		Pass


**Test result: Level = Read Level + Cable Loss.**

**The unit does meet the FCC requirements.**


**Result plot as follows:**

**802.11b mode with 1Mbps data rate**


Channel 1: 2.412GHz:




Channel 6: 2.437GHz:




Channel 11: 2.462GHz:


**802.11g mode with 6Mbps data rate**


Channel 1: 2.412GHz:



Channel 6: 2.437GHz:




Channel 11: 2.462GHz:




**802.11n(HT20) mode with 7.2Mbps data rate**


Channel 1: 2.412GHz:



Channel 6: 2.437GHz:



Channel 11: 2.462GHz:



## 7.9 Band Edges Requirement

Test Requirement: FCC Part 15 C section 15.247


(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Frequency Band: 2400 MHz to 2483.5 MHz

Test Method: FCC/KDB-558074 D01 v03r05 Clause 13.3.1

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set instrument center frequency to the frequency of the emission to be measured(must be within 2MHz of the authorized band edge).
3. Set span to 2MHz,
4. RBW=100kHz,
5.  $VBW \geq 3 \times RBW$
6. Detector=peak
7. Sweep time =auto,
8. Trace mode=max hold.
9. Allow sweep to continue until the trace stabilizes(required measurement time may increase for low duty cycle applications)

---

10. Compute the power by integrating the spectrum over 1MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency( $f_{\text{emission}}$ ) $\pm 0.5\text{MHz}$ . If the instrument does not have a band power function, the sum the amplitude levels(in power units) at 100kHz intervals extending across the 1MHz spectrum defined by  $f_{\text{emission}}\pm 0.5\text{MHz}$ .

Note: 1/2 Represent the value of antenna 1/2, The worst data is Antenna 1, only shown Antenna 1 Plot.


**Test result with plots as follows:**

Compare with the output power of the lowest frequency, the Lower Edges attenuated more than 20dB

Compare with the output power of the highest frequency, the Upper Edges attenuated more than 20dB.


**802.11b mode with 1 Mbps data rate**

Channel1: 2.412 GHz




**802.11b mode with 1 Mbps data rate**

Channel11: 2.462 GHz




**802.11g mode with 6 Mbps data rate**

Channel1: 2.412 GHz



**802.11g mode with 6 Mbps data rate**

Channel11: 2.462 GHz




**802.11n(HT20) mode with 7.2Mbps data rate**

Channel1: 2.412 GHz


**802.11n(HT20) mode with 7.2Mbps data rate**

Channel11: 2.462 GHz



## 7.10 Conducted Spurious Emissions


Test Requirement: FCC Part 15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 6.7

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=100 KHz, VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
3. Measure the Conducted Spurious Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse case.


Note: 1/2 Represent the value of antenna 1/2, The worst data is Antenna 1, only shown Antenna 1 Plot

**Result plot as follows:**


**802.11b mode with 1Mbps data rate**

Channel 1: 2.412GHz:


30 MHz to 1 GHz




1 G to 3 GHz



## 3 G to 13 GHz




## 13 G to 25 GHz




Channel 6: 2.437GHz:


30 MHz to 1 GHz




1 G to 3 GHz



## 3 G to 13 GHz




## 13 G to 25 GHz




Channel 11:2.462 GHz


30 MHz to 1 GHz




1 G to 3 GHz



## 3 G to 13 GHz




## 13 G to 25 GHz




**802.11g mode with 6Mbps data rate**

Channel 1: 2.412GHz:


30 MHz to 1 GHz




1 G to 3 GHz



## 3 G to 13 GHz




## 13 G to 25 GHz




Channel 6: 2.437GHz:


30 MHz to 1 GHz




1 G to 3 GHz



## 3 G to 13 GHz




## 13 G to 25 GHz




Channel 11:2.462 GHz


30 MHz to 1 GHz




1 G to 3 GHz



## 3 G to 13 GHz




## 13 G to 25 GHz




**802.11n(HT20) mode with 7.2Mbps data rate**

Channel 1: 2.412GHz:


30 MHz to 1 GHz




1 G to 3 GHz



## 3 G to 13 GHz




## 13 G to 25 GHz




Channel 6: 2.437GHz:


30 MHz to 1 GHz




1 G to 3 GHz



## 3 G to 13 GHz




## 13 G to 25 GHz




Channel 11:2.462 GHz


30 MHz to 1 GHz




1 G to 3 GHz



## 3 G to 13 GHz



## 13 G to 25 GHz




## 8 Photographs

### 8.1 Radiated Spurious Emission Test Setup

Below 1GHz:



Above 1GHz:



## 8.2 Conducted Emission Test Setup



## 9 APPENDIX-Photographs of EUT Constructional Details

Please refer to report E-F1609004-1.

**\*\*End of report\*\***