

Use Manual:

Rating Voltage:120V

Rating Valtage Frequency:60Hz

CAUTION:

**Always hold plastic base when installing or uninstalling.
Use for indoor fixture or recessed fixtures with open
Ventilation holes.**

Not suitable for damp or dust surrounding.

Reliable starting temperature - 5℃.

Not for use with dimmers.

Risk of electric shock-use in dry location only.

Not for use in totally enclosed recessed fixtures.

Not for use where exposed to the weather.

**This device is not intended for use with emergency
exit fixtures or emergency exit light.**

**CFL may cause electromagnetic interference with
radios, cordless phones, televisions, and remote
controls. If interference occurs, move the product
away from the device or plug into a different outlet.**

FCC Statement

- 1 . This device complies with Part 18 of the FCC Rules.
- 2 . Information on the following matters shall be provided to the user in the instruction manual:
 - (a) The interference potential of the device or system;
 - (b) Maintenance of the system;
 - (c) Simple measures that can be taken by the user to correct interference;
 - (d) Manufacturers of RF lighting devices must provide an advisory statement, either on the product packaging or with other user documentation, similar to the following: This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz. Variations of this language are permitted provided all the points of the statement are addressed and may be presented in any legible font or text style.