

RF Exposure Evaluation declaration

Product Name : GSM Gateway

Model No. : V100-VoIP, G100 FCC ID. : VLW-V100-G100

Applicant: Soundwin Network Inc.

Address: 10F-4, No. 295, Sec. 2, Kuangfu Rd., Hsinchu

City, Taiwan

Date of Receipt: 2007/07/24

Issued Date : 2007/09/12

Report No. : 077317R-RF-US-Exp

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.



1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time	
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm ²)	(Minutes)	
(A) Limits for Occupational/ Control Exposures					
300-1500			F/300	6	
1500-100,000			5	6	
(B) Limits for General Population/ Uncontrolled Exposures					
300-1500			F/1500 6		
1500-100,000			1	30	

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout*G)/(4*pi*r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

Page: 2 of 4 Version:1.0



1.3. Test Result of RF Exposure Evaluation

Product	GSM Gateway
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.29dBi or 2.685 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

850 MHz					
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)		
128	824.20	1352	0.72255		
190	836.60	1345	0.71881		
251	848.80	1399	0.74767		

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Page: 3 of 4 Version:1.0



Product	GSM Gateway
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.29dBi or 2.685 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

1900 MHz					
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)		
512	185020	818.46	0.43741		
661	1880.00	744.73	0.39800		
810	1909.80	660.69	0.35309		

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².