



深圳市迪比通通讯设备有限公司

SHENZHEN DIBITONG TELECOMMUNICATION TECHNOLOGY CO.,LTD.

移动通信终端天线

Mobile communication terminal antenna

产品设计与制造规格书

Product design and manufacturing specifications

- ◆ 客户名称/ Customer: 天彩
- ◆ 项目名称/Projec: VSW12
- ◆ 物料名称/Name: WiFi 天线
- ◆ 天线材质/Antenna materials: FPC+Cable
- ◆ 物料编号/Part no:
- ◆ 设计/Designer:
- ◆ 审核/Check:
- ◆ 客户确认签章/Approved:

地址/Add: 深圳市南山区西丽镇平山一路云谷二期 8 栋 505

Rm505, 8th building, Yungu 2nd period, pingshan No.1 Road, Xili Town, Nanshan District, ShenZhen , China

电话/Tel: 86-755-83763273/13927478525

传真/Fax: 86-755-83763348

电邮/Email: dbt1668@163.com

目录/list

1.天线 2D 图/Antenna 2D diagram

2.技术指标/Technical target

3.动态测试说明/Dynamic test instruction


4.匹配电路/Matching Circuit

5.天线测试数据/Antenna test report

6.天线安装位置/Antenna installation position

7.包装方式/Packing method

1. 天线 2D 图/Antenna 2D diagram




2.技术指标/ Technical target


A. 电气性能/Electrical Parameter	
工作频率范围/Frequency Range	2400~2500 MHz
驻波比/VSWR	2400~2500 MHz: ≤ 2.0
天线增益/Gain (Max)	2400~2500 MHz: 2.65dBi
平均辐射效率/ Average radiation efficiency	2400~2500 MHz : 54.1%
阻抗/Input Impedance	50 ohm
B. 材料/ Material	
FPC+Cable	
C. 环境/Environmental Science	
工作温度/Working Temperature	- 30°C ~ + 85 °C
储藏温度/Storage temperature	- 30°C ~ + 85 °C

3.动态测试数据--- 天线安置在设备里/Dynamic test instructions - Antennas are placed in electronic scales

测试仪器/ Testing instrument : Anrits CMW500+ Anechoic Chamber 6X4X3m(3D-OTA)



4.匹配电路/Matching Circuit



(The match has not changed)

5.天线实际测试数据/Antenna test report




无源效率/增益//Passive Efficiency/Gain/

Freq (MHz)	Effi (%)	Effi (dB)
2400	53.44	2.16
2410	50.31	1.99
2420	51.31	2.21
2430	50.19	2.12
2440	53.13	2.18
2450	50.91	2.12
2460	53.87	2.2
2470	55.29	2.21
2480	59.14	2.16
2490	55.46	2.26
2500	61.97	2.65

6. 天线安装位置/Antenna installation position



7.包装方式/Packing method

1. 单个产品 2D 图/2D drawing of the product		产品料号/ The product material number		
		产品名称 / Product name		VSW12_WIFI 天线
		产品版本/ Product version		V1
2. 箱内所有层堆放后的照片 /Photos of all stacked layers in the box		3. 整箱封箱后的照片/ Photo of the whole case after sealing		
				整包数量/ Number of full pages 200PCS
		备注:每箱数量以实际为准,左侧图片为参考,按实物为准。 /Remarks: the quantity of each box shall be actual, the picture on the left side shall be for reference, and the actual goods shall be regarded as standard.		
4. 整包的照片/ A whole pack of photos		5. 整箱的箱表面贴的标签的照片/A photograph of the label on the surface of the entire case		储存条件: -10° 至 30° 之间, 湿度 70%RH 以下的室内。 /Storage conditions: between -10 ° to 30 ° , humidity 70% Rh below the indoor.
				
注: 上图中的图片只用做包装标准示范, 不能用做最终资料审核。 /Note: the picture in the picture above is only used for packing standard demonstration, not for final data audit.				
确认者 /Confirmer	杨小平/ Yang Xiaoping		日期/Date	2025-3-20

注/Remark:

1. 以上测试结果限于测试样机/The above test results are limited to the test prototype.

2. 整机壳料工艺、软件版本、配件(摄像头 FPC、喇叭、听筒、马达、电池等)、芯片的改变都会导致整机天线性能变化。/Full shell material technology, software version, accessories (camera, FPC, speaker, receiver, motor, battery, etc.), core
The performance of the whole antenna will change with the change of the chip.

3. 整机的环境处理(如接地位置、尺寸,屏蔽方式等)改变会导致整机性能变化。/The change of environmental treatment (such as grounding position, size, shielding mode, etc.) of the whole machine will lead to the change of the performance of the whole machine.

郑重声明/Solemnly declare:

此款天线设计、研发知识产权为我司所有, 如发现有相同产品未经我司允许供应给贵司, 我司将依法追究相应法律责任, 请尊重知识产权, 您的支持是我们的无限动力, 谢谢合作! /This antenna design and R&D intellectual property rights are owned by our company. If we find that the same products are supplied to your company without our permission, we will pursue the corresponding legal responsibility according to law. Please respect intellectual property rights. Your support is our unlimited power. Thank you for your cooperation.