

## MPE Report

Applicant : Swann Communications Pty Ltd  
Product Type : Swann Wire-Free Video Doorbell  
Trade Name : Swann  
Model Number : SWIFI-DOORBELL  
Test Specification : ANSI / IEEE Std.C95.1-1992 / IEEE Std. 1528-2013  
47 CFR § 2.1091  
47 CFR § 1.1310  
Received Date : May 24, 2019  
Test Period : Jun. 10, 2019  
Issue Date : Jul. 18, 2019  
Test Firm MRA designation number : TW0010

### Issue by

Approved By : Jet Lu  
(Jet Lu)

Tested By : Kris Pan  
(Kris Pan)

A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade District,  
Taoyuan City 33465, Taiwan (R.O.C.)  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

#### Note:

- 1.The test results are valid only for samples provided by customers and under the test conditions described in this report.
- 2.This report shall not be reproduced except in full, without the written approval of A Test Lab Technology Corporation.
- 3.The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which



### **Revision History**

Rev.	Issue Date	Revisions	Revised By
00	Jul. 18, 2019	Initial Issue	Jennifer Liu

## Contents

1.	Description of Equipment under Test (EUT).....	4
2.	Human Exposure Assessment.....	5
3.	RF Output Power .....	6
4.	Test Results .....	7

## 1. Reference Testing Standards

Standard	Description	Version
ANSI/IEEE C95.1	American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.	2005

## 2. Description of Equipment under Test (EUT)

Applicant	Swann Communications Pty Ltd Unit 5B 706 Lorimer Street, Port Melbourne 3207, Australia	
Manufacturer	Chicony Electronics (Dong Guan ) Co.,Ltd. San Zhong Guan Li Qu, Qingxi Town, Dongguan City Guangdong 523651 China	
Product Type	Swann Wire-Free Video Doorbell	
Trade Name	Swann	
Model Number	SWIFI-DOORBELL	
FCC ID	VMISWIFIDOORBELL	
Frequency Range	Operate Band	Frequency Range (MHz)
	IEEE 802.11b / 802.11g IEEE 802.11n 2.4 GHz 20 MHz	2412 - 2462
	IEEE 802.11n 2.4 GHz 40 MHz	2422 - 2452
Antenna Information	Type	Max. Gain (dBi)
	PIFA Antenna	0.44
Antenna Delivery	1TX	
Temperature Range	-20 ~ +50°C	

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1091 / 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties

### 3. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR § 1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons." This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

Exposure evaluation
$S = \frac{PG}{4\pi R^2}$ <p>Where</p> <p>S: power density</p> <p>P: power input to the antenna</p> <p>G: power gain of the antenna in the direction of interest relative to an isotropic radiator.</p> <p>R: distance to the center of radiation of the antenna.</p>

#### 4. RF Output Power

The conducted power turn-up tolerance reference manufacturer specification.

Band	Date Rate (Mbps)	Frequency (MHz)	Average Conducted power (dBm)
IEEE 802.11b	1	2412.0	<b>19.93</b>
		2437.0	19.45
		2462.0	19.09
IEEE 802.11g	6	2412.0	<b>18.92</b>
		2437.0	18.67
		2462.0	17.78
IEEE 802.11n 2.4 GHz 20 MHz	6.5	2412.0	<b>17.99</b>
		2437.0	17.84
		2462.0	16.78
IEEE 802.11n 2.4 GHz 40 MHz	13.5	2422.0	<b>16.86</b>
		2437.0	16.61
		2452.0	16.18

Note: The relevant measured result has the offset with cable loss already.

## 5. Test Results

Antenna	Band	Frequency (MHz)	Limit (mw)	Distance [R] (cm)	Max tune-up Power (upper limit) [P] (dBm)	ANT Gain (dBi)	Numeric Gain [G]	Duty Cycle	Power with Duty cycle [TP] (mW)	Power Density [S] (mw/cm <sup>2</sup> )
Wi-Fi Antenna	2.4 GHz Wi-Fi	2412-2462	1	20	20.00	0.44	1.11	1	111	0.022

Note:

1. Mobile or fixed location transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.
2. The Numeric Gain calculated by  $10^{(ant. Gain(dBi) /10)}$ .
3. Each band max power which perform MPE of any configurations.
4. The MPE results are evaluated by lowest data rate for WLAN.
5. The device operating IEEE 802.11 b/g/n mode is 1TX (SISO).
6. We used the maximum antenna gain and tune-up power to provide MPE results.

---END---