

No. 1 Workshop, M-10, Middle Section, Science & Technology Park,

District Shenzhen, China 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594

Email: sgs\_internet\_operations@sgs.com
FEDERAL COMMUNICATIONS COMMISSION

Registration number: 556682

Report No.: SZEMO09040196101

Page: 1 of 16

# TEST REPORT

Application No.: SZEMO090401961RF

Applicant: SUNWAY ELECTRONICS COMPANY
Manufacturer/ Factory: SUNWAY ELECTRONICS COMPANY

FCC ID: VN2-SUN0906 Fundamental Frequency: 433.99 MHz

**Equipment Under Test (EUT):** 

Name: Clock-Sound Centre-DE-MS/ Clock-Sound Centre-MS/

Thermometer-Dig In/Out-DE-MS/ Therm-Dig In-Outdoor II-S3-MS

Model No.: 1626283(DG601C), 1617033(DG602C),

1626282(DG603C), 1624965(DG605C) .

Please refer to section 2 of this report which indicates which item was

actually tested and which were electrically identical.

Standards: FCC PART 15, SUBPART C : 2008 (Section 15.231)

Date of Receipt: 29 April 2009

Date of Test: 29 April to 26 May 2009

Date of Issue: 27 May 2009

Test Result : PASS \*

Authorized Signature:

Robinson Lo Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sqs.com/terms">www.sqs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sqs.com/terms">www.sqs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEMO09040196101

Page: 2 of 16

# 2 Test Summary

Test	Test Requirement	Standard Paragraph	Result
Radiated Emission (30MHz to 5000MHz)	FCC PART 15 : 2008	Section 15.231	PASS
Dwell time	FCC PART 15 : 2008	Section 15.231	PASS
Occupied Bandwidth	FCC PART 15 : 2008	Section 15.215	PASS

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

#### Remark:

Item No.: 1626283(DG601C), 1617033(DG602C), 1626282(DG603C), 1624965(DG605C)

Only the Item 1624965(DG605C)/ 1617033(DG602C) were tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above items, with only difference being the outer decoration.



Report No.: SZEMO09040196101

Page: 3 of 16

## 3 Contents

		Pag	
2	TEST	SUMMARY	
3		'ENTS	
4		RAL INFORMATION	
	4.2 D 4.3 D 4.4 T 4.5 C	CLIENT INFORMATION  DETAILS OF E.U.T  DESCRIPTION OF SUPPORT UNITS  TEST LOCATION  DITHER INFORMATION REQUESTED BY THE CUSTOMER  TEST FACILITY	<sup>2</sup> <sup>2</sup> <sup>2</sup>
5	TEST	RESULTS	6
	5.2 E 5.3 T <i>5.3.1</i> <i>5.3.2</i>	FEST INSTRUMENTS	? ?



Report No.: SZEMO09040196101

Page: 4 of 16

## 4 General Information

#### 4.1 Client information

Applicant: SUNWAY ELECTRONICS COMPANY
Manufacturer/ Factory: SUNWAY ELECTRONICS COMPANY

Address of Applicant: Rm1710, Nan Fung Centre 264-298 Castle Peak Rd., Tusuen

Wan, N.T Hong Kong

Address of Manufacturer: Shiting Jiangkou Township Putian CityFujian Province China Address of Factory: Shiting Jiangkou Township Putian CityFujian Province China

### 4.2 Details of E.U.T

Name: Clock-Sound Centre-DE-MS/ Clock-Sound Centre-MS/

Thermometer-Dig In/Out-DE-MS/ Therm-Dig In-Outdoor II-S3-MS

Model No.: 1626283(DG601C), 1617033(DG602C),

1626282(DG603C), 1624965(DG605C)

Power Supply: DC3.0V(2\*1.5V"AAA"Size Batteries)

Power Cord: N/A-

## 4.3 Description of Support Units

The EUT was tested as an independent unit: a 433 MHz Remote Control

#### 4.4 Test Location

All tests were performed at:

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

## 4.5 Other Information Requested by the Customer

None.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEMO09040196101

Page: 5 of 16

## 4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations

#### • CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### VCCI

The 3m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197 and C-2383 respectively. Date of Registration: September 29, 2008. Valid until September 28, 2011.

#### FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 556682, June 27, 2008.

#### Industry Canada (IC)

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.



Report No.: SZEMO09040196101

Page: 6 of 16

## 5 Test Results

### 5.1 Test Instruments

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2008	15-06-2010
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	12-12-2008	11-12-2009
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	Coaxial cable	SGS	N/A	SEL0028	18-06-2009	17-06-2010
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0014	12-08-2008	11-08-2009
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	18-06-2009	17-06-2010
7	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0005	12-08-2008	11-08-2009
8	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	12-08-2008	11-08-2009
9	Pre-amplifier (1-18GHz)	Rohde & Schwarz	AFS42-00101 800-25-S-42	SEL0081	18-06-2009	17-06-2010
10	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33- 18002650-30- 8P-44	SEL0080	18-06-2009	17-06-2010
11	Band filter	Amindeon	82346	SEL0094	18-06-2009	17-06-2010
12	Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	15-06-2009	14-06-2010



Report No.: SZEMO09040196101

Page: 7 of 16

## 5.2 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C Humidity: 52 % RH Atmospheric Pressure: 1010 mbar

## 5.3 Test Procedure & Measurement Data

#### 5.3.1 Radiated Emissions

**Test Requirement:** FCC Part15 C Section 15.231, 15.209

Test Method: ANSI C63.4

Measurement 3m (Semi-Anechoic Chamber and OATS)

Distance:

**Test mode:** Keep the EUT in transmitting mode.

Frequency range: 30 MHz – 5.0GHz

Receiver setup: RBW=120kHz VBW=300KHz (30MHz to 1000MHz)

RBW=1MHz VBW=3MHz (Above 1GHz)

Limit:

According to FCC 15.231(e) requirement:

In addition to the provisions of 15.205, the field strength of emissions from intentional radiator operated under this section shall not exceed the following:

#### Fundamental and harmonics emission limits

Fundamental Frequency MHz	Field Strength of Fundamental (dBμV/m @ 3m)	Field Strength of Harmonics and Spurious Emissions (dBµV/m @ 3m)
433.99	72.87	52.87

Remark: The table above tighter limit applies at the band edges.



Report No.: SZEMO09040196101

Page: 8 of 16

#### **Test Procedure:**

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.
- 7. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

An initial pre-scan was performed in the 3m chamber using the spectrum analyzer in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bilog antenna with 2 orthogonal polarities.

The following test results were performed on the EUT:

1. Fundamental emission




Report No.: SZEMO09040196101


Page: 9 of 16

## **Configuration of Measurement:**

#### **Blow 1GHz**



#### **Above 1GHz**



"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEMO09040196101

Page: 10 of 16

#### Field Strength of Fundamental

#### Peak value:

Test Frequency	Peak (di	BμV/m)	Limits	Margi	n (dB)
(MHz)	Vertical	Horizontal	(dBμV/m)	Vertical	Horizontal
433.99MHz	55.40	35.69	92.87	37.47	57.18

#### Average value:

Average value = Peak value + PDCF

Ton time=0.5ms

Duty cycle= Ton time / T period = 0.5X31ms/100ms=0.155

PDCF=20 log(Duty cycle) =20\*(-0.943)= -16.19

Average value=55.40-16.19=39.21dBuv/m


Please see the diagrams below:




Report No.: SZEMO09040196101

Page: 11 of 16

#### Time slot:



Date: 6.MAY.2009 14:16:13



Date: 7.JUL.2009 12:58:02

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms-e-document.htm">www.sgs.com/terms-e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEMO09040196101

Page: 12 of 16

#### Test Frequency 30MHz-1GHz

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
37.760	0.60	11.95	28.11	29.53	13.97	40.00	-26.03
66.860	0.80	6.99	28.01	29.91	9.69	40.00	-30.31
110.510	1.23	8.57	27.77	30.28	12.31	43.50	-31.19
180.350	1.37	9.91	27.26	30.50	14.52	43.50	-28.98
777.870	3.14	22.01	27.01	32.25	30.39	46.00	-15.61

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
85.290	1.10	8.26	27.97	29.79	11.18	40.00	-28.82
106.630	1.22	8.77	27.81	30.44	12.62	43.50	-30.88
179.380	1.37	9.87	27.26	31.21	15.19	43.50	-28.31
264.740	1.74	12.61	26.85	31.39	18.89	46.00	-27.11
731.310	3.00	21.62	27.17	31.40	28.85	46.00	-17.15



Report No.: SZEMO09040196101

Page: 13 of 16

## Test frequency above 1GHz

#### Peak measurement

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polariza tion
1315	3.50	27.67	37.74	37.81	31.24	74.00	-42.76	V
1790	4.15	30.36	37.95	36.52	33.08	74.00	-40.92	V
2395	4.97	32.24	37.97	36.58	35.82	74.00	-38.18	V
3025	5.11	33.39	37.50	36.21	37.21	74.00	-36.79	V
3395	5.53	33.24	37.54	35.84	37.07	74.00	-36.93	V
1230	3.37	27.61	37.39	37.81	31.40	74.00	-42.60	Н
1720	4.06	29.82	37.97	37.84	33.75	74.00	-40.25	Н
2425	5.01	32.26	38.06	37.89	37.10	74.00	-36.90	Н
3360	5.50	33.25	37.53	37.18	38.40	74.00	-35.60	Н
4550	6.50	34.09	38.34	36.65	38.90	74.00	-35.10	Н

#### Average measurement

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polariza tion
1315	3.50	27.67	37.74	35.44	28.87	54.00	-25.13	V
1790	4.15	30.36	37.95	34.11	30.67	54.00	-23.33	V
2395	4.97	32.24	37.97	32.98	32.22	54.00	-21.78	V
3025	5.11	33.39	37.50	33.78	34.78	54.00	-19.22	V
3395	5.53	33.24	37.54	34.56	35.79	54.00	-18.21	V
1230	3.37	27.61	37.39	32.49	26.08	54.00	-27.92	Н
1720	4.06	29.82	37.97	35.58	31.49	54.00	-22.51	Н
2425	5.01	32.26	38.06	33.67	32.88	54.00	-21.12	Н
3360	5.50	33.25	37.53	35.49	36.71	54.00	-17.29	Н
4550	6.50	34.09	38.34	30.89	33.14	54.00	-20.86	Н



Report No.: SZEMO09040196101

Page: 14 of 16

According to the standards used, where limits are specified by agencies for both average and peak (or quasi-peak) detection, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

#### Remark:

According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.

TEST RESULTS: The unit does meet the FCC Part 15 C Section 15.231 requirements.



Report No.: SZEMO09040196101

Page: 15 of 16

## 5.3.2 Occupy Bandwidth

Test Requirement: FCC Part15 C

**Test Method:** ANSI C63.4 section 13 & FCC Part 2.1049

**Requirements:** 15.231 (c3) The bandwidth of the emission shall be no wider than

0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the


modulated carrier.

**Limit:** 15.231(c)

Method of A small sample of the transmitter output was fed into the Spectrum Analyzer and the attached plot was taken. The vertical is set to

10dB per division. The horizontal scale is set to 200KHz per division.

The graph as below: represents the emissions take for this device.



Date: 6.MAY.2009 14:09:47

The results: The unit does meet the FCC Part 15C Section 15.231 requirements.

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEMO09040196101

Page: 16 of 16


#### 5.3.3 Dwell time

Test Requirement: FCC Part15 C

**Test Method:** FCC Part15 C Section 15.231.

Requirements:

1. Regulation 15.231 (e) In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.



Date: 6.MAY.2009 14:30:35

The results: The unit does meet the FCC Part 15C Section 15.231 requirements.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."