

---

## REPORT ON

RF Exposure Assessment  
TCM Mobile Ltd. Wifi Sector Communication Unit  
Part Number TCM-BS-T001

---

**Doc Number 75901050 Report 01 Issue 1**

**September 2007**



Product Service





Choose certainty. Add value.

Commercial-in-Confidence

TUV Product Service Ltd, Octagon House, Concorde Way, Segensworth North,  
Fareham, Hampshire, United Kingdom, PO15 5RL  
Tel: +44 (0) 1489 558100. Website: [www.tuvps.co.uk](http://www.tuvps.co.uk); [www.babt.com](http://www.babt.com)

**REPORT ON** RF Exposure Assessment TCM Mobile Ltd. Wifi Sector Communication Unit  
Part Number TCM-BS-T001

Doc Number 75901050 Report 01 Issue 1

September 2007

**PREPARED FOR** TCM Mobile Ltd.  
11 Amal Street - Park Afeq  
Rosh Ha'ain  
48092 Israel

**ATTESTATION** The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields (10 MHz - 300 MHz) - General public. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s).

All reported calculations were carried out on a sample of equipment to demonstrate compliance with the applied test specification(s) the sample tested was found to comply with the requirements of the applied rules.

**PREPARED BY**   
A. Miller  
Principal Engineer

**APPROVED BY**   
M. Jenkins  
Authorised Signatory

**DATED** 27<sup>th</sup> September 2007



Product Service

## CONTENTS

Section	Page No
<b>1 Report Summary.....</b>	<b>3</b>
1.1 Status.....	4
1.2 Test Specifications .....	4
1.3 References .....	4
1.4 Summary .....	5
1.5 Required Minimum Separartion Distances.....	5
<b>2 Test Details.....</b>	<b>6</b>
2.1 Rationale for Assessment of the RF Exposure .....	7
2.2 Defined Limits .....	8
2.3 Establishing Wavelength and 1/4 Wavelength.....	8
2.4 Far Field Calculations.....	9
2.5 Field Representations.....	9
<b>3 Figures.....</b>	<b>10</b>
3.1 Field Representations.....	11
<b>4 Disclaimers and Copyright.....</b>	<b>12</b>
4.1 Disclaimers and Copyright.....	13



Product Service

## SECTION 1

### REPORT SUMMARY

#### SUMMARY

Based upon the supplied data for Wifi Sector Communication Unit Model Number TCM-BS-T001 and point of investigation being **21.0 cm** (0.210 m)

#### GENERAL PUBLIC LIMITS

The calculations have shown that they **meet** the General Public Exposure Levels described in the FCC 47 CFR § 1.1310 Guidelines

#### OCCUPATIONAL LIMITS

The calculations have shown that they **meet** the Occupational Exposure Levels described in the FCC 47CFR § 1.1310 Guidelines



Product Service

## 1.1 STATUS

<b>APPLICANT</b>	TCM Mobile Ltd.
<b>MANUFACTURING DESCRIPTION</b>	Wifi Sector Communication Unit
<b>PART NUMBER</b>	TCM-BS-T001
<b>FCC ID</b>	VN9BST001
<b>HARDWARE VERSION</b>	Rev-B

## 1.2 TEST SPECIFICATIONS

1. OET Bulletin 65 Edition 97-01 August 1997 - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

## 1.3 REFERENCES

2. National Council on Radiation Protection and Measurements (NRPC) - Report No. 86(1986) "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields".
3. FCC Guidelines for Evaluating exposure to RF Emissions - 47 CFR § 1.1310; 47 CFR § 1.1307(b) & 47 CFR § 80.83.
4. EN 50383:2002 - Basic standard for the calculation and measurement of electromagnetic field strength and SAR related to human exposure from radio base stations and fixed terminal stations for wireless telecommunication systems (110 MHz - 40 GHz).
5. IEEE Std C95.1-2005: IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3KHz to 300GHz.

## 1.4 SUMMARY

The equipment subject to the RF exposure assessment is a Wifi Sector Communication Unit part number TCM-BS-T001. The RF exposure assessment is based upon the following criteria:-

- The Wifi Sector Communication Unit operates in the frequency range of 2412 MHz to 2462 MHz, the numeric gain of the Wifi Sector Communication Unit is 13.000 gain.
- The length of the Wifi Sector Communication Unit is declared as 27.0 centimetres.
- TCM-BS-T001 radio power is a maximum 0.400 Watt. Based upon a maximum declared output power of 4W with a 10% duty cycle.
- The point of investigation is calculated to be 21.0 cm (0.210 m).

## 1.5 REQUIRED MINIMUM SEPARARTION DISTANCES

### Power Density Field 'S'

The minimum separation distance based upon occupational limit level for the Power Density field 'S' is:

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2} \quad \text{Transposed to find 'r' =} \quad r = \sqrt{\frac{PG_{(\theta, \phi)}}{4\pi S}}$$

$P = 400.0 \text{ mW}$ ;  $G = 13.000$ ;  $S = 5.000 \text{ mW/cm}^2$

Therefore  $r = 9.097 \text{ cm}$

The minimum separation distance based upon general public limit level for the Power Density field 'S' is:

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2} \quad \text{Transposed to find 'r' =} \quad r = \sqrt{\frac{PG_{(\theta, \phi)}}{4\pi S}}$$

$P = 400.0 \text{ mW}$ ;  $G = 13.000$ ;  $S = 1.000 \text{ mW/cm}^2$

Therefore  $r = 20.342 \text{ cm}$



Product Service

## **SECTION 2**

### **TEST DETAILS**

## 2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields.

The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in BS EN50383:2002 Clause 5.2; E-field or H-field calculation. The method of calculation used is defined in BS EN50383:2002; Clause 8.2.2, 8.2.3 and 8.2.4.

The calculated values have been compared with limits provided in the ICNIRP guidelines. Calculations can be made in three separate regions, based on distance from the antenna. These are called:-

- far-field region,
- radiating near-field region,
- reactive near-field region.

The theory that defines these regions is given in EN50383:2002 Annex A.

### Far-field region

As shown in EN50383 Annex A, the far-field calculations are accurate when the distance,  $r$ , from an antenna of length  $D$  to a point of investigation is greater than

$$r = \frac{2D^2}{\lambda}$$

Where,  $r$  is the distance from the antenna to the point of investigation.

### Radiating near-field region

The radiating near-field region of an antenna of length  $D$  as shown in EN50383 Annex A, this region is defined by

$$\frac{\lambda}{4} < r > \frac{2D^2}{\lambda}$$

### Reactive near-field region

The reactive near-field region of an antenna as shown in EN50383 Annex A, this region is defined by

$$r \leq \frac{\lambda}{4}$$

Where,  $r$  is the distance from the antenna to the point of investigation.

Recommend  $\lambda/4$  as the boundary between the radiated near-field and reactive near-field for RF exposure compliance assessment.



Product Service

## 2.2 DEFINED LIMITS

Normative Reference: ICNIRP Advice on Limiting Exposure to Electromagnetic Fields (0-300GHz). Table A4, Reference Levels for General Public Exposure to Time Varying Electric & Magnetic Fields. Vol 15 No.2. 2004.

Reference levels for occupational exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 2412.000 MHz

Power density (mW/cm<sup>2</sup>) = 5.000

Reference levels for general public exposure to time-varying electric and magnetic fields (unperturbed rms values)

At 2412.000MHz

Power density (mW/cm<sup>2</sup>) = 1.000

## 2.3 ESTABLISHING WAVELENGTH AND 1/4 WAVELENGTH

Frequency (MHz)	$\lambda = \frac{3 \times 10^8}{f}$		$\frac{\lambda}{4}$	
	m	cm	m	cm
2462.000	0.1219	12.19	0.0305	3.05
2437.000	0.1231	12.31	0.0308	3.08
2412.000	0.1244	12.44	0.0311	3.11

## 2.4 FAR FIELD CALCULATIONS

The following calculations are based on: dBi gain antenna

$P = 0.4$  (Power (Watts)) or  $400.0$  (Power milliwatts)

$G = 13.000$  (Numeric Gain)

$r =$  (Distance (meters)) or  $21.000$  (Distance (centimetres))

The power flux:

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2} \quad S = 0.938 \text{ mW/cm}^2$$

The electric field strength

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r} \quad E = 59.476 \text{ Eeff V/m}$$

The magnetic field strength

$$H = \frac{E}{\eta_0} \quad H = 0.158 \text{ A/m}$$

The calculations **meet** the General Public Exposure Levels described in the ICNIRP Guidelines

The calculations **meet** the Occupational Exposure Levels described in the ICNIRP Guidelines

## 2.5 FIELD REPRESENTATIONS




Figure 1 - This graph shows the radiating field representation and is not to scale

Worst case frequency 2412.000 MHz

The Reactive near-field region (from antenna) is less than.....: 3.046 cm

The Radiating near-field region is greater than.....: 3.046 cm

The Radiating near-field region is less than.....: 1.777 cm

The Far-field region is greater than.....: 1.777 cm



Product Service

## **SECTION 3**

### **FIGURES**

### 3.1 FIELD REPRESENTATIONS




Figure 2 - This graph shows the S field ( $\text{mW/cm}^2$ ) strength value with regards to distance from the Antenna (cm)



Product Service

## **SECTION 4**

### **DISCLAIMERS AND COPYRIGHT**



#### **4.1 DISCLAIMERS AND COPYRIGHT**

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of

TUV Product Service Limited

© 2007 TUV Product Service Limited