

EMC TEST REPORT

For

CAR CD AUDIO With BLUETOOTH

Model Number:CU3603

FCC ID: VNACU3603

Report Number : WT078002295

Test Laboratory	:	Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory Guangdong EMC Compliance Test Center
Site Location	:	Bldg. of Metrology &Quality Inspection, Longzhu Road, Shenzhen, Guangdong, China
Tel	:	0086-755-26941637, 26941529, 26941531
Fax	:	0086-755-26941545
Email	:	emclab@sohu.com

TABLE OF CONTENTS

TEST REPORT DECLARATION	4
1. TEST RESULTS SUMMARY	5
2. GENERAL INFORMATION	6
2.1. Report information	6
2.2. Laboratory Accreditation and Relationship to Customer	6
2.3. Measurement Uncertainty	7
3. PRODUCT DESCRIPTION	7
3.1. EUT Description	7
3.2. Related Submittal(s) / Grant (s)	7
3.3. Block Diagram of EUT Configuration	8
3.4. Operating Condition of EUT	8
3.5. Support Equipment List	8
3.6. Test Conditions	8
4. TEST EQUIPMENT USED	9
4.1. Test Equipment Used to Measure Conducted Disturbance	9
5. CONDUCTED DISTURBANCE TEST	10
5.1. Test Standard and Limit	10
5.2. Test Procedure	10
5.3. Test Arrangement	10
5.4. Test Data	10
6. MAXIMUM PEAK OUTPUT POWER	11
6.1. Test Standard and Limit	11
6.2. Test Procedure	11
6.3. Test Arrangement	11
6.4. Test Data	11
7. HOPPING CHANNEL 20 DB BANDWIDTH	12
7.1. Test Standard and Limit	12
7.2. Test Procedure	12
7.3. Test Arrangement	12
7.4. Test Data	12
8. 100KHZ BANDWIDTH OF BAND EDGES MEASUREMENT	15
8.1. Test Standard and Limit	15
8.2. Band Edge FCC 15.247(c) Limit	15
8.3. Test Procedure	15
8.4. Test Arrangement	15
8.5. Test Data	15
9. SPURIOUS RADIATED EMISSION TEST	24
9.1. Test Standard and Limit	24
9.2. Band Edge FCC 15.247(c) Limit	24
9.3. Test Procedure	24
9.4. Test Arrangement	24
9.5. Test Data	24

10.	NUMBER OF HOPPING FREQUENCY.....	29
10.1.	Test Standard and Limit.....	29
10.2.	Band Edge FCC 15.247(c) Limit	29
10.3.	Test Procedure	29
10.4.	Test Arrangement.....	29
10.5.	Test Data	29
11.	FREQUENCY SEPARATION	32
11.1.	Test Standard and Limit.....	32
11.2.	Band Edge FCC 15.247(c) Limit	32
11.3.	Test Procedure	32
11.4.	Test Arrangement.....	32
11.5.	Test Data	32
12.	TIME OF OCCUPANCY (DWELL TIME).....	34
12.1.	Test Standard and Limit.....	34
12.2.	Band Edge FCC 15.247(c) Limit	34
12.3.	Test Procedure	34
12.4.	Test Arrangement.....	34
12.5.	Test Data	34
13.	ANTENNA REQUIREMENT	36
13.1.	Standard Applicable.....	36
13.2.	Antenna Connected Construction	36
APPENDIX I TEST PHOTO.....		37
APPENDIX II EUT PHOTO		39

TEST REPORT DECLARATION

Applicant : Autosound Electronic (HK) Limited
Address : 12/F., Meeco Ind. Bldg., 53-55 Au Pui Wan St., Fo Tan, Shatin, N.T., Hong Kong
Manufacturer : Autosound Electronic (HK) Limited
Address : No.2, Fuk Lung Ind. Estates, Shuk Pai Town, Dongguan, China
EUT Description : CAR CD AUDIO With BLUETOOTH
Model Number : CU3603
FCC ID Number : VNACU3603

Test Standards:

FCC Part 15 15.247

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in fcc test method **DA 00-705** and the energy emitted by the sample EUT tested as described in this report is in compliance with FCC Rules Part 15.247.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Tested by: Winnie Hou Date: Sep.15,2007

(Winnie Hou)

Checked by: Louis Lin Date: Sep.15,2007

(Louis Lin)

Approved by: Peter Lin Date: Sep.15,2007

(Peter Lin)

1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Part 15	Requirement	Result Pass/Fail	Comments
15.207(a)	CONDUCTED Disturbance test	Pass	---
15.247(b)(1)	Maximum Peak Output Power	Pass	---
15.247(a)(1)	20 dB Bandwidth	Pass	---
15.247 (c)	100kHz Out of band & Band Edge measurements	Pass	---
15.209(a) (f)	Spurious Emission	Pass	---
15.247(a)(1)	Frequency Separation	Pass	---
15.247(a)(1)(iii)	Number of the Hopping Frequency	Pass	---
15.247(a)(1)(iii)	Time of Occupancy	Pass	---
15.203, 15.247(b)(4)(i)	Antenna Requirement	Pass	---

2. GENERAL INFORMATION

2.1. Report information

- 2.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.
- 2.1.2. The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 2.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at Bldg. of Metrology & Quality Inspection, Longzhu Road, Nanshan District, Shenzhen, Guangdong, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (**CNAS**) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is listed in the United States of American Federal Communications Commission (**FCC**), and the registration number are **97379**(open area test site) and **274801**(semi anechoic chamber).

The Laboratory is listed in Voluntary Control Council for Interference by Information Technology Equipment (**VCCI**), and the registration number are **R-1974**(open area test site) , **R-1966**(semi anechoic chamber),**C-2117**(mains ports conducted interference measurement) and **T-180**(telecommunication ports conducted interference measurement).

The Laboratory is registered to perform emission tests with Industry Canada (**IC**), and the registration number is **IC4174**.

TUV Rhineland accredits the Laboratory for conformance to IEC and EN standards, the registration number is **E2024086Z02**.

Measurement Uncertainty

2.3. Measurement Uncertainty

Conducted Disturbance : 9kHz~30MHz 3.5dB

Radiated Disturbance: 30MHz~1000MHz 4.5dB
1GHz~18GHz 4.6dB

3. PRODUCT DESCRIPTION

3.1. EUT Description

Description : CAR CD AUDIO With BLUETOOTH

Manufacturer : Autosound Electronic (HK) Limited

Model Number : CU3603

Input Power : DC 12V supply by Battery

Operate Frequency : 2402-2480MHz

Channel Spacing : 1MHz

Antenna Designation : integrate

The EUT include a bluetooth module.

A major technical descriptions of EUT is described as following:


- A). Operation Frequency: 2402 – 2480MHz, 79 channels
- B). Modulation type: Frequency Hopping Spread Spectrum (FHSS)
- C). Antenna Designation: 1.0 dBi, Non-User Replaceable (Fixed)

The test report issued for Blue tooth function only.

3.2. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: VNACU3603 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

3.3. Block Diagram of EUT Configuration



3.4. Operating Condition of EUT

Mode 1: channel low (2402MHz)

Mode 2: channel low (2442MHz)

Mode 3: channel low (2480MHz)

3.5. Support Equipment List

Table 2 Support Equipment List

Name	Model No	S/N	Manufacturer	Used “√”
---	---	---	---	---
---	---	---	---	---
---	---	---	---	---

3.6. Test Conditions

Date of test: Sep11-14, 2007

Date of EUT Receive: Sep.11, 2007

Temperature: 24 °C

Relative Humidity: 55%

4. TEST EQUIPMENT USED

4.1. Test Equipment Used to Measure Conducted Disturbance

Table 3 Test Equipment List

No.	Equipment	Manufacturer	Model No.	Last Cal.	Cal. Interval
SB2603	EMI Test Receiver	Rohde & Schwarz	ESCS30	Jan.25, 2007	1 Year
SB3321	AMN	Rohde & Schwarz	ESH2-Z5	Jan.25, 2007	1 Year
SB2604	AMN	Rohde & Schwarz	ESH3-Z5	Jan.25, 2007	1 Year
SB3436	EMI Test Receiver	Rohde & Schwarz	ESI26	Jan.25, 2007	1 Year
SB3440	Bilog Antenna	Chase	CBL6112B	Jan.25, 2007	1 Year
SB3435	Horn Antenna	Rohde & Schwarz	HF906	Jan.25, 2007	1 Year
SB3434	Horn Antenna	Rohde & Schwarz	HF906	Jan.25, 2007	1 Year
SB3435/01	Amplifier(1-18GH z)	Rohde & Schwarz	---	Jan.25, 2007	1 Year
SB3435/02	Amplifier(18-40G Hz)	Rohde & Schwarz	---	May.05, 2007	1 Year
SB3435/03	Horn Antenna	Rohde & Schwarz	AT4560	May.05, 2007	1 Year
SB3450/01	3m Semi-anechoic chamber	Albatross Projects	9X6X6	Jan 25,2007	1 Year
SB2597/01	Dipole Antenna	Schwarzbeck	VHAP	Jan 30,2005	3 Years
SB2597/02	Dipole Antenna	Schwarzbeck	UHAP	Jan 30,2005	3 Years
SB3438	Signal generator	Rohde & Schwarz	SMR20	Jan.25, 2007	1 Year
SB3732	Tem Chamber	Qingsheng	THS-C7C±1 00	Sep 25,2006	1 Year
SB2599	Spectrum Analyzer	Anritsu	MS2661C	Jan 25,2007	1 Year
SB3174	Antenna	Schwarzbeck	VUBA9117	Jan 25,2007	3 Year
SB3441	Communication tester	Rohde & Schwarz	CMU200	Apr.10,2007	1 Year

5. CONDUCTED DISTURBANCE TEST

5.1. Test Standard and Limit

5.1.1. Test Standard

FCC Part 15 15.207

5.1.2. Test Limit

Table 4 Conducted Disturbance Test Limit (Class B)

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

- Decreasing linearly with logarithm of the frequency
- The lower limit shall apply at the transition frequency.

5.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions form both sides of AC line. According to the requirements in Section 7 and 13 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.

5.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

5.4. Test Data

N/A

6. MAXIMUM PEAK OUTPUT POWER

6.1. Test Standard and Limit

6.1.1. Test Standard

FCC Part15 15.247 (b)

6.1.2. Test Limit

Table 5 Bandwidth Limit

Frequency MHz	Channels	Types of Devices	Power
2400-2483.5	= 75	Hopping	1 Watt

6.2. Test Procedure

Remove the antenna from the EUT and then connect the transmitter output to the power meter via a suitable attenuator. Set the EUT transmitting continuously to each of low, middle, and high frequency.

6.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

6.4. Test Data

Table 6 Test data

Channel	Frequency (MHz)	Reading (dBm)	Limit	Result
Low	2402	-11.7	1W (30dBm)	Pass
Middle	2442	-11.9	1W (30dBm)	Pass
High	2480	-10.7	1W (30dBm)	Pass

7. HOPPING CHANNEL 20 DB BANDWIDTH

7.1. Test Standard and Limit

7.1.1. Test Standard

FCC part 15 15.247 (a)

7.1.2. Test Limit

For frequency hopping systems operating in the 2400MHz-2483.5 MHz no limit for 20dB bandwidth.

7.2. Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Communication tester.
3. used the spectrum function to measure the bandwidth.



7.3. Test Arrangement


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

7.4. Test Data

Table 7 Test data

Channel	Frequency (MHz)	20 dB Bandwidth
Low	2402	0.862MHz
Mid	2441	0.861MHz
High	2480	0.862MHz





8. 100KHZ BANDWIDTH OF BAND EDGES MEASUREMENT

8.1. Test Standard and Limit

8.1.1. Test Standard

FCC Part 15 15.247(c)

8.2. Band Edge FCC 15.247(c) Limit

According to § 15.247(c), in any 100 KHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

8.3. Test Procedure


1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW=300kHz, VBW=1MHz, Span=20MHz, Sweep = auto Mark Peak, .
5. Repeat above procedures until all frequency measured were complete.

8.4. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

8.5. Test Data


Frequency Hopping



UB-8H

Date: 6.AUG.2007 21:08:55


RS



UB-8H

Date: 6.AUG.2007 21:12:02


Frequency Hopping Stop



UB-8H

Date: 6.AUG.2007 21:17:01

RS



UB-8H

Date: 6.AUG.2007 21:15:59

The setting of the spectrum analyzer is
Detector=Peak RBW=1MHz RBW=3MHz
Detector=AV RBW=1MHz RBW=10Hz


RADIATED EMISSION

EUT: CU3603

Manufacturer:


Operating Condition: TX 2402MHz

Test Specification: Horizontal




RADIATED EMISSION

EUT: CU3603
Manufacturer:
Operating Condition: TX 2402MHz
Test Specification: Vertical




RADIATED EMISSION

EUT: CU3603
Manufacturer:
Operating Condition: TX 2480MHz
Test Specification: HORIZONTAL



RADIATED EMISSION

EUT: CU3603
Manufacturer:
Operating Condition: TX 2480MHz
Test Specification: Vertical



9. SPURIOUS RADIATED EMISSION TEST

9.1. Test Standard and Limit

9.1.1. Test Standard

FCC Part 15 15.247(c)

9.2. Band Edge FCC 15.247(c) Limit

According to § 15.247(c), all other emissions outside these bands shall not exceed the general radiated emission limits specified in § 15.209(a). And according to § 15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

9.3. Test Procedure

1. The radiated emission tests were performed in the 3 meter open-test site, using the setup in accordance with the ANSI C63.4-2003.
2. The EUT was put in the front of the test table. The peripherals was placed on the side of the host system. The rear of the EUT and peripherals were placed flushed with the rear of the tabletop.
3. The spacing between the peripherals was 10 centimeters.
4. External I/O cables were draped along the edge of the test table and bundle when necessary.
5. the setting of the EMI test receiver is
30-1000MHz Detector=QP RBW=120kHz VBW=300kHz
1-25GHz Detector=Peak RBW=1MHz RBW=3MHz
Detector=AV RBW=1MHz RBW=10Hz

9.4. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

9.5. Test Data

Radiated Emission Data :

Table 8 Test data

Low Channel (2402MHz)

<i>Ambient temperature: 24°C</i> <i>Relative humidity: 53 %</i>						
<i>Frequency</i> <i>MHz</i>	<i>Emission</i> <i>(dBuV/m)</i>	<i>Read Value</i> <i>(dBuV)</i>	<i>Correction Factor</i> <i>(dB/m)</i>	<i>Polarization</i> <i>n</i>	<i>Limits</i> <i>(dBuV/m)</i>	<i>Detector</i>
32.300	35.3	16.8	18.5	V	40.0	QP
79.700	34.0	23.6	10.4	V	40.0	QP
323.100	33.0	15.7	17.3	V	46.0	QP
456.100	34.0	13.5	20.5	V	46.0	QP
168.100	30.0	17.2	12.8	H	43.5	QP
600.889	33.4	10.5	22.9	H	46.0	QP
4804.120	45.6	43.3	2.3	H	74.0	Peak
4804.120	40.6	38.3	2.3	H	54.0	AV
4804.121	45.0	42.7	2.3	V	74.0	Peak
4804.121	40.0	37.7	2.3	V	54.0	AV
7206.300	47.7	39.6	8.1	H	74.0	Peak
7206.300	43.2	35.1	8.1	H	54.0	AV
7206.300	47.0	38.9	8.1	V	74.0	Peak
7206.300	42.5	34.4	8.1	V	54.0	AV
9608.230	49.3	40.0	9.3	H	74.0	Peak
9608.230	45.0	35.7	9.3	H	54.0	AV
9608.230	48.8	39.5	9.3	V	74.0	Peak
9608.230	44.5	35.2	9.3	V	54.0	AV

Note :

1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)+Amplifier Factor(dB)
3. The other emission levels were very low against the limit(>15dB to limit).

Table 9 Test data

Mid Channel (2442MHz)

Ambient temperature: 24° C Relative humidity: 53 %						
Frequency MHz	Emission (dBuV/m)	Read Value (dBuV)	Correction Factor (dB/m)	Polarization	Limits (dBuV/m)	Note
32.310	35.3	16.8	18.5	V	40.0	QP
79.702	34.2	23.8	10.4	V	40.0	QP
323.100	33.0	15.7	17.3	V	46.0	QP
456.120	34.0	13.5	20.5	V	46.0	QP
168.100	30.4	17.6	12.8	H	43.5	QP
600.902	33.4	10.5	22.9	H	46.0	QP
4884.150	45.7	43.4	2.3	H	74.0	Peak
4884.150	40.7	38.4	2.3	H	54.0	AV
4884.150	45.1	42.8	2.3	V	74.0	Peak
4884.150	40.1	37.8	2.3	V	54.0	AV
7326.305	47.7	39.5	8.1	H	74.0	Peak
7326.305	43.2	35.1	8.1	H	54.0	AV
7326.305	46.9	38.8	8.1	V	74.0	Peak
7326.305	42.4	34.3	8.1	V	54.0	AV
9768.302	49.4	40.1	9.3	H	74.0	Peak
9768.302	45.1	35.8	9.3	H	54.0	AV
9768.302	48.7	39.4	9.3	V	74.0	Peak
9768.302	44.4	35.1	9.3	V	54.0	AV

Note :

1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)+Amplifier Factor(dB)
3. The other emission levels were very low against the limit(>15dB to limit).

Table 10 Test data

High Channel (2480M)

<i>Ambient temperature: 24° C</i> <i>Relative humidity: 53 %</i>						
<i>Frequency</i> <i>MHz</i>	<i>Emission</i> <i>(dBuV/m)</i>	<i>Read Value</i> <i>(dBuV)</i>	<i>Correction Factor</i> <i>(dB/m)</i>	<i>Polarization</i> <i>n</i>	<i>Limits</i> <i>(dBuV/m)</i>	<i>QP</i>
32.310	35.3	16.8	18.5	V	40.0	QP
79.720	34.3	23.9	10.4	V	40.0	QP
323.120	33.0	15.7	17.3	V	46.0	QP
456.100	34.3	13.8	20.5	V	46.0	QP
168.110	30.5	17.7	12.8	H	43.5	QP
600.889	33.3	10.4	22.9	H	46.0	Peak
4960.100	45.6	43.3	2.3	H	74.0	AV
4960.100	40.6	38.3	2.3	H	54.0	Peak
4960.100	45.0	42.7	2.3	V	74.0	AV
4960.100	40.0	37.7	2.3	V	54.0	Peak
7440.300	47.3	39.2	8.1	H	74.0	AV
7440.300	43.0	34.9	8.1	H	54.0	Peak
7440.300	46.8	38.7	8.1	V	74.0	AV
7440.300	42.5	34.4	8.1	V	54.0	Peak
9920.250	49.6	40.3	9.3	H	74.0	AV
9920.250	45.1	35.8	9.3	H	54.0	Peak
9920.250	49.0	39.7	9.3	V	74.0	AV
9920.250	44.5	35.2	9.3	V	54.0	QP

Note :

1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)+Amplifier Factor(dB)
3. The other emission levels were very low against the limit(>15dB to limit).

Table 11 **Restricted Band Radiated Emission Data**

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	
12.51975	-	3345.8 - 3358	
12.52025	240 - 285	3600 - 4400	
12.57675	-		
12.57725	322 - 335.4		
13.36 - 13.41			

All the emission of the above band were less than the limit 20dB.

10. NUMBER OF HOPPING FREQUENCY

10.1. Test Standard and Limit

10.1.1. Test Standard

FCC Part 15 15.247(c)

10.2. Band Edge FCC 15.247(c) Limit

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

10.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = auto.
4. Set the spectrum analyzer as RBW=300kHz, VBW=1MHz,
5. Max hold, view and count how many channel in the band.

10.4. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

10.5. Test Data

The nominal channel spacing of the Bluetooth system is 1Mhz independent of the operating mode.

The maximum “initial carrier frequency tolerance” which is allowed for Bluetooth is $f_{center} = 75 \text{ kHz}$.


This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/07-E) for three frequencies (2402, 2442, 2480 MHz).

Additionally an example for the channel separation is given in the test report

Table 12 Test data

Total No of hopping channel	Limit (CH)	Measurement result (CH)	Result
	>15	79	Pass


RS



UB-8H

Date: 18.JUL.2007 12:28:03

RS



UB-8H

Date: 18.JUL.2007 12:32:10

11. FREQUENCY SEPARATION

11.1. Test Standard and Limit

11.1.1. Test Standard

FCC Part 15 15.247(c) :2006

11.2. Band Edge FCC 15.247(c) Limit

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 20dB bandwidth of the hopping channel, whichever is greater.

11.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel .
4. Set the spectrum analyzer as RBW=300kHz, VBW=1MHz, Adjust Span to 5 MHz, Sweep = auto.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

11.4. Test Arrangement


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

11.5. Test Data

Table 13 Test data

Channel separation	Limit	Result
MHz	kHz	
1.010	$\geq 25\text{KHz}$ or $2/3 \times 20 \text{ dB}$ bandwidth	Pass

RS



UB-8H

Date: 18.JUL.2007 12:40:36

12. TIME OF OCCUPANCY (DWELL TIME)

12.1. Test Standard and Limit

12.1.1. Test Standard

FCC Part 15 15.247(c):2006

12.2. Band Edge FCC 15.247(c) Limit

According to § 15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz.

The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds

multiplied by the number of hopping channel employed.

12.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=100KHz, Span = 0Hz , Adjust Sweep = 2.5ms.
5. Repeat above procedures until all frequency measured were complete.

.

12.4. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

12.5. Test Data


The EUT working on DH1 mode only.

The dwell time of 0.172 s within a 30 second period in data mode is independent from the packet type (packet length). The calculation for a 30 second period is as follows:

Dwell time = time slot length * hop rate / number of hopping channels *30s

A period time = 0.4 (ms) * 79 = 31.6 (s)

DH1 time slot = 0.125 (ms) * (1600/(2*79)) * 31.6 = 40.0 (ms)



UB-8H

Date: 18.JUL.2007 12:38:29

13. ANTENNA REQUIREMENT

13.1. Standard Applicable

For intentional device, according to § 15.203, an intentional radiator shall be designed to ensure that no

antenna other than furnished by the responsible party shall be used with the device.

And according to § 15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively


for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

13.2. Antenna Connected Construction

The directional gains of antenna used for transmitting is 1.0 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Please see EUT photo for details.

APPENDIX I TEST PHOTO

Photo 1 Radiated Emission Test



APPENDIX II EUT PHOTO

Photo 1 Appearance of EUT



Photo 2 Appearance of EUT




Photo 4 Inside of EUT




Photo 5 Inside of EUT



Photo 6 Inside of EUT




Photo 7 Inside of EUT




Photo 8 Inside of EUT




Photo 9 Inside of EUT




Photo 10 Inside of EUT




Photo 11 Inside of EUT




Photo 12 Inside of EUT




Photo 13 Inside of EUT




Photo 14 Inside of EUT




Photo 15 Inside of EUT

