



EMI - TEST REPORT

- FCC Part 15.249, RSS210 -

Type / Model Name : OPUS 4 (internal development name), SONNET 2 / SONNET 2 EAS

(market name), product codes: Me1510, Me1511, Me1512, Me1513 /
Me1520, Me1521, Me1522, Me1523

Product Description : Audio processor for cochlear implant including an inductive remote

control receiver and a 2.4 GHz transceiver with integral antenna

Applicant : MED-EL Elektromedizinische Geraete GmbH

Address : Fuerstenweg 77a

6020 INNSBRUCK, AUSTRIA

Manufacturer : MED-EL Elektromedizinische Geraete GmbH

Address : Fuerstenweg 77a

6020 INNSBRUCK, AUSTRIA

Test Result according to the standards listed in clause 1 test standards:

POSITIVE

Test Report No. :

T42255-03-00KS

28. February 2019

Date of issue



Deutsche
Akkreditierungsstelle
D-PL-12030-01-01
D-PL-12030-01-02

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test results
without the written permission of the test laboratory.



FCC ID: VNP-ME1500

IC: 11986A-ME1500

Contents

1 TEST STANDARDS	3
2 EQUIPMENT UNDER TEST	4
2.1 Photo documentation of the EUT – See ATTACHMENT A	4
2.2 General remarks	4
2.3 Equipment category	4
2.4 Short description of the equipment under test (EUT)	4
2.5 Operation frequency and channel plan	5
2.6 EUT operation modes	5
2.7 Antenna	5
2.8 Power supply system utilised	6
2.9 Peripheral devices and interface cables	6
2.10 Determination of worst case conditions for final measurement	6
3 TEST RESULT SUMMARY	7
3.1 Final assessment	7
4 TEST ENVIRONMENT	8
4.1 Address of the test laboratory	8
4.2 Environmental conditions	8
4.3 Statement of the measurement uncertainty	9
4.4 Measurement protocol for FCC and ISED	10
5 TEST CONDITIONS AND RESULTS	12
5.1 AC power line conducted emissions	12
5.2 Field strength of fundamental	12
5.3 Out-of-band emission, radiated	14
5.4 EBW and OBW	24
5.5 Correction for pulse operation (duty cycle)	30
5.6 Antenna application	32
6 USED TEST EQUIPMENT AND ACCESSORIES	33

ATTACHMENT A as separate supplement



FCC ID: VNP-ME1500

IC: 11986A-ME1500

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules and Regulations Part 15, Subpart A - General (December, 2018)

Part 15, Subpart A, Section 15.31	Measurement standards
Part 15, Subpart A, Section 15.33	Frequency range of radiated measurements
Part 15, Subpart A, Section 15.35	Measurement detector functions and bandwidths

FCC Rules and Regulations Part 15, Subpart C - Intentional Radiators (December, 2018)

Part 15, Subpart C, Section 15.203	Antenna requirement
Part 15, Subpart C, Section 15.204	External radio frequency power amplifiers and antenna modifications
Part 15, Subpart C, Section 15.205	Restricted bands of operation
Part 15, Subpart C, Section 15.207	Conducted limits
Part 15, Subpart C, Section 15.209	Radiated emission limits, general requirements
Part 15, Subpart C, Section 15.249	Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz

ANSI C63.10: 2013 Testing Unlicensed Wireless Devices

ETSI TR 100 028 V1.3.1: 2001-03 Electromagnetic Compatibility and Radio Spectrum Matters (ERM); Uncertainties in the Measurement of Mobile Radio Equipment Characteristics—Part 1 and Part 2



FCC ID: VNP-ME1500

IC: 11986A-ME1500

2 EQUIPMENT UNDER TEST

2.1 Photo documentation of the EUT – See ATTACHMENT A

2.2 General remarks

The EUT contains an inductive remote control receiver and a 2.4 GHz transceiver with integral antenna. The radio frequency of the inductive link is 9.07 kHz, the 2.4 GHz transceiver operates in the frequency band 2.400 GHz - 2.4835 GHz.

In this test report, only the Bluetooth Low Energy Mode is considered.

2.3 Equipment category

Bluetooth Low Energy, portable equipment.

2.4 Short description of the equipment under test (EUT)

The OPUS 4 (internal development name) is an audio processor for a MED-EL cochlear implant including an inductive remote control receiver and a 2.4 GHz transceiver with integral antenna.

Market name: SONNET 2 / SONNET 2 EAS

Product codes: Me1510, Me1511, Me1512, Me1513 / Me1520, Me1521, Me1522, Me1523*.

The OPUS 4 is a medical device similar to a hearing aid. It is worn behind the ear, converts acoustic signals and drives an implanted MED-EL cochlear implant which – based on the information from the audio processor – directly stimulates the acoustic nerve in the inner ear to evoke auditory sensations.

The inductive remote control receiver picks up commands from an external remote control (FineTuner, not part of this testing) which is an accessory to the OPUS 4 that allows the user to modify various parameters as e.g. volume or microphone sensitivity of the OPUS 4.

Similar to the inductive remote control receiver the 2.4 GHz transceiver can receive commands from an external device (e.g. remote control, remote programmer etc.). Additionally, it can transmit acknowledge messages to this external device (the external device is currently under development and not part of this testing).

* The only difference between the devices with the product code Me152x (x = 0, 1, 2, or 3) and the devices with the product code Me151x is that the devices with the product code Me151x do not contain acoustic hearing aid functionality, i.e. do not contain an acoustic only output ("loudspeaker"). The devices with the product code Me152x are referred to as EAS (electric acoustic stimulation) devices. The product code of the control unit determines the product code of the entire audio processor.

The sub variants Me1510, Me1511, Me1512, and Me1513 do not differ in hardware and / or firmware, they just differ in product code. The same is true for the sub variants Me1520, Me1521, Me1522, and Me1523, i.e. they do not differ in hardware and / or firmware, they just differ in product code. These different sub variants are only introduced for marketing and sales purposes. Given the above, testing of only the variant Me1520 is sufficient and representative for all variants.

Number of tested samples: 1 x OPUS 4 CPU EAS (Me1520), ser. no. 000246

The following peripheral devices were used during the measurements:

Battery pack: 1 x SONNET Battery Pack (Ma060106), ser. no. 049645

Coil: 1 x DL Coil, ser. No. 015444



FCC ID: VNP-ME1500

IC: 11986A-ME1500

2.5 Operation frequency and channel plan

The operating frequency is 2400 MHz to 2483.5 MHz.

Channel	Frequency	Channel	Frequency
37	2402	18	2442
0	2404	19	2444
1	2406	20	2446
2	2408	21	2448
3	2410	22	2450
4	2412	23	2452
5	2414	24	2454
6	2416	25	2456
7	2418	26	2458
8	2420	27	2460
9	2422	28	2462
10	2424	29	2464
38	2426	30	2466
11	2428	31	2468
12	2430	32	2470
13	2432	33	2472
14	2434	34	2474
15	2436	35	2476
16	2438	36	2478
17	2440	39	2480

Note: the marked frequencies are determined for final testing.

2.6 EUT operation modes

The equipment under test was operated during the measurement under the following conditions:

- Cont. TX at CH37, CH17 and CH39; packet payload length: 37 octets; packet payload: PRBS9

-

-

2.7 Antenna

The following antennas shall be used with the EUT:

Number	Type	Certification name	Plug	f-range	Gain (dBi)
1	Chip antenna	Fractus FR05-S1-N-0-110	none	2.4 GHz – 2.5 GHz	0.2



FCC ID: VNP-ME1500

IC: 11986A-ME1500

2.8 Power supply system utilised

Power supply voltage, V_{nom} : 2.3 VDC Battery

2.9 Peripheral devices and interface cables

The following peripheral devices and interface cables are connected during the measurements:

- _____ Model : _____
- _____ Model : _____
- _____ Model : _____

2.10 Determination of worst case conditions for final measurement

Measurements have been made in all three orthogonal axes of the EUT to locate at which position the EUT produces the maximum of the emissions.

The EUT uses GFSK and provides following data rate:

1 Mbps (Mbps = *Megabits per second*)

For the final test the following channels and test modes are selected:

Standard	Available channels	Tested channels	Power setting	Modulation	Data rate
BT 4.2 LE	00 to 39	37, 17, 39	4 dBm	GFSK	1000 kbps

2.10.1 Test jig

No special test jig was used.

2.10.2 Test software

The EUT provides the Bluetooth Direct Test Mode (DTM) as specified in the Bluetooth Core Specification 4.2 Vol 6 Part F. The DTM allows a continuous TX mode at a selected frequency. Firmware in the EUT: opus4_wm_2_0_0_DTM



FCC ID: VNP-ME1500

IC: 11986A-ME1500

3 TEST RESULT SUMMARY

Operating in the 2400 MHz – 2483.5 MHz band:

FCC Rule Part	RSS Rule Part	Description	Result
15.35(c)	RSS-Gen, 8.2	Pulsed operation	passed
15.203	RSS-Gen, 6.8	Antenna requirement	passed
15.204	RSS-Gen, 8.3	External radio frequency power amplifiers	not applicable
15.205(a)	RSS-Gen, 8.10	Emissions in restricted bands	passed
15.207(a)	RSS-Gen, 8.8	AC power line conducted emissions	not applicable
15.215(c)	-	EBW	passed
-	RSS-Gen, 6.7	OBW	passed
15.249(a)	RSS-210, B10(a)	Field strength of fundamental	passed
15.249(d)	RSS-210, B10(b)	Out-of-band emission, radiated	passed
-	RSS-Gen, 6.11	Transmitter frequency stability	not applicable

The mentioned RSS Rule Parts in the above table are related to:

RSS-Gen, Issue 5, April 2018

RSS-210, Issue 9, August 2016

3.1 Final assessment

The equipment under test fulfills the EMI requirements cited in clause 1 test standards.

Date of receipt of test sample : acc. to storage records

Testing commenced on : 01 February 2019

Testing concluded on : 14 February 2019

Checked by: Tested by:

Klaus Gegenfurtner
Teamleader Radio

Kathrin Schiebl
Radio Team



FCC ID: VNP-ME1500

IC: 11986A-ME1500

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

CSA Group Bayern GmbH
Ohmstrasse 1-4
94342 STRASSKIRCHEN
GERMANY

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 86-106 kPa



FCC ID: VNP-ME1500

IC: 11986A-ME1500

4.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. It is noted that the expanded measurement uncertainty corresponds to the measurement results from the standard measurement uncertainty multiplied by the coverage factor $k = 2$. The true value is located in the corresponding interval with a probability of 95 %. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16-4-2 / 11.2003 „Uncertainties, statistics and limit modelling – Uncertainty in EMC measurements“ and is documented in the quality system acc. to DIN EN ISO/IEC 17025. For all measurements shown in this report, the measurement uncertainty of the test laboratory, CSA Group Bayern GmbH, is below the measurement uncertainty as defined by CISPR. Therefore, no special measures must be taken into consideration with regard to the limits according to CISPR. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Measurement Type	Range	Confidence Level	Calculated Uncertainty
AC power line conducted emissions	0.15 MHz to 30 MHz	95%	± 3.29 dB
EBW and OBW	2400 MHz to 30000 MHz	95%	$\pm 2.5 \times 10^{-7}$
Output power ERP, radiated	1000 MHz to 7000 MHz	95%	± 2.71 dB
Field strength of the fundamental	1000 MHz to 7000 MHz	95%	± 2.71 dB
Power spectral density	2400 MHz to 3000 MHz	95%	± 0.62 dB
Spurious Emissions, conducted	9 kHz to 10000 MHz	95%	± 2.15 dB
Spurious Emissions, conducted	10000 MHz to 40000 MHz	95%	± 3.47 dB
Spurious Emissions, radiated	9 kHz to 30 MHz	95%	± 3.53 dB
Spurious Emissions, radiated	30 MHz to 1000 MHz	95%	± 4.44 dB
Spurious Emissions, radiated	1000 MHz to 30000 MHz	95%	± 2.34 dB
Spurious Emissions, radiated	30000 MHz to 40000 MHz	95%	± 5.13 dB



FCC ID: VNP-ME1500

IC: 11986A-ME1500

4.4 Measurement protocol for FCC and ISED

4.4.1 General information

The Open Area test site is a listed Open Site under the Canadian Test-Sites File-No:

IC 3009A-1

The Anechoic chamber is a listed test site under the Canadian Test-Sites File-No:

IC 3009A-2

4.4.2 General Standard information

The test methods used comply with ANSI C63.10 - "Testing Unlicensed Wireless Devices".

4.4.2.1 Justification

The equipment under test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral using the appropriate impedance characteristic or left unterminated. Where appropriate, cables are manually manipulated with respect to each other thus obtaining maximum disturbances from the unit.

4.4.2.2 Radiated emission (electrical field 30 MHz - 1 GHz)

Spurious emissions from the EUT are measured in the frequency range of 30 MHz to 1000 MHz using a tuned receiver and appropriate broadband linearly polarised antennas. Measurements between 30 MHz and 1000 MHz are made with 120 kHz/6 dB bandwidth and quasi-peak detection. Table top equipment is placed on a 1.0 X 1.5 m non-conducting table 80 centimetres above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. The setup of the equipment under test is established in accordance with ANSI C63.10. The interface cables that are closer than 40 centimetres to the ground plane are bundled in the center in a serpentine fashion so that they are at least 40 centimetres from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screened room located outside the test area. The antenna is positioned 3, 10 or 30 metres horizontally from the EUT and is repeated vertically. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 metres and the EUT is rotated 360 degrees.

The final level in dB μ V/m is calculated by taking the reading from the EMI receiver (Level dB μ V) and adding the correction factors and cable loss factor (dB). The FCC or CISPR limit is subtracted from this result in order to provide the limit margin listed in the measurement protocol.

The resolution bandwidth setting:

30 MHz – 1000 MHz: RBW: 120 kHz

Example:

Frequency Delta (MHz)	Level (dB μ V)	+	Factor (dB)	=	Level (dB μ V/m)	-	CISPR Limit (dB μ V/m)	=	(dB)
719.0	75.0	+	32.6	=	107.6	-	110.0	=	-2.4



FCC ID: VNP-ME1500

IC: 11986A-ME1500

4.4.2.3 Radiated emission (electrical field 1 GHz - 40 GHz)

Radiated emissions from the EUT are measured in the frequency range 1 GHz up to the maximum frequency as specified in 47 CFR Part 15, Subpart A, Section 15.33, using a spectrum analyser and appropriate linearly polarized antennas. Table top equipment is placed on a 1.0 X 1.5 metre non-conducting table, 1.5 metre above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. The setup of the equipment under test is following set out in ANSI C63.10. The interface cables that are closer than 40 centimetres to the ground plane are bundled in the center in a serpentine fashion so they are at least 40 centimetres from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screened room located outside the test area. Measurements are made in both the horizontal and vertical polarization planes in a fully anechoic room using a spectrum analyzer set to max peak detector function and a resolution 1 MHz and video bandwidth 3 MHz for peak measurement. The conditions determined as worst case will then be used for the final measurements. When the EUT is larger than the beam width of the measuring antenna it will be moved over the surface for the four sides of the equipment. Where appropriate, the test distance may be reduced in order to detect emissions under better uncertainty and are calculated at the specified test distance.



FCC ID: VNP-ME1500

IC: 11986A-ME1500

5 TEST CONDITIONS AND RESULTS

5.1 AC power line conducted emissions

Remarks: Not applicable as the EUT is battery powered and has no AC mains connections.


5.2 Field strength of fundamental

For test instruments and accessories used see section 6 Part **CPR 3**.

5.2.1 Description of the test location

Test location: Anechoic chamber 1
Test distance: 3 m

5.2.2 Photo documentation of the test set-up





FCC ID: VNP-ME1500

IC: 11986A-ME1500

5.2.3 Applicable standard

According to FCC Part 15C, Section 15.249(a):

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the effective limits.

5.2.4 Description of Measurement

The radiated emission of the fundamental wave from the EUT is measured using a spectrum analyser and appropriate linear polarized antennas. The set up of the EUT and the measurement procedure is in accordance to ANSI C63.10, Item 6.5. The EUT is measured in TX continuous mode modulated under normal conditions.

Analyser settings:

Peak measurement: RBW: 3 MHz

VBW: 10 MHz

Detector: Max peak

5.2.5 Test result

Frequency (MHz)	Level PK dB(µV/m)	Limit PK dB(µV/m)	Margin PK (dB)	Level AV dB(µV/m)	Limit AV dB(µV/m)	Margin AV (dB)
2402	92.3	114.0	-21.7	83.2	94.0	-10.8
2440	91.4	114.0	-22.6	82.3	94.0	-11.7
2480	91.4	114.0	-22.5	82.3	94.0	-11.7

Average-Limit according to FCC Part 15C, Section 15.249(a):

Frequency (MHz)	Field strength of fundamental	
	(mV/m)	dB(µV/m)
902 - 928	50	94
2400 - 2483.5	50	94
5725-5875	50	94
24000 - 24250	250	108

Peak-Limit according to FCC Part 15C, Section 15.249(e):

However, the peak fieldstrength shall not exceed the maximum permitted average limit by more than 20 dB.

The requirements are **FULFILLED**.

Remarks: -



FCC ID: VNP-ME1500

IC: 11986A-ME1500

5.3 Out-of-band emission, radiated

For test instruments and accessories used see section 6 Part **SER1, SER 2, SER 3**.


5.3.1 Description of the test location

Test location: OATS 1
Test location: Anechoic chamber 1

Test distance: 3 m

5.3.2 Photo documentation of the test set-up

Test setup 9 kHz – 30 MHz:






FCC ID: VNP-ME1500

IC: 11986A-ME1500

Test setup 30 MHz – 1000 MHz:



Test setup 1 GHz – 18 GHz:






FCC ID: VNP-ME1500

IC: 11986A-ME1500

Test setup 18 GHz – 25 GHz:



5.3.3 Applicable standard

According to FCC Part 15C, Section 15.249 (d):

Emission radiated outside of the specified frequency bands, except harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated limit in FCC Part 15C, Section 15.209, whichever is the lesser attenuation.

5.3.4 Description of Measurement

The radiated emissions from the EUT are measured in the frequency range of 9 kHz to 1000 MHz using a tuned receiver and appropriate broadband linearly polarized antennas. The setup of the EUT and the measurement procedure is in accordance to ANSI C63.10, Item 6.3. In the frequency range above 1 GHz a spectrum analyser is used with appropriate linear polarized antennas. If the emission level in peak mode complies with the average limit testing is stopped and peak values will be reported, otherwise, the emission is measured in average mode again and reported. The EUT is measured in TX continuous mode modulated under normal conditions.

Instrument settings:

9 kHz – 150 kHz	RBW:	200 Hz
150 kHz - 30 MHz	RBW:	9 kHz
30 MHz – 1000 MHz:	RBW:	120 kHz
1000 MHz – 25 GHz	RBW:	1 MHz



FCC ID: VNP-ME1500

IC: 11986A-ME1500


5.3.5 Test result f < 1000 MHz

Frequency (MHz)	Reading Vert. (dB μ V)	Reading Hor. (dB μ V)	Correct. Vert. (dB)	Correct. Hor. (dB)	Level Vert. (dB μ V/m)	Level Hor. (dB μ V/m)	Limit (dB μ V/m)	Dlimit (dB)
80.80	9.6	6.4	10.2	10.0	19.8	16.4	40.0	-20.2
85.22	7.0	8.9	9.3	9.5	16.3	18.4	40.0	-21.6
232.90	7.0	7.5	12.0	12.4	19.0	19.9	46.0	-26.1
354.90	7.9	8.0	17.5	17.2	25.4	25.2	46.0	-20.6

Note: In the frequency range 9 kHz to 1000 MHz no emission could be detected. The frequencies mention the noise level. No difference could be detected between the operating frequencies.

5.3.6 Test result f > 1 GHz

Channel 37







FCC ID: VNP-ME1500

IC: 11986A-ME1500

Average measurement 2400 MHz:




Note: only when the peak value exceeds the average value, an AVG measurement is necessary





FCC ID: VNP-ME1500

IC: 11986A-ME1500





Note: the measurement distance was changed to 1 m for this frequency range, therefore the limit line has to be adjusted and was increased by 10 dB.



FCC ID: VNP-ME1500

IC: 11986A-ME1500


Channel 17






FCC ID: VNP-ME1500

IC: 11986A-ME1500



Note: the measurement distance was changed to 1 m for this frequency range, therefore the limit line has to be adjusted and was increased by 10 dB.



Channel 39





FCC ID: VNP-ME1500

IC: 11986A-ME1500



Note: the measurement distance was changed to 1 m for this frequency range, therefore the limit line has to be adjusted and was increased by 10 dB.



FCC ID: VNP-ME1500

IC: 11986A-ME1500

Limit according to FCC Part 15C, Section 15.209:

Frequency (MHz)	15.209 Limits (μ V/m)	Measurement distance (m)
0.009 - -0.49	2400/f(kHz)	300
0.49 - 1.705	24000/f(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Average limit according to FCC Part 15C, Section 15.249(a):

Fundamental frequency (MHz)	Field strength of harmonics (μ V/m)	dB(μ V/m)
902 - 928	500	54
2400 - 2483.5	500	54
5725 - 5875	500	54
24000 - 24250	2500	68

The requirements are **FULFILLED**.

Remarks: The measurement was performed up to the 10th harmonic (25000 MHz).



FCC ID: VNP-ME1500

IC: 11986A-ME1500


5.4 EBW and OBW

For test instruments and accessories used see section 6 Part **MB**.

5.4.1 Description of the test location

Test location: Anechoic chamber 1

5.4.2 Photo documentation of the test set-up



5.4.3 Applicable standard

According to FCC Part 15, Section 15.215(c):

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in Section 15.217 through Section 15.257, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated.

5.4.4 Description of Measurement

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio of -20 dB (99%). The x-dB-down (OBW) function of the analyser is used. The measurement is performed with normal modulation in TX continuous mode.

Spectrum analyser settings:

RBW: 30 kHz, VBW: 100 kHz, Span: 3 MHz, Trace mode: max. hold, Detector: max. peak;



FCC ID: VNP-ME1500

IC: 11986A-ME1500

5.4.5 Test result

Centre f (MHz)	99% bandwidth f_1	99% bandwidth f_2	Measured OBW (MHz)
2402.025605	2401.51388	2402.537330	1.023450
2440.022220	2439.50637	2440.538070	1.031700
2480.018360	2479.50591	2480.530810	1.024900

Centre f (MHz)	20dB bandwidth f_1	20dB bandwidth f_2	Measured EBW (MHz)
2402.036005	2401.49863	2402.573380	1.074750
2440.021380	2439.48513	2440.557630	1.072500
2480.024005	2479.48438	2480.563630	1.079250

Operating frequency band (MHz)	20 dB Bandwidth (MHz)	
$f_{low} > 2400$	$f_{low} =$	2401.49863
$f_{high} < 2483.5$	$f_{high} =$	2480.56363
Operating Band occupancy	79.07	

Operating Band occupancy percentage	94.69 %
Operating channel occupancy percentage	53.96 %

Limit according to FCC Part 15C, Section 15.215(c):

If frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within the central 80% of the permitted band in order to minimize the possibility of out-of-band operation. Due to the channelising of the operating band into 40 channels with channel bandwidth of 1 MHz the limit central 80% of the permitted band can not be applied. Therefore, the stability of the EUT will be shown staying within the central 80% of the operating channel.

The requirements are **FULFILLED**.

Remarks: For detailed test result please refer to following test protocols.

The OBW99 is measured for RSS only.





FCC ID: VNP-ME1500

IC: 11986A-ME1500

5.4.6 Test protocols


20 dB bandwidth





FCC ID: VNP-ME1500

IC: 11986A-ME1500






FCC ID: VNP-ME1500

IC: 11986A-ME1500


OBW 99%





FCC ID: VNP-ME1500

IC: 11986A-ME1500





FCC ID: VNP-ME1500

IC: 11986A-ME1500


5.5 Correction for pulse operation (duty cycle)

For test instruments and accessories used see section 6 Part **DC**.

5.5.1 Description of the test location

Test location: AREA4

5.5.2 Photo documentation of the test set-up



5.5.3 Applicable standard

According to FCC Part 15A, Section 15.35(c):

When the radiated emission limits are expressed in terms of average value and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete puls train, including blanking intervals, as long as the pulse train does not exceed 0.1s. In cases where the puls train exceeds 0.1s, the measured field strength shall be determined from the average absolute voltage during a 0.1s interval during which the field strength is at its maximum. The exact method of calculating the average field strength shall be submitted.



FCC ID: VNP-ME1500

IC: 11986A-ME1500

5.5.4 Description of Measurement

According to the customer, the duty cycle is calculated as follows:

$$DC = \frac{N \cdot T_{on}}{T_{conn}} = \frac{0.435 \text{ ms} \cdot 6 \cdot 13.3}{100 \text{ ms}} = 0.35$$


T_{on} = on air duration of packet with maximum packet payload length of 37 octets

N = maximum number of packets per connection interval

T_{conn} = minimum connection interval = 7.5ms

$$KE = 20 \log (DC) = 20 \log (0.35) = -9.1 \text{ dB}$$

KE : pulse operation correction factor



Remarks: The minimum connection interval $T_{conn} = 7.5 \text{ ms}$ was multiplied by 13.3 to get an observation period of 100 ms. Therefore, the numerator was multiplied with 13.3 too.



FCC ID: VNP-ME1500

IC: 11986A-ME1500

5.6 Antenna application

5.6.1 Applicable standard

According to FCC Part 15C, Section 15.203(a):

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

5.6.2 Result

The EUT uses an integrated chip antenna. No other antenna than that furnished by the responsible party or external power amplifier can be applied by a customer.

The antenna of the EUT meets the requirement of FCC Part 15C, Section 15.203 and 15.204.

The requirements are **FULFILLED**.

Remarks: _____ - _____



FCC ID: VNP-ME1500

IC: 11986A-ME1500

6 USED TEST EQUIPMENT AND ACCESSORIES

All test instruments used are calibrated and verified regularly. The calibration history is available on request.

Test ID	Model Type	Equipment No.	Next Calib.	Last Calib.	Next Verif.	Last Verif.
CPR 3	FSW43 AMF-6D-01002000-22-10P 3117 18N-20 NMS111-GL200SC01-NMS1102-02/50-17-012 BAM 4.5-P NCD KK-SF106-2X11N-6,5M	02-02/11-15-001 02-02/17-15-004 02-02/24-05-009 02-02/50-17-003 02/50-17-012 02-02/50-17-024 02-02/50-17-025 02-02/50-18-016	19/03/2019	19/03/2018		
DC	ESW26	02-02/03-17-002	13/12/2019	13/12/2018		
MB	EA-PS 3032-10B ESW26	01-05/50-11-011 02-02/03-17-002	13/12/2019	13/12/2018		
SER 1	ESCI HFH 2 - Z 2 NW-2000-NB KK-EF393/U-16N-21N20 m KK-SD_7/8-2X21N-33,0M ANT1010A	02-02/03-15-001 02-02/24-05-020 02-02/50-05-113 02-02/50-12-018 02-02/50-15-028 02-02/50-16-034	11/06/2019 09/08/2020	11/06/2018 09/08/2017	15/01/2020	15/01/2019
SER 2	ESVS 30 VULB 9168 NW-2000-NB KK-EF393/U-16N-21N20 m KK-SD_7/8-2X21N-33,0M	02-02/03-05-006 02-02/24-05-005 02-02/50-05-113 02-02/50-12-018 02-02/50-15-028	06/06/2019 18/04/2019	06/06/2018 18/04/2018		
SER 3	FSW43 JS4-18004000-30-5A AMF-6D-01002000-22-10P 3117 BBHA 9170 WHJS 1000-10EE WHK 3.0/18G-10EF KMS102-0.2 m KMS102-0.2 m 18N-20 NMS111-GL200SC01-NMS1102-02/50-17-012 BAM 4.5-P NCD KK-SF106-2X11N-6,5M	02-02/11-15-001 02-02/17-05-017 02-02/17-15-004 02-02/24-05-009 02-02/24-05-014 02-02/50-05-070 02-02/50-05-180 02-02/50-11-016 02-02/50-11-020 02-02/50-17-003 02/50-17-012 02-02/50-17-024 02-02/50-17-025 02-02/50-18-016	19/03/2019 08/05/2019 12/06/2021	19/03/2018 08/05/2018 12/06/2018	12/12/2019	12/12/2018