



F C C - TEST REPORT

REPORT NO.: 48947A

Address 地址: Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong.

香港新界粉嶺安樂村樂業路31號6樓602-605室

China 中國: IECC (Guangzhou) Services Co., Ltd. 廣州時並進技術服務有限公司

Address 地址: Flat A, 2/F., Block 3, 56 Shuiyin Road, Guangzhou, P.R. of China.

廣州市水蔭路56號3樓2A室

Postcode 郵政編號: 510075

Tel 電話: (852) 2305 2570

Fax 傳真: (852) 2756 4480

Tel 電話: (86-20) 8768 4838

Fax 傳真: (86-20) 8768 3918

E-mail 電子郵件: info@iecc.com.hk

Home Page 網頁: <http://www.iecc.com.hk>

E-mail 電子郵件: info@iecc.net.cn

Home Page 網頁: <http://www.iecc.net.cn>

FCC – Test Report**No. 48947A**Date: 2007-09-19

Page 2 of 17

FCC listed testlab
acc. to Section 2.948 of the FCC - Rules
in compliance with the requirements of
ANSI C63.4 - 2003

Product : RC Bug

Product Class : Low Power Communication Device -
Transmitter

Brand Name : --

Model : DPCL2SCALE001A

Applicant : DESIGN POLYGON CO. LTD

FCC – Test Report**No. 48947A**Date: 2007-09-19

Page 3 of 17

TABLE OF CONTENTS

- 1. Cover sheet**
- 2. Introduction**
- 3. Table of Contents**
- 4. Laboratory Report**
- 5. Test Location and Summary of Test Results**
- 6. Test Equipment List**
- 7. Radiated Emission Test Setup (9kHz – 30MHz)**
- 8. Radiated Emission Test Setup (> 30 MHz)**
- 9. Conducted Emission Test Setup**
- 10. Test Procedure**
- 11. Test Results**
- 12. Measurement Data**
- 13-14. Time Domain Plot**
- 15. Measurement Data**
- 16. Measurement of Emissions within Band Edges (Band Edges Plot)**
- 17. Photo of sample**

FCC – Test ReportDate: 2007-09-19**No. 48947A**

Page 4 of 17

LABORATORY - REPORT

APPLICANT: DESIGN POLYGON CO. LTD
ADDRESS: Room 1502, 15 th Floor, New Landwide Commercial Building
73 Kimberley Road, Kowloon
Hong Kong

DATE OF SAMPLE RECEIVED: 2007-09-15
DATE OF TESTING: 2007-09-17 to 2007-09-18

DESCRIPTION OF SAMPLE:


Product: RC Bug
Product class: Low Power Communication Device - Transmitter
Model number: DPCL2SCALE001A
Rating: DC 3V ('AA' Size Battery x 2)

CONDITION OF TEST SAMPLE: The received sample was under good condition.

INVESTIGATIONS REQUESTED: Measurements to the relevant clauses of F.C.C. Rules and Regulations
Part 15 Subpart C - Intentional Radiators

RESULTS: See the attached sheets

CONCLUSIONS: From the measurement data obtained, the tested sample was considered to have **COMPLIED** with the requirements for the relevant clauses of Federal Communications Commission Rules as specified above.



Authorized Signature

FCC – Test Report

No. 48947A

Date: 2007-09-19

Page 5 of 17

Test Location

International Electrical Certification Centre Ltd.

Unit 602-605, 31 Lok Yip Road, On Lok Tsuen, Fanling, N.T., Hong Kong

Tel : +852 23052570

Fax : +852 27564480

Email : info@iecc.com.hk

Summary of Test Results

Radiated Emission:

Test result: O.K.

Test data: See attached data sheet

Conducted Emission:

Test result: N.A.

Test data: N.A.

Measurement of Emissions within Band Edges

Test result: O.K.

Test data: See attached data sheet

FCC – Test ReportDate: 2007-09-19**No. 48947A**


Page 6 of 17

TEST EQUIPMENT LIST

Equipment	Manufacturer	Model	Serial No.	Last Calibration Date	Next Calibration Date
Test Receiver	Rohde & Schwarz	ESCS 30	100388	12/4/2007	11/4/2008
Antenna	Schaffner	CBL6111C	2791	25/05/2005	24/05/2008
Antenna Mast System	Schwarzbeck	AM9104	--	--	--
Loop Antenna	Rohde & Schwarz	HFH2-Z2	871336/48	18/11/2006	17/11/2009
Turntable with Controller	Drehtisch	DT312	--	--	--
Spectrum Analyzer with Q. Peak	Advantest	R3132	140101852	16/11/2005	15/11/2007

FCC – Test Report**No. 48947A**Date: 2007-09-19

Page 7 of 17

Radiated Emission Test Setup (9kHz – 30MHz)


FCC – Test Report

No. 48947A

Date: 2007-09-19

Page 8 of 17

Radiated Emission Test Setup (3 m distance) (> 30MHz)




FCC – Test Report

No. 48947A

Date: 2007-09-19

Page 9 of 17

Conducted Emission Test Setup



LEGEND:

- 1) Interconnecting cables that hang closer than 40 cm to the groundplane shall be folded back and forth in the center forming a bundle 30 to 40 cm long (see 6.1.4 and 11.2.4).
- 2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.1.4).
- 3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference groundplane (see 5.2.3 and 7.2.1).
 - 3.1) All other equipment powered from additional LISN(s).
 - 3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - 3.3) LISN at least 80 cm from nearest part of EUT chassis.
- 4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use (See 6.2.1.3 and 11.2.4).
- 5) Non-EUT components of EUT system being tested (see also Figure 13).
- 6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop (see 6.2.1.1 and 6.2.1.2).
- 7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the groundplane (see 5.2.2 for options).

FCC – Test Report**No. 48947A**Date: 2007-09-19

Page 10 of 17

Test Procedure**Radiated Emission :**

The EUT was tested according to ANSI 63.4-2003 for the requirements of FCC Part 15 Subpart C Section 15.227 & 15.209.

1. Measurement Frequencies below 30MHz :

During the test, the sample was placed on a turn table and operated under various modes with supply from new battery. The table is 0.8 meter and can rotate 360 degrees to determine the position of the maximum emission level. A loop antenna for the frequency range 9kHz - 30MHz, connected with 10 meters coaxial cable to the test receiver was used for measurement. The center of the loop 1 m above the floor, positioned with its plane vertical at the specified distance and rotated about its vertical axis and placed horizontal for maximum response at each azimuth about the EUT.

An initial pre-scan was performed to find out the maximum emission level of the sample placed at 3 orthogonal planes. Final measurement was then performed to record the data for fundamental emission within the operation band and spurious emissions outside the band under worst-case condition for combination of the antenna orientation and turn table position.

Note : Fundamental emission for this pulse modulated device was measured with the peak detector function of the test receiver and was properly adjusted for the duty cycle correction factor as pulse desensitization to calculate the average emission value.

2. Measurement Frequencies 30MHz – 1000 MHz :

During the test, the sample was also placed on a turn table and operated under various modes with supply from new battery. The table is 0.8 meter above the reference ground plane on the Open Area Test Site and can rotate 360 degrees to determine the position of the maximum emission level. A broad-band antenna for the frequency range 30 - 1000 MHz, connected with 10 meters coaxial cable to the test receiver was used for measurement. The antenna is capable of measuring both horizontal and vertical polarizations. The antenna was raised from 1 to 4 meters to find out the maximum emission level from the EUT.

An initial pre-scan was performed to find out the maximum emission level of the sample placed at 3 orthogonal planes. Final measurement (30 MHz –1000 MHz) was then performed to record the data for the spurious emissions under worst-case condition for combination of the antenna orientation / height and turn table position.

Note : The Open Area Test Site located at IECC was placed on file with the FCC Pursuant to Section 2.948 of the FCC Rules (FCC Registration No. : 97774).

Conducted Emission :**Not Applicable**

FCC – Test ReportDate: 2007-09-19**No. 48947A**

Page 11 of 17

Test Results**Radiated Emission :**

Test Requirement:	FCC Part 15 Subpart C Section 15.227, 15.209
Test Method:	ANSI C63.4 : 2003
Deviations from Standard Test Method:	Nil
Frequency Range:	9kHz – 1000MHz
Measurement Distance:	3 m
Detector:	Peak (Fundamental frequency) Quasi-Peak (Measurement outside the operation band)

Refer to page 12- 15 for emission measurement data
Refer to page 16 for band edge plot

Conducted Emission :

Not Applicable

Radiated Emission

Date : 2007-09-19

Page 12 of 17

Measurement of Radiated Emissions FCC Part 15 Subpart C (15.227)

IECC Ref: 48947A
 Model: DPCL2SCALE001A
 Applicant: DESIGN POLYGON CO. LTD
 Sample No.: 1
 Set under test: RC Bug
 Connected sets: -
 Operating mode: Operate

Test Equipment
 Receiver: ESCS 30 Rohde & Schwarz
 Antenna: HFH2-Z2 Rohde & Schwarz

Radiation Measurement (3 m) below 30MHz

a. Fundamental Frequency

Frequency (MHz)	Maximum Test Result (dB(μV/m))		FCC Limit (dB(μV/m))	
	Peak	Average *	Peak	Average
27.145	53.0	49.2	100	80

Note : (1) The above peak value is the maximum value of the measurement in 3 orthogonal planes

(2) * Calculation for radiation (average) :

Formula :

Duty cycle = $(N1L1 + N2L2 + \dots + Nn-1Ln-1 + NnLn) / 100$ or T

where N1 is number of type 1 pluse, L1 is length of type 1 pulse, etc.
 T is the period of the pulse train (if less than 100 ms)

According to the time domain plots shown in page 11 & 12 :

Duty cycle of the EUT = $(4 \times 1.8 + 10 \times 0.66) / 21.45 = 0.643$

Av correction factor = $20 \times \log(0.643)$ dB
 = - 3.8 dB

Radiation (average) = Radiation (peak) + Av correction factor

Radiation (average) of the EUT = $53.0 - 3.8$ dB(μV/m)
 = 49.2 dB(μV/m)


b. The measured radiation outside the operation band were negligible

Radiated Emission

Date : 2007-09-19

Page 13 of 17

Transmitter Emission - Time Domain Plots




Pulse cycle period = 21.45 ms

Radiated Emission


Date : 2007-09-19

Page 14 of 17

Transmitter Emission - Time Domain Plots



Pulse width = 1.8 ms (total number of pulse : 4)



Pulse width = 0.66 ms (total number of pulse : 10)

Radiated Emission

Measurement of Radiated Emissions
FCC Part 15 Subpart C (15.209)Date : 2007-09-19
Page 15 of 17IECC Ref: 48947A
Model: DPCL2SCALE001A
Applicant: DESIGN POLYGON CO. LTDTest Equipment
Receiver: Rohde & Schwarz ESCS 30
Antenna: Schaffner CBL6111C

Sample No. : 1

Set under test: RC Bug
Connected sets: -
Operating mode: Operate

Frequency (MHz)	Horz. Reading dB(μV)	Vert. Reading dB(μV)	Corr. Factor (dB)	Horiz. Test Result dB(μV/m)	Vert. Test Result dB(μV/m)	Limit dB(μV/m)
30.00	< 16	< 16	17.6	< 33.6	< 33.6	40.0
54.29	< 28	< 20	6.1	< 34.1	< 26.1	40.0
81.44	< 16	< 16	7.1	< 23.1	< 23.1	43.5
108.58	< 16	< 16	10.2	< 26.2	< 26.2	43.5
135.73	< 16	< 16	11.1	< 27.1	< 27.1	43.5
162.87	< 16	< 16	9.5	< 25.5	< 25.5	43.5
190.02	< 16	< 16	8.2	< 24.2	< 24.2	46.0
217.16	< 16	< 16	8.2	< 24.2	< 24.2	46.0
244.31	< 16	< 16	11.3	< 27.3	< 27.3	46.0
271.45	< 20	< 16	12.6	< 32.6	< 28.6	46.0
298.60	< 16	< 16	12.9	< 28.9	< 28.9	46.0
325.74	< 16	< 16	13.6	< 29.6	< 29.6	46.0
352.89	< 16	< 16	14.4	< 30.4	< 30.4	46.0
380.03	< 16	< 16	15.3	< 31.3	< 31.3	46.0
407.18	< 16	< 16	16.0	< 32.0	< 32.0	46.0
434.32	< 16	< 16	16.6	< 32.6	< 32.6	46.0
461.47	< 16	< 16	17.2	< 33.2	< 33.2	46.0
488.61	< 16	< 16	17.7	< 33.7	< 33.7	46.0
515.76	< 20	< 16	18.2	< 38.2	< 34.2	46.0
542.90	< 16	< 16	19.5	< 35.5	< 35.5	46.0
570.05	< 16	< 16	20.1	< 36.1	< 36.1	46.0
597.19	< 16	< 16	19.3	< 35.3	< 35.3	46.0
624.34	< 16	< 16	20.4	< 36.4	< 36.4	46.0
651.48	< 16	< 16	20.1	< 36.1	< 36.1	46.0
678.63	< 16	< 16	20.4	< 36.4	< 36.4	46.0
705.77	< 16	< 16	21.0	< 37.0	< 37.0	46.0
732.92	< 16	< 16	22.2	< 38.2	< 38.2	46.0
760.06	< 16	< 16	22.4	< 38.4	< 38.4	46.0
787.21	< 16	< 16	22.2	< 38.2	< 38.2	46.0
814.35	< 16	< 16	22.3	< 38.3	< 38.3	46.0
841.50	< 16	< 16	23.4	< 39.4	< 39.4	46.0
868.64	< 16	< 16	23.5	< 39.5	< 39.5	46.0
895.79	< 16	< 16	23.4	< 39.4	< 39.4	46.0
922.93	< 16	< 16	24.3	< 40.3	< 40.3	46.0
950.08	< 16	< 16	25.6	< 41.6	< 41.6	54.0
977.22	< 16	< 16	25.0	< 41.0	< 41.0	54.0

Note:

The recorded readings are in quasi-peak values.

The above results were the worst case results with the sample positioned in all 3 axis during the test.

The worst results were recorded with the sample vertically stood on the table for antenna vertical measurement and with the sample horizontally lay on the table for antenna horizontal measurement.

Operator : RT

Address 地址: Units 602-605, 6/F., 31 Lok Yip Rd., On Lok Tsuen, Fanling, N.T., Hong Kong.

香港新界粉嶺安樂村樂業路31號6樓602-605室

China 中國: IECC (Guangzhou) Services Co., Ltd. 廣州時並進技術服務有限公司

Address 地址: Flat A, 2/F., Block 3, 56 Shuiyin Road, Guangzhou, P.R. of China.

廣州市水蔭路56號3樓2A室

Postcode 郵政編號: 510075

Tel 電話: (852) 2305 2570

Fax 傳真: (852) 2756 4480

E-mail 電子郵件: info@iecc.com.hk

Home Page 網頁: http://www.iecc.com.hk

Tel 電話: (86-20) 8768 4838

Fax 傳真: (86-20) 8768 3918

E-mail 電子郵件: info@iecc.net.cn

Home Page 網頁: http://www.iecc.net.cn


FCC – Test Report

Date: 2007-09-19

No. 48947A

Page 16 of 17

Measurement Data of Emissions within Band Edges



Result : The field strength of any emission within the operation band did not exceed 80 dB(μV/m) for average value or 100 dB(μV/m) for peak value. Refer to page 12 for the recorded value for the emission at the fundamental frequency.

FCC – Test ReportDate: 2007-09-19**No. 48947A**

Page 17 of 17

Photo of Sample