

FCC CERTIFICATION  
On Behalf of  
Great American Duck Races, Inc.

Dancing Waters Light & Fountain Show Remote  
Model No.: 3509

FCC ID: VNY-3509

Prepared for : Great American Duck Races, Inc.  
Address : 16043 N. 82<sup>nd</sup> Street, Scottsdale, AZ 85260, USA

Prepared by : Accurate Technology Co., Ltd.  
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.  
Science & Industry Park, Nanshan, Shenzhen, Guangdong  
P.R. China

Tel: (0755) 26503290  
Fax: (0755) 26503396

Report Number : ATE20102683  
Date of Test : December 20-21, 2010  
Date of Report : December 23, 2010

## TABLE OF CONTENTS

	Description	Page
Test Report Certification		
<b>1. GENERAL INFORMATION .....</b>	<b>4</b>	
1.1.    Description of Device (EUT).....	4	
1.2.    Description of Test Facility .....	5	
1.3.    Measurement Uncertainty.....	5	
<b>2. MEASURING DEVICE AND TEST EQUIPMENT .....</b>	<b>6</b>	
<b>3. SUMMARY OF TEST RESULTS.....</b>	<b>7</b>	
<b>4. FUNDAMENTAL AND HARMONICS RADIATED EMISSION FOR SECTION 15.249(A) 8</b>	<b>8</b>	
4.1.    Block Diagram of Test Setup.....	8	
4.2.    The Emission Limit .....	9	
4.3.    Configuration of EUT on Measurement .....	9	
4.4.    Operating Condition of EUT .....	9	
4.5.    Test Procedure .....	10	
4.6.    The Field Strength of Radiation Emission Measurement Results .....	11	
<b>5. SPURIOUS RADIATED EMISSION FOR SECTION 15.249(D) .....</b>	<b>12</b>	
5.1.    Block Diagram of Test Setup.....	12	
5.2.    The Emission Limit For Section 15.249(d) .....	13	
5.3.    EUT Configuration on Measurement .....	13	
5.4.    Operating Condition of EUT .....	13	
5.5.    Test Procedure .....	14	
5.6.    The Emission Measurement Result .....	15	
<b>6. BAND EDGES .....</b>	<b>16</b>	
6.1.    The Requirement .....	16	
6.2.    EUT Configuration on Measurement .....	16	
6.3.    Operating Condition of EUT .....	16	
6.4.    Test Procedure .....	17	
6.5.    The Measurement Result .....	18	
<b>7. ANTENNA REQUIREMENT.....</b>	<b>19</b>	
7.1.    The Requirement .....	19	
7.2.    Antenna Construction .....	19	

APPENDIX I ( TEST CURVES) (6 pages)

## Test Report Certification

Applicant : Great American Duck Races, Inc.  
 Manufacturer : Qualiman Industrial CO., LTD  
 EUT Description : Dancing Waters Light & Fountain Show Remote  
     (A) MODEL NO.: 3509  
     (B) SERIAL NO.: N/A  
     (C) POWER SUPPLY: 9V DC ("9V"battery 1×)

Measurement Procedure Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.249**  
**ANSI C63.4: 2003**

The device described above is tested by Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.249 limits. The measurement results are contained in this test report and Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Accurate Technology Co., Ltd.

Date of Test : February 6-7, 2010

Prepared by :

  
 (Engineer)

Approved & Authorized Signer :

  
 (Manager)

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

EUT : Dancing Waters Light & Fountain Show Remote  
Model Number : 3509  
Power Supply : 9V DC ("9V"battery 1×)  
Operate Frequency : 915MHz  
Channel Number : 1  
Applicant : Great American Duck Races, Inc.  
Address : 16043 N. 82<sup>nd</sup> Street, Scottsdale, AZ 85260, USA  
Manufacturer : Qualiman Industrial CO., LTD  
Address : 1902-05 CHEUNG TAT CENTRE, 18 CHEUNG LEE  
STREET, CHAI WAN, HK  
Date of sample received : December 14, 2010  
Date of Test : December 20-21, 2010

## 1.2.Description of Test Facility

EMC Lab	: Accredited by TUV Rheinland Shenzhen
	Listed by FCC The Registration Number is 752051
	Listed by Industry Canada The Registration Number is 5077A-2
	Accredited by China National Accreditation Committee for Laboratories The Certificate Registration Number is L3193
Name of Firm	: ACCURATE TECHNOLOGY CO. LTD
Site Location	: F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

## 1.3.Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2  
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2  
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2  
(Above 1GHz)

## 2. MEASURING DEVICE AND TEST EQUIPMENT

**Table 1: List of Test and Measurement Equipment**

Kind of equipment	Manufacturer	Type	S/N	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 9, 2011
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 9, 2011
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 9, 2011
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 9, 2011
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 9, 2011
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 9, 2011
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 9, 2011
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 9, 2011
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 9, 2011
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 9, 2011

### 3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.249(a)	Fundamental and Harmonics Radiated Emission	Compliant
Section 15.249(d)	Spurious Radiated Emission	Compliant
Section 15.249(d)	Band Edge	Compliant
Section 15.203	Antenna Requirement	Compliant

Remark: "N/A" means "Not applicable".

## 4. FUNDAMENTAL AND HARMONICS RADIATED EMISSION FOR SECTION 15.249(A)


### 4.1. Block Diagram of Test Setup

#### 4.1.1. Block diagram of connection between the EUT and simulators



(EUT: Dancing Waters Light & Fountain Show Remote)

#### 4.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: Dancing Waters Light & Fountain Show Remote)

## 4.2.The Emission Limit

4.2.1.For intentional radiators, According to section 15.249(a), Operation within the frequency band of 902 to 928MHz, The fundamental field strength shall not exceed 94 dB $\mu$ V/m and the harmonics shall not exceed 54 dB $\mu$ V/m.

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of harmonics (microvolts/meter)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

4.2.2.According to section 15.249(e), as shown in section 15.35(b), the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 4.3.Configuration of EUT on Measurement

The following equipments are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 4.3.1.Dancing Waters Light & Fountain Show Remote (EUT)

Model Number : 3509  
 Serial Number : N/A  
 Manufacturer : Qualiman Industrial CO., LTD

## 4.4.Operating Condition of EUT

4.4.1.Setup the EUT and simulator as shown as Section 4.1.

4.4.2.Turn on the power of all equipment.

4.4.3.Let the EUT work in TX modes measure it. The transmit frequency are 915MHz.

#### 4.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 120kHz in 30-1000MHz. and set at 1MHz in above 1000MHz.

**4.6.The Field Strength of Radiation Emission Measurement Results  
PASS.**

Date of Test:	December 20, 2010	Temperature:	25°C
EUT:	Dancing Waters Light & Fountain Show Remote	Humidity:	50%
Model No.:	3509	Power Supply:	9V DC ("9V"battery 1×)
Test Mode:	TX	Test Engineer:	Joe

**Fundamental Radiated Emissions**

Frequency (MHz)	Reading (dB $\mu$ V/m)	Factor(dB)	Result		Limit		Margin (dB)	Polarization
			Corr.	(dB $\mu$ V/m)	QP	QP		
914.9240	42.34	28.92		71.26	94	94	-22.74	Vertical
914.9240	49.35	28.92		78.27	94	94	-15.73	Horizontal

**Harmonics Radiated Emissions**

Frequency (MHz)	Reading(dB $\mu$ V/m)		Factor(dB)	Result(dB $\mu$ V/m)		Limit(dB $\mu$ V/m)		Margin(dB)		Polarization
	AV	PEAK		Corr.	AV	PEAK	AV	PEAK	AV	
1829.836	56.96	62.14	-9.73	47.23	52.41	54	74	-6.77	-21.59	Vertical
2744.761	48.01	53.17	-6.13	41.88	47.04	54	74	-12.12	-26.96	Vertical
1829.836	57.78	62.92	-9.73	48.05	53.19	54	74	-5.95	-20.81	Horizontal
2744.761	48.39	53.58	-6.12	42.27	47.46	54	74	-11.73	-26.54	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss (if used) and cable loss, and subtracting the amplifier gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss – Amplifier Gain

3. The spectral diagrams in appendix I display the measurement of peak values.

## 5. SPURIOUS RADIATED EMISSION FOR SECTION 15.249(D)


### 5.1. Block Diagram of Test Setup

#### 5.1.1. Block diagram of connection between the EUT and simulators



(EUT: Dancing Waters Light & Fountain Show Remote)

#### 5.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: Dancing Waters Light & Fountain Show Remote)

## 5.2.The Emission Limit For Section 15.249(d)

5.2.1.Emission radiated outside of the specified frequency bands, except for harmonics, shall be comply with the general radiated emission limits in Section 15.209.

### Radiation Emission Measurement Limits According to Section 15.209

Frequency (MHz)	Limit		The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dB $\mu$ V/m)	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	

## 5.3.EUT Configuration on Measurement

The following equipments are installed on the Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 5.3.1.Dancing Waters Light & Fountain Show Remote (EUT)

Model Number : TTU-7WB  
 Serial Number : N/A  
 Manufacturer : Qualiman Industrial CO., LTD

## 5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 915MHz.

## 5.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 120kHz in 30-1000MHz. and set at 1MHz in above 1000MHz.

The frequency range from 30MHz to 10000MHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

## 5.6.The Emission Measurement Result

**PASS.**

Date of Test:	December 20, 2010	Temperature:	25°C
EUT:	Dancing Waters Light & Fountain Show	Humidity:	50%
Model No.:	Remote	Power Supply:	9V DC ("9V"battery 1×)
Test Mode:	3509	Test Engineer:	Joe
Test Mode:	TX		

Frequency (MHz)	Reading (dB $\mu$ V/m)	Factor(dB) Corr.	Result	Limit	Margin	Polarization
			(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss (if used) and cable loss, and subtracting the amplifier gain (if any) from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss – Amplifier Gain

3. The spectral diagrams in appendix I display the measurement of peak values.

## 6. BAND EDGES

### 6.1. The Requirement

6.1.1. Band Edge from 902MHz to 928MHz. Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

### 6.2. EUT Configuration on Measurement

The following equipments are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 6.2.1. Dancing Waters Light & Fountain Show Remote (EUT)

Model Number	:	3509
Serial Number	:	N/A
Manufacturer	:	Qualiman Industrial CO., LTD

### 6.3. Operating Condition of EUT

6.3.1. Setup the EUT and simulator as shown as Section 4.1.

6.3.2. Turn on the power of all equipment.

6.3.3. Let the EUT work in TX modes measure it. The transmit frequency are 915MHz.  
We select 915MHz TX frequency to transmit.

#### 6.4. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 120kHz in 30-1000MHz. and set at 1MHz in above 1000MHz.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

## 6.5.The Measurement Result

**Pass.**

Date of Test:	December 20, 2010	Temperature:	25°C
EUT:	Dancing Waters Light & Fountain Show Remote	Humidity:	50%
Model No.:	3509	Power Supply:	9V DC ("9V"battery 1×)
Test Mode:	TX	Test Engineer:	Joe

Frequency (MHz)	Reading (dB $\mu$ V/m)	Factor(dB) Corr.	Result	Limit	Margin	Polarization
			(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	QP
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss (if used) and cable loss, and subtracting the amplifier gain (if any) from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss – Amplifier Gain

3. The spectral diagrams in appendix I display the measurement of peak values.


## 7. ANTENNA REQUIREMENT

### 7.1. The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 7.2. Antenna Construction

The antenna is a copper, no consideration of replacement. Therefore, the equipment complies with the antenna requirement of Section 15.203.




## APPENDIX I (Test Curves)


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.:	joe #1364	Polarization:	Horizontal
Standard:	FCC Class B 3M Radiated	Power Source:	DC 9V
Test item:	Radiation Test	Date:	2010/12/20
Temp.( C)/Hum.(%)	25 C / 50 %	Time:	15:10:38
EUT:	Dancing Waters Light & Fountain Sh	Engineer Signature:	Joe
Mode:	TX	Distance:	3m
Model:	3509		
Manufacturer:	Qualiman Industrial Co., LTD		
Note:	Sample No.:102957 Report No.:ATE20102683		




**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: joe #1363

Polarization: Vertical

Standard: FCC Class B 3M Radiated

Power Source: DC 9V

Test item: Radiation Test

Date: 2010/12/20

Temp.( C)/Hum.(%) 25 C / 50 %

Time: 15:06:22

EUT: Dancing Waters Light &amp; Fountain Sh

Engineer Signature: Joe


Mode: TX

Distance: 3m

Model: 3509

Manufacturer: Qualiman Industrial Co., LTD

Note: Sample No.:102957 Report No.:ATE20102683



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	914.9240	42.34	28.92	71.26	94.00	-22.74	QP			


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: joe #1368

Polarization: Horizontal

Standard: FCC Class B 3M Radiated

Power Source: DC 9V

Test item: Radiation Test

Date: 2010/12/20

Temp.( C)/Hum.(%) 25 C / 50 %

Time: 15:35:08

EUT: Dancing Waters Light &amp; Fountain Sh

Engineer Signature: Joe


Mode: TX

Distance: 3m

Model: 3509

Manufacturer: Qualiman Industrial Co., LTD

Note: Sample No.:102957 Report No.:ATE20102683



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1829.836	62.92	-9.73	53.19	74.00	-20.81	peak			
2	1829.836	57.78	-9.73	48.05	54.00	-5.95	AVG			
3	2744.761	53.58	-6.12	47.46	74.00	-26.54	peak			
4	2744.761	48.39	-6.12	42.27	54.00	-11.73	AVG			



**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: joe #1367	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 9V
Test item: Radiation Test	Date: 2010/12/20
Temp.( C)/Hum.(%) 25 C / 50 %	Time: 15:30:41
EUT: Dancing Waters Light & Fountain Sh	Engineer Signature: Joe
Mode: TX	Distance: 3m
Model: 3509	
Manufacturer: Qualiman Industrial Co., LTD	

Note: Sample No.:102957 Report No.:ATE20102683



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1829.836	62.14	-9.73	52.41	74.00	-21.59	peak			
2	1829.836	56.96	-9.73	47.23	54.00	-6.77	AVG			
3	2744.761	53.17	-6.13	47.04	74.00	-26.96	peak			
4	2744.761	48.01	-6.13	41.88	54.00	-12.12	AVG			


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: joe #1365	Polarization: Horizontal
Standard: FCC Band Edge	Power Source: DC 9V
Test item: Radiation Test	Date: 2010/12/20
Temp.( C)/Hum.(%) 25 C / 50 %	Time: 15:17:12
EUT: Dancing Waters Light & Fountain Sh	Engineer Signature: Joe
Mode: TX	Distance: 3m
Model: 3509	
Manufacturer: Qualiman Industrial Co., LTD	

Note: Sample No.:102957 Report No.:ATE20102683



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


**ACCURATE TECHNOLOGY CO., LTD.**

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber  
 Tel:+86-0755-26503290  
 Fax:+86-0755-26503396

Job No.: joe #1366

Polarization: Vertical

Standard: FCC Band Edge

Power Source: DC 9V

Test item: Radiation Test

Date: 2010/12/20

Temp.( C)/Hum.(%) 25 C / 50 %

Time: 15:21:25

EUT: Dancing Waters Light &amp; Fountain Sh

Engineer Signature: Joe


Mode: TX

Distance: 3m

Model: 3509

Manufacturer: Qualiman Industrial Co., LTD

Note: Sample No.:102957 Report No.:ATE20102683



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	-------------	------------------	-------------	-----------------	----------------	-------------	----------	-------------	---------------	--------