



Test Report

Product Name	MOBILE PHONE
Model No.	PG220
FCC ID.	VOMTS200

Applicant	CENTURY TELECOM CO., LTD
Address	9F.-8, NO.20, Lane 609, Sec. 5, Chongxin Rd., Sanchong City, Taipei Country 241, Taiwan (R.O.C.)

Date of Receipt	Apr. 15, 2009
Issued Date	May. 26, 2009
Report No.	094287R-RFUSP06V01
Report Version	V1.0

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Test Report Certification

Issued Date: May. 26, 2009

Report No.: 094287R-RFUSP06V01



Product Name	MOBILE PHONE
Applicant	CENTURY TELECOM CO., LTD
Address	9F-8, NO.20, Lane 609, Sec. 5, Chongxin Rd., Sanchong City, Taipei Country 241, Taiwan (R.O.C.)
Manufacturer	MOBILE 2000 CO., LTD.
Model No.	PG220
FCC ID.	VOMTS200
Rated Voltage	AC 120V/60Hz
Working Voltage	AC 100~240V / 50~60Hz
Trade Name	PHONEX
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2007 ANSI C63.4: 2003
Test Result	Complied



The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By :

A handwritten signature in blue ink that appears to read 'Nicole Huang'.



(Engineering Adm. Assistant /
Nicole Huang)

Tested By :

A handwritten signature in blue ink that appears to read 'Vorana Chen'.

(Engineer / Vorana Chen)



Approved By :

A handwritten signature in blue ink that appears to read 'Vincent Lin'.

(Manager / Vincent Lin)

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	5
1.1. EUT Description.....	5
1.2. Operational Description.....	7
1.3. Tested System Details.....	8
1.4. Configuration of Tested System	8
1.5. EUT Exercise Software	8
1.6. Test Facility	9
2. CONDUCTED EMISSION	10
2.1. Test Equipment	10
2.2. Test Setup	10
2.3. Limits.....	11
2.4. Test Procedure	11
2.5. Uncertainty	11
2.6. Test Result of Conducted Emission.....	12
3. PEAK POWER OUTPUT	14
3.1. Test Equipment	14
3.2. Test Setup	14
3.3. Limit	14
3.4. Test Procedure	14
3.5. Uncertainty	14
3.6. Test Result of Peak Power Output.....	15
4. RADIATED EMISSION	16
4.1. Test Equipment	16
4.2. Test Setup	16
4.3. Limits.....	17
4.4. Test Procedure	18
4.5. Uncertainty	18
4.6. Test Result of Radiated Emission.....	19
5. RF ANTENNA CONDUCTED TEST	23
5.1. Test Equipment	23
5.2. Test Setup	23
5.3. Limits.....	23
5.4. Test Procedure	23
5.5. Uncertainty	23
5.6. Test Result of RF Antenna Conducted Test.....	24
6. BAND EDGE	27

6.1.	Test Equipment	27
6.2.	Test Setup	27
6.3.	Limit	28
6.4.	Test Procedure	28
6.5.	Uncertainty	28
6.6.	Test Result of Band Edge	29
7.	CHANNEL NUMBER.....	33
7.1.	Test Equipment	33
7.2.	Test Setup	33
7.3.	Limit	33
7.4.	Test Procedure	33
7.5.	Uncertainty	33
7.6.	Test Result of Channel Number.....	34
8.	CHANNEL SEPARATION.....	35
8.1.	Test Equipment	35
8.2.	Test Setup	35
8.3.	Limit	35
8.4.	Test Procedure	35
8.5.	Uncertainty	35
8.6.	Test Result of Channel Separation.....	36
9.	DWELL TIME.....	37
9.1.	Test Equipment	37
9.2.	Test Setup	37
9.3.	Limit	37
9.4.	Test Procedure	37
9.5.	Uncertainty	37
9.6.	Test Result of Dwell Time	38
10.	OCCUPIED BANDWIDTH	40
10.1.	Test Equipment	40
10.2.	Test Setup	40
10.3.	Limits.....	40
10.4.	Test Procedure	40
10.5.	Uncertainty	40
10.6.	Test Result of Occupied Bandwidth	41
11.	EMI REDUCTION METHOD DURING COMPLIANCE TESTING	44

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	MOBILE PHONE
Trade Name	PHONEX
Model No.	PG220
FCC ID.	VOMTS200
Frequency Range	2402 – 2480MHz
Channel Number	79
Type of Modulation	GFSK(1Mbps)
Antenna Type	Multilayer Chip Antenna
Channel Control	Auto
Antenna Gain	Refer to the table “Antenna List”
Power Adapter	M/N: BMT30UA AC Input: 100V-240V / 50-60Hz, 120mA DC Output: 5.0V, 500mA Cable Out: Non-Shielded 1.1m

Antenna List

No.	Manufacturer	Part No.	Peak Gain
1	MICROGATE	MGMA5220H2450-A01	2 dBi for 2.4 GHz

Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 00:	2402 MHz	Channel 20:	2422 MHz	Channel 40:	2442 MHz	Channel 60:	2462 MHz
Channel 01:	2403 MHz	Channel 21:	2423 MHz	Channel 41:	2443 MHz	Channel 61:	2463 MHz
Channel 02:	2404 MHz	Channel 22:	2424 MHz	Channel 42:	2444 MHz	Channel 62:	2464 MHz
Channel 03:	2405 MHz	Channel 23:	2425 MHz	Channel 43:	2445 MHz	Channel 63:	2465 MHz
Channel 04:	2406 MHz	Channel 24:	2426 MHz	Channel 44:	2446 MHz	Channel 64:	2466 MHz
Channel 05:	2407 MHz	Channel 25:	2427 MHz	Channel 45:	2447 MHz	Channel 65:	2467 MHz
Channel 06:	2408 MHz	Channel 26:	2428 MHz	Channel 46:	2448 MHz	Channel 66:	2468 MHz
Channel 07:	2409 MHz	Channel 27:	2429 MHz	Channel 47:	2449 MHz	Channel 67:	2469 MHz
Channel 08:	2410 MHz	Channel 28:	2430 MHz	Channel 48:	2450 MHz	Channel 68:	2470 MHz
Channel 09:	2411 MHz	Channel 29:	2431 MHz	Channel 49:	2451 MHz	Channel 69:	2471 MHz
Channel 10:	2412 MHz	Channel 30:	2432 MHz	Channel 50:	2452 MHz	Channel 70:	2472 MHz
Channel 11:	2413 MHz	Channel 31:	2433 MHz	Channel 51:	2453 MHz	Channel 71:	2473 MHz
Channel 12:	2414 MHz	Channel 32:	2434 MHz	Channel 52:	2454 MHz	Channel 72:	2474 MHz
Channel 13:	2415 MHz	Channel 33:	2435 MHz	Channel 53:	2455 MHz	Channel 73:	2475 MHz
Channel 14:	2416 MHz	Channel 34:	2436 MHz	Channel 54:	2456 MHz	Channel 74:	2476 MHz
Channel 15:	2417 MHz	Channel 35:	2437 MHz	Channel 55:	2457 MHz	Channel 75:	2477 MHz
Channel 16:	2418 MHz	Channel 36:	2438 MHz	Channel 56:	2458 MHz	Channel 76:	2478 MHz
Channel 17:	2419 MHz	Channel 37:	2439 MHz	Channel 57:	2459 MHz	Channel 77:	2479 MHz
Channel 18:	2420 MHz	Channel 38:	2440 MHz	Channel 58:	2460 MHz	Channel 78:	2480 MHz
Channel 19:	2421 MHz	Channel 39:	2441 MHz	Channel 59:	2461 MHz		

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. The transmitter is presented with a continuous data stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its 79 channels and over the minimum number of hopping channels (75 channels).

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Note:

1. This device is an MOBILE PHONE with a built-in 2.4GHz Bluetooth transceiver.
2. These tests were conducted on a sample for the purpose of demonstrating compliance of Bluetooth transmitter with Part 15 Subpart C Paragraph 15.247 for spread spectrum devices.
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
4. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

1.2. Operational Description

The EUT is a MOBILE PHONE with built-in 2.4GHz Bluetooth transceiver. The number of the channels is 79 in 2402-2480MHz. The device adapts the frequency hopping spread spectrum modulation. The antenna is Multilayer Chip Antenna and provides diversity function to improve the receiving function.

This device provides wireless technology that revolutionizes personal connectivity. It is the solution for the seamless integration of Bluetooth technology into personal computer enabling short-range wireless connections between desktop/laptop computers, Bluetooth-enabled peripherals, and portable handheld devices.

Test Mode	Mode 1: Transmitter - 1Mbps (GFSK)
-----------	------------------------------------


1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	FCC ID	Power Cord
(1) N/A	N/A	N/A	N/A	N/A	N/A

Signal Cable Type	Signal cable Description
A. N/A	N/A

1.4. Configuration of Tested System



1.5. EUT Exercise Software

- (1) Setup the EUT as shown in section 1.4
- (2) Power on the EUT.
- (3) Execute “BT TX Power” Program
- (4) Click on the test channel to transmit continuously.
- (5) Verify that the EUT works properly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	30-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from QuieTek Corporation's Web Site : <http://tw.quietek.com/modules/myalbum/>

The address and introduction of QuieTek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>

Site Description: File on

Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Registration Number: 92195



Accreditation on NVLAP
NVLAP Lab Code: 200533-0



Site Name: Quietek Corporation
Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,
Lin-Kou Shiang, Taipei,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com

FCC Accreditation Number: TW1014



2. Conducted Emission


2.1. Test Equipment

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/100367	Aug., 2008	
2	L.I.S.N.	R & S	ESH3-Z5/836679/023	Jul., 2008	EUT
3	L.I.S.N.	R & S	ESH3-Z5/836679/017	Feb., 2009	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2/357.8810.52	Sep., 2008	
5	No.8 Shielded Room			N/A	

Note: All instruments are calibrated every one year.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

Remarks: In the above table, the tighter limit applies at the band edges.

2.4. Test Procedure

The EUT and Peripherals are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

2.5. Uncertainty

± 2.26 dB

2.6. Test Result of Conducted Emission

Product : MOBILE PHONE
 Test Item : Conducted Emission Test
 Power Line : Line 1
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK) (2441MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV	dB	dBuV
LINE 1					
Quasi-Peak					
0.205	9.703	23.720	33.423	-31.006	64.429
0.267	9.665	25.010	34.675	-27.982	62.657
0.490	9.640	35.070	44.710	-11.576	56.286
1.123	9.670	19.650	29.320	-26.680	56.000
1.888	9.680	16.830	26.510	-29.490	56.000
5.877	9.720	19.040	28.760	-31.240	60.000
Average					
0.205	9.703	11.830	21.533	-32.896	54.429
0.267	9.665	12.060	21.725	-30.932	52.657
0.490	9.640	22.300	31.940	-14.346	46.286
1.123	9.670	8.090	17.760	-28.240	46.000
1.888	9.680	2.830	12.510	-33.490	46.000
5.877	9.720	6.070	15.790	-34.210	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "  " means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : MOBILE PHONE
 Test Item : Conducted Emission Test
 Power Line : Line 2
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK) (2441MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV	dB	dBuV
LINE 2					
Quasi-Peak					
0.205	9.713	19.670	29.383	-35.046	64.429
0.263	9.677	19.480	29.157	-33.614	62.771
0.478	9.640	27.230	36.870	-19.759	56.629
0.966	9.670	19.450	29.120	-26.880	56.000
1.431	9.670	16.740	26.410	-29.590	56.000
2.310	9.680	14.450	24.130	-31.870	56.000
Average					
0.205	9.713	6.990	16.703	-37.726	54.429
0.263	9.677	5.250	14.927	-37.844	52.771
0.478	9.640	12.370	22.010	-24.619	46.629
0.966	9.670	8.190	17.860	-28.140	46.000
1.431	9.670	1.820	11.490	-34.510	46.000
2.310	9.680	0.960	10.640	-35.360	46.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. " " means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

3. Peak Power Output


3.1. Test Equipment

The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Power Meter	Anritsu	ML2495A/6K00003357	May, 2009
Power Sensor	Anritsu	MA2491A/034457	May, 2009

Note: 1. All equipments are calibrated every one year.

3.2. Test Setup



3.3. Limit

The maximum peak power shall be less 1Watt.

3.4. Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

3.5. Uncertainty

± 1.27 dB

3.6. Test Result of Peak Power Output

Product : MOBILE PHONE
Test Item : Peak Power Output
Test Site : CTR
Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)

Channel No.	Frequency (MHz)	Measurement	Required Limit	Result
Channel 00	2402.00	-1.54 dBm	1 Watt= 30 dBm	Pass
Channel 39	2441.00	-1.62 dBm	1 Watt= 30 dBm	Pass
Channel 78	2480.00	-1.99 dBm	1 Watt= 30 dBm	Pass

4. Radiated Emission

4.1. Test Equipment


The following test equipments are used during the radiated emission test:

Test Site	Equipment		Manufacturer	Model No./Serial No.	Last Cal.
Site # 2	X	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2008
	X	Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2008
	X	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2008
	X	Pre-Amplifier	AGILENT	8447D/2944A09549	Sep., 2008
	X	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2008
	X	Spectrum Analyzer	Advantest	R3162/91700283	Oct., 2008
	X	Coaxial Cable	QuiTek	QTK-CABLE/ CAB5	Feb., 2009
	X	Controller	QuiTek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A


Note: 1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

4.2. Test Setup

Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



4.3. Limits

➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	uV/m @ 3m	dBuV/m @ 3m
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Remarks:

1. RF Voltage (dBuV) = $20 \log \text{RF Voltage (uV)}$
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

4.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003 and tested according to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2003 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

Radiated emission measurements below 1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB beamwidth of the antenna.

The worst radiated emission is measured on the Final Measurement.

The frequency range from 30MHz to 10th harmonics is checked.

4.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

4.6. Test Result of Radiated Emission

Product : MOBILE PHONE
 Test Item : Harmonic Radiated Emission
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)(2402MHz)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
------------------	-------------------------	--------------------------	--------------------------------	--------------	-----------------

Horizontal

Peak Detector:

4804.000	0.643	43.360	44.003	-29.997	74.000
7206.000	5.014	42.680	47.694	-26.306	74.000
9608.000	8.255	41.890	50.144	-23.856	74.000

Average

Detector:

--

Vertical

Peak Detector:

4804.000	0.643	42.720	43.363	-30.637	74.000
7206.000	5.014	41.960	46.974	-27.026	74.000
9608.000	8.255	41.390	49.644	-24.356	74.000

Average

Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz .
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:10Hz; Span:20MHz .
4. Emission Level = Reading Level + Correct Factor.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : MOBILE PHONE
 Test Item : Harmonic Radiated Emission
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)(2441MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m

Horizontal

Peak Detector:

4882.000	0.623	43.370	43.993	-30.007	74.000
7323.000	5.086	41.490	46.576	-27.424	74.000
9764.000	8.696	40.970	49.666	-24.334	74.000

Average

Detector:

--

Vertical

Peak Detector:

4882.000	0.623	43.630	44.253	-29.747	74.000
7323.000	5.086	41.480	46.566	-27.434	74.000
9764.000	8.696	40.350	49.046	-24.954	74.000

Average

Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz .
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:10Hz; Span:20MHz .
4. Emission Level = Reading Level + Correct Factor.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : MOBILE PHONE
 Test Item : Harmonic Radiated Emission
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)(2480MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m

Horizontal

Peak Detector:

4960.000	1.553	43.030	44.583	-29.417	74.000
7440.000	5.714	40.020	45.734	-28.266	74.000
9920.000	8.878	40.380	49.258	-24.742	74.000

Average

Detector:

--

Vertical

Peak Detector:

4960.000	1.553	42.960	44.513	-29.487	74.000
7440.000	5.714	40.160	45.874	-28.126	74.000
9920.000	8.878	40.300	49.178	-24.822	74.000

Average

Detector:

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz .
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:10Hz; Span:20MHz .
4. Emission Level = Reading Level + Correct Factor.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : MOBILE PHONE
 Test Item : General Radiated Emission
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)(2441MHz)

Frequency	Correct Factor	Reading Level	Measurement Level	Margin	Limit
MHz	dB	dBuV	dBuV/m	dB	dBuV/m
Horizontal					
34.625	17.320	4.116	21.436	-18.564	40.000
57.635	7.405	4.569	11.974	-28.026	40.000
159.020	12.529	2.174	14.703	-28.797	43.500
288.065	15.661	3.498	19.160	-26.840	46.000
475.265	21.852	8.141	29.993	-16.007	46.000
834.250	26.382	2.675	29.057	-16.943	46.000
Vertical					
88.660	10.047	14.911	24.958	-18.542	43.500
178.265	11.333	12.583	23.916	-19.584	43.500
227.880	13.060	9.858	22.918	-23.082	46.000
378.590	19.256	3.680	22.936	-23.064	46.000
677.325	23.983	3.338	27.321	-18.679	46.000
962.350	27.980	1.738	29.718	-24.282	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. “ ” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.
4. The radiated emissions below 1GHz of the lowest, middle, highest frequency are pretested. Only the worst case is shown on the report.


5. RF Antenna Conducted Test

5.1. Test Equipment

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100339	Jun, 2009
X Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2009
Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr, 2009

Note: 1. All equipments are calibrated every one year.
2. The test instruments Marked "X" are used to measure the final test results.

5.2. Test Setup



5.3. Limits

According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

5.4. Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

5.5. Uncertainty

± 150Hz

5.6. Test Result of RF Antenna Conducted Test

Product : MOBILE PHONE
 Test Item : RF Antenna Conducted Test
 Test Site : CTR
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)

Figure Channel 00: 30MHz-1GHz





Figure Channel 00: 1GHz -25GHz



Product : MOBILE PHONE
 Test Item : RF Antenna Conducted Test
 Test Site : CTR
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)

Figure Channel 39: 30MHz-1GHz





Figure Channel 39: 1GHz -25GHz



Product : MOBILE PHONE
 Test Item : RF Antenna Conducted Test
 Test Site : CTR
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)

Figure Channel 78: 30MHz-1GHz





Figure Channel 39: 1GHz -25GHz



6. Band Edge

6.1. Test Equipment

The following test equipments are used during the band edge tests:


Test Site	Equipment		Manufacturer	Model No./Serial No.	Last Cal.
Site # 2	X	Bilog Antenna	Schaffner Chase	CBL6112B/2673	Sep., 2008
	X	Horn Antenna	Schwarzbeck	BBHA9120D/D305	Sep., 2008
	X	Horn Antenna	Schwarzbeck	BBHA9170/208	Jul., 2008
	X	Pre-Amplifier	AGILENT	8447D/2944A09549	Sep., 2008
	X	Test Receiver	R & S	ESCS 30/ 825442/018	Sep., 2008
	X	Spectrum Analyzer	Advantest	R3162/91700283	Oct., 2008
	X	Coaxial Cable	Quietek	QTK-CABLE/ CAB5	Feb., 2009
	X	Controller	Quietek	QTK-CONTROLLER/ CTRL3	N/A
	X	Coaxial Switch	Anritsu	MP59B/6200265729	N/A

Note: 1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

6.2. Test Setup

RF Radiated Measurement:

Above 1GHz



6.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

6.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4:2003 on radiated measurement.

The bandwidth below 1GHz setting on the field strength meter is 120 kHz, above 1GHz are 1 MHz. The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

6.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

6.6. Test Result of Band Edge


Product : MOBILE PHONE
Test Item : Band Edge
Test Site : No.2 OATS
Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
00 (Peak)	2390.000	-6.742	54.404	47.663	74.00	54.00	Pass

Figure Channel 00:

Horizontal (Peak)




Note: RBW=1MHz, VBW=1MHz, Sweep=500ms

Product : MOBILE PHONE
Test Item : Band Edge
Test Site : No.2 OATS
Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
00 (Peak)	2390.000	-6.742	58.411	51.670	74.00	54.00	Pass


Figure Channel 00:**Vertical (Peak)**

Note: RBW=1MHz, VBW=1MHz, Sweep=500ms


Product : MOBILE PHONE
 Test Item : Band Edge
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
78 (Peak)	2483.500	-6.419	63.025	56.606	74.00	54.00	Pass
78 (Average)	2483.500	-6.419	46.895	40.476	74.00	54.00	Pass

Figure Channel 78:
Horizontal (Peak)


Note: RBW=1MHz, VBW=1MHz, Sweep=500ms


Figure Channel 78:
Horizontal (Average)


Note: RBW=1MHz, VBW=30Hz, Sweep=2s

Product : MOBILE PHONE
 Test Item : Band Edge
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Average Limit (dBuV/m)	Result
78 (Peak)	2483.500	-6.419	54.796	48.377	74.00	54.00	Pass

Figure Channel 78:
Vertical (Peak)


Note: RBW=1MHz, VBW=1MHz, Sweep=500ms

7. Channel Number

7.1. Test Equipment


The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100339	Jun, 2009
X Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2009
Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2009

Note: 1. All equipments are calibrated every one year.

2. The test instruments marked by "X" are used to measure the final test results.

7.2. Test Setup



7.3. Limit

Frequency hopping systems operating in the 2400-2483.5 MHz bands shall use at least 75 hopping frequencies.

7.4. Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

7.5. Uncertainty


N/A

7.6. Test Result of Channel Number


Product : MOBILE PHONE
 Test Item : Channel Number
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)

Frequency Range (MHz)	Measurement (Hopping Channel)	Required Limit (Hopping Channel)	Result
2402 ~ 2480	79	>75	Pass


2402-2421MHz




2422-2441MHz



2442-2461MHz



2462-2480MHz



8. Channel Separation


8.1. Test Equipment

The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100339	Jun, 2009
X Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2009
Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2009

Note: 1. All equipments are calibrated every one year.
2. The test instruments mark by "X" are used to measure the final test results.

8.2. Test Setup



8.3. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the $2/3 \times (20 \text{ dB bandwidth})$ of the hopping channel, whichever is greater.

8.4. Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

8.5. Uncertainty


$\pm 150\text{Hz}$

8.6. Test Result of Channel Separation

Product : MOBILE PHONE
 Test Item : Channel Separation
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)

Frequency (MHz)	Measurement Level (kHz)	Limit (kHz)	Limit of (2/3)*20dB Bandwidth (kHz)	Result
2402	1000	>25 kHz	444	Pass
2441	1000	>25 kHz	444	Pass
2480	1000	>25 kHz	499	Pass


Channel 00 2402MHz



Channel 39 2441MHz



Channel 78 2480 MHz



9. Dwell Time


9.1. Test Equipment

The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100339	Jun, 2009
X Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2009
Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2009

Note: 1. All equipments are calibrated every one year.
2. The test instruments marked by “X” are used to measure the final test results.

9.2. Test Setup



9.3. Limit

The dwell time shall be the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

9.4. Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

9.5. Uncertainty

± 25msec

9.6. Test Result of Dwell Time


Product : MOBILE PHONE
 Test Item : Dwell Time
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK) (Channel 00,39,78 –DH5)

Frequency (MHz)	Time slot length (ms)	Hopping of Number	Sweep time (ms)	Duty cycle	Dwell Time (Sec)	Limit (Sec)	Result
2402	3.650	13	50	0.95	0.380	0.4	Pass
2441	3.650	13	50	0.95	0.380	0.4	Pass
2480	3.700	13	50	0.96	0.385	0.4	Pass


Duty cycle =((Time slot length(ms)*Hopping of Number) / Sweep time (ms)

Dwell time = (Duty cycle /79) * (79*0.4)


Hopping of Number




Time slot length





Hopping of Number



Time slot length



Hopping of Number

Time slot length

Note:

The dwell times of the packet type of DH1, DH3, and DH5 are tested. Only the worst case is shown on the report.

10. Occupied Bandwidth


10.1. Test Equipment

The following test equipments are used during the radiated emission tests:

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100339	Jun, 2009
X Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2009
Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2009

Note: 1. All equipments are calibrated every one year.
2. The test instruments marked by “X” are used to measure the final test results.

10.2. Test Setup



10.3. Limits

N/A

10.4. Test Procedure

The EUT was setup to ANSI C63.4, 2003; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

10.5. Uncertainty


± 150Hz

10.6. Test Result of Occupied Bandwidth

Product : MOBILE PHONE
Test Item : Occupied Bandwidth Data
Test Site : No.2 OATS
Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)(2402MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
00	2402	665.8	--	NA


Figure Channel 00:



Product : MOBILE PHONE
 Test Item : Occupied Bandwidth Data
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)(2441MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
39	2441	665.8	--	NA


Figure Channel 39:



Product : MOBILE PHONE
 Test Item : Occupied Bandwidth Data
 Test Site : No.2 OATS
 Test Mode : Mode 1: Transmitter - 1Mbps (GFSK)(2480MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
78	2480	748.1	--	NA

Figure Channel 78:



11. EMI Reduction Method During Compliance Testing

No modification was made during testing.