

# **RF Exposure Report**

Report No.: SA161028C01

FCC ID: VPQ-PIXIUMDHXA222

Test Model: DHXA-222

Received Date: Nov. 11, 2016

Test Date: Feb. 02 ~ Feb. 23, 2017

**Issued Date:** Mar. 07, 2017

**Applicant: TRIXELL** 

Address: 460, rue du Pommarin 38430 Moirans, France

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan,

R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA161028C01 Page No. 1 / 5 Report Format Version: 6.1.1



# **Table of Contents**

Rele	ease Control Record	3
1	Certificate of Conformity	4
	RF Exposure	
2. 2.	1 Limits for Maximum Permissible Exposure (MPE)	5 5
3	Calculation Result of Maximum Conducted Power	5



# **Release Control Record**

Issue No.	Description	Date Issued
SA161028C01	Original release.	Mar. 07, 2017



#### 1 Certificate of Conformity

Product: pixium 3543 DR

**Brand: TRIXELL** 

Test Model: DHXA-222

Sample Status: Engineering sample

**Applicant:** TRIXELL

**Test Date:** Feb. 02 ~ Feb. 23, 2017

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

**IEEE C95.1** 

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , Date: Mar. 07, 2017

Suntee Liu / Specialist

**Approved by:** Mar. 07, 2017

Ken Liu / Senior Manager



### 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
300-1500			F/1500	30				
1500-100,000			1.0	30				

F = Frequency in MHz

### 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm <sup>2</sup> )
WLAN 2412~2462	20.21	2.24	20	0.035	1
WLAN 5180~5240	17.78	4.84	20	0.036	1
WLAN 5260~5320	18.21	4.84	20	0.040	1
WLAN 5500~5700	18.26	4.84	20	0.041	1
WLAN 5745~5825	17.42	4.84	20	0.033	1

Note:

2.4GHz: Directional gain = -0.77dBi + 10log(2) = 2.24dBi 5GHz: Directional gain = 1.83dBi + 10log(2) = 4.84dBi

---END---