

RF Exposure Statement:

Page 1 of 1

Client: Murata Manufacturing Co.,Ltd

10-1, Higashikotari 1-chome Nagaokakyo-shi ,Kyoto ,Japan

Test item: WIFI Module

Identification: Mode name : CMWC1ZZAAF

FCC ID: VPYAAF

# **FCC Requirement**

According to FCC 2.1091, mobile equipment must comply with the following applicable limit for maximum permissible exposure (MPE) specified in FCC 1.1310:

Equipment Use	Frequency Range	Power Density [mW/cm <sup>2</sup> ]	Average Time [min]
General Population / Uncontrolled Exposure	1.5 – 100GHz	1	6

# **IC Requirement**

According to RSS-102 (Issue 4), clause 2.5.2, no routine RF exposure evaluation is required if the transmitter power (e.i.r.p.) is below the following threshold:

Frequency Range	SAR Limitation [W]	
Above 1.5GHz	5	

#### **Measurement Result**

The maximum measured transmitter power is the following:

Conducted Output Power P <sub>out</sub> [mW]	Maximum Antenna Gain [dBi]	P <sub>out</sub> EIRP [mW]	Power Density at 20cm [mW/cm <sup>2</sup> ]
150	3.3	322	0.063

### Note:

The power density S in mW/cm<sup>2</sup> is calculated according to the Friis formula:  $S = (P_{out} \cdot G) / (4\pi \cdot D^2)$ , where  $S = power density in mW/cm^2$ 

Pout = antenna conducted output power in mW

G = antenna gain in linear scale (here: 3.3dBi=10log(G))

D = distance between observation point and radiating structure in cm (here: 20cm)

### Conclusion

The device complies with the FCC and IC RF exposure requirements since the maximum transmitter power density is below the FCC limit and the e.i.r.p. power is below the IC RF exposure evaluation exemption threshold.

Refer to test report 15063930 001 for more details.