



Pref test Plot








Antenna2

Test Mode	Channel	Verdict
11B	LCH	PASS

Pref test Plot




Pref test Plot







Test Mode	Channel	Verdict
11B	MCH	PASS

Pref test Plot




Pref test Plot







Test Mode	Channel	Verdict
11B	HCH	PASS

Pref test Plot






Pref test Plot







Test Mode	Channel	Verdict
11G	LCH	PASS


Pref test Plot






Pref test Plot







Test Mode	Channel	Verdict
11G	MCH	PASS

Pref test Plot




Pref test Plot







Test Mode	Channel	Verdict
11G	HCH	PASS

Pref test Plot






Pref test Plot







Test Mode	Channel	Verdict
11N20 MIMO	LCH	PASS

Pref test Plot




Pref test Plot







Test Mode	Channel	Verdict
11N20 MIMO	MCH	PASS

Pref test Plot






Pref test Plot







Test Mode	Channel	Verdict
11N20 MIMO	HCH	PASS

Pref test Plot




Pref test Plot







Test Mode	Channel	Verdict
11N40MIMO	LCH	PASS

Pref test Plot






Pref test Plot







Test Mode	Channel	Verdict
11N40MIMO	MCH	PASS

Pref test Plot




Pref test Plot







Test Mode	Channel	Verdict
11N40MIMO	HCH	PASS

Pref test Plot





Pref test Plot



6.6. RADIATED TEST RESULTS

6.6.1. LIMITS AND PROCEDURE

LIMITS

Please refer to FCC §15.205, §15.209 and RSS-GEN Clause 8.9

Please refer to FCC KDB 558074

Radiation Disturbance Test Limit for FCC (Class B) (9 KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.



Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

Restricted bands of operation


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyzer

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

Below 1G




The setting of the spectrum analyzer

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurements above 1 GHz, the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector, max hold to be run for at least 50 x (1/duty cycle) traces for average measurements.
6. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration).

ABOVE 1G




The setting of the spectrum analyzer

RBW	1M
VBW	PEAK:3M AVG: See note6
Sweep	Auto
Detector	Peak/Average(10Hz)
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector, max hold to be run for at least 50 x (1/duty cycle) traces for average measurements..
8. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

X axis, Y axis, Z axis positions:



Note: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (Z axis) data recorded in the report.

6.6.2.RESTRICTED BANDEDGE

Test Result Table

Test Mode	Test Antenna	Channel	P _{uw} (dBm)	Verdict
11B	Antenna 1+2	LCH	<Limit	PASS
		MCH	<Limit	PASS
		HCH	<Limit	PASS
11G	Antenna 1+2	LCH	<Limit	PASS
		MCH	<Limit	PASS
		HCH	<Limit	PASS
11N20 MIMO	Antenna 1+2	LCH	<Limit	PASS
		MCH	<Limit	PASS
		HCH	<Limit	PASS
11N40MIMO	Antenna 1+2	LCH	<Limit	PASS
		MCH	<Limit	PASS
		HCH	<Limit	PASS


Remark: For this product, it has two antennas, antenna1 and antenna2, it can transmit at the same time during work at 802.11B & 802.11G & 802.11N20 & 802.11N40 modes, but only the 802.11N20 & 802.11N40 modes support the MIMO technical.



Test Graphs:

Antenna 1+2

Test Mode	Channel	Polarization	Verdict
11B	LCH	Horizontal	PASS




No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2333.1670	51.68	74.00	-22.32	peak
	2333.1670	37.59	54.00	-16.41	average
2	2390.000	56.13	74.00	-17.87	peak
	2390.000	43.13	54.00	-10.87	average

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=10 Hz.



Test Mode	Channel	Polarization	Verdict
11B	LCH	Vertical	PASS




No.	Frequency	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dBuV/m)	(dB)	
1	2336.3654	52.52	74.00	-21.48	peak
	2336.3654	37.99	54.00	-16.01	average
2	2390.000	55.21	74.00	-18.79	peak
	2390.000	42.04	54.00	-11.96	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=10 Hz.



Test Mode	Channel	Polarization	Verdict
11B	HCH	Horizontal	PASS




No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	57.61	74.00	-16.39	peak
	2483.500	43.63	54.00	-10.37	average
2	2538.9629	51.90	74.00	-22.10	peak
	2538.9629	38.67	54.00	-15.33	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=10 Hz.



Test Mode	Channel	Polarization	Verdict
11B	HCH	Vertical	PASS




No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	58.62	74.00	-15.38	peak
	2483.500	41.70	54.00	-12.30	average
2	2541.5661	58.62	74.00	-15.38	peak
	2541.5661	51.87	74.00	-22.13	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=10 Hz.



Test Mode	Channel	Polarization	Verdict
11G	LCH	Horizontal	PASS




No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2326.9264	56.04	74.00	-17.96	peak
	2326.9264	37.03	54.00	-16.97	average
2	2390.000	62.67	74.00	-11.33	peak
	2390.000	46.25	54.00	-7.75	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=1/T Hz.



Test Mode	Channel	Polarization	Verdict
11G	LCH	Vertical	PASS




No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2331.8659	53.03	74.00	-20.97	peak
	2331.8659	37.74	54.00	-16.26	average
2	2390.000	57.81	74.00	-16.19	peak
	2390.000	42.13	54.00	-11.87	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=1/T Hz.



Test Mode	Channel	Polarization	Verdict
11G	HCH	Horizontal	PASS




No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	66.86	74.00	-7.14	peak
	2483.500	49.65	54.00	-4.35	average
2	2526.0502	52.49	74.00	-21.51	peak
	2526.0502	38.60	54.00	-15.40	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=1/T Hz.



Test Mode	Channel	Polarization	Verdict
11G	HCH	Vertical	PASS




No.	Frequency	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	62.37	74.00	-11.63	peak
	2483.500	46.09	54.00	-7.91	average
2	2528.6481	51.83	74.00	-22.17	peak
	2528.6481	38.62	54.00	-15.38	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=1/T Hz.



Test Mode	Channel	Polarization	Verdict
11N20 MIMO	LCH	Horizontal	PASS




No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2327.1824	53.15	74.00	-20.85	peak
	2327.1824	39.26	54.00	-14.74	average
2	2390.000	59.58	74.00	-14.42	peak
	2390.000	45.70	54.00	-8.30	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=1/T Hz.



Test Mode	Channel	Polarization	Verdict
11N20 MIMO	LCH	Vertical	PASS




No.	Frequency	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dBuV/m)	(dB)	
1	2328.0171	53.29	74.00	-20.71	peak
	2328.0171	38.81	54.00	-15.19	average
2	2390.000	56.25	74.00	-17.75	peak
	2390.000	42.18	54.00	-11.82	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=1/T Hz.



Test Mode	Channel	Polarization	Verdict
11N20 MIMO	HCH	Horizontal	PASS



No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	60.44	74.00	-13.56	peak
	2483.500	44.75	54.00	-9.25	average
2	2547.3467	52.48	74.00	-21.52	peak
	2547.3467	38.88	54.00	-15.12	average

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. For average power measurement, set the VBW to Minimum VBW=1/T Hz.