

Page: 81 of 234

#### **Measurement Procedure** 11.4

- The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules .
- The EUT was placed on a turn table with 0.8m for frequency< 1GHz and 1.5m for frequency> 3. 1GHz above ground plane.
- 4. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 5. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- Set the spectrum analyzer as RBW=120 kHz and VBW=300 kHz for Peak Detector (PK) and Quasi-peak (QP) at frequency below 1 GHz.
- Set the spectrum analyzer as RBW=1 MHz, VBW=3 MHz for Peak Detector at frequency above 1 GHz.
- Set the spectrum analyzer as RBW=1 MHz, VBW=10 Hz (Duty cycle > 98%) or VBW ≥ 1/T (Duty cycle < 98%) for Average Detector at frequency above 1 GHz.
- Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 10. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 11. Repeat above procedures until all frequency measured were complete.

#### 11.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

Actual FS(dB $\mu$ V/m) = SPA. Reading level(dB $\mu$ V) + Factor(dB)

Factor(dB) = Antenna Factor(dBµV/m) + Cable Loss(dB) - Pre\_Amplifier Gain(dB)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 82 of 234

## 11.6 Test Results of Radiated Spurious Emissions form 9 KHz to 30 MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit per 15.31(o) & RSS-GEN §6.13.2 was not reported.

Pre-scanned was done at frequency 5.47 GHz and 5.85 GHz for bandedge measurement of straddle channels 138, 142 and 144 which was 20dB lower than the limit per 15.31(o) & RSS-GEN §6.13.2 was not reported.

#### 11.7 Measurement Result

Refer to next page for tabular data sheets.




Page: 83 of 234

# **Radiated Spurious Emission Measurement Result Below 1GHz Worst-Case Data:**

## 802.11a 5150~5250 MHz

**Project Number** :T190506W05 **Operation Band** :802.11a / Band1 **Fundamental Frequency** :5220 MHz :Tx CH Mid **Operation Mode** EUT Pol. :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
105.66	Peak	33.56	-11.02	22.54	43.50	-20.96
120.21	Peak	28.35	-8.88	19.47	43.50	-24.03
194.90	Peak	28.95	-10.06	18.89	43.50	-24.61
293.84	Peak	28.21	-8.32	19.89	46.00	-26.11
376.29	Peak	28.86	-6.37	22.49	46.00	-23.51
447.10	Peak	27.97	-3.94	24.03	46.00	-21.97

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 84 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band1 :5220 MHz :Tx CH Mid :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
105.66	Peak	35.11	-11.02	24.09	43.50	-19.41
191.99	Peak	27.89	-10.55	17.34	43.50	-26.16
279.29	Peak	28.67	-8.40	20.27	46.00	-25.73
332.64	Peak	29.54	-7.17	22.37	46.00	-23.63
503.36	Peak	26.93	-3.03	23.90	46.00	-22.10
551.86	Peak	29.13	-2.22	26.91	46.00	-19.09

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 85 of 234

#### 802.11a 5250~5350 MHz

**Proiect Number** :T190506W05 **Operation Band** :802.11a / Band2

**Fundamental Frequency** :5300 MHz **Operation Mode** :Tx CH Mid

EUT Pol. :E2 Plan **Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
105.66	Peak	31.53	-11.02	20.51	43.50	-22.99
120.21	Peak	28.82	-8.88	19.94	43.50	-23.56
359.80	Peak	29.98	-6.59	23.39	46.00	-22.61
440.31	Peak	27.09	-4.04	23.05	46.00	-22.95
503.36	Peak	27.59	-3.03	24.56	46.00	-21.44
551.86	Peak	30.82	-2.22	28.60	46.00	-17.40

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 86 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band2 :5300 MHz :Tx CH Mid

:E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμ̈V	dB	dBμV/m	dBµV/m	dB
105.66	Peak	35.37	-11.02	24.35	43.50	-19.15
120.21	Peak	28.03	-8.88	19.15	43.50	-24.35
277.35	Peak	28.88	-8.41	20.47	46.00	-25.53
366.59	Peak	28.59	-6.50	22.09	46.00	-23.91
503.36	Peak	26.89	-3.03	23.86	46.00	-22.14
551.86	Peak	28.29	-2.22	26.07	46.00	-19.93

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 87 of 234

### 802.11a 5470~5725 MHz

**Proiect Number** :T190506W05 **Operation Band** :802.11a / Band3 :5580 MHz

**Fundamental Frequency Operation Mode** :Tx CH Mid

EUT Pol. :E2 Plan **Test Date** :2019-05-21 Temp./Humi. :21/52 :Kane Engineer Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
93.05	Peak	35.23	-14.62	20.61	43.50	-22.89
105.66	Peak	31.92	-11.02	20.90	43.50	-22.60
374.35	Peak	28.82	-6.37	22.45	46.00	-23.55
449.04	Peak	28.00	-3.88	24.12	46.00	-21.88
503.36	Peak	27.40	-3.03	24.37	46.00	-21.63
551.86	Peak	31.15	-2.22	28.93	46.00	-17.07

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 88 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band3 :5580 MHz :Tx CH Mid :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
105.66	Peak	34.66	-11.02	23.64	43.50	-19.86
183.26	Peak	28.30	-11.23	17.07	43.50	-26.43
282.20	Peak	27.60	-8.42	19.18	46.00	-26.82
343.31	Peak	28.69	-7.14	21.55	46.00	-24.45
444.19	Peak	26.42	-4.11	22.31	46.00	-23.69
551.86	Peak	29.30	-2.22	27.08	46.00	-18.92

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 89 of 234

#### 802.11a 5725~5850 MHz

**Proiect Number** :T190506W05 **Operation Band** :802.11a / Band4

**Fundamental Frequency** :5785 MHz **Operation Mode** :Tx CH Mid

EUT Pol. :E2 Plan **Test Date** :2019-05-21 Temp./Humi. :21/52 :Kane Engineer Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
94.99	Peak	34.16	-14.24	19.92	43.50	-23.58
105.66	Peak	32.47	-11.02	21.45	43.50	-22.05
359.80	Peak	28.49	-6.59	21.90	46.00	-24.10
449.04	Peak	27.84	-3.88	23.96	46.00	-22.04
503.36	Peak	27.39	-3.03	24.36	46.00	-21.64
551.86	Peak	31.83	-2.22	29.61	46.00	-16.39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 90 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band4 :5785 MHz

:Tx CH Mid :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
N. AL. I	Mode	Reading Level	ID.	FS ID V	@3m	ID
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dΒμV/m	dB
105.66	Peak	35.12	-11.02	24.10	43.50	-19.40
190.05	Peak	29.07	-10.77	18.30	43.50	-25.20
274.44	Peak	27.23	-8.44	18.79	46.00	-27.21
325.85	Peak	28.33	-7.32	21.01	46.00	-24.99
444.19	Peak	27.07	-4.11	22.96	46.00	-23.04
551.86	Peak	28.35	-2.22	26.13	46.00	-19.87

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 91 of 234


#### 802.11ac 5150~5250 MHz

**Proiect Number** :T190506W05

**Operation Band** :802.11ac80 / Band1 **Fundamental Frequency** :5210 MHz

**Operation Mode** :Tx CH Low EUT Pol. :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
91.11	Peak	34.83	-15.12	19.71	43.50	-23.79
191.99	Peak	29.28	-10.55	18.73	43.50	-24.77
354.95	Peak	28.34	-6.80	21.54	46.00	-24.46
449.04	Peak	27.66	-3.88	23.78	46.00	-22.22
503.36	Peak	27.04	-3.03	24.01	46.00	-21.99
551.86	Peak	31.91	-2.22	29.69	46.00	-16.31

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 92 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11ac80 / Band1

:5210 MHz :Tx CH Low :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
105.66	Peak	35.17	-11.02	24.15	43.50	-19.35
182.29	Peak	29.15	-11.28	17.87	43.50	-25.63
275.41	Peak	28.22	-8.42	19.80	46.00	-26.20
330.70	Peak	27.84	-7.08	20.76	46.00	-25.24
490.75	Peak	25.63	-3.09	22.54	46.00	-23.46
551.86	Peak	28.29	-2.22	26.07	46.00	-19.93

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 93 of 234


#### 802.11ac 5250~5350 MHz

**Proiect Number** :T190506W05 **Operation Band** :802.11ac80 / Band2

**Fundamental Frequency** :5290 MHz

**Operation Mode** :Tx CH High EUT Pol. :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
105.66	Peak	31.94	-11.02	20.92	43.50	-22.58
191.99	Peak	29.11	-10.55	18.56	43.50	-24.94
372.41	Peak	28.46	-6.40	22.06	46.00	-23.94
449.04	Peak	27.11	-3.88	23.23	46.00	-22.77
503.36	Peak	27.14	-3.03	24.11	46.00	-21.89
551.86	Peak	32.32	-2.22	30.10	46.00	-15.90

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 94 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11ac80 / Band2

:5290 MHz :Tx CH High :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
105.66	Peak	35.31	-11.02	24.29	43.50	-19.21
190.05	Peak	28.88	-10.77	18.11	43.50	-25.39
284.14	Peak	27.47	-8.44	19.03	46.00	-26.97
330.70	Peak	28.02	-7.08	20.94	46.00	-25.06
447.10	Peak	26.83	-3.94	22.89	46.00	-23.11
551.86	Peak	28.97	-2.22	26.75	46.00	-19.25

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 95 of 234


#### 802.11ac 5470~5725 MHz

**Proiect Number** :T190506W05 **Operation Band** :802.11ac80 / Band3

**Fundamental Frequency** :5610 MHz

**Operation Mode** :Tx CH Mid EUT Pol. :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
MHz	Mode PK/QP/AV	Reading Level dBµV	dB	FS dBµV/m	@3m dBµV/m	dB
94.99	Peak	34.68	-14.24	20.44	43.50	-23.06
120.21	Peak	29.22	-8.88	20.34	43.50	-23.16
190.05	Peak	30.91	-10.77	20.14	43.50	-23.36
353.01	Peak	28.90	-6.85	22.05	46.00	-23.95
456.80	Peak	27.83	-3.76	24.07	46.00	-21.93
551.86	Peak	32.10	-2.22	29.88	46.00	-16.12

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 96 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11ac80 / Band3

:5610 MHz :Tx CH Mid :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
105.66	Peak	36.10	-11.02	25.08	43.50	-18.42
194.90	Peak	27.24	-10.06	17.18	43.50	-26.32
275.41	Peak	27.66	-8.42	19.24	46.00	-26.76
325.85	Peak	27.93	-7.32	20.61	46.00	-25.39
444.19	Peak	26.38	-4.11	22.27	46.00	-23.73
551.86	Peak	26.94	-2.22	24.72	46.00	-21.28

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 97 of 234

#### 802.11ac 5725~5850 MHz

**Proiect Number** :T190506W05


**Operation Band** :802.11ac80 / Band4

:5775 MHz

**Fundamental Frequency** 

**Operation Mode** :Tx CH High

EUT Pol. :E2 Plan **Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
105.66	Peak	31.45	-11.02	20.43	43.50	-23.07
143.49	Peak	29.10	-9.86	19.24	43.50	-24.26
191.99	Peak	29.88	-10.55	19.33	43.50	-24.17
357.86	Peak	28.95	-6.68	22.27	46.00	-23.73
456.80	Peak	27.49	-3.76	23.73	46.00	-22.27
551.86	Peak	32.21	-2.22	29.99	46.00	-16.01

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 98 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11ac80 / Band4

:5775 MHz :Tx CH High :E2 Plan

**Test Date** :2019-05-21 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
105.66	Peak	36.21	-11.02	25.19	43.50	-18.31
192.96	Peak	28.47	-10.44	18.03	43.50	-25.47
294.81	Peak	27.98	-8.32	19.66	46.00	-26.34
411.21	Peak	25.27	-5.00	20.27	46.00	-25.73
537.31	Peak	25.59	-2.16	23.43	46.00	-22.57
551.86	Peak	28.29	-2.22	26.07	46.00	-19.93

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 99 of 234

#### Above 1GHz Worst-Case Data:

## Radiated Spurious Emission Measurement Result 802.11a 5150~5250 MHz

**Project Number** :T190506W05 Test Date :2019-05-16 **Operation Band** :802.11a / Band1 Temp./Humi. :21/52 **Fundamental Frequency** :5180 MHz Engineer :Kane :Tx CH Low **Operation Mode** Measurement Antenna Pol. :VERTICAL

EUT Pol. :E2 Plan



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	_
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
10360.00	Peak	35.94	14.73	50.67	68.20	-17.53

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 100 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band1 :5180 MHz :Tx CH Low :E2 Plan

**Test Date** :2019-05-16 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



	Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin	
		Mode	Reading Level		FS	@3m		
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB	
_	10360.00	Peak	35.47	14.73	50.20	68.20	-18.00	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 101 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band1 :5220 MHz :Tx CH Mid :E2 Plan

**Test Date** :2019-05-16 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	-
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
 10440.00	Peak	33.60	15.66	49.26	68.20	-18.94

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 102 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band1 :5220 MHz :Tx CH Mid :E2 Plan

**Test Date** :2019-05-16 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



	Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin	
		Mode	Reading Level		FS	@3m		
_	MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB	_
	10440.00	Peak	33.46	15.66	49.12	68.20	-19.08	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 103 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band1 :5240 MHz :Tx CH High :E2 Plan

**Test Date** :2019-05-16 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	_
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
10480.00	Peak	32.78	16.48	49.26	68.20	-18.94

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 104 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band1 :5240 MHz :Tx CH High :E2 Plan

**Test Date** :2019-05-16 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



	Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin	
		Mode	Reading Level		FS	@3m		
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB	
	10480.00	Peak	32.96	16.48	49.44	68.20	-18.76	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 105 of 234

## Radiated Spurious Emission Measurement Result 802.11a 5250MHz-5350MHz

**Project Number** :T190506W05 Test Date :2019-05-16 **Operation Band** :802.11a / Band2 Temp./Humi. :21/52

**Fundamental Frequency** Engineer :Kane :5260 MHz **Operation Mode** :Tx CH Low Measurement Antenna Pol. :VERTICAL

EUT Pol. :E2 Plan



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
10520.00	Peak	33.74	15.99	49.73	68.20	-18.47

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 106 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band2 :5260 MHz

:Tx CH Low :E2 Plan

**Test Date** :2019-05-16 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	-
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
 10520.00	Peak	34.43	15.99	50.42	68.20	-17.78

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 107 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band2 :5300 MHz

:Tx CH Mid :E2 Plan

**Test Date** :2019-05-16 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin	
	Mode	Reading Level		FS	@3m		
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB	
10600.00	Average	23.74	15.27	39.01	54.00	-14.99	
10600.00	Peak	33.38	15.27	48.65	74.00	-25.35	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 108 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band2 :5300 MHz

:Tx CH Mid :E2 Plan

**Test Date** :2019-05-16 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμ̈V	dB	dBµV/m	dBµV/m	dB
10600.00	Average	23.85	15.27	39.12	54.00	-14.88
10600.00	Peak	32.42	15.27	47.69	74.00	-26.31

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 109 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band2 :5320 MHz :Tx CH High :E2 Plan

**Test Date** :2019-05-16 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
10640.00	Average	23.76	16.05	39.81	54.00	-14.19
10640.00	Peak	32.11	16.05	48.16	74.00	-25.84

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 110 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band2 :5320 MHz :Tx CH High

:E2 Plan

**Test Date** :2019-05-16 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dΒμV/m	dB
10640.00	Average	24.02	16.05	40.07	54.00	-13.93
10640.00	Peak	31.87	16.05	47.92	74.00	-26.08

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



EUT Pol.


Report No.: T190506W05-RP4

Page: 111 of 234

## Radiated Spurious Emission Measurement Result 802.11a 5470~5725 MHz

:E2 Plan

**Project Number** :T190506W05 Test Date :2019-05-18 **Operation Band** :802.11a / Band3 Temp./Humi. :21/52 **Fundamental Frequency** :5500 MHz Engineer :Kane **Operation Mode** :Tx CH Low Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
 MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
 11000.00	Average	25.12	17.44	42.56	54.00	-11.44
11000.00	Peak	32.86	17.44	50.30	74.00	-23.70

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 112 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band3 :5500 MHz :Tx CH Low

:E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
11000.00	Average	25.17	17.44	42.61	54.00	-11.39
11000.00	Peak	32.40	17.44	49.84	74.00	-24.16

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 113 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band3 :5580 MHz :Tx CH Mid

:E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin	
	Mode	Reading Level		FS	@3m		
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB	
11160.00	Average	25.04	16.85	41.89	54.00	-12.11	
11160.00	Peak	33.25	16.85	50.10	74.00	-23.90	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 114 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band3 :5580 MHz :Tx CH Mid

:E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμ̈V	dB	dBµV/m	dBµV/m	dB
11160.00	Average	24.98	16.85	41.83	54.00	-12.17
11160.00	Peak	33.92	16.85	50.77	74.00	-23.23

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 115 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band3 :5700 MHz :Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
11400.00	Average	25.09	16.89	41.98	54.00	-12.02
11400.00	Peak	32.62	16.89	49.51	74.00	-24.49

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 116 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band3 :5700 MHz :Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Detector	Spectrum	Factor	Actual	Limit	Margin	
Mode	Reading Level		FS	@3m		
PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB	
) Average	25.25	16.89	42.14	54.00	-11.86	
) Peak	33.46	16.89	50.35	74.00	-23.65	
	Mode PK/QP/AV Average	Mode Reading Level PK/QP/AV dBμV Average 25.25	Mode         Reading Level           PK/QP/AV         dBμV         dB           0         Average         25.25         16.89	Mode Peading Level         FS PK/QP/AV         dBμV         dB dBμV/m           0 Average         25.25         16.89         42.14	Mode PK/QP/AV         Reading Level PK/QP/AV         FS @3m dBμV/m           0 Average         25.25         16.89         42.14         54.00	Mode         Reading Level         FS         @3m           PK/QP/AV         dBμV         dB         dBμV/m         dBμV/m         dB           0         Average         25.25         16.89         42.14         54.00         -11.86

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 117 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band3/4 :5720 MHz

:Tx CH 144 :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
11440.00	Average	25.02	17.09	42.11	54.00	-11.89
11440.00	Peak	32.20	17.09	49.29	74.00	-24.71

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 118 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band3/4

:5720 MHz :Tx CH 144 :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
11440.00	Average	25.07	17.09	42.16	54.00	-11.84
11440.00	Peak	32.72	17.09	49.81	74.00	-24.19

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



EUT Pol.


Report No.: T190506W05-RP4

Page: 119 of 234

# Radiated Spurious Emission Measurement Result 802.11a 5725~5850 MHz

:E2 Plan

**Project Number** :T190506W05 Test Date :2019-05-18 **Operation Band** :802.11a / Band4 Temp./Humi. :21/52 **Fundamental Frequency** :5745 MHz Engineer :Kane **Operation Mode** :Tx CH Low Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
11490.00	Average	25.11	15.95	41.06	54.00	-12.94
11490.00	Peak	33.65	15.95	49.60	74.00	-24.40

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 120 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band4 :5745 MHz :Tx CH Low :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
11490.00	Average	25.06	15.95	41.01	54.00	-12.99
11490.00	Peak	32.01	15.95	47.96	74.00	-26.04

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 121 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band4 :5785 MHz :Tx CH Mid

:E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
11570.00	Average	25.11	16.41	41.52	54.00	-12.48
11570.00	Peak	33.27	16.41	49.68	74.00	-24.32

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 122 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band4 :5785 MHz

:Tx CH Mid :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμ̈V	dB	dBµV/m	dBµV/m	dB
11570.00	Average	24.99	16.41	41.40	54.00	-12.60
11570.00	Peak	33.95	16.41	50.36	74.00	-23.64

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 123 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band4 :5825 MHz :Tx CH High

:E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
11650.00	Average	25.08	16.21	41.29	54.00	-12.71
11650.00	Peak	33.41	16.21	49.62	74.00	-24.38

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 124 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11a / Band4 :5825 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
11650.00	Average	25.21	16.21	41.42	54.00	-12.58
11650.00	Peak	34.17	16.21	50.38	74.00	-23.62

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



EUT Pol.


Report No.: T190506W05-RP4

Page: 125 of 234

## Radiated Spurious Emission Measurement Result 802.11n HT20 5150~5250 MHz

:E2 Plan

**Project Number** :T190506W05 Test Date :2019-05-18 **Operation Band** :802.11n20 / Band1 Temp./Humi. :21/52 **Fundamental Frequency** Engineer :Kane :5180 MHz **Operation Mode** :Tx CH Low Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
10360.00	Peak	34.79	14.73	49.52	68.20	-18.68

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 126 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band1 :5180 MHz :Tx CH Low

:E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
10360 00	Peak	35 18	14 73	49 91	68 20	-18 29

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 127 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band1 :5220 MHz

:Tx CH Mid :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	-
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
10440.00	Peak	34.41	15.66	50.07	68.20	-18.13

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 128 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band1 :5220 MHz

:Tx CH Mid :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



	Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin	
		Mode	Reading Level		FS	@3m		
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB	_
	10440.00	Peak	33.87	15.66	49.53	68.20	-18.67	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 129 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band1 :5240 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	-
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
10480.00	Peak	33.62	16.48	50.10	68.20	-18.10

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 130 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band1 :5240 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



	Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	-
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
	10480.00	Peak	34.86	16.48	51.34	68.20	-16.86

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 131 of 234

## Radiated Spurious Emission Measurement Result 802.11n HT20 5250~5350 MHz

:E2 Plan

**Project Number** :T190506W05 Test Date :2019-05-18 **Operation Band** :802.11n20 / Band2 Temp./Humi. :21/52 **Fundamental Frequency** :5260 MHz Engineer :Kane **Operation Mode** :Tx CH Low Measurement Antenna Pol. :VERTICAL EUT Pol.



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
10520.00	Peak	33.75	15.99	49.74	68.20	-18.46

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 132 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band2 :5260 MHz

:Tx CH Low :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	-
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
10520.00	Peak	33.58	15.99	49.57	68.20	-18.63

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 133 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band2 :5300 MHz

:Tx CH Mid :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
10600.00	Average	24.85	15.27	40.12	54.00	-13.88
10600.00	Peak	33.92	15.27	49.19	74.00	-24.81

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 134 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band2 :5300 MHz

:Tx CH Mid :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμ̈V	dB	dBµV/m	dBµV/m	dB
10600.00	Average	24.37	15.27	39.64	54.00	-14.36
10600.00	Peak	33.98	15.27	49.25	74.00	-24.75

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 135 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band2 :5320 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin	
	Mode	Reading Level		FS	@3m		
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB	
10640.00	Average	24.87	16.05	40.92	54.00	-13.08	
10640.00	Peak	33.38	16.05	49.43	74.00	-24.57	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 136 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band2 :5320 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
 MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
10640.00	Average	23.78	16.05	39.83	54.00	-14.17
10640.00	Peak	33.57	16.05	49.62	74.00	-24.38

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



EUT Pol.


Report No.: T190506W05-RP4

Page: 137 of 234

## Radiated Spurious Emission Measurement Result 802.11n HT20 5470~5725 MHz

:E2 Plan

**Project Number** :T190506W05 Test Date :2019-05-18 **Operation Band** :802.11n20 / Band3 Temp./Humi. :21/52 **Fundamental Frequency** :5500 MHz Engineer :Kane **Operation Mode** :Tx CH Low Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
 MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
 11000.00	Average	23.81	17.44	41.25	54.00	-12.75
11000.00	Peak	33.83	17.44	51.27	74.00	-22.73

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 138 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band3 :5500 MHz

:Tx CH Low :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
11000.00	Average	23.79	17.44	41.23	54.00	-12.77
11000.00	Peak	33.90	17.44	51.34	74.00	-22.66

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 139 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band3 :5580 MHz

:Tx CH Mid :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμ̈V	dB	dBµV/m	dBµV/m	dB
11160.00	Average	24.32	16.85	41.17	54.00	-12.83
11160.00	Peak	34.18	16.85	51.03	74.00	-22.97

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 140 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band3 :5580 MHz

:Tx CH Mid :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
11160.00	Average	24.13	16.85	40.98	54.00	-13.02
11160.00	Peak	34.51	16.85	51.36	74.00	-22.64

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 141 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band3 :5700 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
11140.00	Average	24.16	17.00	41.16	54.00	-12.84
11140.00	Peak	33.44	17.00	50.44	74.00	-23.56

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 142 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band3

:5700 MHz :Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
11140.00	Average	24.17	17.00	41.17	54.00	-12.83
11140.00	Peak	33.40	17.00	50.40	74.00	-23.60

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 143 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20/ Band3/4

:5720 MHz :Tx CH 144 :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



eq.	Detector	Spectrum	Factor	Actual	Limit	Margin	
	Mode	Reading Level		FS	@3m		
Hz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB	
40.00	Average	23.93	17.09	41.02	54.00	-12.98	
40.00	Peak	33.74	17.09	50.83	74.00	-23.17	
	Hz 40.00	Mode Hz PK/QP/AV 40.00 Average	Mode Reading Level Hz PK/QP/AV dBµV 40.00 Average 23.93	Mode         Reading Level           Hz         PK/QP/AV         dBμV         dB           40.00         Average         23.93         17.09	Mode         Reading Level         FS           Hz         PK/QP/AV         dBμV         dB         dBμV/m           40.00         Average         23.93         17.09         41.02	Mode         Reading Level         FS         @3m           Hz         PK/QP/AV         dBμV         dB         dBμV/m         dBμV/m           40.00         Average         23.93         17.09         41.02         54.00	Mode         Reading Level         FS         @3m           Hz         PK/QP/AV         dBμV         dB         dBμV/m         dBμV/m         dB           40.00         Average         23.93         17.09         41.02         54.00         -12.98

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 144 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20/ Band3/4

:5720 MHz :Tx CH 144 :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



η. Detector	Spectrum	Factor	Actual	Limit	Margin	
Mode	Reading Level		FS	@3m		
z PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB	
.00 Average	24.05	17.09	41.14	54.00	-12.86	
.00 Peak	33.42	17.09	50.51	74.00	-23.49	
)	Mode z PK/QP/AV 0.00 Average	Mode Reading Level z PK/QP/AV dBµV 0.00 Average 24.05	Mode         Reading Level           z         PK/QP/AV         dBμV         dB           0.00         Average         24.05         17.09	Mode         Reading Level         FS           z         PK/QP/AV         dBμV         dB         dBμV/m           0.00         Average         24.05         17.09         41.14	Mode         Reading Level         FS         @3m           z         PK/QP/AV         dBμV         dB         dBμV/m         dBμV/m           0.00         Average         24.05         17.09         41.14         54.00	Mode         Reading Level         FS         @3m           z         PK/QP/AV         dBμV         dB         dBμV/m         dBμV/m         dB           0.00         Average         24.05         17.09         41.14         54.00         -12.86

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



EUT Pol.


Report No.: T190506W05-RP4

Page: 145 of 234

## Radiated Spurious Emission Measurement Result 802.11n HT20 5725~5850 MHz

:E2 Plan

**Project Number** :T190506W05 Test Date :2019-05-18 **Operation Band** :802.11n20 / Band4 Temp./Humi. :21/52 **Fundamental Frequency** :5745 MHz Engineer :Kane **Operation Mode** :Tx CH Low Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
 MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
 11490.00	Average	23.89	15.95	39.84	54.00	-14.16
11490.00	Peak	33.58	15.95	49.53	74.00	-24.47

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 146 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band4

:5745 MHz :Tx CH Low :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
 MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
11490.00	Average	24.26	15.95	40.21	54.00	-13.79
11490.00	Peak	33.61	15.95	49.56	74.00	-24.44

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 147 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band4

:5785 MHz :Tx CH Mid :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin	
	Mode	Reading Level		FS	@3m		
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB	_
11570.00	Average	23.86	16.41	40.27	54.00	-13.73	
11570.00	Peak	33.62	16.41	50.03	74.00	-23.97	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 148 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band4

:5785 MHz :Tx CH Mid :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμ̈V	dB	dBµV/m	dBµV/m	dB
11570.00	Average	24.41	16.41	40.82	54.00	-13.18
11570.00	Peak	33.83	16.41	50.24	74.00	-23.76

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 149 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band4 :5825 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
11650.00	Average	24.08	16.21	40.29	54.00	-13.71
11650.00	Peak	33.79	16.21	50.00	74.00	-24.00

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 150 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n20 / Band4 :5825 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
11650.00	Average	24.07	16.21	40.28	54.00	-13.72
11650.00	Peak	35.14	16.21	51.35	74.00	-22.65

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



EUT Pol.


Report No.: T190506W05-RP4

Page: 151 of 234

## Radiated Spurious Emission Measurement Result 802.11n HT40 5150~5250 MHz

:E2 Plan

**Project Number** :T190506W05 Test Date :2019-05-18 **Operation Band** :802.11n40 / Band1 Temp./Humi. :21/52 **Fundamental Frequency** Engineer :Kane :5190 MHz **Operation Mode** :Tx CH Low Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
10380.00	Peak	33.94	14.82	48.76	68.20	-19.44

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 152 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n40 / Band1 :5190 MHz

:Tx CH Low :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	-
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
10380.00	Peak	33.89	14.82	48.71	68.20	-19.49

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 153 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n40 / Band1 :5230 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
10460.00	Peak	33.52	16.01	49.53	68.20	-18.67

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 154 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n40 / Band1 :5230 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	_
 MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
 10460.00	Peak	34.26	16.01	50.27	68.20	-17.93

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



EUT Pol.


Report No.: T190506W05-RP4

Page: 155 of 234

## Radiated Spurious Emission Measurement Result 802.11n HT40 5250~5350 MHz

:E2 Plan

**Project Number** :T190506W05 Test Date :2019-05-18 **Operation Band** :802.11n40 / Band2 Temp./Humi. :21/52 **Fundamental Frequency** Engineer :5270 MHz :Kane **Operation Mode** :Tx CH Low Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
10540.00	Peak	34.17	15.67	49.84	68.20	-18.36

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 156 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n40 / Band2 :5270 MHz

:Tx CH Low :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
10540.00	Peak	34.31	15.67	49.98	68.20	-18.22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




Page: 157 of 234

**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n40 / Band2 :5310 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
10620.00	Average	23.71	15.66	39.37	54.00	-14.63
10620.00	Peak	33.49	15.66	49.15	74.00	-24.85

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 158 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n40 / Band2 :5310 MHz

:Tx CH High :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
10620.00	Average	23.98	15.66	39.64	54.00	-14.36
10620.00	Peak	33.76	15.66	49.42	74.00	-24.58

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



EUT Pol.


Report No.: T190506W05-RP4

Page: 159 of 234

## Radiated Spurious Emission Measurement Result 802.11n HT40 5470~5725 MHz

:E2 Plan

**Project Number** :T190506W05 Test Date :2019-05-18 **Operation Band** :802.11n40 / Band3 Temp./Humi. :21/52 **Fundamental Frequency** Engineer :5510 MHz :Kane **Operation Mode** :Tx CH Low Measurement Antenna Pol. :VERTICAL



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
11020.00	Average	24.14	17.69	41.83	54.00	-12.17
11020.00	Peak	33.81	17.69	51.50	74.00	-22.50

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Page: 160 of 234


**Project Number Operation Band Fundamental Frequency Operation Mode** EUT Pol.

:T190506W05 :802.11n40 / Band3 :5510 MHz

:Tx CH Low :E2 Plan

**Test Date** :2019-05-18 Temp./Humi. :21/52 Engineer :Kane

Measurement Antenna Pol. :HORIZONTAL



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin	
	Mode	Reading Level		FS	@3m		
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB	
11020.00	Average	24.17	17.69	41.86	54.00	-12.14	
11020.00	Peak	33.72	17.69	51.41	74.00	-22.59	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.