


Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (CDD), (serial no. A-7)

11ac-20, Chain 1



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (CDD), (serial no. B-5)

Chain 0+1		CDD		Applied limit: 15.407, mobile and portable client device									
Tested Frequency	PSD (Conducted)						PSD (c.i.r.p.)						
	Antenna			Result	Limit	Margin	Antenna			Result	Limit	Margin	
	Chain 0	Chain 1	Sum				Chain 0	Chain 1	Sum				
[MHz]	[mW/MHz]	[mW/MHz]	[mW/MHz]	[dBm/MHz]	[dBm/MHz]	[dB]	[mW/MHz]	[mW/MHz]	[mW/MHz]	[dBm/MHz]	[dBm/MHz]	[dB]	
5180	0.91	0.94	1.84	2.66	11.00	8.34	2.87	2.95	5.82	7.65	17.00	9.35	
5220	0.93	1.05	1.98	2.96	11.00	8.04	2.93	3.31	6.24	7.95	17.00	9.05	
5240	0.95	0.95	1.89	2.77	11.00	8.23	2.99	2.98	5.97	7.76	17.00	9.24	
5260	0.96	1.03	1.99	3.00	11.00	8.00	3.04	3.25	6.29	7.99	17.00	9.01	
5300	0.97	1.04	2.01	3.03	11.00	7.97	3.05	3.29	6.33	8.02	17.00	8.98	
5320	0.92	1.07	1.99	3.00	11.00	8.00	2.91	3.38	6.29	7.99	17.00	9.01	
5500	0.98	1.13	2.11	3.23	11.00	7.77	3.08	3.56	6.64	8.22	17.00	8.78	
5580	1.07	1.12	2.19	3.40	11.00	7.60	3.39	3.52	6.90	8.39	17.00	8.61	
5700	0.91	1.02	1.93	2.85	11.00	8.15	2.87	3.22	6.08	7.84	17.00	9.16	
5720	0.94	1.00	1.94	2.87	11.00	8.13	2.95	3.16	6.11	7.86	17.00	9.14	
5745	0.52	0.55	1.07	0.28	30.00	29.72	1.64	1.73	3.37	5.27	36.00	30.73	
5785	0.39	0.57	0.96	-0.16	30.00	30.16	1.25	1.80	3.04	4.83	36.00	31.17	
5825	0.52	0.54	1.06	0.25	30.00	29.75	1.63	1.72	3.34	5.24	36.00	30.76	

			Chain 0						Chain 1					
Tested Frequency	Duty Factor	RBW Correction Factor	PSD Reading	Cable Loss	Atten. Loss	Directional Gain	PSD Result		PSD Reading	Cable Loss	Atten. Loss	Directional Gain	PSD Result	
							Cond.	e.i.r.p.					Cond.	e.i.r.p.
[MHz]	[dB]	[dB]	[dBm/MHz]	[dB]	[dB]	[dBi]	[dBm/MHz]	[dBm/MHz]	[dBm/MHz]	[dB]	[dB]	[dBi]	[dBm/MHz]	[dBm/MHz]
5180	0.00	0.00	-14.23	3.91	9.90	4.99	-0.42	4.57	-15.16	4.66	10.21	4.99	-0.29	4.70
5220	0.00	0.00	-14.15	3.92	9.91	4.99	-0.32	4.67	-14.67	4.67	10.21	4.99	0.21	5.20
5240	0.00	0.00	-14.07	3.93	9.91	4.99	-0.23	4.76	-15.14	4.69	10.21	4.99	-0.24	4.75
5260	0.00	0.00	-14.01	3.94	9.91	4.99	-0.16	4.83	-14.78	4.70	10.21	4.99	0.13	5.12
5300	0.00	0.00	-14.01	3.95	9.91	4.99	-0.15	4.84	-14.74	4.71	10.21	4.99	0.18	5.17
5320	0.00	0.00	-14.21	3.95	9.91	4.99	-0.35	4.64	-14.63	4.72	10.21	4.99	0.30	5.29
5500	0.00	0.00	-14.03	4.00	9.92	4.99	-0.11	4.88	-14.49	4.80	10.22	4.99	0.53	5.52
5580	0.00	0.00	-13.61	4.01	9.91	4.99	0.31	5.30	-14.56	4.81	10.22	4.99	0.47	5.46
5700	0.00	0.00	-14.21	3.89	9.90	4.99	-0.42	4.57	-14.87	4.72	10.23	4.99	0.08	5.07
5720	0.00	0.00	-14.08	3.89	9.90	4.99	-0.29	4.70	-14.95	4.73	10.23	4.99	0.01	5.00
5745	0.00	6.99	-23.64	3.90	9.90	4.99	-2.85	2.14	-24.56	4.73	10.23	4.99	-2.61	2.38
5785	0.00	6.99	-24.83	3.91	9.89	4.99	-4.04	0.95	-24.41	4.74	10.24	4.99	-2.44	2.55
5825	0.00	6.99	-23.68	3.92	9.89	4.99	-2.88	2.11	-24.62	4.75	10.24	4.99	-2.64	2.35

Sample Calculation:

PSD: Power Spectral Density

The PSD within 5725 MHz to 5825 MHz are based on any 500 kHz band.

RBW Correction Factor = $10 \cdot \log(\text{Specified bandwidth} / \text{Measured bandwidth})$

PSD Result (Conducted) = Reading + Cable Loss (including the cable(s) customer supplied) + Atten. Loss + Duty Factor + RBW Correction Factor

PSD Result (e.i.r.p.) = Conducted PSD Result + Directional Gain

Directional Gain = G ANT + Array Gain

G ANT = Set equal to the gain of the antenna having the highest gain

Array Gain = $10 \log(N \text{ ANT} / N \text{ SS})$ dB.

N ANT = number of transmit antennas = 2

N SS = number of spatial streams = 1

Although the EUT operates on Master mode, more stringent limit for Client device was applied. (W52 for FCC)

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (CDD), (serial no. B-5)


11ac-20, Chain 0





Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (CDD), (serial no. B-5)

11ac-20, Chain 0






Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (CDD), (serial no. B-5)


11ac-20, Chain 1



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (CDD), (serial no. B-5)


11ac-20, Chain 1



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (CDD), (serial no. B-5)

11ac-20, Chain 1



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. A-7)

Chain 0+1		MIMO					Applied limit: 15.407, mobile and portable client device						
Tested Frequency	PSD (Conducted)						PSD (c.i.r.p.)						
	Antenna			Result	Limit	Margin	Antenna			Result	Limit	Margin	
	Chain 0	Chain 1	Sum				Chain 0	Chain 1	Sum				
	[mW/MHz]	[mW/MHz]	[mW/MHz]				[dBm/MHz]	[dBm/MHz]	[dB]				[mW/MHz]
[MHz]													
5180	0.91	1.06	1.97	2.94	11.00	8.06	1.16	1.35	2.50	3.98	17.00	13.02	
5220	0.89	0.94	1.84	2.64	11.00	8.36	1.14	1.20	2.33	3.68	17.00	13.32	
5240	0.88	0.96	1.84	2.64	11.00	8.36	1.12	1.22	2.34	3.68	17.00	13.32	
5260	0.84	0.87	1.72	2.35	11.00	8.65	1.07	1.11	2.18	3.39	17.00	13.61	
5300	0.93	0.90	1.83	2.63	11.00	8.37	1.18	1.15	2.33	3.67	17.00	13.33	
5320	0.91	0.93	1.84	2.65	11.00	8.35	1.16	1.18	2.34	3.69	17.00	13.31	
5500	1.02	1.01	2.03	3.07	11.00	7.93	1.30	1.28	2.57	4.11	17.00	12.89	
5580	0.94	0.90	1.84	2.66	11.00	8.34	1.20	1.14	2.34	3.70	17.00	13.30	
5700	1.00	1.11	2.11	3.23	11.00	7.77	1.27	1.41	2.68	4.27	17.00	12.73	
5720	0.93	1.15	2.08	3.17	11.00	7.83	1.18	1.46	2.64	4.21	17.00	12.79	
5745	0.46	0.61	1.07	0.29	30.00	29.71	0.59	0.77	1.36	1.33	36.00	34.67	
5785	0.49	0.56	1.05	0.21	30.00	29.79	0.62	0.71	1.33	1.25	36.00	34.75	
5825	0.46	0.53	0.99	-0.05	30.00	30.05	0.58	0.68	1.26	0.99	36.00	35.01	

Tested Frequency [MHz]	Duty Factor [dB]	RBW Correction Factor [dB]	Chain 0					Chain 1				
			PSD Reading	Cable Loss	Atten. Loss	Antenna Gain	PSD Result	PSD Reading	Cable Loss	Atten. Loss	Antenna Gain	PSD Result
			[dBm/MHz]	[dB]	[dB]	[dBi]	Cond. e.i.r.p.	[dBm/MHz]	[dB]	[dB]	[dBi]	Cond. e.i.r.p.
							[dBm/MHz]					[dBm/MHz]
5180	0.00	0.00	-14.22	3.91	9.90	1.04	-0.41 0.63	-13.97	4.01	10.21	1.04	0.25 1.29
5220	0.00	0.00	-14.32	3.92	9.91	1.04	-0.49 0.55	-14.48	4.02	10.21	1.04	-0.25 0.79
5240	0.00	0.00	-14.40	3.93	9.91	1.04	-0.56 0.48	-14.43	4.04	10.21	1.04	-0.18 0.86
5260	0.00	0.00	-14.58	3.94	9.91	1.04	-0.73 0.31	-14.85	4.05	10.21	1.04	-0.59 0.45
5300	0.00	0.00	-14.18	3.95	9.91	1.04	-0.32 0.72	-14.72	4.06	10.21	1.04	-0.45 0.59
5320	0.00	0.00	-14.27	3.95	9.91	1.04	-0.41 0.63	-14.59	4.07	10.21	1.04	-0.31 0.73
5500	0.00	0.00	-13.83	4.00	9.92	1.04	0.09 1.13	-14.35	4.15	10.22	1.04	0.02 1.06
5580	0.00	0.00	-14.18	4.01	9.91	1.04	-0.26 0.78	-14.83	4.16	10.22	1.04	-0.45 0.59
5700	0.00	0.00	-13.79	3.89	9.90	1.04	0.00 1.04	-13.86	4.07	10.23	1.04	0.44 1.48
5720	0.00	0.00	-14.10	3.89	9.90	1.04	-0.31 0.73	-13.72	4.08	10.23	1.04	0.59 1.63
5745	0.00	6.99	-24.15	3.90	9.90	1.04	-3.36 -2.32	-23.47	4.08	10.23	1.04	-2.17 -1.13
5785	0.00	6.99	-23.88	3.91	9.89	1.04	-3.09 -2.05	-23.84	4.09	10.24	1.04	-2.52 -1.48
5825	0.00	6.99	-24.21	3.92	9.89	1.04	-3.41 -2.37	-24.06	4.10	10.24	1.04	-2.73 -1.69

Sample Calculation:

PSD: Power Spectral Density

The PSD within 5725 MHz to 5825 MHz are based on any 500 kHz band.

RBW Correction Factor = $10 \cdot \log(\text{Specified bandwidth} / \text{Measured bandwidth})$

PSD Result (Conducted) = Reading + Cable Loss (including the cable(s) customer supplied) + Atten. Loss + Duty Factor + RBW Correction Factor


PSD Result (e.i.r.p.) = Conducted PSD Result + Antenna Gain

Although the EUT operates on Master mode, more stringent limit for Client device was applied. (W52 for FCC)

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. A-7)


11ac-20, Chain 0



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. A-7)

11ac-20, Chain 0



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. A-7)

11ac-20, Chain 0



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. A-7)


11ac-20, Chain 1



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. A-7)

11ac-20, Chain 1



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. A-7)

11ac-20, Chain 1



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. B-5)

Chain 0+1		MIMO						Applied limit: 15.407, mobile and portable client device					
Tested Frequency	PSD (Conducted)						PSD (c.i.r.p.)						
	Antenna			Result	Limit	Margin	Antenna			Result	Limit	Margin	
	Chain 0	Chain 1	Sum				Chain 0	Chain 1	Sum				
[MHz]	[mW/MHz]	[mW/MHz]	[mW/MHz]	[dBm/MHz]	[dBm/MHz]	[dB]	[mW/MHz]	[mW/MHz]	[mW/MHz]	[dBm/MHz]	[dBm/MHz]	[dB]	
5180	0.90	0.97	1.88	2.73	11.00	8.27	1.15	1.53	2.68	4.28	17.00	12.72	
5220	0.94	1.04	1.98	2.96	11.00	8.04	1.19	1.64	2.83	4.52	17.00	12.48	
5240	0.96	1.06	2.01	3.04	11.00	7.96	1.22	1.67	2.88	4.60	17.00	12.40	
5260	0.95	1.02	1.97	2.95	11.00	8.05	1.21	1.61	2.82	4.50	17.00	12.50	
5300	0.89	0.96	1.86	2.68	11.00	8.32	1.14	1.52	2.65	4.24	17.00	12.76	
5320	0.92	1.07	1.99	2.99	11.00	8.01	1.17	1.68	2.85	4.56	17.00	12.44	
5500	0.91	1.14	2.05	3.11	11.00	7.89	1.15	1.80	2.95	4.70	17.00	12.30	
5580	1.04	1.17	2.21	3.44	11.00	7.56	1.32	1.84	3.16	5.00	17.00	12.00	
5700	0.89	1.01	1.90	2.79	11.00	8.21	1.13	1.60	2.72	4.35	17.00	12.65	
5720	0.95	1.01	1.96	2.92	11.00	8.08	1.21	1.59	2.80	4.47	17.00	12.53	
5745	0.53	0.57	1.10	0.43	30.00	29.57	0.68	0.90	1.58	1.98	36.00	34.02	
5785	0.53	0.56	1.09	0.37	30.00	29.63	0.68	0.88	1.55	1.91	36.00	34.09	
5825	0.53	0.56	1.09	0.37	30.00	29.63	0.68	0.88	1.55	1.92	36.00	34.08	

Tested Frequency [MHz]	Chain 0							Chain 1						
	Duty Factor	RBW Correction Factor	PSD		Cable Loss	Atten. Loss	Antenna Gain	PSD Result		Cable Loss	Atten. Loss	Antenna Gain	PSD Result	
			Reading	Cond.				Cond.	e.i.r.p.				Cond.	e.i.r.p.
	[dB]	[dB]	[dBm/MHz]	[dBm/MHz]	[dB]	[dB]	[dBi]	[dBm/MHz]	[dBm/MHz]	[dBm/MHz]	[dB]	[dB]	[dBm/MHz]	[dBm/MHz]
5180	0.00	0.00	-14.25	-0.44	3.91	9.90	1.04	0.60	0.60	-14.99	4.66	10.21	1.98	-0.12
5220	0.00	0.00	-14.10	-0.27	3.92	9.91	1.04	0.77	0.77	-14.72	4.67	10.21	1.98	0.16
5240	0.00	0.00	-14.03	-0.19	3.93	9.91	1.04	0.85	0.85	-14.66	4.69	10.21	1.98	0.24
5260	0.00	0.00	-14.08	-0.23	3.94	9.91	1.04	0.81	0.81	-14.82	4.70	10.21	1.98	0.09
5300	0.00	0.00	-14.35	-0.49	3.95	9.91	1.04	0.55	0.55	-15.09	4.71	10.21	1.98	-0.17
5320	0.00	0.00	-14.21	-0.35	3.95	9.91	1.04	0.69	0.69	-14.65	4.72	10.21	1.98	0.28
5500	0.00	0.00	-14.35	-0.43	4.00	9.92	1.04	0.61	0.61	-14.44	4.80	10.22	1.98	0.58
5580	0.00	0.00	-13.74	0.18	4.01	9.91	1.04	1.22	1.22	-14.36	4.81	10.22	1.98	0.67
5700	0.00	0.00	-14.31	-0.52	3.89	9.90	1.04	0.52	0.52	-14.90	4.72	10.23	1.98	0.06
5720	0.00	0.00	-14.01	-0.22	3.89	9.90	1.04	0.82	0.82	-14.92	4.73	10.23	1.98	0.04
5745	0.00	6.99	-23.51	-2.72	3.90	9.90	1.04	-1.68	-1.68	-24.39	4.73	10.23	1.98	-2.44
5785	0.00	6.99	-23.54	-2.75	3.91	9.89	1.04	-1.71	-1.71	-24.51	4.74	10.24	1.98	-2.54
5825	0.00	6.99	-23.53	-2.73	3.92	9.89	1.04	-1.69	-1.69	-24.53	4.75	10.24	1.98	-2.55

Sample Calculation:

PSD: Power Spectral Density

The PSD within 5725 MHz to 5825 MHz are based on any 500 kHz band.

RBW Correction Factor = $10 \cdot \log(\text{Specified bandwidth} / \text{Measured bandwidth})$

PSD Result (Conducted) = Reading + Cable Loss (including the cable(s) customer supplied) + Atten. Loss + Duty Factor + RBW Correction Factor


PSD Result (e.i.r.p.) = Conducted PSD Result + Antenna Gain

Although the EUT operates on Master mode, more stringent limit for Client device was applied. (W52 for FCC)

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. B-5)


11ac-20, Chain 0



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. B-5)


11ac-20, Chain 0



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. B-5)


11ac-20, Chain 0



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. B-5)


11ac-20, Chain 1



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11ac-20 (MIMO), (serial no. B-5)

11ac-20, Chain 1



UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (CDD), (serial no. A-7)

Chain 0+1		CDD		Applied limit: 15.407, mobile and portable client device									
Tested Frequency	PSD (Conducted)						PSD (c.i.r.p.)						
	Antenna	Result		Limit	Margin	Antenna	Result		Limit	Margin			
Chain 0	Chain 1	Sum				Chain 0	Chain 1	Sum					
[mW/MHz]	[mW/MHz]	[mW/MHz]	[dBm/MHz]	[dBm/MHz]	[dB]	[mW/MHz]	[mW/MHz]	[mW/MHz]	[dBm/MHz]	[dBm/MHz]	[dB]		
5190	0.54	0.51	1.05	0.21	11.00	10.79	1.37	1.29	2.67	4.26	17.00		
5230	0.52	0.49	1.01	0.03	11.00	10.97	1.32	1.24	2.56	4.08	17.00		
5270	0.49	0.45	0.94	-0.29	11.00	11.29	1.24	1.14	2.38	3.76	17.00		
5310	0.51	0.49	1.01	0.03	11.00	10.97	1.30	1.26	2.56	4.08	17.00		
5510	0.58	0.58	1.16	0.65	11.00	10.35	1.47	1.48	2.95	4.70	17.00		
5550	0.54	0.53	1.07	0.29	11.00	10.71	1.38	1.34	2.72	4.34	17.00		
5670	0.46	0.54	1.00	0.00	11.00	11.00	1.17	1.37	2.54	4.05	17.00		
5710	0.48	0.47	0.96	-0.20	11.00	11.20	1.22	1.20	2.43	3.85	17.00		
5755	0.23	0.27	0.50	-3.03	30.00	33.03	0.58	0.69	1.27	1.02	36.00		
5795	0.27	0.29	0.55	-2.58	30.00	32.58	0.68	0.73	1.40	1.47	36.00		

Tested Frequency [MHz]	Duty Factor [dB]	Chain 0					Chain 1				
		PSD Reading [dBm/MHz]	Cable Loss [dB]	Atten. Loss [dB]	Directional Gain [dBi]	PSD Result Cond. [dBm/MHz]	PSD Result e.i.r.p. [dBm/MHz]	PSD Reading [dBm/MHz]	Cable Loss [dB]	Atten. Loss [dB]	Directional Gain [dBi]
5190	0.00	0.00	-16.49	3.92	9.90	4.05	-2.67	1.38	-17.16	4.02	10.21
5230	0.00	0.00	-16.70	3.93	9.91	4.05	-2.86	1.19	-17.35	4.03	10.21
5270	0.00	0.00	-16.96	3.94	9.91	4.05	-3.11	0.94	-17.76	4.05	10.21
5310	0.00	0.00	-16.76	3.95	9.91	4.05	-2.90	1.15	-17.33	4.06	10.21
5510	0.00	0.00	-16.30	4.00	9.92	4.05	-2.38	1.67	-16.71	4.15	10.22
5550	0.00	0.00	-16.57	4.00	9.91	4.05	-2.66	1.39	-17.15	4.15	10.22
5670	0.00	0.00	-17.21	3.95	9.90	4.05	-3.36	0.69	-17.04	4.12	10.23
5710	0.00	0.00	-16.96	3.89	9.90	4.05	-3.17	0.88	-17.56	4.08	10.23
5755	0.00	6.99	-27.23	3.90	9.90	4.05	-6.44	-2.39	-26.99	4.09	10.24
5795	0.00	6.99	-26.53	3.91	9.89	4.05	-5.74	-1.69	-26.76	4.09	10.24

Sample Calculation:

PSD: Power Spectral Density

The PSD within 5725 MHz to 5825 MHz are based on any 500 kHz band.

RBW Correction Factor = $10 \cdot \log(\text{Specified bandwidth} / \text{Measured bandwidth})$

PSD Result (Conducted) = Reading + Cable Loss (including the cable(s) customer supplied) + Atten. Loss + Duty Factor + RBW Correction Factor

PSD Result (e.i.r.p.) = Conducted PSD Result + Directional Gain

Directional Gain = G ANT + Array Gain

G ANT = Set equal to the gain of the antenna having the highest gain

Array Gain = $10 \log(N \text{ ANT} / N \text{ SS})$ dB.

N ANT = number of transmit antennas = 2

N SS = number of spatial streams = 1

Although the EUT operates on Master mode, more stringent limit for Client device was applied. (W52 for FCC)

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN


Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (CDD), (serial no. A-7)


11n-40, Chain 0



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (CDD), (serial no. A-7)


11n-40, Chain 0



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (CDD), (serial no. A-7)


11n-40, Chain 1



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (CDD), (serial no. A-7)

11n-40, Chain 1



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (CDD), (serial no. B-5)

Chain 0+1		CDD		Applied limit: 15.407, mobile and portable client device									
Tested Frequency	PSD (Conducted)						PSD (e.i.r.p.)						
	Antenna			Result	Limit	Margin	Antenna			Result	Limit	Margin	
	Chain 0	Chain 1	Sum				Chain 0	Chain 1	Sum				
	[mW/MHz]	[mW/MHz]	[mW/MHz]				[dBm/MHz]	[dBm/MHz]	[dB]				[mW/MHz]
[MHz]													
5190	0.52	0.52	1.04	0.18	11.00	10.82	1.63	1.66	3.29	5.17	17.00	11.83	
5230	0.48	0.47	0.95	-0.21	11.00	11.21	1.51	1.49	3.01	4.78	17.00	12.22	
5270	0.44	0.46	0.89	-0.48	11.00	11.48	1.38	1.45	2.82	4.51	17.00	12.49	
5310	0.47	0.50	0.97	-0.15	11.00	11.15	1.47	1.57	3.05	4.84	17.00	12.16	
5510	0.48	0.52	1.01	0.02	11.00	10.98	1.52	1.65	3.17	5.01	17.00	11.99	
5550	0.52	0.53	1.05	0.22	11.00	10.78	1.66	1.67	3.32	5.21	17.00	11.79	
5670	0.50	0.54	1.04	0.16	11.00	10.84	1.57	1.70	3.27	5.15	17.00	11.85	
5710	0.47	0.53	1.00	0.02	11.00	10.98	1.49	1.67	3.17	5.01	17.00	11.99	
5755	0.27	0.28	0.55	-2.58	30.00	32.58	0.85	0.89	1.74	2.41	36.00	33.59	
5795	0.27	0.27	0.55	-2.62	30.00	32.62	0.87	0.86	1.72	2.37	36.00	33.63	

Chain 0								Chain 1						
Tested Frequency	Duty Factor	RBW Correction Factor	PSD Reading	Cable Loss	Atten. Loss	Directional Gain	PSD Result		PSD Reading	Cable Loss	Atten. Loss	Directional Gain	PSD Result	
							Cond.	e.i.r.p.					Cond.	e.i.r.p.
[MHz]	[dB]	[dB]	[dBm/MHz]	[dB]	[dB]	[dBi]	[dBm/MHz]	[dBm/MHz]	[dBm/MHz]	[dB]	[dB]	[dBi]	[dBm/MHz]	[dBm/MHz]
5190	0.00	0.00	-16.68	3.92	9.90	4.99	-2.86	2.13	-17.68	4.67	10.21	4.99	-2.80	2.19
5230	0.00	0.00	-17.03	3.93	9.91	4.99	-3.19	1.80	-18.14	4.68	10.21	4.99	-3.25	1.75
5270	0.00	0.00	-17.45	3.94	9.91	4.99	-3.60	1.39	-18.30	4.70	10.21	4.99	-3.39	1.60
5310	0.00	0.00	-17.17	3.95	9.91	4.99	-3.31	1.68	-17.94	4.71	10.21	4.99	-3.02	1.97
5510	0.00	0.00	-17.08	4.00	9.92	4.99	-3.16	1.83	-17.84	4.80	10.22	4.99	-2.82	2.17
5550	0.00	0.00	-16.71	4.00	9.91	4.99	-2.80	2.19	-17.80	4.80	10.22	4.99	-2.78	2.21
5670	0.00	0.00	-16.87	3.95	9.90	4.99	-3.02	1.97	-17.69	4.77	10.23	4.99	-2.69	2.30
5710	0.00	0.00	-17.03	3.89	9.90	4.99	-3.24	1.75	-17.72	4.73	10.23	4.99	-2.76	2.23
5755	0.00	6.99	-26.49	3.90	9.90	4.99	-5.70	-0.71	-27.45	4.74	10.24	4.99	-5.48	-0.49
5795	0.00	6.99	-26.40	3.91	9.89	4.99	-5.61	-0.62	-27.63	4.74	10.24	4.99	-5.66	-0.66

Sample Calculation:

PSD: Power Spectral Density

The PSD within 5725 MHz to 5825 MHz are based on any 500 kHz band.

RBW Correction Factor = $10 \cdot \log(\text{Specified bandwidth} / \text{Measured bandwidth})$

PSD Result (Conducted) = Reading + Cable Loss (including the cable(s) customer supplied) + Atten. Loss + Duty Factor + RBW Correction Factor

PSD Result (e.i.r.p.) = Conducted PSD Result + Directional Gain

Directional Gain = G ANT + Array Gain

G ANT = Set equal to the gain of the antenna having the highest gain

Array Gain = $10 \log(N \text{ ANT} / N \text{ SS})$ dB.

N ANT = number of transmit antennas = 2


N SS = number of spatial streams = 1

Although the EUT operates on Master mode, more stringent limit for Client device was applied. (W52 for FCC)

Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (CDD), (serial no. B-5)


11n-40, Chain 0



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (CDD), (serial no. B-5)


11n-40, Chain 0



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (CDD), (serial no. B-5)


11n-40, Chain 1



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 27, 2019
Temperature / Humidity 26 deg. C / 42 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (CDD), (serial no. B-5)

11n-40, Chain 1



Maximum Power Spectral Density

Report No. 13004393S-E-R2
Test place Shonan EMC Lab. No.3 Shielded Room
Date September 28, 2019
Temperature / Humidity 24 deg. C / 50 % RH
Engineer Kazuya Noda
Mode Tx, 11n-40 (MIMO), (serial no. A-7)

Chain 0+1		MIMO						Applied limit: 15.407, mobile and portable client device					
Tested Frequency	PSD (Conducted)						PSD (e.i.r.p.)						
	Antenna			Result	Limit	Margin	Antenna			Result	Limit	Margin	
	Chain 0	Chain 1	Sum				Chain 0	Chain 1	Sum				
	[MHz]	[mW/MHz]	[mW/MHz]				[mW/MHz]	[dBm/MHz]	[dBm/MHz]				[dB]
5190	0.48	0.42	0.90	-0.45	11.00	11.45	0.61	0.54	1.15	0.59	17.00	16.41	
5230	0.50	0.50	1.00	0.00	11.00	11.00	0.63	0.64	1.27	1.04	17.00	15.96	
5270	0.50	0.47	0.96	-0.16	11.00	11.16	0.63	0.59	1.22	0.88	17.00	16.12	
5310	0.52	0.46	0.99	-0.06	11.00	11.06	0.66	0.59	1.25	0.98	17.00	16.02	
5510	0.54	0.54	1.08	0.34	11.00	10.66	0.68	0.69	1.37	1.38	17.00	15.62	
5550	0.52	0.51	1.04	0.16	11.00	10.84	0.67	0.65	1.32	1.20	17.00	15.80	
5670	0.46	0.52	0.98	-0.08	11.00	11.08	0.58	0.67	1.25	0.96	17.00	16.04	
5710	0.50	0.47	0.97	-0.14	11.00	11.14	0.63	0.60	1.23	0.90	17.00	16.10	
5755	0.22	0.27	0.49	-3.05	30.00	33.05	0.28	0.35	0.63	-2.01	36.00	38.01	
5795	0.25	0.28	0.54	-2.69	30.00	32.69	0.32	0.36	0.68	-1.65	36.00	37.65	

			Chain 0						Chain 1					
Tested Frequency	Duty Factor	RBW Correction Factor	PSD Reading	Cable Loss	Atten. Loss	Antenna Gain	PSD Cond.	Result e.i.r.p.	PSD Reading	Cable Loss	Atten. Loss	Antenna Gain	PSD Cond.	Result e.i.r.p.
[MHz]	[dB]	[dB]	[dBm/MHz]	[dB]	[dB]	[dBi]	[dBm/MHz]	[dBm/MHz]	[dBm/MHz]	[dB]	[dB]	[dBi]	[dBm/MHz]	[dBm/MHz]
5190	0.00	0.00	-17.01	3.92	9.90	1.04	-3.19	-2.15	-17.97	4.02	10.21	1.04	-3.74	-2.70
5230	0.00	0.00	-16.89	3.93	9.91	1.04	-3.05	-2.01	-17.21	4.03	10.21	1.04	-2.97	-1.93
5270	0.00	0.00	-16.88	3.94	9.91	1.04	-3.03	-1.99	-17.58	4.05	10.21	1.04	-3.32	-2.28
5310	0.00	0.00	-16.69	3.95	9.91	1.04	-2.83	-1.79	-17.60	4.06	10.21	1.04	-3.33	-2.29
5510	0.00	0.00	-16.63	4.00	9.92	1.04	-2.71	-1.67	-17.01	4.15	10.22	1.04	-2.64	-1.60
5550	0.00	0.00	-16.72	4.00	9.91	1.04	-2.81	-1.77	-17.27	4.15	10.22	1.04	-2.90	-1.86
5670	0.00	0.00	-17.25	3.95	9.90	1.04	-3.40	-2.36	-17.16	4.12	10.23	1.04	-2.81	-1.77
5710	0.00	0.00	-16.80	3.89	9.90	1.04	-3.01	-1.97	-17.60	4.08	10.23	1.04	-3.29	-2.25
5755	0.00	6.99	-27.30	3.90	9.90	1.04	-6.51	-5.47	-26.98	4.09	10.24	1.04	-5.66	-4.62
5795	0.00	6.99	-26.73	3.91	9.89	1.04	-5.94	-4.90	-26.79	4.09	10.24	1.04	-5.47	-4.43

Sample Calculation:

PSD: Power Spectral Density

The PSD within 5725 MHz to 5825 MHz are based on any 500 kHz band.

RBW Correction Factor = $10 \cdot \log(\text{Specified bandwidth} / \text{Measured bandwidth})$

PSD Result (Conducted) = Reading + Cable Loss (including the cable(s) customer supplied) + Atten. Loss + Duty Factor + RBW Correction Factor

PSD Result (e.i.r.p.) = Conducted PSD Result + Antenna Gain

Although the EUT operates on Master mode, more stringent limit for Client device was applied. (W52 for FCC)