


FCC RADIO TEST REPORT

Applicant's company	Ralink Technology Corporation
Applicant Address	5F., No.36, Taiyuan St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.
FCC ID	VQF-RT2700E-LNA
Manufacturer's company	Ralink Technology Corporation
Manufacturer Address	5F., No.36, Taiyuan St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.

Product Name	11b/g/n 1T2R WLAN Mini Card
Brand Name	Ralink
Model Name	RT2700E-LNA
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	May. 5, 2008
Final Test Date	May 16, 2008
Submission Type	Original Equipment



Statement

Test result included is only for the Draft n part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	7
3.6. Table for Testing Locations.....	8
3.7. Table for Supporting Units	8
3.8. Table for Parameters of Test Software Setting	9
3.9. Test Configurations	10
4. TEST RESULT	15
4.1. AC Power Line Conducted Emissions Measurement.....	15
4.2. Maximum Conducted Output Power Measurement.....	19
4.3. Power Spectral Density Measurement	28
4.4. 6dB Spectrum Bandwidth Measurement	37
4.5. Radiated Emissions Measurement	46
4.6. Band Edge Emissions Measurement	78
4.7. Antenna Requirements	87
5. LIST OF MEASURING EQUIPMENTS	88
6. TEST LOCATION.....	89
7. TAF CERTIFICATE OF ACCREDITATION	90
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A8
APPENDIX B. TEST PHOTOS.....	B1 ~ B8
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~C3
APPENDIX D. ANTENNA LIST.....	D1 ~ D4

History of This Test Report

Original Issue Date: Jun. 10, 2008

Report No.: FR852306AA


- ☒ No additional attachment.
- ☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

1. CERTIFICATE OF COMPLIANCE

Product Name : 11b/g/n 1T2R WLAN Mini Card
Brand Name : Ralink
Model Name : RT2700E-LNA
Applicant : Ralink Technology Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on May. 5, 2008 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.


Wayne Hsu

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	11.41 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	4.59 dB
4.3	15.247(e)	Power Spectral Density	Complies	14.42 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	2.74 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.32 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (1TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	see the below table for draft n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for Draft n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz) : 17.96 MHz MCS0 (40MHz) : 36.40 MHz
Conducted Output Power	MCS0 (20MHz) : 25.41 dBm MCS0 (40MHz) : 21.68 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)	
Band width Mode	20 MHz	40 MHz
802.11b	V	X
802.11g	V	X
Draft n	V	V

Draft n spec

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Data rate(Mbps)	
									800nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	$\frac{1}{2}$	1	52	108	26	54	6.5	13.5
1	1	QPSK	$\frac{1}{2}$	2	104	216	52	108	13.0	27.0
2	1	QPSK	$\frac{3}{4}$	2	104	216	78	162	19.5	40.5
3	1	16-QAM	$\frac{1}{2}$	4	208	432	104	216	26.0	54.0
4	1	16-QAM	$\frac{3}{4}$	4	208	432	156	324	39.0	81.0
5	1	64-QAM	$\frac{2}{3}$	6	312	648	208	432	52.0	108.0
6	1	64-QAM	$\frac{3}{4}$	6	312	648	234	486	58.5	121.5
7	1	64-QAM	$\frac{5}{6}$	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories

N/A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
A1	VSO	S79-1800710-V03	PCB Antenna	MHF PLUG	0.75
A2	VSO	S79-1800700-V03	PCB Antenna	MHF PLUG	0.75
B1	MICHIGAN	6036B0014401	PIFA Antenna	IPEX	2.95
B2	MICHIGAN	6036B0016901	PIFA Antenna	IPEX	2.95


Note:

(1) There are 39 antennas in this product; the two antenna ports are with receiver diversity function.
Only one of them is used as transmitting antenna.

Due to Ant. B is the highest gain value among PIFA antennas, only Ant. B (6036B0014401) was tested and recorded in this report.

Please refer to Appendix. D for all 39 antennas. (Including PCB and PIFA antennas)

(2) The EUT has two antenna ports, and the Port 1 have both TX/RX function , Port 2 have only RX function.



3.4. Table for Carrier Frequencies

There are two bandwidth systems for draft n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Peak Conducted Output Power	MCS0/20MHz	6.5 Mbps	1/6/11	A / B
	MCS0/40MHz	13.5 Mbps	3/6/9	A / B
Power Spectral Density 6dB Spectrum Bandwidth	MCS0/20MHz	6.5 Mbps	1/6/11	A / B
	MCS0/40MHz	13.5 Mbps	3/6/9	A / B
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 th Harmonic	MCS0/20MHz	6.5 Mbps	1/6/11	A / B
	MCS0/40MHz	13.5 Mbps	3/6/9	A / B
Band Edge Emissions	MCS0/20MHz	6.5 Mbps	1/11	A / B
	MCS0/40MHz	13.5 Mbps	3/9	A / B

Note:

Test Mode:

Mode 1(PCB Antenna) : EUT + Ant. A

Mode 2 (PIFA Antenna): EUT + Ant. B

For Conducted Emissions Test :

Due to Mode 1 (Ant. A) generated the worst test result, so it was recorded in this report.

For Radiated Emissions Test :

Mode 1 (Ant. A) and Mode 2 (Ant. B) for Radiated emission test were performed and recorded in this report.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	PPD-AR5BXB61
Modem	ACEEX	DM1414	IFAXDM1414
Mouse	QSKY	Lx-619B	DOC
Wireless AP	Planex	GW-AP54SGX	DOC

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of Draft n MCS0 20MHz - Mode 1 (Ant A.)

Test Software Version	RALINK QA		
Frequency	2412 MHz	2437 MHz	2462 MHz
Draft n Ant. A	11	1F	11

Power Parameters of Draft n MCS0 40MHz - Mode 2 (Ant B.)

Test Software Version	RALINK QA		
Frequency	2422 MHz	2437 MHz	2452 MHz
Draft n Ant. B	0F	16	10

An executive program, EMCTEST.EXE under WIN XP, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The program was executed as follows:

- Turn on the power of all equipment.
- The NB sends " H " messages to the panel, and the panel displays " H " patterns on the screen.
- The NB sends " H " messages to the modem.
- Repeat the steps from b to c.

At the same time, the following programs were executed:


Executed " RALINK QA " to control the EUT continuously transmit RF signal.

3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration


Test Configuration: 30KHz~1GHz

Test Mode: Mode 1 (PCB Antenna)




Test Configuration: 30KHz~1GHz

Test Mode: Mode 2 (PIFA Antenna)




Test Configuration: Above 1GHz

Test Mode : Mode 1 (PCB Antenna)




Test Configuration: Above 1GHz

Test Mode : Mode 2 (PIFA Antenna)



3.9.2. AC Power Line Conduction Emissions Test Configuration

Test Mode: Mode 1 (PCB Antenna)



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	54%
Test Engineer	Rex Chiu	Phase	Line
Configuration	Normal Link / Mode 1 (Ant A.)		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.17961	51.20	-13.30	64.50	50.85	0.15	0.20	QP
2	0.17961	43.09	-11.41	54.50	42.74	0.15	0.20	AVERAGE
3	0.30118	41.08	-19.13	60.21	40.78	0.10	0.20	QP
4	0.30118	34.85	-15.36	50.21	34.55	0.10	0.20	AVERAGE
5	0.42521	34.63	-22.72	57.35	34.33	0.10	0.20	QP
6	0.42521	27.35	-20.00	47.35	27.05	0.10	0.20	AVERAGE
7	0.54262	34.15	-21.86	56.00	33.87	0.08	0.20	QP
8	0.54262	25.93	-20.08	46.00	25.65	0.08	0.20	AVERAGE
9	4.269	30.00	-26.00	56.00	29.70	0.00	0.30	QP
10	4.269	14.16	-31.84	46.00	13.86	0.00	0.30	AVERAGE
11	4.598	31.65	-24.35	56.00	31.34	0.01	0.30	QP
12	4.598	16.01	-29.99	46.00	15.70	0.01	0.30	AVERAGE

Temperature	25°C	Humidity	54%
Test Engineer	Rex Chiu	Phase	Neutral
Configuration	Normal Link / Mode 1 (Ant A.)		



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.17866	51.30	-13.25	64.55	50.85	0.25	0.20	QP
2	0.17866	42.71	-11.84	54.55	42.26	0.25	0.20	AVERAGE
3	0.18566	49.96	-14.27	64.23	49.51	0.25	0.20	QP
4	0.18566	39.45	-14.78	54.23	39.00	0.25	0.20	AVERAGE
5	0.30169	41.66	-18.54	60.20	41.31	0.15	0.20	QP
6	0.30169	36.32	-13.88	50.20	35.97	0.15	0.20	AVERAGE
7	0.42065	28.18	-19.26	47.44	27.88	0.10	0.20	AVERAGE
8	0.42065	35.10	-22.34	57.44	34.80	0.10	0.20	QP
9	1.868	33.41	-22.59	56.00	33.13	0.10	0.18	QP
10	1.868	17.80	-28.20	46.00	17.52	0.10	0.18	AVERAGE
11	4.501	32.59	-23.41	56.00	32.19	0.10	0.30	QP
12	4.501	16.90	-29.10	46.00	16.50	0.10	0.30	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	rms
Trace	Max Hold
Sweep Time	Auto

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	Draft n / Mode 1 (Ant A.)


Configuration Draft n MCS0 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	19.73	30.00	Complies
6	2437 MHz	25.41	30.00	Complies
11	2462 MHz	18.51	30.00	Complies

Configuration Draft n MCS0 40MHz Ant. A


Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	17.20	30.00	Complies
6	2437 MHz	21.68	30.00	Complies
9	2452 MHz	18.86	30.00	Complies

Conducted Output Power Plot on Configuration Draft n MCS0 20MHz Ant. A / 2412 MHz




Date: 8.MAY.2008 18:44:20

Conducted Output Power Plot on Configuration Draft n MCS0 20MHz Ant. A / 2437 MHz




Date: 8.MAY.2008 18:45:27

Conducted Output Power Plot on Configuration Draft n MCS0 20MHz Ant. A / 2462 MHz




Date: 8.MAY.2008 18:46:25

Conducted Output Power Plot on Configuration Draft n MCS0 40MHz Ant. A / 2422 MHz




Date: 8.MAY.2008 18:48:17

Conducted Output Power Plot on Configuration Draft n MCS0 40MHz Ant. A / 2437 MHz



Date: 8.MAY.2008 18:49:01

Conducted Output Power Plot on Configuration Draft n MCS0 40MHz Ant. A / 2452 MHz



Date: 8.MAY.2008 18:50:09

Temperature	23°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	Draft n / Mode 2 (Ant B.)


Configuration Draft n MCS0 20MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	19.71	30.00	Complies
6	2437 MHz	24.40	30.00	Complies
11	2462 MHz	17.29	30.00	Complies

Configuration Draft n MCS0 40MHz Ant. B


Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	16.14	30.00	Complies
6	2437 MHz	19.90	30.00	Complies
9	2452 MHz	14.23	30.00	Complies

Conducted Output Power Plot on Configuration Draft n MCS0 20MHz Ant. B / 2412 MHz




Date: 8.MAY.2008 18:20:40

Conducted Output Power Plot on Configuration Draft n MCS0 20MHz Ant. B / 2437 MHz




Date: 8.MAY.2008 18:21:34

Conducted Output Power Plot on Configuration Draft n MCS0 20MHz Ant. B / 2462 MHz




Date: 8.MAY.2008 18:22:41

Conducted Output Power Plot on Configuration Draft n MCS0 40MHz Ant. B / 2422 MHz




Date: 8.MAY.2008 18:24:49

Conducted Output Power Plot on Configuration Draft n MCS0 40MHz Ant. B / 2437 MHz



Date: 8.MAY.2008 18:26:36

Conducted Output Power Plot on Configuration Draft n MCS0 40MHz Ant. B / 2452 MHz



Date: 8.MAY.2008 18:27:25

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	Draft n / Mode 1 (Ant A.)


Configuration Draft n MCS0 20MHz Ant. A

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-10.79	8.00	Complies
6	2437 MHz	-7.34	8.00	Complies
11	2462 MHz	-13.11	8.00	Complies

Configuration Draft n MCS0 40MHz Ant. A


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-17.30	8.00	Complies
6	2437 MHz	-13.92	8.00	Complies
9	2452 MHz	-16.44	8.00	Complies

Power Density Plot on Configuration Drafft n MCS0 20MHz Ant. A / 2412 MHz




Date: 8.MAY.2008 19:34:25

Power Density Plot on Configuration Drafft n MCS0 20MHz Ant. A / 2437 MHz




Date: 8.MAY.2008 19:35:23

Power Density Plot on Configuration Drafft n MCS0 20MHz Ant. A / 2462 MHz




Date: 8.MAY.2008 19:36:13

Power Density Plot on Configuration Drafft n MCS0 40MHz Ant. A / 2422 MHz




Date: 8.MAY.2008 19:38:18

Power Density Plot on Configuration Drafft n MCS0 40MHz Ant. A / 2437 MHz



Date: 8.MAY.2008 19:39:27

Power Density Plot on Configuration Drafft n MCS0 40MHz Ant. A / 2452 MHz



Date: 8.MAY.2008 19:40:22

Temperature	23°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	Draft n / Mode 2 (Ant B.)


Configuration Draft n MCS0 20MHz Ant. B

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-13.24	8.00	Complies
6	2437 MHz	-6.42	8.00	Complies
11	2462 MHz	-14.34	8.00	Complies

Configuration Draft n MCS0 40MHz Ant. B


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-18.54	8.00	Complies
6	2437 MHz	-13.68	8.00	Complies
9	2452 MHz	-19.40	8.00	Complies

Power Density Plot on Configuration Drafft n MCS0 20MHz Ant. B / 2412 MHz




Date: 8.MAY.2008 20:14:46

Power Density Plot on Configuration Drafft n MCS0 20MHz Ant. B / 2437 MHz




Date: 8.MAY.2008 20:15:50

Power Density Plot on Configuration Drafft n MCS0 20MHz Ant. B / 2462 MHz




Date: 8.MAY.2008 20:16:46

Power Density Plot on Configuration Drafft n MCS0 40MHz Ant. B / 2422 MHz




Date: 8.MAY.2008 20:18:23

Power Density Plot on Configuration Drafft n MCS0 40MHz Ant. B / 2437 MHz



Date: 8.MAY.2008 20:36:36

Power Density Plot on Configuration Drafft n MCS0 40MHz Ant. B / 2452 MHz



Date: 8.MAY.2008 20:20:37

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	23°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	Draft n / Mode 1 (Ant A.)


Configuration Draft n MCS0 20MHz Ant. A

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.64	17.80	500	Complies
6	2437 MHz	17.64	17.60	500	Complies
11	2462 MHz	17.60	17.80	500	Complies

Configuration Draft n MCS0 40MHz Ant. A


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.40	35.84	500	Complies
6	2437 MHz	36.32	35.84	500	Complies
9	2452 MHz	36.40	35.92	500	Complies

6 dB Bandwidth Plot on Configuration Draft n MCS0 20MHz Ant. A / 2412 MHz




Date: 8.MAY.2008 19:34:00

6 dB Bandwidth Plot on Configuration Draft n MCS0 20MHz Ant. A / 2437 MHz




Date: 8.MAY.2008 19:35:07

6 dB Bandwidth Plot on Configuration Draft n MCS0 20MHz Ant. A / 2462 MHz




Date: 8.MAY.2008 19:35:58

6 dB Bandwidth Plot on Configuration Draft n MCS0 40MHz Ant. A/ 2422 MHz




Date: 8.MAY.2008 19:37:53

6 dB Bandwidth Plot on Configuration Draft n MCS0 40MHz Ant. A / 2437 MHz



Date: 8.MAY.2008 19:39:02

6 dB Bandwidth Plot on Configuration Draft n MCS0 40MHz Ant. A / 2452 MHz



Date: 8.MAY.2008 19:39:57

Temperature	23°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	Draft n / Mode 2 (Ant B.)


Configuration Draft n MCS0 20MHz Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.44	17.80	500	Complies
6	2437 MHz	17.60	17.96	500	Complies
11	2462 MHz	17.60	17.52	500	Complies

Configuration Draft n MCS0 40MHz Ant. B


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.24	36.40	500	Complies
6	2437 MHz	36.40	35.84	500	Complies
9	2452 MHz	36.32	36.32	500	Complies

6 dB Bandwidth Plot on Configuration Draft n MCS0 20MHz Ant. B / 2412 MHz




Date: 8.MAY.2008 20:14:21

6 dB Bandwidth Plot on Configuration Draft n MCS0 20MHz Ant. B / 2437 MHz




Date: 8.MAY.2008 20:15:34

6 dB Bandwidth Plot on Configuration Drafft n MCS0 20MHz Ant. B / 2462 MHz




Date: 8.MAY.2008 20:16:31

6 dB Bandwidth Plot on Configuration Drafft n MCS0 40MHz Ant. B / 2422 MHz




Date: 8.MAY.2008 20:17:57

6 dB Bandwidth Plot on Configuration Drafft n MCS0 40MHz Ant. B / 2437 MHz



Date: 8.MAY.2008 20:19:05

6 dB Bandwidth Plot on Configuration Drafft n MCS0 40MHz Ant. B / 2452 MHz



Date: 8.MAY.2008 20:20:12

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1000KHz / 1000KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Normal Link

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Normal Link / Mode 1 (Ant A.)

Horizontal



	Freq	Level	Over	Limit	ReadAntenna	Preamp	Cable	Remark	Table	Ant	
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss		Pos	Pos	Pol/Phase
			dB	dBuV/m	dBuV	dB/m	dB		deg	cm	
1	117.300	30.05	-13.45	43.50	44.92	11.45	27.52	1.20 Peak	0	100	HORIZONTAL
2	299.660	32.63	-13.37	46.00	44.54	12.90	26.90	2.10 Peak	0	100	HORIZONTAL
3	498.510	37.60	-8.40	46.00	45.75	17.24	28.09	2.70 Peak	0	100	HORIZONTAL
4 !	700.270	40.65	-5.35	46.00	46.01	19.33	27.99	3.30 Peak	0	100	HORIZONTAL
5 @	797.270	43.26	-2.74	46.00	47.67	19.89	27.61	3.31 QP	325	125	HORIZONTAL
6	901.060	36.81	-9.19	46.00	40.18	20.43	27.39	3.60 Peak	0	100	HORIZONTAL

Vertical



	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable	Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB	deg	cm
1	35.820	31.26	-8.74	40.00	44.02	14.50	27.80	0.54	0	400
2	299.660	32.30	-13.70	46.00	44.20	12.90	26.90	2.10	0	400
3	497.540	39.34	-6.66	46.00	47.49	17.24	28.09	2.69	0	400
4	700.270	35.31	-10.69	46.00	40.67	19.33	27.99	3.30	0	400
5	800.180	38.06	-7.94	46.00	42.46	19.90	27.60	3.30	0	400
6 !	909.790	40.54	-5.46	46.00	44.10	20.20	27.36	3.60	0	400

Note:


The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Normal Link / Mode 2 (Ant B.)

Horizontal



	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable	Remark	Table	Ant	
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss		Pos	Pos	Pol/Phase
			dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	98.870	33.43	-10.07	43.50	49.75	10.10	27.61	1.18	Peak	0	400	HORIZONTAL
2	497.540	36.63	-9.37	46.00	44.79	17.24	28.09	2.69	Peak	0	400	HORIZONTAL
3	665.350	35.91	-10.09	46.00	41.62	18.88	28.03	3.44	Peak	0	400	HORIZONTAL
4	700.270	37.94	-8.06	46.00	43.30	19.33	27.99	3.30	Peak	0	400	HORIZONTAL
5	797.270	42.32	-3.68	46.00	46.73	19.89	27.61	3.31	Peak	31	125	HORIZONTAL
6	897.180	39.05	-6.95	46.00	42.46	20.41	27.41	3.59	Peak	0	400	HORIZONTAL

Vertical



	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable	Table	Ant	
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss	Pos	Pos	Pol/Phase
			dB	dBuV/m	dBuV	dB/m	dB	dB	deg	cm	
1	35.820	28.80	-11.20	40.00	41.56	14.50	27.80	0.54	0	400	VERTICAL
2	98.870	28.60	-14.90	43.50	44.92	10.10	27.61	1.18	0	400	VERTICAL
3	284.140	29.76	-16.24	46.00	42.12	12.54	26.93	2.04	0	400	VERTICAL
4	497.540	37.85	-8.15	46.00	46.00	17.24	28.09	2.69	0	400	VERTICAL
5	664.380	35.54	-10.46	46.00	41.24	18.89	28.04	3.44	0	400	VERTICAL
6	800.180	36.55	-9.45	46.00	40.95	19.90	27.60	3.30	0	400	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 20MHz Ch 1 / Mode 1 (Ant A.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4824.060	33.84	-20.16	54.00	32.33	33.39	3.37	35.25	AVERAGE	154	181	HORIZONTAL
2	4826.860	46.69	-27.31	74.00	45.18	33.39	3.37	35.25	PEAK	154	181	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4823.540	33.42	-20.58	54.00	31.91	33.39	3.37	35.25	AVERAGE	100	97	VERTICAL
2	4824.760	46.88	-27.12	74.00	45.37	33.39	3.37	35.25	PEAK	100	97	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 20MHz Ch 6 / Mode 1 (Ant A.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4873.100	48.05	-25.95	74.00	46.43	33.48	3.38	35.25	PEAK	152	182	HORIZONTAL
2 @	4874.290	35.47	-18.53	54.00	33.85	33.48	3.38	35.25	AVERAGE	152	182	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4872.200	46.75	-27.25	74.00	45.17	33.45	3.38	35.25	PEAK	100	80	VERTICAL
2 @	4872.600	34.57	-19.43	54.00	32.95	33.48	3.38	35.25	AVERAGE	100	80	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 20MHz Ch11 / Mode 1 (Ant A.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4923.400	31.69	-22.31	54.00	29.96	33.58	3.40	35.24	AVERAGE	140	185	HORIZONTAL
2	4924.300	43.80	-30.20	74.00	42.07	33.58	3.40	35.24	PEAK	140	185	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4924.000	31.35	-22.65	54.00	29.62	33.58	3.40	35.24	AVERAGE	100	96	VERTICAL
2	4925.100	43.73	-30.27	74.00	42.00	33.58	3.40	35.24	PEAK	100	96	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 20MHz Ch 1 / Mode 2 (Ant B.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4821.840	50.02	-23.98	74.00	48.51	33.39	3.37	35.25	PEAK	100	212	HORIZONTAL
2 @	4823.720	37.00	-17.00	54.00	35.49	33.39	3.37	35.25	AVERAGE	100	212	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4823.600	41.03	-12.97	54.00	39.52	33.39	3.37	35.25	AVERAGE	110	352	VERTICAL
2 @	4824.240	54.48	-19.52	74.00	52.97	33.39	3.37	35.25	PEAK	110	352	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 20MHz Ch 6 / Mode 2 (Ant B.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4873.640	34.83	-19.17	54.00	33.21	33.48	3.38	35.25	AVERAGE	100	210	HORIZONTAL
2	4876.460	47.93	-26.07	74.00	46.31	33.48	3.38	35.25	PEAK	100	210	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4873.100	50.20	-23.80	74.00	48.58	33.48	3.38	35.25	PEAK	100	86	VERTICAL
2	4873.900	37.57	-16.43	54.00	35.95	33.48	3.38	35.25	AVERAGE	100	86	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 20MHz Ch11 / Mode 2 (Ant B.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4924.240	31.61	-22.39	54.00	29.88	33.58	3.40	35.24	AVERAGE	100	188	HORIZONTAL
2	4933.000	43.98	-30.02	74.00	42.25	33.58	3.40	35.24	PEAK	100	188	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4930.600	31.92	-22.08	54.00	30.19	33.58	3.40	35.24	AVERAGE	107	314	VERTICAL
2	4932.120	45.14	-28.86	74.00	43.41	33.58	3.40	35.24	PEAK	107	314	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 40MHz Ch 3 / Mode 1 (Ant A.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4843.890	32.51	-21.49	54.00	30.97	33.42	3.38	35.25	AVERAGE	100	5	HORIZONTAL
2	4844.620	44.50	-29.50	74.00	42.95	33.42	3.38	35.25	PEAK	100	5	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4843.940	31.71	-22.29	54.00	30.16	33.42	3.38	35.25	AVERAGE	100	84	VERTICAL
2	4844.830	44.06	-29.94	74.00	42.51	33.42	3.38	35.25	PEAK	100	84	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 40MHz Ch 6 / Mode 1 (Ant A.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4874.650	33.42	-20.58	54.00	31.80	33.48	3.38	35.25	AVERAGE	104	5	HORIZONTAL
2	4875.400	46.03	-27.97	74.00	44.41	33.48	3.38	35.25	PEAK	104	5	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4874.190	32.68	-21.32	54.00	31.06	33.48	3.38	35.25	AVERAGE	100	84	VERTICAL
2	4875.370	45.16	-28.84	74.00	43.54	33.48	3.38	35.25	PEAK	100	84	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 40MHz Ch 9 / Mode 1 (Ant A.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4904.160	31.04	-22.96	54.00	29.35	33.54	3.39	35.24	AVERAGE	106	329	HORIZONTAL
2	4906.430	43.55	-30.45	74.00	41.86	33.54	3.39	35.24	PEAK	106	332	HORIZONTAL

Vertical



	Freq	Level	over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4903.310	43.04	-30.96	74.00	41.35	33.54	3.39	35.24	PEAK	100	250	VERTICAL
2	4904.180	30.66	-23.34	54.00	28.97	33.54	3.39	35.24	AVERAGE	100	250	VERTICAL

Note:


The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 40MHz Ch 3 / Mode 2 (Ant B.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4843.920	44.83	-29.17	74.00	43.28	33.42	3.38	35.25	PEAK	100	212	HORIZONTAL
2 @	4844.120	32.59	-21.41	54.00	31.04	33.42	3.38	35.25	AVERAGE	100	212	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4843.700	35.14	-18.86	54.00	33.59	33.42	3.38	35.25	AVERAGE	108	352	VERTICAL
2	4844.140	47.42	-26.58	74.00	45.87	33.42	3.38	35.25	PEAK	108	352	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 40MHz Ch 6 / Mode 2 (Ant B.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4875.380	44.74	-29.26	74.00	43.12	33.48	3.38	35.25	PEAK	107	215	HORIZONTAL
2	4875.470	30.70	-23.30	54.00	29.08	33.48	3.38	35.25	AVERAGE	107	215	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4874.000	33.24	-20.76	54.00	31.62	33.48	3.38	35.25	AVERAGE	100	360	VERTICAL
2	4877.200	44.64	-29.36	74.00	43.02	33.48	3.38	35.25	PEAK	100	360	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 40MHz Ch 9 / Mode 2 (Ant B.)

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4904.930	31.09	-22.91	54.00	29.40	33.54	3.39	35.24	AVERAGE	109	331	HORIZONTAL
2	4906.060	43.95	-30.05	74.00	42.26	33.54	3.39	35.24	PEAK	109	330	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4903.380	44.03	-29.97	74.00	42.34	33.54	3.39	35.24	PEAK	100	68	VERTICAL
2	4904.950	32.09	-21.91	54.00	30.40	33.54	3.39	35.24	AVERAGE	100	68	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 20MHz Ch 1, 6, 11 / Mode 1 (Ant A.)
Test Date	May. 07, 2008		

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2389.600	72.04	-1.96	74.00	41.64	28.05	2.35	0.00 PEAK	100	329	VERTICAL
2 @	2390.000	51.24	-2.76	54.00	20.83	28.05	2.36	0.00 AVERAGE	100	329	VERTICAL
3 @	2413.200	105.37			74.91	28.09	2.36	0.00 PEAK	100	329	VERTICAL
4 @	2415.000	96.16			65.70	28.09	2.36	0.00 AVERAGE	100	329	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2432.600	111.67			81.15	28.13	2.38	0.00 PEAK	100	200	HORIZONTAL
2 @	2433.800	102.41			71.90	28.13	2.38	0.00 AVERAGE	100	200	HORIZONTAL
3 @	2488.300	65.56	-8.44	74.00	34.85	28.30	2.41	0.00 PEAK	100	200	HORIZONTAL
4 @	2489.500	51.30	-2.70	54.00	20.58	28.30	2.41	0.00 AVERAGE	100	200	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2465.200	99.25			68.63	28.22	2.40	0.00 AVERAGE	104	201	HORIZONTAL
2 @	2469.600	111.01			80.38	28.22	2.41	0.00 PEAK	104	201	HORIZONTAL
3 @	2483.500	73.10	-0.90	74.00	42.43	28.26	2.41	0.00 PEAK	104	201	HORIZONTAL
4 @	2483.500	52.60	-1.40	54.00	21.93	28.26	2.41	0.00 AVERAGE	104	201	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 20MHz Ch 1, 6, 11 / Mode 2 (Ant B.)
Test Date	May. 07, 2008		

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	2390.000	53.43	-0.57	54.00	23.02	28.05	2.36	0.00	AVERAGE	100	33	VERTICAL
2 @	2390.000	71.36	-2.64	74.00	40.94	28.05	2.36	0.00	PEAK	100	33	VERTICAL
3 @	2413.400	104.02			73.56	28.09	2.36	0.00	PEAK	100	33	VERTICAL
4 @	2415.200	98.32			67.86	28.09	2.36	0.00	AVERAGE	100	33	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	2438.600	113.78			83.22	28.18	2.38	0.00	PEAK	100	190	VERTICAL
2 @	2440.200	104.13			73.58	28.18	2.38	0.00	AVERAGE	100	190	VERTICAL
3 @	2483.500	65.33	-8.67	74.00	34.66	28.26	2.41	0.00	PEAK	100	190	VERTICAL
4 @	2489.100	50.31	-3.69	54.00	19.60	28.30	2.41	0.00	AVERAGE	100	190	VERTICAL

Item 1, 2 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	2458.800	98.62			68.01	28.22	2.40	0.00	AVERAGE	100	190	VERTICAL
2 @	2459.000	110.05			79.44	28.22	2.40	0.00	PEAK	100	190	VERTICAL
3 @	2483.500	71.58	-2.42	74.00	40.91	28.26	2.41	0.00	PEAK	100	190	VERTICAL
4 @	2483.500	50.04	-3.96	54.00	19.37	28.26	2.41	0.00	AVERAGE	100	190	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 40MHz Ch 3, 6, 9 / Mode 1 (Ant A.)
Test Date	May. 07, 2008		

Channel 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2388.800	68.03	-5.97	74.00	37.63	28.05	2.35	0.00	PEAK	100	327 VERTICAL
2 @	2390.000	53.68	-0.32	54.00	23.26	28.05	2.36	0.00	AVERAGE	100	327 VERTICAL
3 @	2426.800	93.18			62.67	28.13	2.38	0.00	AVERAGE	100	327 VERTICAL
4 @	2427.200	102.35			71.84	28.13	2.38	0.00	PEAK	100	327 VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2390.000	64.47	-9.53	74.00	34.05	28.05	2.36	0.00	PEAK	105	203 HORIZONTAL
2 @	2390.000	51.37	-2.63	54.00	20.95	28.05	2.36	0.00	AVERAGE	105	203 HORIZONTAL
3 @	2441.000	108.75			78.18	28.18	2.40	0.00	PEAK	105	203 HORIZONTAL
4 @	2443.000	98.22			67.65	28.18	2.40	0.00	AVERAGE	105	203 HORIZONTAL
5 @	2483.500	53.61	-0.39	54.00	22.94	28.26	2.41	0.00	AVERAGE	105	203 HORIZONTAL
6 @	2483.900	67.88	-6.12	74.00	37.21	28.26	2.41	0.00	PEAK	105	203 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2462.800	105.20			74.59	28.22	2.40	0.00	PEAK	103	202 HORIZONTAL
2 @	2462.800	95.98			65.36	28.22	2.40	0.00	AVERAGE	103	202 HORIZONTAL
3 @	2483.500	53.68	-0.32	54.00	23.01	28.26	2.41	0.00	AVERAGE	103	202 HORIZONTAL
4 @	2483.500	67.42	-6.58	74.00	36.75	28.26	2.41	0.00	PEAK	103	202 HORIZONTAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level.

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS0 40MHz Ch 3, 6, 9 / Mode 2 (Ant B.)
Test Date	May. 07, 2008		

Channel 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2388.800	66.87	-7.13	74.00	36.47	28.05	2.35	0.00 PEAK	100	33	VERTICAL
2 @	2390.000	53.55	-0.45	54.00	23.13	28.05	2.36	0.00 AVERAGE	100	33	VERTICAL
3 @	2415.200	100.86			70.41	28.09	2.36	0.00 PEAK	100	33	VERTICAL
4 @	2426.400	91.84			61.33	28.13	2.38	0.00 AVERAGE	100	33	VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2387.600	66.39	-7.61	74.00	35.99	28.05	2.35	0.00 PEAK	100	34	VERTICAL
2 @	2390.000	53.39	-0.61	54.00	22.97	28.05	2.36	0.00 AVERAGE	100	34	VERTICAL
3 @	2429.000	106.87			76.35	28.13	2.38	0.00 PEAK	100	34	VERTICAL
4 @	2430.600	96.63			66.12	28.13	2.38	0.00 AVERAGE	100	34	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2462.800	104.33			73.72	28.22	2.40	0.00 PEAK	100	190	VERTICAL
2 @	2462.800	95.14			64.52	28.22	2.40	0.00 AVERAGE	100	190	VERTICAL
3 @	2483.500	53.44	-0.56	54.00	22.77	28.26	2.41	0.00 AVERAGE	100	190	VERTICAL
4 @	2483.900	68.49	-5.51	74.00	37.82	28.26	2.41	0.00 PEAK	100	190	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration Draft n MCS0 20MHz Ant. A / 2412 MHz




Date: 8.MAY.2008 19:34:33

High Band Edge Plot on Configuration Draft n MCS0 20MHz Ant. A / 2462 MHz




Date: 8.MAY.2008 19:36:21

Low Band Edge Plot on Configuration Drafft n MCS0 20MHz Ant. B / 2412 MHz



Date: 8.MAY.2008 20:14:54


High Band Edge Plot on Configuration Drafft n MCS0 20MHz Ant. B / 2462 MHz



Date: 8.MAY.2008 20:16:54


For Emission not in Restricted Band

Low Band Edge Plot on Configuration Draft n MCS0 40MHz Ant. A / 2422 MHz




Date: 8.MAY.2008 19:38:26

High Band Edge Plot on Configuration Draft n MCS0 40MHz Ant. A / 2452 MHz




Date: 8.MAY.2008 19:40:30

Low Band Edge Plot on Configuration Drafft n MCS0 40MHz Ant. B / 2422 MHz



Date: 8.MAY.2008 20:18:31

High Band Edge Plot on Configuration Drafft n MCS0 40MHz Ant. B / 2452 MHz



Date: 8.MAY.2008 20:20:45

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Mar. 03, 2008	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2008	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2008	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2008	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz – 30MHz	Mar. 27, 2008	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2007	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 14, 2008	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jun. 07, 2007	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100305	9 kHz - 40 GHz	Sep. 27, 2007	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 21, 2007	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 04, 2008	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.18, 2008	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 10, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 27, 2007	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 04, 2007*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2008	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2007	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2007	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2007	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 14, 2007	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 10, 2008	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

* Calibration Interval of instruments listed above is two year.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : LI190-070110

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 10, 2007

PI, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.

Appendix D. Antenna List

1. Table for Filed Antenna

Item	Note	Antenna		
		Brand	P/N	Gain (Peak)
1	PIFA (Main)	WNC	81.EEZ15.019	2.8
1	PIFA (Aux)	WNC	81.EEZ15.020	2.42
2	PIFA (Main)	WNC	81.EEZ15.005	1.99
2	PIFA (Aux)	WNC	81.EEZ15.005	-1.34
3	PIFA (Main)	WNC	81.EEW15.006	-1.34
3	PIFA (Aux)	WNC	81.EEW15.006	1.47
4	PIFA (Main)	SmartAnt	CPL06-22107A	1.79
4	PIFA (Aux)	SmartAnt	CPL06-22107A	1.25
5	PIFA (Main)	SmartAnt	CPL06-220120A01	2.39
5	PIFA (Aux)	SmartAnt	CPL06-220120A01	0.95
6	PIFA (Main)	FVC	K05007003702	0.71
6	PIFA (Aux)	FVC	K05007003802	1.73
7	PIFA (Main)	WGT	SKM66WIP101F	-0.19
7	PIFA (Aux)	WGT	SKM66WIP101F	-0.19
8	PIFA (Main)	FVC	K05007003652	2.02
8	PIFA (Aux)	WGT	SK900WIP101A	0.37
9	PIFA (Main)	WGT	SK720WIP101+B	1.3
9	PIFA (Aux)	WGT	SK72RWIP103+B	-0.09
10	PIFA (Main)	FVC	K05007003201	1.8
10	PIFA (Aux)	FVC	K05007003352	0.63
11	PIFA (Main)	VSO	821-101-01210380	-0.47
11	PIFA (Aux)	VSO	821-101-01210390	1
12	PIFA (Main)	VSO	821-101-01210420	-2.63
12	PIFA (Aux)	VSO	821-101-01210420	-2.63
13	PIFA (Main)	VSO	821-103-01210170	1.17
13	PIFA (Aux)	VSO	821-103-01210180	0.75
14	PIFA (Main)	Hitachi Cable	HFT40-LG01	2.38
14	PIFA (Aux)	Hitachi Cable	HFT40-LG02	2.81
15	PIFA (Main)	Hitachi Cable	HFT45	1.33
15	PIFA (Aux)	Hitachi Cable	HFT46	0.85
16	PIFA (Main)	Hitachi Cable	TLA-A-285/630-LG01	0.73
16	PIFA (Aux)	Hitachi Cable	TLA-A-285/630-LG01	0.73

17	PIFA	(Main)	ACON	ASAA 002	1.67
17	PIFA	(Aux)	ACON	ASAA 002	0.5
18	PIFA	(Main)	ACON	ASAA 003	2.25
18	PIFA	(Aux)	ACON	ASAA 003	0.87
19	PIFA	(Main)	Tyco	ASAT 002	2.32
19	PIFA	(Aux)	Tyco	ASAT 002	2.16
20	PIFA	(Main)	Tyco	ASAT 003	2.48
20	PIFA	(Aux)	Tyco	ASAT 003	1.61
21	PIFA	(Main)	Yageo	ASAY 002	2.53
21	PIFA	(Aux)	Yageo	ASAY 002	-1.58
22	PIFA	(Main)	Yageo	ASAY 003	2.51
22	PIFA	(Aux)	Yageo	ASAY 003	0.99
23	PIFA	(Main)	JEM	422817400001	1.64
23	PIFA	(Aux)	JEM	422817400001	2.48
24	PIFA	(Main)	ACON	APP8P-700003	1.82
24	PIFA	(Aux)	ACON	APP8P-700004	-0.85
25	PIFA	(Main)	Asus	A33/ 14G150012200	2.62
25	PIFA	(Aux)	Asus	A33/ 14G150012000	0.39
26	PIFA	(Main)	Tyco	MTC	2.59
26	PIFA	(Aux)	Tyco	MTC	1.58
27	PIFA	(Main)	Medion	CAN4313 555 012501B / 022501B	1.93
27	PIFA	(Aux)	Medion	CAN4313 555 012501B / 022501B	1.93
28	PIFA	(Main)	ASUS	T12KG / CAN4313 555 012501B	1.93
28	PIFA	(Aux)	ASUS	T12KG / CAN4313 555 022501B	1.93
29	PIFA	(Main)	ACON	EeePC P901 / APP6P-700155	2.47
29	PIFA	(Aux)	ACON	EeePC P901 / APP6P-700154	2.47
30	PIFA	(Main)	Tyco	Eee Box (B202) / 2023839-1	1.28
30	PIFA	(Aux)	Tyco	Eee Box (B202) / 2023901-1	1.28
31	PIFA	(Main)	YAGEO	Eee Box (B202) / CAN4313 748 012501B	-0.23
31	PIFA	(Aux)	YAGEO	Eee Box (B202) / CAN4313 748 032501B	-0.23
32	PIFA	(Main)	YAGEO	EeePC P901 / CAN4313 741 012501B	2.13
32	PIFA	(Aux)	YAGEO	EeePC P901 / CAN4313 741 022501B	2.13
33	PIFA	(Main)	YAGEO	ES5000 / CAN4313 766 012501B	1.98
33	PIFA	(Aux)	YAGEO	ES5000 / CAN4313 766 022501B	1.98
34	PIFA	(Main)	YAGEO	Eee PC 1001H/ CAN4313 762 012501B	2.83
34	PIFA	(Aux)	YAGEO	Eee PC 1001H/ CAN4313 762 012501B	0.17

35	PIFA	(Main)	ACON	Eee PC 1000H/ APP6P-700172	1.23
35	PIFA	(Aux)	ACON	Eee PC 1000H/ APP6P-700172	1.10
36	PIFA	(Main)	WGT	Eee PC 1001H AW-NE766/ W651	1.83
36	PIFA	(Aux)	WGT	Eee PC 1001H AW-NE766/ W651	1.83
37	PIFA	(Main)	WGT	Eee PC 1001H AW-NE766/ W351	0.9
37	PIFA	(Aux)	WGT	Eee PC 1001H AW-NE766/ W351	0.9
38	PIFA	(Main)	MICHIGAN	6036B0014401	2.95
38	PIFA	(Aux)	MICHIGAN	6036B0016901	2.95
39	PCB	(Main)	VSO	S79-1800710-V03	0.75
39	PCB	(Aux)	VSO	S79-1800700-V03	0.75