

# Appendix C. Maximum Permissible Exposure

FCC ID: VQF-RT3090-1T1R Page No. : C1 of C3



# 1. Maximum Permissible Exposure

## 1.1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

#### (A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E ², H ² or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842 / f	4.89 / f	(900 / f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-100,000			5	6	

#### (B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz; \*Plane-wave equivalent power density

### 1.2. MPE Calculation Method

E (V/m) = 
$$\frac{\sqrt{30 \times P \times G}}{d}$$
 Power Density:  $Pd$  (W/m²) =  $\frac{E^2}{377}$ 

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

FCC ID: VQF-RT3090-1T1R Page No. : C2 of C3



Report No.: FR8N2012-01

# 1.3. Calculated Result and Limit

For 2.4GHz Band: 802.11b/g Antenna Type : PIFA Antenna

Max Conducted Power for IEEE 11b/g Ant.A: 21.08 dBm

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power ( mW )	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.99	1.9907	21.0800	128.2331	0.050810	1	Complies

FCC ID: VQF-RT3090-1T1R Page No. : C3 of C3