Co-location Report

Page No. : 1 of 11

1 TEST RESULT

1.1 Radiated Emissions Measurement

1.1.1 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

1.1.2 Measuring Instruments and Setting

Please refer to section 2 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

Page No. : 2 of 11

1.1.3 Test Procedures


Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8
meter above ground. The phase center of the receiving antenna mounted on the top of a
height-variable antenna tower was placed 3 meters far away from the turntable.

- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.


Page No. : 3 of 11

1.1.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade form 3m to 1m.

Distance extrapolation factor = 20 log (specific distance [3m] / test distance [1m]) (dB); Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

1.1.5 Test Deviation

There is no deviation with the original standard.

1.1.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

Page No. : 4 of 11

1.1.7 Results of Radiated Emissions (9kHz~30MHz)

Final Test Date	May 26, 2011	Test Site No.	03CH03-HY
Temperature	25℃	Humidity	55%
Test Engineer	Streak		

Freq.	Level	Over Limit	Limit Line	Remark
(MHz)	(dBuV)	(dB)	(dBuV)	
-	=	=	=	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = 40 log (specific distance / test distance) (dB); Limit line = specific limits (dBuV) + distance extrapolation factor.

Page No. : 5 of 11

1.1.8 Results of Radiated Emissions (30MHz~1GHz)

Final Test Date	May 26, 2011	Test Site No.	03CH03-HY
Temperature	25 ℃	Humidity	55%
Test Engineer	Streak	Configuration	WLAN 2.4G (1TX) & Bluetooth


Horizontal



	Freq	Level	Over Limit	Limit Line		Antenna Factor			Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	BuV dB/m	dB	dB	5.5
1	35.820	22.04	-17.96	40.00	35.29	14.94	-0.75	27.43	Peak
2	97.900	20.81	-22.69	43.50	36.54	10.86	0.84	27.43	Peak
2	280.260	21.66	-24.34	46.00	34.83	13.23	1.77	28.17	Peak
4	327.790	26.24	-19.76	46.00	38.03	14.51	2.08	28.38	Peak
5 @	801.150	39.13	-6.87	46.00	43.43	20.75	4.41	29.47	Peak
6	877.780	29.57	-16.43	46.00	33.25	20.95	4.76	29.39	Peak

Page No. : 6 of 11





	Freq	Level	Over Limit			Antenna Factor		Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	- дв	
1	97.900	27.75	-15.75	43.50	43.48	10.86	0.84	27.43	Peak
2	105.660	24.25	-19.25	43.50	38.86	11.92	0.91	27.44	Peak
3	242.430	20.88	-25.12	46.00	35.45	11.88	1.54	28.00	Peak
4	458.740	27.21	-18.79	46.00	36.23	17.26	2.71	28.99	Peak
5	801.150	38.26	-7.74	46.00	42.56	20.75	4.41	29.47	Peak
6	904.940	30.20	-15.80	46.00	33.55	21.06	4.92	29.34	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = $20 \log Emission$ level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Page No. : 7 of 11

1.1.9 Results for Radiated Emissions (1GHz~10th Harmonic)

Final Test Date	May 26, 2011	Test Site No.	03CH03-HY
Temperature	25 ℃	Humidity	55%
Test Engineer	Streak	Configuration	WLAN 2.4G (1TX) & Bluetooth

Horizontal




	Freq	Level	Over Limit			Antenna Factor		Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	0.5
1 @	4804.000	49.53	-4.47	54.00	43.71	33.02	5.43	32.64	PK
2 @	4874.000	48.02	-5.98	54.00	42.06	33.16	5.43	32.62	PK
3	7206.000	48.84			41.22	35.46	5.04	32.87	Peak
4 @	7311.000	49.88	-4.12	54.00	41.74	35.68	5.36	32.90	PK
5	9608.000	53.90			42.25	38.31	6.68	33.34	Peak
6	9748.000	53.68			41.66	38.62	6.74	33.34	Peak

Note: The Items 3, 5 and 6 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Page No. : 8 of 11

Vertical



				Over	Limit	Readi	Antenna	Cable	Preamp	
		Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Remark
		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	5.5
1	0	4804.000	50.59	-3,41	54.00	44.77	33.02	5.43	32.64	PK
2	e	4874.000	47.76	-6.24	54.00	41.80	33.16	5.43	32.62	PK
3		7206.000	48.59			40.97	35.46	5.04	32.87	Peak
4	0	7311.000	49.81	-4.19	54.00	41.67	35.68	5.36	32.90	PK
5		9608.000	54.12			42.47	38.31	6.68	33.34	Peak
6		9748.000	53.86			41.84	38.62	6.74	33.34	Peak

Note: The Items 3, 5 and 6 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Page No. : 9 of 11

2 LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz	Jun. 18, 2010	Radiation
Chamber				3m		(03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 25, 2011	Radiation
7 tinpinior	OOT WITH THE	00/10201/1	10007	3 KHZ Z 3HZ	0dii. 20, 2011	(03CH03-HY)
Amplifior	Agilopt	8449B	3008A02120	1 GHz - 26.5 GHz	Aug 02 2010	Radiation
Amplifier	Agilent	0449D	3000A02120	1 GHZ - 20.5 GHZ	Aug. 02, 2010	(03CH03-HY)
Spectrum	000	ECD40	100004	9 kHz - 40 GHz	Nov. 17, 2010	Radiation
Analyzer	R&S	FSP40	100004	9 KHZ - 40 GHZ	Nov. 17, 2010	(03CH03-HY)
Dilan Antanna	CCHAFFNED	CDL C440D	00007	20 MH - 4 CH-	0-+ 40 0040	Radiation
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Oct. 16, 2010	(03CH03-HY)
Llorn Antonno	EMCO	2445	6741	1GHz ~ 18GHz	May 30, 2011	Radiation
Horn Antenna	EMCO	3115	0/41	10112 ~ 100112	Way 30, 2011	(03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.13, 2011	Radiation
HOITI AITIEITIIA	SCHWARZBECK	ББПАЭ170	ББПА9170154	15 GHZ - 40 GHZ	Jan. 13, 2011	(03CH03-HY)
RF Cable-R03m	luo Doo	RG142	CB021	30 MHz - 1 GHz	lon 10 2011	Radiation
RF Cable-R03III	Jye Bao	KG142	CB021	30 MHZ - 1 GHZ	Jan. 18, 2011	(03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	lon 10 2011	Radiation
RF Cable-HIGH	SURINER	SUCUFLEX 106	03CH03-H Y	1 GHZ - 40 GHZ	Jan. 18, 2011	(03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 360 dograd	N/A	Radiation
rum rable	חט	D3 420	420/000/00	0 – 360 degree	IN/A	(03CH03-HY)
Antonno Most	JL	MA 240	240/560/00	1 m - 4 m	NI/A	Radiation
Antenna Mast	HD	MA 240	240/560/00	1 111 - 4 111	N/A	(03CH03-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 29, 2010*	Radiation
						(03CH03-HY)

Note: Calibration Interval of instruments listed above is two year.

Page No. : 10 of 11

3 TEST LOCATION

SHIJR	ADD	:	6FI., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C.
	TEL	:	886-2-2696-2468
	FAX	:	886-2-2696-2255
HWA YA	ADD	:	No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
	TEL	:	886-3-327-3456
	FAX	:	886-3-318-0055
LINKOU	ADD	:	No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C
	TEL	:	886-2-2601-1640
	FAX	:	886-2-2601-1695
DUNGHU	ADD	:	No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C.
	TEL	:	886-2-2631-4739
	FAX	:	886-2-2631-9740
JUNGHE	ADD	:	7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C.
	TEL	:	886-2-8227-2020
	FAX	:	886-2-8227-2626
NEIHU	ADD	:	4FI., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C.
	TEL	:	886-2-2794-8886
	FAX	:	886-2-2794-9777
JHUBEI	ADD	:	No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.
	TEL	:	886-3-656-9065
	FAX	:	886-3-656-9085

Page No. : 11 of 11