

FCC TEST REPORT (RFID)

REPORT NO.: RF110715C25A-4

MODEL NO.: F-01E

FCC ID: VQK-F01E

RECEIVED: Jul. 15, 2011

TESTED: Aug. 22 ~ Aug. 24, 2011

ISSUED: Sep. 17, 2012

APPLICANT: FUJITSU LIMITED

ADDRESS: 1-1, Kamikodanaka 4-chome, Nakahara-ku,

Kawasaki 211-8588, Japan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,

Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan

Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



Table of Contents

RELE/	ASE CONTROL RECORD	3
1.	CERTIFICATION	
2.	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	5
3.	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	9
3.4	DESCRIPTION OF SUPPORT UNITS	
4.	TEST TYPES AND RESULTS	10
4.1	RADIATED EMISSION MEASUREMENT	
4.1.1	LIMITS OF RADIATED EMISSION MEASUREMENT	
4.1.2	TEST INSTRUMENTS	
4.1.3	TEST PROCEDURES	12
4.1.4	DEVIATION FROM TEST STANDARD	
4.1.5	TEST SETUP	
4.1.6	EUT OPERATING CONDITIONS	
4.1.7	TEST RESULTS	
4.2	FREQUENCY STABILITY	
4.2.1	LIMITS OF FREQUENCY STABILITY MEASUREMENT	
4.2.2	TEST INSTRUMENTS	
4.2.3	TEST PROCEDURE	
4.2.4	DEVIATION FROM TEST STANDARD	
4.2.5	TEST SETUP	
4.2.6	EUT OPERATING CONDITION	
4.2.7	TEST RESULTS	
4.3	20DB BANDWIDTHLIMITS OF 20DB BANDWIDTH MEASUREMENT	
4.3.1 4.3.2		
4.3.2	TEST PROCEDURE	
4.3.4	TEST PROCEDURE DEVIATION FROM TEST STANDARD	
4.3.5	TEST SETUP	
4.3.6	EUT OPERATING CONDITION	
4.3.7	TEST RESULTS	
4 .3.7 5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	
5. 6.	INFORMATION ON THE TESTING LABORATORIES	
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGE	
٠.	TO THE EUT BY THE LAB	
		_



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED	
RF110715C25A-4	Original release	Sep. 17, 2012	

Report No.: RF110715C25A-4 Reference No.: 110715C25, 120821C26 3 of 25 Report Format Version 5.0.0



1. CERTIFICATION

PRODUCT: Mobile Phone

MODEL NO.: F-01E

BRAND: FOMA

APPLICANT: FUJITSU LIMITED

TEST SAMPLE: ENGINEERING SAMPLE

TESTED: Aug. 22 ~ Aug. 24, 2011

STANDARDS: FCC Part 15, Subpart C (Section 15.225)

FCC Part 15, Subpart C (Section 15.215)

ANSI C63.10-2009

The above equipment (model: F-01E) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY

Pettie Chen / Senior Specialist

DATE: Sep. 17, 2012

APPROVED BY

Gary Changy Technical Manager

DATE: Sep. 17, 2012



2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.225, 15.215)						
STANDARD SECTION	TEST TYPE AND LIMIT	REMARK				
15.225 (a)	The field strength of any emissions within the band 13.553-13.567 MHz	PASS	Meet the requirement of limit. Minimum passing margin is -72.3dB at 13.56MHz.			
The field strength of any emissions 15.225 (d) appearing outside of the 13.110-14.010 MHz band		PASS	Meet the requirement of limit. Minimum passing margin is -9.9dB at 597.63MHz.			
15.225 (e) The frequency tolerance		PASS	Meet the requirement of limit.			
15.215 (c)	20dB Bandwidth	PASS	Meet the requirement of limit.			

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY	
Radiated emissions	30MHz ~ 200MHz	3.34 dB	
Radiated emissions	200MHz ~1000MHz	3.35 dB	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Mobile Phone	
MODEL NO.	F-01E	
POWER SUPPLY	3.7Vdc (Li-ion battery)	
POWER SUPPLY	5.4Vdc (Adapter)	
MODULATION TYPE	ASK	
OPERATING FREQUENCY	13.56MHz	
ANTENNA TYPE	Loop antenna	
DATA CABLE	NA	
I/O PORTS	Refer to user's manual	
ACCESSORY DEVICES	Battery	

NOTE:

- There are two samples for the EUT. The differences between these two samples are HW
 versions and GPS function (sample 1 is without GPS function, sample 2 is with GPS function).
 The difference of two HW versions is the mechanical part of top cover. Since no effect is on RFID
 function, so test is performed for sample 1 only.
- 2. The EUT use the following internal Li-ion battery:

BRAND	Fujitsu Limited
MODEL	F19
RATING	3.7Vdc, 830mAh

3. The following accessories are for optional units only.

PRODUCT	BRAND	MODEL	DESCRIPTION
ADAPTER	SMK		I/P: 100-240Vac, 0.12A, 50-60Hz O/P: 5.4Vdc, 700mA
USB cable	NA	NA	0.8m non-shielded cable without core

4. The following table is for HW and SW.

ITEM	HARDWARE VERSION	SOFTWARE VERSION	
Sample 1	V2.2	R17.2	
Sample 2	V1.2.0	R08.2	

5. The following table is for IMEI code.

ITEM	IMEI code
Sample 1	357261040007442
Sample 2	353705050008017

6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.




3.2 DESCRIPTION OF TEST MODES

The EUT only have one channel.

CHANNEL	FREQUENCY (MHz)
1	13.56

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



7 of 25



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE		APPLICABLE TO	DESCRIPTION		
MODE	RE	FT	BW	DESCRIPTION	
-	√	√ √	√	-	

Where

RE: Radiated Emission

FT: Frequency Tolerance

BW: 20dB Bandwidth

RADIATED EMISSION TEST:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE AVAILABLE MODE CHANNEL		TESTED CHANNEL	MODULATION TYPE	AXIS
-	1	1	ASK	Υ

FREQUENCY TOLERANCE:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	AXIS
-	1	1	ASK	Υ

20dB BANDWIDTH:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	1	1	ASK

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE	25deg. C, 65%RH	120Vac, 60Hz	David Huang
FT	25deg. C, 65%RH	120Vac, 60Hz	David Huang
BW	20deg. C, 45%RH	120Vac, 60Hz	Long Chen

Report No.: RF110715C25A-4 Reference No.: 110715C25, 120821C26 8 of 25

Report Format Version 5.0.0



3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RFID Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.225) FCC Part 15, Subpart C (15.215)

ANSI C63.4-2003

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B. The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit.



4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Report No.: RF110715C25A-4 Reference No.: 110715C25, 120821C26 10 of 25

Report Format Version 5.0.0



4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100212	Aug. 02, 2011	Aug. 01, 2012
Spectrum Analyzer ROHDE & SCHWARZ	FSP 40	100041	Jul. 21, 2011	Jul. 20, 2012
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Apr. 13, 2011	Apr. 12, 2012
HORN Antenna SCHWARZBECK	9120D	9120D-405	Feb. 08, 2011	Feb. 07, 2012
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Dec. 27, 2010	Dec. 26, 2011
Preamplifier Agilent	8447D	2944A10633	Nov. 02, 2010	Nov. 01, 2011
Preamplifier Agilent	8449B	3008A01964	Nov. 02, 2010	Nov. 01, 2011
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	295014/4	Aug. 19, 2011	Aug. 18, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	12738/6	Aug. 19, 2011	Aug. 18, 2012
Software ADT.	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA	NA
Turn Table ADT.	TT100.	TT93021703	NA	NA
Turn Table Controller ADT.	SC100.	SC93021703	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 3.
- 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The FCC Site Registration No. is 988962.
- 5. The IC Site Registration No. is IC 7450F-3.



4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

Report No.: RF110715C25A-4 Reference No.: 110715C25, 120821C26 12 of 25

Report Format Version 5.0.0



4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.



4.1.7 TEST RESULTS

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 1	FREQUENCY RANGE	13.553 ~ 13.567MHz	
INPUT POWER	3.7Vdc	DETECTOR FUNCTION	Quasi-Peak	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	David Huang	

ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA OPEN AT 3m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	13.56	51.7	124.0	-72.3	1.00	101	31.9	19.8

REMARKS:

- 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. Above limits have been translated by the formula


The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example:

13.56MHz = 15848uV/m 30m

= 84dBuV/m 30m = $84+20log(30/3)^2$ 3m

= 124dBuV/m





EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 1	FREQUENCY RANGE	13.553 ~ 13.567MHz	
INPUT POWER	3.7Vdc	DETECTOR FUNCTION	Quasi-Peak	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	David Huang	

	ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA CLOSE AT 3m							
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	13.56	54.4	124.0	-76.3	1.00	187	27.9	19.8

REMARKS:


- 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. Above limits have been translated by the formula

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance) Example:

13.56MHz = 15848uV/m

30m 84dBuV/m 30m $84+20\log(30/3)^2$ 3m

124dBuV/m





EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 1	FREQUENCY RANGE	Below 30MHz	
INPUT POWER	3.7Vdc	DETECTOR FUNCTION	Quasi-Peak	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	David Huang	

	ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA OPEN AT 3m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	
1	13.553	41.0	69.5	-28.5	1.00	101	21.2	19.8	
2	13.567	43.2	69.5	-26.3	1.00	101	23.4	19.8	
3	27.120	31.5	69.5	-38.0	1.00	214	11.2	20.3	
ANTENNA POLARITY & TEST DISTANCE: LOOP ANTENNA CLOSE AT 3m									
	ANII	ENNA POLA	KITY & TES	ST DISTANC	E: LOOP A	<u>NTENNA CL</u>	<u>.OSE AT 3m</u>	1	
No.	Freq. (MHz)	ENNA POLA Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	EE: LOOP A Antenna Height (m)	Table Angle (Degree)	OSE AT 3m Raw Value (dBuV)	Correction Factor (dB/m)	
No.	Freq.	Emission Level	Limit	Margin	Antenna Height	Table Angle	Raw Value	Correction Factor	
No. 1 2	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	

REMARKS:

- 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz	
INPUT POWER	3.7Vdc	DETECTOR FUNCTION	Quasi-Peak	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	David Huang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	94.06	29.60 QP	43.5	-13.9	2.25 H	1	20.40	9.20
2	121.28	28.90 QP	43.5	-14.6	1.25 H	355	16.30	12.60
3	393.48	31.60 QP	46.0	-14.4	1.00 H	70	14.40	17.20
4	420.70	34.00 QP	46.0	-12.0	2.00 H	253	16.00	18.00
5	597.63	36.10 QP	46.0	-9.9	1.25 H	277	13.70	22.40
6	976.77	40.10 QP	54.0	-13.9	1.25 H	295	12.30	27.80
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
NO .	FREQ. (MHz) 39.62	LEVEL		MARGIN (dB) -16.3	7	ANGLE		FACTOR
	` ,	LEVEL (dBuV/m)	(dBuV/m)	,	HEIGHT (m)	ANGLE (Degree)	(dBuV)	FACTOR (dB/m)
1	39.62	LEVEL (dBuV/m) 23.70 QP	(dBuV/m) 40.0	-16.3	HEIGHT (m)	ANGLE (Degree)	(dBuV)	FACTOR (dB/m) 14.30
1 2	39.62 66.84	LEVEL (dBuV/m) 23.70 QP 22.10 QP	(dBuV/m) 40.0 40.0	-16.3 -17.9	1.00 V 2.25 V	ANGLE (Degree) 199 289	(dBuV) 9.40 9.70	FACTOR (dB/m) 14.30 12.40
1 2 3	39.62 66.84 94.06	LEVEL (dBuV/m) 23.70 QP 22.10 QP 23.00 QP	(dBuV/m) 40.0 40.0 43.5	-16.3 -17.9 -20.5	1.00 V 2.25 V 1.00 V	ANGLE (Degree) 199 289 223	9.40 9.70 13.80	FACTOR (dB/m) 14.30 12.40 9.20

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).

- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.



4.2 FREQUENCY STABILITY

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of –20 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
SPECTRUM ANALYZER R&S	FSP40	100040	Aug. 01, 2011	Jul. 31, 2012
WIT STANDARD TEMPERATURE AND HUMIDITY CHAMBER	TH-4S-C	W981030	Jun. 15, 2011	Jun. 14, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.2.3 TEST PROCEDURE


- a. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- b. Turn the EUT on and couple its output to a spectrum analyzer.
- c. Turn the EUT off and set the chamber to the highest temperature specified.
- d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.



4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



4.2.6 EUT OPERATING CONDITION

Same as Item 4.1.6.



4.2.7 TEST RESULTS

FREQUEMCY STABILITY VERSUS TEMP.									
		0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
TEMP. (℃)	POWER SUPPLY (Vdc)	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift
		(MHz)	%	(MHz)	%	(MHz)	%	(MHz)	%
55	3.7	13.560201	0.0014800	13.560211	0.0015537	13.560196	0.0014441	13.560177	0.0013037
50	3.7	13.560053	0.0003926	13.560096	0.0007105	13.560108	0.0007948	13.560112	0.0008281
40	3.7	13.560153	0.0011277	13.560170	0.0012505	13.560125	0.0009235	13.560204	0.0015012
30	3.7	13.560200	0.0014720	13.560166	0.0012211	13.560210	0.0015462	13.560152	0.0011206
20	3.7	13.560190	0.0014046	13.560185	0.0013611	13.560206	0.0015171	13.560237	0.0017483
10	3.7	13.560165	0.0012134	13.560213	0.0015733	13.560174	0.0012834	13.560161	0.0011856
0	3.7	13.560138	0.0010146	13.560137	0.0010139	13.560134	0.0009900	13.560132	0.0009771
-10	3.7	13.560241	0.0017799	13.560164	0.0012106	13.560199	0.0014653	13.560185	0.0013627
-20	3.7	13.560223	0.0016454	13.560170	0.0012519	13.560221	0.0016289	13.560177	0.0013056

FREQUEMCY STABILITY VERSUS VOLTAGE									
TEMP. (℃)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift
		(MHz)	%	(MHz)	%	(MHz)	%	(MHz)	%
	4.07	13.560169	0.0012448	13.560197	0.0014524	13.560154	0.0011370	13.560180	0.0013260
20	3.70	13.560199	0.0014685	13.560185	0.0013654	13.560140	0.0010297	13.560196	0.0014483
	3.33	13.560166	0.0012216	13.560165	0.0012200	13.560204	0.0015045	13.560164	0.0012096



4.3 20dB BANDWIDTH

4.3.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT

The 20dB bandwidth shall be specified in operating frequency band.

4.3.2 TEST INSTRUMENTS

Same as Item 4.1.2.

4.3.3 TEST PROCEDURE

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 1kHz RBW and 1kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP

Same as Item 4.1.5.


4.3.6 EUT OPERATING CONDITION

Same as Item 4.1.6.



4.3.7 TEST RESULTS

20dBc point (Low)	20dBc point (HIGH)	Operating frequency band (MHz)	PASS/FAIL
13.559 MHz	13.56058 MHz	13.553~13.567	PASS





5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).							



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:Hsin Chu EMC/RF Lab:Tel: 886-2-26052180Tel: 886-3-5935343Fax: 886-2-26051924Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---