



A D T

# FCC TEST REPORT (15.247: WLAN)

**REPORT NO.:** RF120823C14-3

**MODEL NO.:** F-03E

**FCC ID:** VQK-F03E

**RECEIVED:** Aug. 23, 2012

**TESTED:** Oct. 01 ~ Oct. 05, 2012

**ISSUED:** Oct. 09, 2012

**APPLICANT:** FUJITSU LIMITED

**ADDRESS:** 1-1, Kamikodanaka 4-chome, Nakahara-ku,  
Kawasaki 211-8588, Japan

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,  
New Taipei City, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim  
product certification, approval, or endorsement by  
TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	4
1. CERTIFICATION .....	5
2. SUMMARY OF TEST RESULTS .....	6
2.1 MEASUREMENT UNCERTAINTY .....	6
3. GENERAL INFORMATION.....	7
3.1 GENERAL DESCRIPTION OF EUT .....	7
3.2 DESCRIPTION OF TEST MODES.....	8
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	9
3.3 DESCRIPTION OF SUPPORT UNITS .....	11
3.3.1 CONFIGURATION OF SYSTEM UNDER TEST .....	12
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	12
4. TEST TYPES AND RESULTS .....	13
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	13
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	13
4.1.2 TEST INSTRUMENTS .....	14
4.1.3 TEST PROCEDURES .....	15
4.1.4 DEVIATION FROM TEST STANDARD .....	15
4.1.5 TEST SETUP .....	16
4.1.6 EUT OPERATING CONDITIONS .....	16
4.1.7 TEST RESULTS .....	17
4.2 CONDUCTED EMISSION MEASUREMENT .....	37
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	37
4.2.2 TEST INSTRUMENTS .....	37
4.2.3 TEST PROCEDURES .....	38
4.2.4 DEVIATION FROM TEST STANDARD .....	38
4.2.5 TEST SETUP .....	38
4.2.6 EUT OPERATING CONDITIONS .....	38
4.2.7 TEST RESULTS .....	39
4.3 6dB BANDWIDTH MEASUREMENT .....	41
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	41
4.3.2 TEST SETUP .....	41
4.3.3 TEST INSTRUMENTS .....	41
4.3.4 TEST PROCEDURE .....	41
4.3.5 DEVIATION FROM TEST STANDARD .....	41
4.3.6 EUT OPERATING CONDITIONS .....	41
4.3.7 TEST RESULTS .....	42
4.4 CONDUCTED OUTPUT POWER .....	43
4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....	43
4.4.2 TEST SETUP .....	43
4.4.3 TEST INSTRUMENTS .....	43
4.4.4 TEST PROCEDURES .....	43
4.4.5 DEVIATION FROM TEST STANDARD .....	43
4.4.6 EUT OPERATING CONDITIONS .....	43
4.4.7 TEST RESULTS .....	44
4.5 POWER SPECTRAL DENSITY MEASUREMENT .....	45
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	45
4.5.2 TEST SETUP .....	45
4.5.3 TEST INSTRUMENTS .....	45
4.5.4 TEST PROCEDURE .....	45



A D T

4.5.5	DEVIATION FROM TEST STANDARD .....	45
4.5.6	EUT OPERATING CONDITION .....	45
4.5.7	TEST RESULTS .....	46
4.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	47
4.6.1	LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....	47
4.6.2	TEST SETUP .....	47
4.6.3	TEST INSTRUMENTS .....	47
4.6.4	TEST PROCEDURE .....	47
4.6.5	DEVIATION FROM TEST STANDARD .....	48
4.6.6	EUT OPERATING CONDITION .....	48
4.6.7	TEST RESULTS .....	48
4.6.8	TEST RESULTS .....	49
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	52
6.	INFORMATION ON THE TESTING LABORATORIES .....	53
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	54



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120823C14-3	Original release	Oct. 09, 2012



A D T

## 1. CERTIFICATION

**PRODUCT:** Mobile Phone

**MODEL NO.:** F-03E

**BRAND:** NTT DOCOMO

**APPLICANT:** FUJITSU LIMITED


**TESTED:** Oct. 01 ~ Oct. 05, 2012

**TEST SAMPLE:** ENGINEERING SAMPLE

**STANDARDS:** FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10-2009

The above equipment (model: F-03E) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** :  , DATE : Oct. 09, 2012

Pettie Chen / Senior Specialist

**APPROVED BY** :  , DATE : Oct. 09, 2012

Ken Liu / Manager



## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -1.10dB at 13.55859MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -8.09dB at 30.27MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



A D T

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>EUT</b>	Mobile Phone
<b>MODEL NO.</b>	F-03E
<b>POWER SUPPLY</b>	5.1Vdc (adapter or host equipment) 3.8Vdc (battery)
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	802.11b:11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 72.2Mbps
<b>OPERATING FREQUENCY</b>	2412 ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>OUTPUT POWER</b>	122.180mW
<b>ANTENNA TYPE</b>	PCB antenna with 0.36dBi gain
<b>ANTENNA CONNECTOR</b>	NA
<b>DATA CABLE</b>	Refer to Note as below
<b>I/O PORTS</b>	Refer to user's manual
<b>ACCESSORY DEVICES</b>	Refer to Note as below

**NOTE:**

1. The EUT contains following accessory and components.

ITEM	BRAND	MODEL	SPECIFICATION
Battery	FUJITSU	F29	Rating: 3.8Vdc, 1810mAh Type: Li-ion
LCD Panel	JDI	GCX162BLP-7	--
Photo Camera	ALTEK	AOA0803	--
Video Camera	ALTEK	ASF0104	--

2. The following accessories are for support units only.

ITEM	BRAND	MODEL	SPECIFICATION
Adapter	Motorola	DC4050US0301	Input: 100-240Vac, 50/60Hz, 0.2A Output: 5.1Vdc, 850mA
USB cable	Motorola	NA	1.0m

3. SW version is LYDV01R13Ge
4. HW version is DVT2.
5. IMEI code: 353737050009323, 353737050011543.
6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

### 3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		



A D T

### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE $<$ 1G	PLC	APCM	
-	✓	✓	✓	✓	-

Where RE $\geq$ 1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

RE $<$ 1G: Radiated Emission below 1GHz

APCM: Antenna Port Conducted Measurement

#### RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	7.2

#### RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11g	1 to 11	6	OFDM	BPSK	6.0

#### POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11g	1 to 11	6	OFDM	BPSK	6.0

\*Test condition: WIFI+Bluetooth+NFC



A D T

**BANDEDGE MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	7.2

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	7.2

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	26deg. C, 58%RH	120Vac, 60Hz	Kay Wu
RE<1G	26deg. C, 58%RH	120Vac, 60Hz	Kay Wu
PLC	26deg. C, 65%RH	120Vac, 60Hz	David Huang
APCM	25deg. C, 65%RH	120Vac, 60Hz	Phoenix Chen



### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Earphone	DONGMEI	D-D606	NA	NA
2	Wireless charger Cradle	NTT docomo	AAF39571	NA	NA


NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.32m non-shielded cable without core
2	NA

**NOTE:**


1. All power cords of the above support units are non-shielded (1.8 m).
2. Item 1, 2 were provided by client.

### 3.3.1 CONFIGURATION OF SYSTEM UNDER TEST

#### For Radiated Emissions Test



#### For AC Power Conducted Emission



### 3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**558074 D01 DTS Meas Guidance v01**

**ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



## 4. TEST TYPES AND RESULTS

### 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver Agilent	N9038A	MY51210203	Dec. 22, 2011	Dec. 21, 2012
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 21, 2011	Dec. 20, 2012
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 20, 2011	Dec. 19, 2012
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Dec. 20, 2011	Dec. 19, 2012
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 20, 2011	Dec. 19, 2012
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier EMCI	EMC 012645	980115	Dec. 30, 2011	Dec. 29, 2012
Preamplifier EMCI	EMC 330H	980112	Dec. 30, 2011	Dec. 29, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4	Oct. 21, 2011	Oct. 20, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Jan. 02, 2012	Jan. 01, 2013
RF signal cable Worken	RG-213	NA	Jan. 02, 2012	Jan. 01, 2013
Software	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
High Speed Peak Power Meter	ML2495A	0842014	Apr. 28, 2012	Apr. 27, 2013
Power Sensor	MA2411B	0738404	Apr. 28, 2012	Apr. 27, 2013

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.  
3. The test was performed in HwaYa Chamber 9.  
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.  
5. The FCC Site Registration No. is 460141.  
6. The IC Site Registration No. is IC 7450F-4.



A D T

#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


##### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 100kHz and video bandwidth is 300kHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



A D T

#### 4.1.7 TEST RESULTS


##### ABOVE 1GHz WORST-CASE DATA : 802.11b



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5  
Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF HORIZONTAL  
Brand/Model: F-03E  
Remark : 11B TX CH01  
Tested by : Kay Wu  
Temprature : 25°C  
Humidity : 65%  
Plane : Cradle  
Rate : 1M  
Power : 9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2390.00	35.44	40.83	54.00	-18.56	27.26	4.87	37.52	103	238 Average
2	2390.00	51.12	56.51	74.00	-22.88	27.26	4.87	37.52	103	238 Peak
3 pp	2412.00	95.44	100.78			27.31	4.87	37.52	103	238 Average
4 pk	2412.00	99.38	104.72			27.31	4.87	37.52	103	238 Peak
5	2488.00	35.14	39.99	54.00	-18.86	27.55	4.92	37.32	103	238 Average
6	2488.00	51.65	56.50	74.00	-22.35	27.55	4.92	37.32	103	238 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF VERTICAL

Brand/Model: F-03E

Remark : 11B TX CH01

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : 1M

Power : 9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
1	2388.00	35.02	40.41	54.00	-18.98	27.26	4.85	37.50	122	211 Average
2	2388.00	51.42	56.81	74.00	-22.58	27.26	4.85	37.50	122	211 Peak
3 pp	2412.00	94.05	99.39			27.31	4.87	37.52	122	211 Average
4 pk	2412.00	98.07	103.41			27.31	4.87	37.52	122	211 Peak
5	2496.00	35.03	39.79	54.00	-18.97	27.55	4.94	37.25	122	211 Average
6	2496.00	51.76	56.52	74.00	-22.24	27.55	4.94	37.25	122	211 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5  
Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF HORIZONTAL  
Brand/Model: F-03E  
Remark : 11B TX CH06  
Tested by : Kay Wu  
Temprature : 25°C  
Humidity : 65%  
Plane : Cradle  
Rate : 1M  
Power : 9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2356.00	34.60	40.11	54.00	-19.40	27.16	4.82	37.49	132	241 Average
2	2356.00	51.97	57.48	74.00	-22.03	27.16	4.82	37.49	132	241 Peak
3 pp	2437.00	96.77	101.94			27.40	4.89	37.46	132	241 Average
4 pk	2437.00	100.52	105.69			27.40	4.89	37.46	132	241 Peak
5	2496.00	36.26	41.02	54.00	-17.74	27.55	4.94	37.25	132	241 Average
6	2496.00	52.41	57.17	74.00	-21.59	27.55	4.94	37.25	132	241 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF VERTICAL

Brand/Model: F-03E

Remark : 11B TX CH06

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : 1M

Power : 9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2380.00	34.69	40.13	54.00	-19.31	27.21	4.85	37.50	100	212 Average
2	2380.00	51.31	56.75	71.00	-22.69	27.21	4.85	37.50	100	212 Peak
3 pp	2437.00	93.49	98.66			27.40	4.89	37.46	100	212 Average
4 pk	2437.00	97.25	102.42			27.40	4.89	37.46	100	212 Peak
5	2492.00	35.34	40.10	54.00	-18.66	27.55	4.94	37.25	100	212 Average
6	2492.00	51.24	56.00	74.00	-22.76	27.55	4.94	37.25	100	212 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF HORIZONTAL

Brand/Model: F-03E

Remark : 11B TX CH11

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : 1M

Power : 9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Freq	Level	Line	Limit Factor	Loss	Factor	dB	cm	
1	2368.00	34.68	40.17	54.00	-19.32	27.16	4.85	37.50	126	240 Average
2	2368.00	51.65	57.14	74.00	-22.35	27.16	4.85	37.50	126	240 Peak
3 pp	2462.00	96.45	101.48			27.45	4.91	37.39	126	240 Average
4 pk	2462.00	100.58	105.61			27.45	4.91	37.39	126	240 Peak
5	2486.00	37.32	42.22	54.00	-16.68	27.50	4.92	37.32	126	240 Average
6	2486.00	52.32	57.22	74.00	-21.68	27.50	4.92	37.32	126	240 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF VERTICAL

Brand/Model: F-03E

Remark : 11B TX CH11

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : 1M

Power : 9

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg
1	2364.00	34.49	40.00	54.00	-19.51	27.16	4.82	37.49	121	211 Average
2	2364.00	51.39	56.90	74.00	-22.61	27.16	4.82	37.49	121	211 Peak
3 pp	2462.00	93.44	98.47			27.45	4.91	37.39	121	211 Average
4 pk	2462.00	97.45	102.48			27.45	4.91	37.39	121	211 Peak
5	2494.00	36.03	40.79	54.00	-17.97	27.55	4.94	37.25	121	211 Average
6	2494.00	52.15	56.91	74.00	-21.85	27.55	4.94	37.25	121	211 Peak



A D T


## 802.11g



A D T

Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

Data: 19



Site : 966 Chamber 5  
Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF HORIZONTAL  
Brand/Model: F-03E  
Remark : 11G TX CH01  
Tested by : Kay Wu  
Temprature : 25°C  
Humidity : 65%  
Plane : Cradle  
Rate : 6M  
Power : 8

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2390.00	42.36	47.75	54.00	-11.64	27.26	4.87	37.52	130	240 Average
2	2390.00	60.41	65.80	74.00	-13.59	27.26	4.87	37.52	130	240 Peak
3 pp	2412.00	90.86	96.20			27.31	4.87	37.52	130	240 Average
4 pk	2412.00	101.57	106.91			27.31	4.87	37.52	130	240 Peak
5	2490.00	35.48	40.33	54.00	-18.52	27.55	4.92	37.32	130	240 Average
6	2490.00	52.23	57.08	74.00	-21.77	27.55	4.92	37.32	130	240 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF VERTICAL

Brand/Model: F-03E

Remark : 11G TX CH01

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : 6M

Power : 8

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor			
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2390.00	38.89	44.28	54.00	-15.11	27.26	4.87	37.52	100	210 Average
2	2390.00	57.99	63.38	74.00	-16.01	27.26	4.87	37.52	100	210 Peak
3 pp	2412.00	86.40	91.74			27.31	4.87	37.52	100	210 Average
4 pk	2412.00	96.54	101.88			27.31	4.87	37.52	100	210 Peak
5	2486.00	34.97	39.87	54.00	-19.03	27.50	4.92	37.32	100	210 Average
6	2486.00	51.42	56.32	74.00	-22.58	27.50	4.92	37.32	100	210 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF HORIZONTAL

Brand/Model: F-03E

Remark : 11G TX CH06

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : 6M

Power : 8

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg
1	2386.00	34.86	40.25	54.00	-19.14	27.26	4.85	37.50	129	241 Average
2	2386.00	51.15	56.54	74.00	-22.85	27.26	4.85	37.50	129	241 Peak
3 pp	2437.00	90.24	95.41			27.40	4.89	37.46	129	241 Average
4 pk	2437.00	100.75	105.92			27.40	4.89	37.46	129	241 Peak
5	2490.00	39.13	43.98	54.00	-14.87	27.55	4.92	37.32	129	241 Average
6	2490.00	53.12	57.97	74.00	-20.88	27.55	4.92	37.32	129	241 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF VERTICAL

Brand/Model: F-03E

Remark : 11G TX CH06

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : 6M

Power : 8

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor			
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2370.00	34.57	40.01	54.00	-19.43	27.21	4.85	37.50	100	210 Average
2	2370.00	50.83	56.27	74.00	-23.17	27.21	4.85	37.50	100	210 Peak
3 pp	2437.00	85.93	91.10			27.40	4.89	37.46	100	210 Average
4 pk	2437.00	96.11	101.28			27.40	4.89	37.46	100	210 Peak
5	2492.00	36.25	41.01	54.00	-17.75	27.55	4.94	37.25	100	210 Average
6	2492.00	51.19	55.95	74.00	-22.81	27.55	4.94	37.25	100	210 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5  
Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF HORIZONTAL  
Brand/Model: F-03E  
Remark : 11G TX CH11  
Tested by : Kay Wu  
Temprature : 25°C  
Humidity : 65%  
Plane : Cradle  
Rate : 6M  
Power : 8

Freq	Level	Read	Limit	OverAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Freq	Level	Line	Limit Factor	Cable	Preamp	A/Pos	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg
1	2368.00	34.70	40.19	54.00	-19.30	27.16	4.85	37.50	127 237 Average
2	2368.00	51.47	56.96	74.00	-22.53	27.16	4.85	37.50	127 237 Peak
3 pp	2462.00	90.98	96.01			27.45	4.91	37.39	127 237 Average
4 pk	2462.00	101.00	106.03			27.45	4.91	37.39	127 237 Peak
5	2484.00	45.49	50.39	54.00	-8.51	27.50	4.92	37.32	127 237 Average
6	2484.00	62.68	67.58	74.00	-11.32	27.50	4.92	37.32	127 237 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF VERTICAL

Brand/Model: F-03E

Remark : 11G TX CH11

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : 6M

Power : 8

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Freq	Level	Line	Limit Factor	Loss	Factor	dB	cm	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2372.00	34.61	40.05	54.00	-19.39	27.21	4.85	37.50	119	212 Average
2	2372.00	51.74	57.18	74.00	-22.26	27.21	4.85	37.50	119	212 Peak
3 pp	2462.00	86.52	91.55			27.45	4.91	37.39	119	212 Average
4 pk	2462.00	96.64	101.67			27.45	4.91	37.39	119	212 Peak
5	2484.00	42.22	47.12	54.00	-11.78	27.50	4.92	37.32	119	212 Average
6	2484.00	60.20	65.10	74.00	-13.80	27.50	4.92	37.32	119	212 Peak



A D T

## 802.11n(20MHz)




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19

Level (dBuV/m)

Date: 2012-10-03



Site : 966 Chamber 5  
Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF HORIZONTAL  
Brand/Model: F-03E  
Remark : 11N\_HT20 CH01  
Tested by : Kay Wu  
Temprature : 25°C  
Humidity : 65%  
Plane : Cradle  
Rate : MCS0  
Power : 4

Freq	Read Level	Limit Level	OverLine	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	
									MHz	dBuV/m
1	2390.00	36.68	42.07	54.00	-17.32	27.26	4.87	37.52	102	224 Average
2	2390.00	53.85	59.24	74.00	-20.15	27.26	4.87	37.52	102	224 Peak
3 pp	2412.00	84.49	89.83			27.31	4.87	37.52	102	224 Average
4 pk	2412.00	94.69	100.03			27.31	4.87	37.52	102	224 Peak
5	2498.00	35.32	40.08	54.00	-18.68	27.55	4.94	37.25	102	224 Average
6	2498.00	51.16	55.92	74.00	-22.84	27.55	4.94	37.25	102	224 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF VERTICAL

Brand/Model: F-03E

Remark : 11N\_HT20 CH01

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : MCS0

Power : 4

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
1	2390.00	35.56	40.95	54.00	-18.44	27.26	4.87	37.52	120	219 Average
2	2390.00	51.83	57.22	74.00	-22.17	27.26	4.87	37.52	120	219 Peak
3 pp	2412.00	82.52	87.86			27.31	4.87	37.52	120	219 Average
4 pk	2412.00	92.72	98.06			27.31	4.87	37.52	120	219 Peak
5	2500.00	35.03	39.79	54.00	-18.97	27.55	4.94	37.25	120	219 Average
6	2500.00	51.96	56.72	74.00	-22.04	27.55	4.94	37.25	120	219 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF HORIZONTAL

Brand/Model: F-03E

Remark : 11N\_HT20 CH06

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : MCS0

Power : 4

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Freq	Level	Line	Limit Factor	Loss	Factor	dB	cm	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2372.00	34.56	40.00	54.00	-19.44	27.21	4.85	37.50	132	238 Average
2	2372.00	50.89	56.33	74.00	-23.11	27.21	4.85	37.50	132	238 Peak
3 pp	2437.00	84.84	90.01			27.40	4.89	37.46	132	238 Average
4 pk	2437.00	96.06	101.23			27.40	4.89	37.46	132	238 Peak
5	2498.00	36.71	41.47	54.00	-17.29	27.55	4.94	37.25	132	238 Average
6	2498.00	51.63	56.39	74.00	-22.37	27.55	4.94	37.25	132	238 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF VERTICAL

Brand/Model: F-03E

Remark : 11N\_HT20 CH06

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : MCS0

Power : 4

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Freq	Level	Line	Limit Factor	Loss	Factor	dB	cm	
1	2324.00	34.35	39.97	54.00	-19.65	27.06	4.79	37.47	121	210 Average
2	2324.00	51.21	56.83	74.00	-22.79	27.06	4.79	37.47	121	210 Peak
3 pp	2437.00	81.64	86.81			27.40	4.89	37.46	121	210 Average
4 pk	2437.00	92.01	97.18			27.40	4.89	37.46	121	210 Peak
5	2492.00	36.04	40.80	54.00	-17.96	27.55	4.94	37.25	121	210 Average
6	2492.00	51.56	56.32	74.00	-22.44	27.55	4.94	37.25	121	210 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 19



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF HORIZONTAL

Brand/Model: F-03E

Remark : 11N\_HT20 CH11

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : MCS0

Power : 5

Freq	Level	Read	Limit	OverAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit Factor	Loss	Factor	cm	deg	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg
1	2358.00	34.70	40.21	54.00	-19.30	27.16	4.82	37.49	100 226 Average
2	2358.00	51.46	56.97	74.00	-22.54	27.16	4.82	37.49	100 226 Peak
3 pp	2462.00	85.97	91.00			27.45	4.91	37.39	100 226 Average
4 pk	2462.00	96.02	101.05			27.45	4.91	37.39	100 226 Peak
5	2483.50	39.71	44.61	54.00	-14.29	27.50	4.92	37.32	100 226 Average
6	2483.50	57.67	62.57	74.00	-16.33	27.50	4.92	37.32	100 226 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 20



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_18G~40G\_HF VERTICAL

Brand/Model: F-03E

Remark : 11N\_HT20 CH11

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cradle

Rate : MCS0

Power : 5

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	cm	deg	
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg
1	2386.00	34.60	39.99	54.00	-19.40	27.26	4.85	37.50	108	281 Average
2	2386.00	51.89	57.28	74.00	-22.11	27.26	4.85	37.50	108	281 Peak
3 pp	2462.00	83.71	88.74			27.45	4.91	37.39	108	281 Average
4 pk	2462.00	93.75	98.78			27.45	4.91	37.39	108	281 Peak
5	2483.50	38.34	43.24	54.00	-15.66	27.50	4.92	37.32	108	281 Average
6	2483.50	54.40	59.30	74.00	-19.60	27.50	4.92	37.32	108	281 Peak



A D T


**BELOW 1GHz WORST-CASE DATA : 802.11g**



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5  
Condition : FCC CLASS-B 3m ANT\_30M~1G\_LF HORIZONTAL  
Brand/Model: F-03E  
Remark : WIFI TX LF  
Tested by : Kay Wu  
Temprature : 25°C  
Humidity : 65%  
Plane : Cardle

Freq	Level	Read	Limit	OverAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
		Level	Line	Limit Factor	Loss	Factor				
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1 pp	42.42	24.70	41.50	40.00	-15.30	13.58	0.70	31.08	120	231 Peak
2	95.88	25.12	47.27	43.50	-18.38	8.76	1.05	31.96	102	225 Peak
3	232.50	17.20	36.54	46.00	-28.80	10.75	1.75	31.84	102	332 Peak
4	367.20	18.57	33.64	46.00	-27.43	14.56	2.30	31.93	220	215 Peak
5	568.10	22.29	32.49	46.00	-23.71	18.88	3.00	32.08	110	12 Peak
6	698.30	24.97	32.54	46.00	-21.03	20.80	3.43	31.80	132	223 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT\_30M~1G\_LF VERTICAL

Brand/Model: F-03E

Remark : WIFI TX LF

Tested by : Kay Wu

Temprature : 25°C

Humidity : 65%

Plane : Cardle

Freq	Level	Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Level	Line	Limit	Factor	Loss	Factor	dB	cm	
MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1 pp	30.27	31.91	50.50	40.00	-8.09	11.98	0.57	31.14	133	220 Peak
2	42.42	31.76	48.56	40.00	-8.24	13.58	0.70	31.08	142	222 Peak
3	76.44	28.50	50.08	40.00	-11.50	9.09	0.95	31.62	156	220 Peak
4	402.90	18.61	32.88	46.00	-27.39	15.39	2.43	32.09	100	0 Peak
5	561.10	21.77	32.13	46.00	-24.23	18.72	2.98	32.06	100	133 Peak
6	667.50	25.27	33.39	46.00	-20.73	20.42	3.31	31.85	100	205 Peak



A D T

## 4.2 CONDUCTED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

**NOTE:** 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Nov. 19, 2011	Nov. 18, 2012
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 29, 2011	Dec. 28, 2012
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 30, 2011	Dec. 29, 2012
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 06, 2012	Jul. 05, 2013
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations

are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.

3. The VCCI Site Registration No. is C-2047.

#### 4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

#### 4.2.7 TEST RESULTS


##### CONDUCTED WORST-CASE DATA : 802.11g

PHASE		Line 1		6dB BANDWIDTH		9kHz	
-------	--	--------	--	---------------	--	------	--

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.34922	0.16	43.58	35.41	43.74	35.57	58.98	48.98	-15.24	-13.41
2	0.50000	0.17	38.39	25.70	38.56	25.87	56.00	46.00	-17.44	-20.13
3	0.91172	0.19	39.79	28.66	39.98	28.85	56.00	46.00	-16.02	-17.15
4	2.00781	0.26	48.01	35.57	48.27	35.83	56.00	46.00	-7.73	-10.17
5	3.51172	0.32	40.54	29.37	40.86	29.69	56.00	46.00	-15.14	-16.31
6	13.55859	0.50	55.22	48.40	55.72	48.90	60.00	50.00	-4.28	-1.10

##### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH		9kHz	
-------	--------	---------------	--	------	--

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	Q.P.	AV.	Q.P.	AV.
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.19687	0.14	38.20	30.32	38.34	30.46	63.74	53.74	-25.40	-23.28
2	0.23203	0.14	32.88	15.57	33.02	15.71	62.38	52.38	-29.35	-36.66
3	0.53281	0.17	36.60	27.42	36.77	27.59	56.00	46.00	-19.23	-18.41
4	0.88828	0.18	39.99	27.44	40.17	27.62	56.00	46.00	-15.83	-18.38
5	1.83203	0.25	48.91	35.69	49.16	35.94	56.00	46.00	-6.84	-10.06
6	13.55859	0.57	54.36	47.30	54.93	47.87	60.00	50.00	-5.07	-2.13

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST SETUP



#### 4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 TEST PROCEDURE

- a. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

#### 4.3.7 TEST RESULTS

##### 802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.58	0.5	PASS
6	2437	8.11	0.5	PASS
11	2462	8.57	0.5	PASS

##### 802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.51	0.5	PASS
6	2437	16.57	0.5	PASS
11	2462	16.52	0.5	PASS

##### 802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.68	0.5	PASS
6	2437	17.77	0.5	PASS
11	2462	17.80	0.5	PASS

## 4.4 CONDUCTED OUTPUT POWER

### 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

### 4.4.2 TEST SETUP



### 4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.



A D T

#### 4.4.7 TEST RESULTS

##### 802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	51.523	17.12	30	PASS
6	2437	58.345	17.66	30	PASS
11	2462	48.641	16.87	30	PASS

##### 802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	105.682	20.24	30	PASS
6	2437	122.180	20.87	30	PASS
11	2462	91.833	19.63	30	PASS

##### 802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	66.374	18.22	30	PASS
6	2437	76.560	18.84	30	PASS
11	2462	81.283	19.10	30	PASS

## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 TEST PROCEDURE

- a. Set the RBW = 100 kHz, VBW =300 kHz, Detector = peak.
- b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
- d. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where  $BWCF = 10\log(3 \text{ kHz}/100\text{kHz})$

### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6



A D T

#### 4.5.7 TEST RESULTS

##### 802.11b

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	6.31	-8.89	8	PASS
6	2437	6.78	-8.42	8	PASS
11	2462	6.07	-9.13	8	PASS

##### 802.11g

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	0.46	-14.74	8	PASS
6	2437	0.86	-14.34	8	PASS
11	2462	0.42	-14.78	8	PASS

##### 802.11n (20MHz)


Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-3.46	-18.66	8	PASS
6	2437	-3.29	-18.49	8	PASS
11	2462	-2.48	-17.68	8	PASS

## 4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

### 4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST SETUP



### 4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 TEST PROCEDURE

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



A D T

## MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

### 4.6.7 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.




A D T


## 4.6.8 TEST RESULTS

### 802.11b


#### CH 1



#### CH 6



#### CH 11







A D T

## 802.11g


### CH 1



### CH 6



### CH 11







A D T

## 802.11n (20MHz)


### CH 1



### CH 6



### CH 11





A D T

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180  
Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab**

Tel: 886-3-3183232  
Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.



A D T

## 7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---