

# FCC Test Report

**FCC ID** : VQK-F05F  
**Equipment** : Mobile Phone  
**Model No.** : F-05F  
**Brand Name** : FUJITSU  
**Applicant** : FUJITSU LIMITED  
**Address** : 1-1, Kamikodanaka 4-chome, Nakahara-ku,  
Kawasaki 211-8588, Japan  
**Standard** : 47 CFR FCC Part 15.247  
**Received Date** : Dec. 25, 2013  
**Tested Date** : Mar. 03 ~ Mar. 05, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



---

Gary Chang / Manager



## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Local Support Equipment List .....	7
1.3	Test Setup Chart .....	7
1.4	The Equipment List .....	8
1.5	Test Standards .....	9
1.6	Measurement Uncertainty .....	9
<b>2</b>	<b>TEST CONFIGURATION.....</b>	<b>10</b>
2.1	Testing Condition .....	10
2.2	The Worst Test Modes and Channel Details .....	10
<b>3</b>	<b>TRANSMITTER TEST RESULTS.....</b>	<b>11</b>
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth .....	14
3.3	RF Output Power.....	16
3.4	Power Spectral Density .....	18
3.5	Unwanted Emissions into Restricted Frequency Bands .....	20
3.6	Unwanted Emissions into Non-Restricted Frequency Bands .....	30
<b>4</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>33</b>

## Release Record

Report No.	Version	Description	Issued Date
FR3D2502AE	Rev. 01	Initial issue	Mar. 20, 2014

## Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.154MHz 46.40 (Margin -9.38dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 41.64MHz 34.25 (Margin -5.75dB) - PK	Pass
15.247(b)(3)	Fundamental Emission Output Power	Power [dBm]: 1.41	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

## 1 General Description

### 1.1 Information

#### 1.1.1 Product Details

Product Name	Mobile Phone
Brand Name	FUJITSU
Model Name	F-05F
IMEI Code	359401050022851, 359401050022695
H/W Version	V2.1.0
S/W Version	R18Ae

#### 1.1.2 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Freq. (MHz)	Channel Number	Data Rate
2400-2483.5	BT LE	2402-2480	0-39 [40]	1 Mbps

#### 1.1.3 Antenna Details

Type	Gain (dBi)	Connector	Remark
$\lambda/4$ Monopole	-6.8	---	---

#### 1.1.4 EUT Operational Condition

Power Supply Type	Battery: 3.75Vdc / 3200mAh Adapter: DC5.0V 1.8A, DC9.0V 1.8A
-------------------	---

#### 1.1.5 Accessories

Accessories		
No.	Equipment	Description
1	Battery (Built-in battery)	Brand Name: Panasonic Model Name: CA54310-0052 Power Rating: O/P: 3.75Vdc, 3200mA

### 1.1.6 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
37	2402	18	2442
0	2404	19	2444
1	2406	20	2446
2	2408	21	2448
3	2410	22	2450
4	2412	23	2452
5	2414	24	2454
6	2416	25	2456
7	2418	26	2458
8	2420	27	2460
9	2422	28	2462
10	2424	29	2464
38	2426	30	2466
11	2428	31	2468
12	2430	32	2470
13	2432	33	2472
14	2434	34	2474
15	2436	35	2476
16	2438	36	2478
17	2440	39	2480

### 1.1.7 Test Tool and Power Setting


Test tool	QRCT, Ver 3.0.7.0		
Modulation Mode	<b>Test Frequency (MHz)</b>		
	<b>2402</b>	<b>2440</b>	<b>2480</b>
GFSK/1Mbps	Default	Default	Default

## 1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	Adapter	NTT docomo	AC Adaptor 05	---	---	1.2m non-shielded with 2 cores
2	Earphone	Apple	MD827FE/A	---	---	1.2m non-shielded w/o core

Note: Item 1 was provided by client.

## 1.3 Test Setup Chart



## 1.4 The Equipment List

<b>Test Item</b>	Radiated Emission				
<b>Test Site</b>	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Jan. 25, 2014	Jan. 24, 2015
Receiver	R&S	ESR3	101658	Jan. 10, 2014	Jan. 09, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jan. 02, 2014	Jan. 01, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Feb. 13, 2014	Feb. 12, 2015
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014
Preamplifier	Burgeon	BPA-530	SN:100219	Nov. 22, 2013	Nov. 21, 2014
Preamplifier	Agilent	83017A	MY39501308	Dec. 16, 2013	Dec. 15, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 16, 2013	Dec. 15, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 16, 2013	Dec. 15, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 16, 2013	Dec. 15, 2014
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 16, 2013	Dec. 15, 2014
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 16, 2013	Dec. 15, 2014

Note: Calibration Interval of instruments listed above is one year.

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
Preamplifier	EM	EM18G40G	060572	Jun. 20, 2013	Jun. 19, 2014
Note: Calibration Interval of instruments listed above is two year.					

<b>Test Item</b>	RF Conducted				
<b>Test Site</b>	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2014	Feb. 16, 2015
Power Meter	Anritsu	ML2495A	1241002	Oct. 24, 2013	Oct. 23, 2014
Power Sensor	Anritsu	MA2411B	1207366	Oct. 24, 2013	Oct. 23, 2014

Note: Calibration Interval of instruments listed above is one year.

<b>Test Item</b>	Conducted Emission				
<b>Test Site</b>	Conduction room 1 / (CO01-WS)				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 24, 2013	Apr. 23, 2014
50 ohm terminal (Support Unit)	NA	50	04	Apr. 22, 2013	Apr. 21, 2014

Note: Calibration Interval of instruments listed above is one year.

## 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2009

FCC KDB 558074 D01 DTS Meas Guidance v03r01

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±35.286 Hz
Conducted power	±0.536 dB
Frequency error	±35.286 Hz
Temperature	±0.3 °C
Conducted emission	±2.946 dB
AC conducted emission	±2.43 dB
Radiated emission	±2.49 dB

## 2 Test Configuration

### 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	13°C / 60%	Skys Huang
Radiated Emissions	03CH01-WS	23°C / 64%	Brad Wu / Haru Yang
RF Conducted	TH01-WS	22°C / 64%	Felix Sung

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-1

### 2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data rate (Mbps)	Test Configuration
AC Power Line Conducted Emissions	BT LE	2402	1Mbps	---
Radiated Emissions ≤ 1GHz	BT LE	2402	1Mbps	---
Radiated Emissions > 1GHz	BT LE	2402 / 2440 / 2480	1Mbps	---
Fundamental Emission Output Power	BT LE	2402 / 2440 / 2480	1Mbps	---
6dB bandwidth				
Power spectral density				

**NOTE:**

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Z-plane** results were found as the worst case and were shown in this report.

## 3 Transmitter Test Results

### 3.1 Conducted Emissions

#### 3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.

#### 3.1.2 Test Procedures


1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


#### 3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.4 Test Result of Conducted Emissions





## 3.2 6dB and Occupied Bandwidth


### 3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

### 3.2.2 Test Procedures


1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

### 3.2.3 Test Setup



### 3.2.4 Test Result of 6dB and Occupied Bandwidth

Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.670	1.06	500
BT LE	2440	0.670	1.06	500
BT LE	2480	0.674	1.06	500



### 3.3 RF Output Power

#### 3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.

- Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.
- Antenna gain > 6dBi
  - Non Fixed, point to point operations.  
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
  - Fixed, point to point operations  
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.  
Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

#### 3.3.2 Test Procedures

- Maximum Peak Conducted Output Power
  - Spectrum analyzer**
    1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
    2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
    3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
  - Power meter**
    1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Output Power ( For reference only )
  - Spectrum analyzer**
    1. Set RBW = 1MHz, VBW = 3MHz, Detector = RMS.
    2. Set the sweep time to:  $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$ .
    3. Perform the measurement over a single sweep.
    4. Use the spectrum analyzer's band power measurement function with band limits set equal to the EBW(26dBc) band edges.
  - Power meter**
    1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

### 3.3.3 Test Setup



### 3.3.4 Test Result of Maximum Output Power

Mode	Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)
BT LE	2402	1.371	1.37	30
BT LE	2440	1.384	1.41	30
BT LE	2480	1.081	0.34	30

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	1.321	1.21	30
BT LE	2440	1.327	1.23	30
BT LE	2480	1.045	0.19	30

Note: Average power is for reference only

## 3.4 Power Spectral Density


### 3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

### 3.4.2 Test Procedures


- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
  1. Set the RBW = 3kHz, VBW = 10kHz.
  2. Detector = Peak, Sweep time = auto couple.
  3. Trace mode = max hold, allow trace to fully stabilize.
  4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
  1. Set the RBW = 10kHz, VBW = 30 kHz.
  2. Detector = RMS, Sweep time = auto couple.
  3. Set the sweep time to:  $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$ .
  4. Perform the measurement over a single sweep.
  5. Use the peak marker function to determine the maximum amplitude level.\

### 3.4.3 Test Setup



### 3.4.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BT LE	2402	-13.70	8
BT LE	2440	-13.63	8
BT LE	2480	-14.82	8



## 3.5 Unwanted Emissions into Restricted Frequency Bands

### 3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

**Note 1:**  
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

### 3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

### 3.5.3 Test Setup


#### Radiated Emissions below 1 GHz




#### Radiated Emissions above 1 GHz



### 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2440																																																																																	
Polarization	Horizontal																																																																																			
																																																																																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding-bottom: 2px;">Freq.</th> <th style="text-align: left; padding-bottom: 2px;">Emission</th> <th style="text-align: left; padding-bottom: 2px;">Limit</th> <th style="text-align: left; padding-bottom: 2px;">Margin</th> <th style="text-align: left; padding-bottom: 2px;">SA</th> <th style="text-align: left; padding-bottom: 2px;">Factor</th> <th style="text-align: left; padding-bottom: 2px;">Remark</th> <th style="text-align: left; padding-bottom: 2px;">ANT</th> <th style="text-align: left; padding-bottom: 2px;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th>dBuV</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>85.29</td> <td>26.70</td> <td>40.00</td> <td>-13.30</td> <td>49.04</td> <td>-22.34</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>2</td> <td>130.88</td> <td>31.22</td> <td>43.50</td> <td>-12.28</td> <td>49.42</td> <td>-18.20</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>307.42</td> <td>22.29</td> <td>46.00</td> <td>-23.71</td> <td>38.27</td> <td>-15.98</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>4</td> <td>520.82</td> <td>22.75</td> <td>46.00</td> <td>-23.25</td> <td>33.95</td> <td>-11.20</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>835.10</td> <td>25.25</td> <td>46.00</td> <td>-20.75</td> <td>31.59</td> <td>-6.34</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>6</td> <td>965.08</td> <td>27.45</td> <td>54.00</td> <td>-26.55</td> <td>32.04</td> <td>-4.59</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dBuV/m	dB	reading	reading	High	Table						dBuV	dB	cm	deg	1	85.29	26.70	40.00	-13.30	49.04	-22.34	Peak	---	2	130.88	31.22	43.50	-12.28	49.42	-18.20	Peak	---	3	307.42	22.29	46.00	-23.71	38.27	-15.98	Peak	---	4	520.82	22.75	46.00	-23.25	33.95	-11.20	Peak	---	5	835.10	25.25	46.00	-20.75	31.59	-6.34	Peak	---	6	965.08	27.45	54.00	-26.55	32.04	-4.59	Peak	---
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																												
MHz	level	dBuV/m	dBuV/m	dB	reading	reading	High	Table																																																																												
					dBuV	dB	cm	deg																																																																												
1	85.29	26.70	40.00	-13.30	49.04	-22.34	Peak	---																																																																												
2	130.88	31.22	43.50	-12.28	49.42	-18.20	Peak	---																																																																												
3	307.42	22.29	46.00	-23.71	38.27	-15.98	Peak	---																																																																												
4	520.82	22.75	46.00	-23.25	33.95	-11.20	Peak	---																																																																												
5	835.10	25.25	46.00	-20.75	31.59	-6.34	Peak	---																																																																												
6	965.08	27.45	54.00	-26.55	32.04	-4.59	Peak	---																																																																												
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.																																																																																				




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK


Modulation	GFSK	Test Freq. (MHz)	2402																																																																								
Polarization	Horizontal																																																																										
																																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding-bottom: 2px;">Freq.</th> <th style="text-align: left; padding-bottom: 2px;">Emission</th> <th style="text-align: left; padding-bottom: 2px;">Limit</th> <th style="text-align: left; padding-bottom: 2px;">Margin</th> <th style="text-align: left; padding-bottom: 2px;">SA</th> <th style="text-align: left; padding-bottom: 2px;">Factor</th> <th style="text-align: left; padding-bottom: 2px;">Remark</th> <th style="text-align: left; padding-bottom: 2px;">ANT</th> <th style="text-align: left; padding-bottom: 2px;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dBuV</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> </thead> <tbody> <tr> <td style="text-align: left;">1</td> <td style="text-align: left;">1594.00</td> <td style="text-align: left;">25.15</td> <td style="text-align: left;">54.00</td> <td style="text-align: left;">-28.85</td> <td style="text-align: left;">31.96</td> <td style="text-align: left;">-6.81</td> <td style="text-align: left;">Average</td> <td style="text-align: left;">---</td> </tr> <tr> <td style="text-align: left;">2</td> <td style="text-align: left;">1594.00</td> <td style="text-align: left;">39.43</td> <td style="text-align: left;">74.00</td> <td style="text-align: left;">-34.57</td> <td style="text-align: left;">46.24</td> <td style="text-align: left;">-6.81</td> <td style="text-align: left;">Peak</td> <td style="text-align: left;">---</td> </tr> <tr> <td style="text-align: left;">3</td> <td style="text-align: left;">2390.00</td> <td style="text-align: left;">27.25</td> <td style="text-align: left;">54.00</td> <td style="text-align: left;">-26.75</td> <td style="text-align: left;">30.93</td> <td style="text-align: left;">-3.68</td> <td style="text-align: left;">Average</td> <td style="text-align: left;">---</td> </tr> <tr> <td style="text-align: left;">4</td> <td style="text-align: left;">2390.00</td> <td style="text-align: left;">45.07</td> <td style="text-align: left;">74.00</td> <td style="text-align: left;">-28.93</td> <td style="text-align: left;">48.75</td> <td style="text-align: left;">-3.68</td> <td style="text-align: left;">Peak</td> <td style="text-align: left;">---</td> </tr> <tr> <td style="text-align: left;">5</td> <td style="text-align: left;">4804.00</td> <td style="text-align: left;">34.22</td> <td style="text-align: left;">54.00</td> <td style="text-align: left;">-19.78</td> <td style="text-align: left;">29.26</td> <td style="text-align: left;">4.96</td> <td style="text-align: left;">Average</td> <td style="text-align: left;">---</td> </tr> <tr> <td style="text-align: left;">6</td> <td style="text-align: left;">4804.00</td> <td style="text-align: left;">45.73</td> <td style="text-align: left;">74.00</td> <td style="text-align: left;">-28.27</td> <td style="text-align: left;">40.77</td> <td style="text-align: left;">4.96</td> <td style="text-align: left;">Peak</td> <td style="text-align: left;">---</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dBuV	Factor	High	Table	1	1594.00	25.15	54.00	-28.85	31.96	-6.81	Average	---	2	1594.00	39.43	74.00	-34.57	46.24	-6.81	Peak	---	3	2390.00	27.25	54.00	-26.75	30.93	-3.68	Average	---	4	2390.00	45.07	74.00	-28.93	48.75	-3.68	Peak	---	5	4804.00	34.22	54.00	-19.78	29.26	4.96	Average	---	6	4804.00	45.73	74.00	-28.27	40.77	4.96	Peak	---
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																			
MHz	level	dBuV/m	dB	reading	dBuV	Factor	High	Table																																																																			
1	1594.00	25.15	54.00	-28.85	31.96	-6.81	Average	---																																																																			
2	1594.00	39.43	74.00	-34.57	46.24	-6.81	Peak	---																																																																			
3	2390.00	27.25	54.00	-26.75	30.93	-3.68	Average	---																																																																			
4	2390.00	45.07	74.00	-28.93	48.75	-3.68	Peak	---																																																																			
5	4804.00	34.22	54.00	-19.78	29.26	4.96	Average	---																																																																			
6	4804.00	45.73	74.00	-28.27	40.77	4.96	Peak	---																																																																			
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																																											



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2440																																																																								
<b>Polarization</b>	Horizontal																																																																										
																																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Freq.</th> <th style="text-align: left;">Emission</th> <th style="text-align: left;">Limit</th> <th style="text-align: left;">Margin</th> <th style="text-align: left;">SA</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">Remark</th> <th style="text-align: left;">ANT</th> <th style="text-align: left;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dB</th> <th></th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1594.00</td> <td>25.66</td> <td>54.00</td> <td>-28.34</td> <td>32.47</td> <td>-6.81</td> <td>Average</td> <td>---</td> </tr> <tr> <td>2</td> <td>1594.00</td> <td>39.21</td> <td>74.00</td> <td>-34.79</td> <td>46.02</td> <td>-6.81</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>4880.00</td> <td>34.62</td> <td>54.00</td> <td>-19.38</td> <td>29.51</td> <td>5.11</td> <td>Average</td> <td>---</td> </tr> <tr> <td>4</td> <td>4880.00</td> <td>46.03</td> <td>74.00</td> <td>-27.97</td> <td>40.92</td> <td>5.11</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>7320.00</td> <td>38.00</td> <td>54.00</td> <td>-16.00</td> <td>28.66</td> <td>9.34</td> <td>Average</td> <td>---</td> </tr> <tr> <td>6</td> <td>7320.00</td> <td>50.59</td> <td>74.00</td> <td>-23.41</td> <td>41.25</td> <td>9.34</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dB		High	Table	1	1594.00	25.66	54.00	-28.34	32.47	-6.81	Average	---	2	1594.00	39.21	74.00	-34.79	46.02	-6.81	Peak	---	3	4880.00	34.62	54.00	-19.38	29.51	5.11	Average	---	4	4880.00	46.03	74.00	-27.97	40.92	5.11	Peak	---	5	7320.00	38.00	54.00	-16.00	28.66	9.34	Average	---	6	7320.00	50.59	74.00	-23.41	41.25	9.34	Peak	---
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																			
MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																			
1	1594.00	25.66	54.00	-28.34	32.47	-6.81	Average	---																																																																			
2	1594.00	39.21	74.00	-34.79	46.02	-6.81	Peak	---																																																																			
3	4880.00	34.62	54.00	-19.38	29.51	5.11	Average	---																																																																			
4	4880.00	46.03	74.00	-27.97	40.92	5.11	Peak	---																																																																			
5	7320.00	38.00	54.00	-16.00	28.66	9.34	Average	---																																																																			
6	7320.00	50.59	74.00	-23.41	41.25	9.34	Peak	---																																																																			

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2440																																																																								
<b>Polarization</b>	Vertical																																																																										
																																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Freq.</th> <th style="text-align: left;">Emission</th> <th style="text-align: left;">Limit</th> <th style="text-align: left;">Margin</th> <th style="text-align: left;">SA</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">Remark</th> <th style="text-align: left;">ANT</th> <th style="text-align: left;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dB</th> <th></th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1594.00</td> <td>35.67</td> <td>54.00</td> <td>-18.33</td> <td>42.48</td> <td>-6.81</td> <td>Average</td> <td>---</td> </tr> <tr> <td>2</td> <td>1594.00</td> <td>52.78</td> <td>74.00</td> <td>-21.22</td> <td>59.59</td> <td>-6.81</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>4880.00</td> <td>38.17</td> <td>54.00</td> <td>-15.83</td> <td>33.06</td> <td>5.11</td> <td>Average</td> <td>---</td> </tr> <tr> <td>4</td> <td>4880.00</td> <td>48.30</td> <td>74.00</td> <td>-25.70</td> <td>43.19</td> <td>5.11</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>7320.00</td> <td>39.07</td> <td>54.00</td> <td>-14.93</td> <td>29.73</td> <td>9.34</td> <td>Average</td> <td>---</td> </tr> <tr> <td>6</td> <td>7320.00</td> <td>50.89</td> <td>74.00</td> <td>-23.11</td> <td>41.55</td> <td>9.34</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dB		High	Table	1	1594.00	35.67	54.00	-18.33	42.48	-6.81	Average	---	2	1594.00	52.78	74.00	-21.22	59.59	-6.81	Peak	---	3	4880.00	38.17	54.00	-15.83	33.06	5.11	Average	---	4	4880.00	48.30	74.00	-25.70	43.19	5.11	Peak	---	5	7320.00	39.07	54.00	-14.93	29.73	9.34	Average	---	6	7320.00	50.89	74.00	-23.11	41.55	9.34	Peak	---
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																			
MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																			
1	1594.00	35.67	54.00	-18.33	42.48	-6.81	Average	---																																																																			
2	1594.00	52.78	74.00	-21.22	59.59	-6.81	Peak	---																																																																			
3	4880.00	38.17	54.00	-15.83	33.06	5.11	Average	---																																																																			
4	4880.00	48.30	74.00	-25.70	43.19	5.11	Peak	---																																																																			
5	7320.00	39.07	54.00	-14.93	29.73	9.34	Average	---																																																																			
6	7320.00	50.89	74.00	-23.11	41.55	9.34	Peak	---																																																																			

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2480																																																																																										
<b>Polarization</b>	Horizontal																																																																																												
																																																																																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Freq.</th> <th style="text-align: left;">Emission</th> <th style="text-align: left;">Limit</th> <th style="text-align: left;">Margin</th> <th style="text-align: left;">SA</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">Remark</th> <th style="text-align: left;">ANT</th> <th style="text-align: left;">Turn</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dBuV</th> <th style="text-align: left;">dB</th> <th style="text-align: left;">High</th> <th style="text-align: left;">Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1594.00</td> <td>25.97</td> <td>54.00</td> <td>-28.03</td> <td>32.78</td> <td>-6.81</td> <td>Average</td> <td>---</td> </tr> <tr> <td>2</td> <td>1594.00</td> <td>39.53</td> <td>74.00</td> <td>-34.47</td> <td>46.34</td> <td>-6.81</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>2483.50</td> <td>28.11</td> <td>54.00</td> <td>-25.89</td> <td>31.41</td> <td>-3.30</td> <td>Average</td> <td>---</td> </tr> <tr> <td>4</td> <td>2483.50</td> <td>43.61</td> <td>74.00</td> <td>-30.39</td> <td>46.91</td> <td>-3.30</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>4960.00</td> <td>33.85</td> <td>54.00</td> <td>-20.15</td> <td>28.57</td> <td>5.28</td> <td>Average</td> <td>---</td> </tr> <tr> <td>6</td> <td>4960.00</td> <td>45.61</td> <td>74.00</td> <td>-28.39</td> <td>40.33</td> <td>5.28</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>7</td> <td>7440.00</td> <td>38.13</td> <td>54.00</td> <td>-15.87</td> <td>28.54</td> <td>9.59</td> <td>Average</td> <td>---</td> </tr> <tr> <td>8</td> <td>7440.00</td> <td>50.49</td> <td>74.00</td> <td>-23.51</td> <td>40.90</td> <td>9.59</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>				Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading	dBuV	dB	High	Table	1	1594.00	25.97	54.00	-28.03	32.78	-6.81	Average	---	2	1594.00	39.53	74.00	-34.47	46.34	-6.81	Peak	---	3	2483.50	28.11	54.00	-25.89	31.41	-3.30	Average	---	4	2483.50	43.61	74.00	-30.39	46.91	-3.30	Peak	---	5	4960.00	33.85	54.00	-20.15	28.57	5.28	Average	---	6	4960.00	45.61	74.00	-28.39	40.33	5.28	Peak	---	7	7440.00	38.13	54.00	-15.87	28.54	9.59	Average	---	8	7440.00	50.49	74.00	-23.51	40.90	9.59	Peak	---
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																					
MHz	level	dBuV/m	dB	reading	dBuV	dB	High	Table																																																																																					
1	1594.00	25.97	54.00	-28.03	32.78	-6.81	Average	---																																																																																					
2	1594.00	39.53	74.00	-34.47	46.34	-6.81	Peak	---																																																																																					
3	2483.50	28.11	54.00	-25.89	31.41	-3.30	Average	---																																																																																					
4	2483.50	43.61	74.00	-30.39	46.91	-3.30	Peak	---																																																																																					
5	4960.00	33.85	54.00	-20.15	28.57	5.28	Average	---																																																																																					
6	4960.00	45.61	74.00	-28.39	40.33	5.28	Peak	---																																																																																					
7	7440.00	38.13	54.00	-15.87	28.54	9.59	Average	---																																																																																					
8	7440.00	50.49	74.00	-23.51	40.90	9.59	Peak	---																																																																																					

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

## 3.6 Unwanted Emissions into Non-Restricted Frequency Bands

### 3.6.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

### 3.6.2 Test Procedures


#### Reference Level Measurement

1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Set Sweep time = auto couple, Trace mode = max hold.
3. Allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.


#### Unwanted Emissions Level Measurement

1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Trace Mode = max hold, Sweep = auto couple.
3. Allow the trace to stabilize.
4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.


### 3.6.3 Test Setup




### 3.6.4 Unwanted Emissions into Non-Restricted Frequency Bands



**TX Freq 2480MHz / 30MHz~25GHz (down 20dBc)**



---



---

## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

### Linkou

Tel: 886-2-2601-1640  
No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

### Kwei Shan

Tel: 886-3-271-8666  
No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666  
Fax: 886-3-318-0155  
Email: [ICC\\_Service@icertifi.com.tw](mailto:ICC_Service@icertifi.com.tw)

==END==