

FCC CERTIFICATION TEST REPORT

REPORT NO.: FC140129C11

MODEL NO.: F-07F

FCC ID: VQK-F07F

RECEIVED: Jan. 29, 2014

TESTED: Mar. 13 ~ Mar. 14, 2014

ISSUED: Mar. 17, 2014

APPLICANT: FUJITSU LIMITED

ADDRESS: 1-1, Kamikodanaka 4-chome, Nakahara-ku,

Kawasaki 211-8588, Japan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB ADDRESS: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF, NVLAP, NIST or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Report No.: FC140129C11 1 of 27 Report Format Version 5.0.2



Table of Contents

RELEA	ASE CONTROL RECORD	3
1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	DESCRIPTION OF SUPPORT UNITS	8
3.4	CONFIGURATION OF SYSTEM UNDER TEST	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2	TEST INSTRUMENTS	9
4.1.3	TEST PROCEDURES	10
4.1.4	DEVIATION FROM TEST STANDARD	10
4.1.5	TEST SETUP	.11
4.1.6	EUT OPERATING CONDITIONS	.11
4.1.7	TEST RESULTS	12
4.2	RADIATED EMISSION MEASUREMENT	14
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	
4.2.2	TEST INSTRUMENTS	16
4.2.3	TEST PROCEDURES	18
4.2.4	DEVIATION FROM TEST STANDARD	
4.2.5	TEST SETUP	20
4.2.6	EUT OPERATING CONDITIONS	20
4.2.7	TEST RESULTS	21
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	25
6	INFORMATION ON THE TESTING LABORATORIES	26
7	APPENDIX A – MODIFICATION RECORDERS FOR ENGINEERING CHANGES TO THE	
	EUT BY THE LAB	27



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FC140129C11	Original release	Mar. 17, 2014



1 CERTIFICATION

PRODUCT: Mobile Phone

MODEL: F-07F

BRAND: FUJITSU

APPLICANT: FUJITSU LIMITED

TEST SAMPLE: ENGINEERING SAMPLE

TESTED: Mar. 13 ~ Mar. 14, 2014

STANDARD: FCC Part 15, Subpart B, Class B

ICES-003:2012 Issue 5, Class B

ANSI C63.4:2009

The above equipment (Model: F-07F) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Celine Chon, DATE: Mar. 17, 2014

Celine Chou / Specialist

David Liu / Technical Manager



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications.

EMISSION						
Standard	Test Type	Result	Remarks			
FCC Part 15, Subpart B, Class B	Conducted emissions test	PASS	Meet the requirement of limit. Minimum passing margin is -17.83dB at 0.16181MHz.			
ICES-003:2012 Issue 5, Class B	Radiated emissions test (30MHz~18GHz)	PASS	Meet the requirement of limit. Minimum passing margin is -4.74dB at 44.020MHz.			

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Frequency	Uncertainty
Conducted emissions	150kHz ~ 30MHz	2.44 dB
Dadiated assistant	30MHz ~ 1GHz	4.70 dB
Radiated emissions	Above 1GHz	2.26 dB

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Mobile Phone		
MODEL NO.	F-07F		
POWER SUPPLY	3.7Vdc (Battery) 5.4Vdc (Adapter or cradle or host equipment)		
I/O PORTS	Refer to users' manual		
ACCESSORY DEVICES	Refer to Note as below		

NOTE:

1. The EUT contains the following accessories.

No.	Product	Brand	Model	Description
1	Battery	Fujitsu limited	CA54310-0028	3.7Vdc, 1000mA

- 2. SW version is R05A.
- 3. HW version is V2.1.0.
- 4. IMEI Code: 355276050003166.
- 5. The EUT's highest operating frequency is 2.4GHz. Therefore the radiated emissions tests are tested up to 18GHz.
- 6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 DESCRIPTION OF TEST MODES

The EUT consumes power from adapter, which is designed with AC power supply of 100-240Vac, 50-60Hz or from cradle with AC power supply of 100-240Vac.

For conducted emissions test, the EUT has been pre-tested under the following test modes, and test **mode 2** was found to be the worst case for final test.

Test Mode	Test Condition				
1	GSM 1900 Idle + WIFI Idle + BT Idle + MP4 (SD card) + Adapter				
2	GSM 1900 Idle + WIFI Idle + BT Idle + Camera + Adapter				
3	WCDMA Band 5 Idle + WIFI Idle + BT Idle + GPS + Adapter				
4	EUT Charging + Adapter + Cradle				

For radiated emissions below 1GHz test, the EUT has been pre-tested under the following test modes, and **test mode 4** was found to be the worst case for final test.

Test Mode	Test Condition
1	GSM 1900 Idle + WIFI Idle + BT Idle + MP4 (SD card) + Adapter – Stand-up
2	GSM 1900 Idle + WIFI Idle + BT Idle + MP4 (SD card) + Adapter – Laying-flat
3	WCDMA Band 5 Idle + WIFI Idle + BT Idle + MP4 (SD card) + Earphone + Battery
4	GSM 1900 Idle + WIFI Idle + BT Idle + Camera + Adapter
5	WCDMA Band 5 Idle + WIFI Idle + BT Idle + GPS + Adapter
6	GSM 1900 Idle + WIFI Idle + BT Idle + RFID Idle + Earphone + Battery
7	EUT Charging + Adapter + Cradle

Test results are presented in the report as below.

Test Result	sult Test Condition				
Conducted emissions test					
-	- GSM 1900 Idle + WIFI Idle + BT Idle + Camera + Adapter				
Radiated emissions test					
-	- GSM 1900 Idle + WIFI Idle + BT Idle + Camera + Adapter				



3.3 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID	Remark
A.	Universal Radio Communication Tester	R&S	CMU200	122554	NA	-
В.	BLUETOOTH EARPHONE	ELECOM	LBT-MPHS400	N/A	NA	-
C.	Wireless N Dual band Router	D-LINK	DIR-815	PVK21B5000399	KA21R815A1	-
D.	Adapter	NTT docomo	AC Adaptor 02	NA	NA	-
E.	SIM Card	R&S	CMW-Z04	NA	NA	-

NOTE:

- 1. All power cords of the above support units are non-shielded (1.8 m).
- 2. Items A-C acted as communication partners to transfer data.
- 3. Item D is provided by the client.

3.4 CONFIGURATION OF SYSTEM UNDER TEST



Remote site





4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSIONS MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

TEST STANDARD:

FCC Part 15, Subpart B (section: 15.107) ICES-003:2012 Issue 5 (section: 6.1)

Eroguenov (MHz)	Class A	Class A (dBuV)		(dBuV)
Frequency (MHz)	Quasi-peak	Average	Quasi-peak	Average
0.15-0.5	79	66	66-56	56-46
0.5-5	73	60	56	46
5-30	73	60	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

- The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Nov. 29, 2013	Nov. 28, 2014
RF signal cable Woken	5D-FB	Cable-HYC01-01	Dec. 27, 2013	Dec. 26, 2014
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 13, 2014	Feb. 12, 2015
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 17, 2013	Jul. 16, 2014
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 1.
- 3. The VCCI Site Registration No. is C-2040.



4.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under Limit 20dB was not recorded.

111	DEVIATION	FROM TEST	STANDARD
4 1 4	1 /1 V I A I IV /1 V	1 133 /101 11 331	O LAINI JAINI J

Nο	de.	via	tıc	าก



4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the on the test table.
- b. Camera function of EUT was enabled during testing.
- c. The EUT linked with the Universal Radio Communication Tester, Wireless Router, and Bluetooth Earphone, which acted as communication partners, and then set the GSM, WIFI and Bluetooth functions in idle condition.




4.1.7 TEST RESULTS

Frequency Range	150kHz ~ 30MHz	IX. RECOILITION	Quasi-Peak (QP), 9kHz Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	20℃, 60%RH
Tested by	Ben Huang	Test Date	2014/3/13

	Phase Of Power : Line (L)									
	Frequency	Correction	Readin	g Value	Emissio	n Level	Lir	nit	Ma	rgin
No		Factor	(dB	uV)	(dB	uV)	(dB	uV)	(d	B)
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18122	0.10	42.58	30.44	42.68	30.54	64.43	54.43	-21.75	-23.89
2	0.21256	0.09	41.79	29.71	41.88	29.80	63.10	53.10	-21.22	-23.30
3	0.28288	0.10	31.80	20.19	31.90	20.29	60.73	50.73	-28.83	-30.44
4	0.59183	0.14	31.88	23.25	32.02	23.39	56.00	46.00	-23.98	-22.61
5	0.84208	0.18	32.04	23.65	32.22	23.83	56.00	46.00	-23.78	-22.17
6	24.25124	1.24	29.14	24.64	30.38	25.88	60.00	50.00	-29.62	-24.12

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 9kHz Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	20℃, 60%RH
Tested by	Ben Huang	Test Date	2014/3/13

	Phase Of Power : Neutral (N)									
	Frequency	Correction	Readin	g Value	Emissic	n Level	Lir	nit	Ma	rgin
No		Factor	(dB	uV)	(dB	uV)	(dB	uV)	(d	B)
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16181	0.06	47.48	34.10	47.54	34.16	65.37	55.37	-17.83	-21.21
2	0.19305	0.08	43.53	32.51	43.61	32.59	63.90	53.90	-20.29	-21.31
3	0.22429	0.10	38.69	24.58	38.79	24.68	62.66	52.66	-23.87	-27.98
4	0.25166	0.11	38.24	26.28	38.35	26.39	61.70	51.70	-23.35	-25.31
5	1.06494	0.22	27.23	20.99	27.45	21.21	56.00	46.00	-28.55	-24.79
6	3.26627	0.25	28.17	22.80	28.42	23.05	56.00	46.00	-27.58	-22.95

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value





4.2 RADIATED EMISSIONS MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSIONS MEASUREMENT

TEST STANDARD:

FCC Part 15, Subpart B (section: 15.109) ICES-003:2012 Issue 5 (section: 6.2)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBµV/m)						
Frequencies (MHz)	FCC 15B/ ICES-003, Class A	CISPR 22, Class A	CISPR 22, Class B			
30-88	39	29.5				
88-216	43.5	33.1	40	30		
216-230	46.4	35.6				
230-960	40.4	33.0	47	37		
960-1000	49.5	43.5	47	37		
1000-3000	Avg: 49.5	Avg: 43.5	Not defined	Not defined		
Above 3000	Peak: 69.5	Peak: 63.5	Not defined	Not defined		

Radiated Emissions Limits at 3 meters (dBμV/m)						
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B		
30-88	49.5	40				
88-216	54	43.5	50.5	40.5 47.5		
216-230	56.9	46				
230-960	50.9	40	57.5			
960-1000	60	54	57.5	47.5		
1000-3000	Avg: 60	Avg: 54	Avg: 56 Peak: 76	Avg: 50 Peak: 70		
Above 3000	Peak: 80	Peak: 74	Avg: 60 Peak: 80	Avg: 54 Peak: 74		

NOTE: 1. The lower limit shall apply at the transition frequencies.

- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- 4. QP detector shall be applied if not specified.



FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower



4.2.2 TEST INSTRUMENTS

Frequency range 30MHz~1GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ (V)	ESR-7	101240	Sep. 23, 2013	Sep. 22, 2014
Test Receiver ROHDE & SCHWARZ (H)	ESR-7	101264	Nov. 29, 2013	Nov. 28, 2014
BILOG Antenna SCHWARZBECK (V)	VULB9168	9168-148	Feb. 25, 2014	Feb. 24, 2015
BILOG Antenna SCHWARZBECK (H)	VULB9168	9168-149	Feb. 25, 2014	Feb. 24, 2015
Preamplifier Agilent (V)	8447D	2944A10636	Oct. 18, 2013	Oct. 17, 2014
Preamplifier Agilent (H)	8447D	2944A10637	Oct. 18, 2013	Oct. 17, 2014
Preamplifier Agilent	8449B	3008A01959	Oct. 18, 2013	Oct. 17, 2014
RF signal cable Woken (V)	8D-FB	Cable-Hych1-01	Oct. 26, 2013	Oct. 25, 2014
RF signal cable Woken (H)	8D-FB	Cable-Hych1-02	Oct. 26, 2013	Oct. 25, 2014
Software BV ADT	BV ADT_Radiated_ V 8.7.07	NA	NA	NA
Antenna Tower (V)	MFA-440	9707	NA	NA
Antenna Tower (H)	MFA-440	970705	NA	NA
Turn Table	DS430	50303	NA	NA
Controller (V)	MF7802	074	NA	NA
Controller (H)	MF7802	08093	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 1.
- 3. The FCC Site Registration No. is 477732.
- 4. The IC Site Registration No. is IC 7450F-1.
- 5. The VCCI Site Registration No. is R-1893, G-113.



Frequency range above 1GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Oct. 24, 2013	Oct. 23, 2014
Spectrum Analyzer Agilent	E4446A	MY44360124	Feb. 12, 2014	Feb. 11, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Feb. 26, 2014	Feb. 25, 2015
RF signal cable Woken	8D-FB	NA	Mar. 22, 2013	Mar. 21, 2014
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-404	Jan. 05, 2014	Jan. 04, 2015
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Jan. 09, 2014	Jan. 08, 2015
Preamplifier Agilent (Below 1GHz)	8447D	2944A10629	Oct. 18, 2013	Oct. 17, 2014
Preamplifier Agilent (Above 1GHz)	8449B	3008A01959	Oct. 18, 2013	Oct. 17, 2014
RF signal cable HUBER+SUHNER	SUCOFLEX 104	MWX322+MW X2211308S029 5	Sep. 09, 2013	Sep. 08, 2014
Software BV ADT	BV ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Controller BV ADT	SC100	SC93021702	NA	NA
RF signal cable HUBER+SUHNNER	SUCOFLEX 102	38218/2+ 37433/2	Oct. 26, 2013	Oct. 25, 2014
Fix tool for Boresight antenna tower	BAF-01	2	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 2.
- 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The FCC Site Registration No. is 686814.
- 5. The IC Site Registration No. is IC 7450F-2.
- 6. The VCCI Site Registration No. is G-18.



4.2.3 TEST PROCEDURES

Frequency range 30MHz~1GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE: The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-Peak (QP) detection at frequency below 1GHz.



Frequency range above 1GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from 1 meter to 4 meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.

NOTE:


- 1. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak (PK) detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz for Average (AV) detection at frequency above 1GHz.
- 2. For measurement of frequency above 1000MHz, the EUT was set 3 meters away from the receiver antenna.

4.2.4 DEVIATION FROM TEST STANDARD




4.2.5 TEST SETUP

Frequency range 30MHz~1GHz



Frequency range above 1GHz



*: depends on the EUT height and the antenna 3dB beamwidth both.

For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.




4.2.7 TEST RESULTS

Frequency Range	30MHz ~ 1GHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 120kHz
Input Power	120Vac, 60Hz	Environmental Conditions	18℃, 61%RH
Tested by	Scott Yang	Test Date	2014/3/13

	Antenna Polarity & Test Distance : Horizontal at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	
1	43.730	14.56 QP	30.00	-15.44	2.50 H	330	29.31	-14.75	
2	62.550	13.90 QP	30.00	-16.10	3.00 H	195	29.29	-15.39	
3	140.050	12.65 QP	30.00	-17.35	3.50 H	199	27.43	-14.78	
4	151.940	13.19 QP	30.00	-16.81	3.50 H	211	27.34	-14.15	
5	188.020	12.80 QP	30.00	-17.20	3.50 H	216	28.95	-16.15	
6	236.040	12.69 QP	37.00	-24.31	2.00 H	308	27.83	-15.14	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 Pre-Amplifier Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value






Frequency Range		Detector Function & Resolution Bandwidth	Quasi-Peak (QP), 120kHz
Input Power	120Vac, 60Hz	Environmental Conditions	18℃, 61%RH
Tested by	Scott Yang	Test Date	2014/3/13

	Antenna Polarity & Test Distance : Vertical at 10 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)	
1	36.980	23.73 QP	30.00	-6.27	3.50 V	214	38.72	-14.99	
2	44.020	25.26 QP	30.00	-4.74	2.00 V	320	39.34	-14.08	
3	62.550	25.04 QP	30.00	-4.96	2.50 V	160	39.84	-14.80	
4	135.440	15.36 QP	30.00	-14.64	1.00 V	202	29.98	-14.62	
5	150.870	15.78 QP	30.00	-14.22	1.00 V	210	29.28	-13.50	
6	180.940	14.86 QP	30.00	-15.14	2.00 V	196	29.50	-14.64	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 - Pre-Amplifier Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value






Frequency Range	1GHz ~ 18GHz	Detector Function & Resolution Bandwidth	Peak (PK), 1MHz Average (AV), 1MHz
Input Power	120Vac, 60Hz	Environmental Conditions	22℃, 77%RH
Tested by	Daniel Lin	Test Date	2014/3/14

	Antenna Polarity & Test Distance : Horizontal at 3 m									
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)		
1	1085.300	36.20 PK	74.00	-37.80	1.10 H	124	45.19	-8.99		
2	1085.300	26.50 AV	54.00	-27.50	1.10 H	124	35.49	-8.99		
3	1538.200	37.19 PK	74.00	-36.81	1.14 H	119	44.17	-6.98		
4	1538.200	23.50 AV	54.00	-30.50	1.14 H	119	30.48	-6.98		
5	3635.220	41.69 PK	74.00	-32.31	1.00 H	126	42.42	-0.73		
6	3635.220	32.50 AV	54.00	-21.50	1.00 H	126	33.23	-0.73		

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 - Pre-Amplifier Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value






Frequency Range	1GHz ~ 18GHz	Detector Function & Resolution Bandwidth	Peak (PK), 1MHz Average (AV), 1MHz
Input Power	120Vac, 60Hz	Environmental Conditions	22℃, 77%RH
Tested by	Daniel Lin	Test Date	2014/3/14

	Antenna Polarity & Test Distance : Vertical at 3 m									
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)		
1	1056.000	36.10 PK	74.00	-37.90	1.00 V	124	45.25	-9.15		
2	1056.000	28.20 AV	54.00	-25.80	1.00 V	124	37.35	-9.15		
3	1283.600	37.12 PK	74.00	-36.88	1.12 V	200	45.18	-8.06		
4	1283.600	26.10 AV	54.00	-27.90	1.12 V	200	34.16	-8.06		
5	3295.600	40.64 PK	74.00	-33.36	1.00 V	112	42.32	-1.68		
6	3295.600	29.50 AV	54.00	-24.50	1.00 V	112	31.18	-1.68		

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 - Pre-Amplifier Factor (dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value





5 PHOTOGRAPHS OF THE TEST CONFIGURATION Please refer to the attached file (Test Setup Photo).



6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Hsin Chu EMC/RF Lab

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180 Tel: 886-3-5935343 Fax: 886-2-26051924 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



7 APPENDIX A – MODIFICATION RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.
--- END ---