

FCC Test Report

(PART 22)

Report No.: RF150303C31

FCC ID: VQK-F09B2

Test Model: F-09B

Received Date: Mar. 04, 2015

Test Date: Mar. 11 ~ Mar. 14, 2015

Issued Date: Mar. 20, 2015

Applicant: FUJITSU LIMITED

Address: 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki 211-8588, Japan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C.)

Test Location: No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

Report No.: RF150303C31 Page No. 1 / 37 Report Format Version: 6.1.1



Table of Contents

R	Release Control Record3					
1	C	ertificate of Conformity	. 4			
2	S	ummary of Test Results	. 5			
	2.1 2.2	Measurement Uncertainty Test Site and Instruments				
3	G	eneral Information	. 7			
	3.1	General Description of EUT	. 7			
	3.2	Configuration of System Under Test				
	3.2.1	Description of Support Units				
	3.3	Test Mode Applicability and Tested Channel Detail	. 9			
	3.4	EUT Operating Conditions	10			
	3.5	General Description of Applied Standards	10			
4	Т	est Types and Results	11			
	4.1	Output Power Measurement	11			
	4.1.1	Limits of Output Power Measurement	11			
		Test Procedures				
		Test Setup				
		Test Results				
	4.2	Frequency Stability Measurement				
	4.2.1					
		Test Procedure				
		Test Setup				
		Test Results				
	4.3	Occupied Bandwidth Measurement				
		Test Procedure				
		Test Setup Test Result				
	4.3.3	Band Edge Measurement				
	4.4.1					
		Test Setup				
		Test Procedures.				
		Test Results				
	4.5	Peak To Average Ratio.				
		Limits of Peak To Average Ratio Measurement				
		Test Setup				
		Test Procedures				
	4.5.4	Test Results	22			
	4.6	Conducted Spurious Emissions	23			
	4.6.1	Limits of Conducted Spurious Emissions Measurement	23			
		Test Setup				
		Test Procedure				
		Test Results				
	4.7	Radiated Emission Measurement				
		Limits of Radiated Emission Measurement				
		Test Procedure				
		Deviation from Test Standard				
		Test Setup Test Results				
5	P	ictures of Test Arrangements	36			
A	ppend	lix – Information on the Testing Laboratories	37			



Release Control Record

Issue No.	Description	Date Issued
RF150303C31	Original release.	Mar. 20, 2015



1 Certificate of Conformity

Product: Mobile phone

Brand: Fujitsu

Test Model: F-09B

Sample Status: Engineering sample

Applicant: FUJITSU LIMITED

Test Date: Mar. 11 ~ Mar. 14, 2015

Standards: FCC Part 22, Subpart H

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prenared by: Mar 20, 2015

₩y Lin / Specialist

Approved by: Mar. 20, 2015

Bruce Chen / Project Engineer



2 Summary of Test Results

	Applied Standard: FCC Part 22 & Part 2						
FCC Clause	Test Item	Result	Remarks				
2.1046 22.913 (a)	Effective radiated power	PASS	Meet the requirement of limit.				
Peak To Average Ratio		PASS	Meet the requirement of limit.				
2.1055 22.355	Frequency Stability	PASS	Meet the requirement of limit.				
2.1049	Occupied Bandwidth	PASS	Meet the requirement of limit.				
22.917	Band Edge Measurements	PASS	Meet the requirement of limit.				
2.1051 22.917	Conducted Spurious Emissions	PASS	Meet the requirement of limit.				
2.1053 22.917	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -37.95dB at 94.02MHz.				

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Padiated Emissions up to 1 CHz	30MHz ~ 200MHz	3.59 dB
Radiated Emissions up to 1 GHz	200MHz ~1000MHz	3.60 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
Natifaced Effiliasions above 1 GHZ	18GHz ~ 40GHz	2.29 dB



2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Oct. 06, 2014	Oct. 05, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Jul. 25, 2014	Jul. 24, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Feb. 06, 2015	Feb. 05, 2016
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-1170	Feb. 05, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Feb. 09, 2015	Feb. 08, 2016
Preamplifier Agilent	8449B	3008A01961	Oct. 18, 2014	Oct. 17, 2015
Preamplifier Agilent	8447D	2944A10738	Oct. 18, 2014	Oct. 17, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309220/4	Aug. 09, 2014	Aug. 08, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250724/4	Aug. 09, 2014	Aug. 08, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	295012/4	Aug. 09, 2014	Aug. 08, 2015
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA	NA
Turn Table BV ADT	TT100.	TT93021704	NA	NA
Turn Table Controller BV ADT	SC100.	SC93021704	NA	NA
Mini-Circuits Power Splitter	ZN2PD-9G	NA NA	Apr. 25, 2014	Apr. 24, 2015
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 4.
- 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The FCC Site Registration No. is 460141.
- 5. The IC Site Registration No. is IC7450F-4.



3 General Information

3.1 General Description of EUT

Product	Mobile phone
Brand	Fujitsu
Test Model	F-09B
Status of EUT	Engineering sample
Dower Supply Pating	3.7Vdc (Battery)
Power Supply Rating	5.4Vdc (Cradle or Adapter)
Modulation Type	QPSK
Modulation Technology	WCDMA, HSDPA
Operating Frequency	826.4MHz ~ 846.6MHz
Max. ERP Power	272.898mW (24.36dBm)
WCDMA Release Version	8
Antenna Type	λ/4 Monopole antenna with -2.0dBi gain
Accessory Device	Refer to Note as below
Data Cable Supplied	N/A

Note:


1. The EUT contains the following accessories.


No.	Product	Brand	Model	Description
1	Battery	Fujitsu Limited	F17	3.7Vdc, 800mA
2	Cradle	Fujitsu Limited	F30	Input : 5.4Vdc , 700mA Output :5.4Vdc , 700mA

- 2. SW version is R66.2.
- 3. HW version is V2.1.0.
- 4. IMEI Code: 355864060318151.
- 5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



3.2 Configuration of System Under Test





3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Adapter	NTT docomo	AC Adaptor 02	N/A	N/A	Provided by the client
В.	Universal Radio Communication Tester	R&S	CMU200	117260	NA	

Note:

- 1. All power cords of the above support units are non-shielded (1.8m).
- 2. Item B acted as a communication partner to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1. DC cable		1	1.5	-	0	Provided by the client



3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on X-plane. Following channel(s) was (were) selected for the final test as listed below:

Test modes are presented in the report as below.

Test Mode	Test Condition	
Α	Power from adapter	
В	Power from battery	

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
Α	ERP	4132 to 4233	4132, 4182, 4233	WCDMA
В	Frequency Stability	4132 to 4233	4182	WCDMA
В	Occupied Bandwidth	4132 to 4233	4132, 4182, 4233	WCDMA, HSDPA
В	Band Edge	4132 to 4233	4132, 4233	WCDMA, HSDPA
В	Peak To Average Ratio	4132 to 4233	4132, 4182, 4233	WCDMA, HSDPA
В	Conducted Emission	4132 to 4233	4132, 4182, 4233	WCDMA, HSDPA
А	Radiated Emission Below 1GHz	4132 to 4233	4132	WCDMA
А	Radiated Emission Above 1GHz	4132 to 4233	4132, 4182, 4233	WCDMA

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP	27deg. C, 64%RH	120Vac, 60Hz	Chris Lin
Frequency Stability	24deg. C, 64%RH	3.7Vdc	Match Tsui
Occupied Bandwidth	24deg. C, 64%RH	3.7Vdc	Match Tsui
Band Edge	24deg. C, 64%RH	3.7Vdc	Match Tsui
Peak To Average Ratio	24deg. C, 64%RH	3.7Vdc	Match Tsui
Conducted Emission	24deg. C, 64%RH	3.7Vdc	Match Tsui
Radiated Emission	27deg. C, 64%RH	120Vac, 60Hz	Chris Lin



3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

KDB 971168 D01 Power Meas License Digital Systems v02r01

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.



4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 7 watts e.r.p.

4.1.2 Test Procedures

EIRP / ERP Measurement:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5MHz for WCDMA mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G
- d. EIRP = Output power level of S.G TX cable loss + Antenna gain of substitution horn.E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power 2.15dBi.


Conducted Power Measurement:

The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.




4.1.3 Test Setup

EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).



4.1.4 Test Results

CONDUCTED OUTPUT POWER (dBm)

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	23.44	23.56	23.13
HSDPA Subtest-1	23.44	23.55	23.13
HSDPA Subtest-2	22.24	22.27	21.97
HSDPA Subtest-3	22.26	22.29	21.99
HSDPA Subtest-4	22.26	22.29	21.99



ERP Power (dBm)

MOD	IODE TX channel 4132							
	Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	No. Freq. (MHz) Reading S.G Power Correction (dBm) Value (dBm) Factor (dB) ERP (dBm) Limit (dBm)					Margin (dB)		
1	826.4	-6.81	24.30	0.06	24.36	38.45	-14.09	
	Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	
1	826.4	-13.52	18.26	0.06	18.32	38.45	-20.13	

MODE TX channel 4182							
		Antenna	Polarity & Te	st Distance: F	Horizontal at 3	М	
No. Freq. (MHz) Reading S.G Power Correction (dBm) Value (dBm) Factor (dB) ERP (dE				ERP (dBm)	Limit (dBm)	Margin (dB)	
1	836.4	-7.2	23.84	0.29	24.13	38.45	-14.32
	Antenna Polarity & Test Distance: Vertical at 3 M						
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	836.4	-15.39	16.3	0.29	16.59	38.45	-21.86

MOD	MODE TX channel 4233						
	Antenna Polarity & Test Distance: Horizontal at 3 M						
No. Freq. (MHz)			Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	
1	846.6	-7.65	22.73	0.47	23.20	38.45	-15.25
		Antenn	a Polarity & T	est Distance:	Vertical at 3 I	M	
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	846.6	-15.24	15.98	0.47	16.45	38.45	-22.00

NOTE: ERP (dBm) = S.G Power Value (dBm) + Correction Factor (dB).



4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stability Measurement


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

4.2.2 Test Procedure

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ±0.5 during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



Report No.: RF150303C31 Page No. 15 / 37 Report Format Version: 6.1.1



4.2.4 Test Results

Frequency Error vs. Voltage

\/altaga (\/alta\	Frequency Error (ppm)	Limit (nnm)
Voltage (Volts)	WCDMA	Limit (ppm)
4.07	-0.023	2.5
3.70	-0.019	2.5
3.33	-0.019	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.33Vdc to 4.07Vdc.

Frequency Error vs. Temperature.

Temp. ()	Frequency Error (ppm)	Limit (ppm)	
remp. ()	WCDMA		
60	-0.033	2.5	
50	-0.032	2.5	
40	-0.029	2.5	
30	-0.023	2.5	
20	-0.019	2.5	
10	-0.025	2.5	
0	-0.037	2.5	
-10	-0.041	2.5	
-20	-0.044	2.5	




4.3 Occupied Bandwidth Measurement

4.3.1 Test Procedure

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.


4.3.2 Test Setup





4.3.3 Test Result

Ohamal	Freq. (MHz)	99% Occupied Bandwidth (MHz)			
Channel		WCDMA	HSDPA		
4132	826.4	4.15	4.17		
4182	836.6	4.18	4.17		
4233	846.6	4.15	4.17		






4.4 Band Edge Measurement

4.4.1 Limits of Band Edge Measurement

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.4.2 Test Setup




4.4.3 Test Procedures

- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 10MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).
- c. Record the max trace plot into the test report.



4.4.4 Test Results






4.5 Peak To Average Ratio

4.5.1 Limits of Peak To Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed $13~\mathrm{dB}$

4.5.2 Test Setup




4.5.3 Test Procedures

- 1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- 2. Set the number of counts to a value that stabilizes the measured CCDF curve;
- 3. Record the maximum PAPR level associated with a probability of 0.1%.



4.5.4 Test Results

01	Freq. (MHz)	Peak To Average Ratio (dB)		
Channel		WCDMA	HSDPA	
4132	826.4	2.57	3.07	
4182	836.4	3.05	2.99	
4233	846.6	3.08	3.04	






4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit equal to –13dBm.

4.6.2 Test Setup




4.6.3 Test Procedure


- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 9 kHz to 9GHz. 20dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.




4.6.4 Test Results



























4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit equal to –13dBm.

4.7.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. EIRP = Output power level of S.G TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power 2.15dBi.


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.7.3 Deviation from Test Standard

No deviation.



4.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).



4.7.5 Test Results

Below 1GHz

Mode	TX channel 4132	Frequency Range	Below 1000MHz
Environmental Conditions	27deg. C, 64%RH	Input Power	120Vac, 60Hz
Tested By	Chris Lin		

	Antenna Polarity & Test Distance: Horizontal at 3 M								
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)		
1	66.86	-45.62	-45.82	-5.82	-51.64	-13.00	-38.64		
2	189.08	-56.60	-69.34	4.08	-65.26	-13.00	-52.26		
3	379.20	-63.16	-69.53	5.25	-64.28	-13.00	-51.28		
4	617.82	-68.13	-71.86	4.58	-67.28	-13.00	-54.28		
5	782.72	-66.34	-65.41	4.25	-61.16	-13.00	-48.16		
6	937.92	-65.01	-61.81	3.92	-57.89	-13.00	-44.89		
		Antenna	Polarity & Te	est Distance: '	Vertical at 3 N	1			
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)		
1	94.02	-45.68	-51.97	1.02	-50.95	-13.00	-37.95		
2	220.12	-61.87	-67.75	5.45	-62.30	-13.00	-49.30		
3	462.62	-62.56	-68.67	5.02	-63.65	-13.00	-50.65		
4	681.84	-68.27	-68.42	5.10	-63.32	-13.00	-50.32		
5	780.78	-67.31	-65.28	4.27	-61.01	-13.00	-48.01		
6	937.92	-64.99	-60.11	3.92	-56.19	-13.00	-43.19		



Above 1GHz

Mode	TX channel 4132	Frequency Range	Above 1000MHz
Environmental Conditions	27deg. C, 64%RH	Input Power	120Vac, 60Hz
Tested By	Chris Lin		

	Antenna Polarity & Test Distance: Horizontal at 3 M							
No. Freq. (MHz) Reading (dBm) S.G Power Correction (dBm) ERP (dBm) Limit (dBm) Margin (dBm) Factor (dB)							Margin (dB)	
1	1652.80	-55.21	-58.42	5.49	-52.93	-13.00	-39.93	
	Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	
1	1652.80	-60.11	-61.17	5.49	-55.68	-13.00	-42.68	

Remarks:

- 1. Output Power (dBm) = S.G Value (dBm) + Correction Factor (dB).
- 2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).



Mode	TX channel 4182	Frequency Range	Above 1000MHz	
Environmental Conditions	27deg. C, 64%RH	Input Power	120Vac, 60Hz	
Tested By	Chris Lin			

	Antenna Polarity & Test Distance: Horizontal at 3 M						
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1672.80	-55.30	-58.35	5.54	-52.81	-13.00	-39.81
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1672.80	-58.57	-59.39	5.54	-53.85	-13.00	-40.85

Remarks:

- Output Power (dBm) = S.G Value (dBm) + Correction Factor (dB).
 Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).



Mode	TX channel 4233	Frequency Range	Above 1000MHz	
Environmental Conditions	27deg. C, 64%RH	Input Power	120Vac, 60Hz	
Tested By	Chris Lin			

	Antenna Polarity & Test Distance: Horizontal at 3 M						
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1693.20	-59.07	-61.95	5.59	-56.36	-13.00	-43.36
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1693.20	-59.02	-59.59	5.59	-54.00	-13.00	-41.00

Remarks:

- Output Power (dBm) = S.G Value (dBm) + Correction Factor (dB).
 Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB).



5 Pictures of Test Arrangements				
Please refer to the attached file (Test Setup Photo).				

Report No.: RF150303C31 Page No. 36 / 37 Report Format Version: 6.1.1



Appendix - Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab/Telecom Lab

Tel: 886-2-26052180 Tel: 886-3-5935343 Fax: 886-2-26051924 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---