

# FCC TEST REPORT (BLUETOOTH LE4.0)

**REPORT NO.:** RF130517C12A-5

MODEL NO.: F-09E

FCC ID: VQK-F09E

**RECEIVED:** May 17, 2013

**TESTED:** May 28 ~ Jul. 10, 2013

**ISSUED:** Jul. 19, 2013

**APPLICANT: FUJITSU LIMITED** 

ADDRESS: 1-1, Kamikodanaka 4-chome, Nakahara-ku,

Kawasaki 211-8588, Japan

**ISSUED BY:** Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,

New Taipei City, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



# **Table of Contents**

RELEAS	SE CONTROL RECORD	4
1.	CERTIFICATION	5
2.	SUMMARY OF TEST RESULTS	6
2.1	MEASUREMENT UNCERTAINTY	6
3.	GENERAL INFORMATION	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	DESCRIPTION OF TEST MODES	8
3.2.1	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	9
3.3	DESCRIPTION OF SUPPORT UNITS	11
3.3.1	CONFIGURATION OF SYSTEM UNDER TEST	11
3.4	GENERAL DESCRIPTION OF APPLIED STANDARDS	12
4.	TEST TYPES AND RESULTS	13
4.1	RADIATED EMISSION AND BANDEDGE MEASUREMENT	13
4.1.1	LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	13
4.1.2	TEST INSTRUMENTS	14
4.1.3	TEST PROCEDURES	15
4.1.4	DEVIATION FROM TEST STANDARD	15
4.1.5	TEST SETUP	16
4.1.6	EUT OPERATING CONDITIONS	16
4.1.7	TEST RESULTS	17
4.2	CONDUCTED EMISSION MEASUREMENT	22
4.2.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	22
4.2.2	TEST INSTRUMENTS	22
4.2.3	TEST PROCEDURES	23
4.2.4	DEVIATION FROM TEST STANDARD	23
4.2.5	TEST SETUP	24
4.2.6	EUT OPERATING CONDITIONS	24
4.2.7	TEST RESULTS	25
4.3	6dB BANDWIDTH MEASUREMENT	29
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	29
4.3.2	TEST SETUP	29
4.3.3	TEST INSTRUMENTS	29
4.3.4	TEST PROCEDURE	29
4.3.5	DEVIATION FROM TEST STANDARD	29
4.3.6	EUT OPERATING CONDITIONS	29
4.3.7	TEST RESULTS	30
4.4	CONDUCTED OUTPUT POWER	31
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	31



4.4.2	TEST SETUP	31
4.4.3	TEST INSTRUMENTS	31
4.4.4	TEST PROCEDURES	31
4.4.5	DEVIATION FROM TEST STANDARD	31
4.4.6	EUT OPERATING CONDITIONS	31
4.4.7	TEST RESULTS	31
4.5	POWER SPECTRAL DENSITY MEASUREMENT	32
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	32
4.5.2	TEST SETUP	32
4.5.3	TEST INSTRUMENTS	32
4.5.4	TEST PROCEDURE	32
4.5.5	DEVIATION FROM TEST STANDARD	32
4.5.6	EUT OPERATING CONDITION	32
4.5.7	TEST RESULTS	32
4.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT	33
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	33
4.6.2	TEST SETUP	33
4.6.3	TEST INSTRUMENTS	33
4.6.4	TEST PROCEDURE	33
4.6.5	DEVIATION FROM TEST STANDARD	34
4.6.6	EUT OPERATING CONDITION	34
4.6.7	TEST RESULTS	34
4.6.8	TEST RESULTS	35
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	36
6.	INFORMATION ON THE TESTING LABORATORIES	37
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE	ΗE
	EUT BY THE LAB	38



# **RELEASE CONTROL RECORD**

ISSUE NO. REASON FOR CHANGE		DATE ISSUED
RF130517C12A-5	Original release	Jul. 19, 2013

Report No.: RF130517C12A-5 Reference No.: 130703C01 4 of 38 Report Format Version 5.1.0



#### 1. CERTIFICATION

**PRODUCT:** Mobile Phone

**MODEL NO.:** F-09E

**BRAND: FUJITSU** 

**APPLICANT:** FUJITSU LIMITED

**TESTED:** May 28 ~ Jul. 10, 2013

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10-2009

The above equipment (model: F-09E) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: My Lin, DATE: Jul. 19, 2013

Ivy/Lin / Specialist

Ken Liu / Senior Manager



## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)							
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK				
15.207 AC Power Conducted Emission		PASS	Meet the requirement of limit. Minimum passing margin is -7.16dB at 0.46183MHz.				
15.247(d) 15.209	· · · Radialed Finissions		Meet the requirement of limit. Minimum passing margin is -8.7dB at 2483.50MHz.				
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.				
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.				
15.247(b) Conducted power		PASS	Meet the requirement of limit.				
15.247(e)	15.247(e) Power Spectral Density		Meet the requirement of limit.				
15.203	Antenna Requirement	PASS	No antenna connector is used.				

#### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emission	150kHz ~ 30MHz	2.44 dB
	30MHz ~ 200MHz	2.93 dB
Radiated emissions	200MHz ~1000MHz	2.95 dB
Radiated emissions	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



# 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

EUT	Mobile Phone
MODEL NO.	F-09E
POWER SUPPLY	3.8Vdc (Battery)
POWER SUPPLY	5.0Vdc (Adapter or cradle or host equipment)
MODULATION TYPE	GFSK
TRANSFER RATE	1Mbps
OPERATING FREQUENCY	2402 ~ 2480MHz
NUMBER OF CHANNEL	40
CHANNEL SPACING	2MHz
OUTPUT POWER	0.966mW
ANTENNA TYPE	λ/4 Monopole antenna with -3.9 dBi gain
ANTENNA CONNECTOR	N/A
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	Refer to Note as below

#### NOTE:

- 1. This report is issued as a supplementary report to the original BV ADT report no.: RF130517C12-5 (FCC ID: VQK-F08E). The differences compared with the original report are changing model, FCC ID, enclosure dimension and updating versions of SW and HW. Therefore, only radiated emission below 1GHz had been re-tested and the other original test data are kept in this report.
- 2. The EUT contains the following accessories.

No.	Product	Brand	Model	Description
1	Battery	Fujitsu limited	CA54310-0047	Rating: 3.8V, 2100mA Type: Li-ion
2	Cradle	Fujitsu Limited	L Δ50601-1871	Input: 5.0Vdc, 1.5A Output: 5.0Vdc, 1.5A

- 3. SW version is R03.2e.
- 4. HW version is V2.1.0.
- 5. IMEI Code: 355755050013655 & 357598050000142
- 6. The above EUT information is declared by manufacturer and for more detailed feature description, please refer to the manufacturer's specifications or User's Manual.



# 3.2 DESCRIPTION OF TEST MODES

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



#### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT	APPLICABLE TO				
CONFIGURE MODE	RE≥1G	RE<1G	PLC	APCM	DESCRIPTION
А	V	V	V	<b>V</b>	Power from adapter
В	-	√	√	-	Power from cradle

Where RE≥1G: Radiated Emission above 1GHz RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission APCM: Antenna Port Conducted Measurement

NOTE 1: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

NOTE 2: "-"means no effect.

#### **RADIATED EMISSION TEST (ABOVE 1GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
Α	0 to 39	0, 19, 39	GFSK	1.0

#### **RADIATED EMISSION TEST (BELOW 1GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A, B	0 to 39	39	GFSK	1.0

#### **POWER LINE CONDUCTED EMISSION:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
A, B	0 to 39	39	GFSK	1.0

Report No.: RF130517C12A-5 9 of 38 Report Format Version 5.1.0

Reference No.: 130703C01



#### **ANTENNA PORT CONDUCTED MEASUREMENT:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)	
Α	0 to 39	0, 19, 39	GFSK	1.0	

#### **TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY	
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Cedric Wu	
RE<1G	27deg. C, 71%RH	120Vac, 60Hz	Cedric Wu	
PLC	25deg. C, 60%RH	120Vac, 60Hz	Nick Chen	
APCM	24deg. C, 64%RH	120Vac, 60Hz	Nick Chen	

Report No.: RF130517C12A-5 10 of 38 Report Format Version 5.1.0 Reference No.: 130703C01



#### 3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	ADAPTER	NTT docomo	AC Adaptor 04	NA	NA


NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA

#### NOTE:


- 1. 1.05m DC cable with 2 cores.
- 2. Item 1 is provided by the client.

#### 3.3.1 CONFIGURATION OF SYSTEM UNDER TEST

#### **Test Mode A**



#### **Test Mode B**



11 of 38



#### 3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247) 558074 D01 DTS Meas Guidance v03r01 ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



#### 4. TEST TYPES AND RESULTS

#### 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.1.2 TEST INSTRUMENTS

Tested date: May 28 ~ Jul. 10, 2013

DESCRIPTION & MODEL NO.		SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION	
Test Receiver ROHDE & SCHWARZ	E60.630		Nov. 16, 2012	Nov. 15, 2013	
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Jan. 28, 2013	Jan. 27, 2014	
BILOG Antenna SCHWARZBECK	VULB9168	9168-156	Mar. 22, 2013	Mar. 21, 2014	
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-209	Sep. 03, 2012	Sep. 02, 2013	
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 11, 2012	Jul. 10, 2013	
Preamplifier Agilent	8449B	3008A01911	Oct. 25, 2012	Oct. 24, 2013	
Preamplifier Agilent	8447D	2944A10638	Oct. 25, 2012	Oct. 24, 2013	
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	295013/4 283403/4	Aug. 28, 2012	Aug. 27, 2013	
RF signal cable Worken	8D-FB	Cable-HYCH9-01	Aug. 11, 2012	Aug. 10, 2013	
Software BV ADT	ADT_Radiated_ V7.6.15.9.3	NA	NA	NA	
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA	
Turn Table EMCO	2087-2.03	NA	NA	NA	
Antenna Tower &Turn Table Controller EMCO	2090	NA	NA	NA	
High Speed Peak Power Meter	ML2495A	0824012	Aug. 22, 2012	Aug. 21, 2013	
Power Sensor	MA2411B	0738171	Jul. 30, 2012	Jul. 29, 2013	

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 9.
- 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The FCC Site Registration No. is 215374.
- 5. The IC Site Registration No. is IC 7450F-9.



#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

#### NOTE:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz(Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

Report No.: RF130517C12A-5 Reference No.: 130703C01 15 of 38

Report Format Version 5.1.0



#### 4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

# 4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



#### 4.1.7 TEST RESULTS

#### **ABOVE 1GHz DATA**

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL Channel 0		FREQUENCY RANGE	1 ~ 25GHz	
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Cedric Wu	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	2390.00	55.6 PK	74.0	-18.4	1.40 H	169	23.70	31.90		
2	2390.00	44.5 AV	54.0	-9.5	1.40 H	169	12.60	31.90		
3	*2402.00	91.8 PK			1.42 H	167	59.80	32.00		
4	*2402.00	87.6 AV			1.42 H	167	55.60	32.00		
5	4804.00	45.4 PK	74.0	-28.6	1.00 H	110	6.80	38.60		
6	4804.00	32.1 AV	54.0	-21.9	1.00 H	110	-6.50	38.60		
		ANTENNA	POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M			
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	2390.00	54.7 PK	74.0	-19.3	1.00 V	310	22.80	31.90		
2	2390.00	43.8 AV	54.0	-10.2	1.00 V	310	11.90	31.90		
3	*2402.00	84.5 PK			1.00 V	308	52.50	32.00		
4	*2402.00	80.8 AV			1.00 V	308	48.80	32.00		
5	4804.00	44.5 PK	74.0	-29.5	1.00 V	320	5.90	38.60		
6	4804.00	31.0 AV	54.0	-23.0	1.00 V	320	-7.60	38.60		

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL Channel 19		FREQUENCY RANGE	1 ~ 25GHz	
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Cedric Wu	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	*2440.00	94.2 PK			1.08 H	171	62.10	32.10			
2	*2440.00	89.8 AV			1.08 H	171	57.70	32.10			
3	4880.00	46.1 PK	74.0	-27.9	1.00 H	118	7.40	38.70			
4	4880.00	32.8 AV	54.0	-21.2	1.00 H	118	-5.90	38.70			
		ANTENNA	POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M				
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	*2440.00	86.6 PK			1.00 V	312	54.50	32.10			
					4.00.17	040		00.40			
2	*2440.00	82.9 AV			1.00 V	312	50.80	32.10			
3	*2440.00 4880.00	82.9 AV 45.1 PK	74.0	-28.9	1.00 V 1.00 V	233	50.80 6.40	32.10 38.70			

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.



<b>EUT TEST CONDITION</b>		MEASUREMENT DETAIL		
CHANNEL Channel 39		FREQUENCY RANGE	1 ~ 25GHz	
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Cedric Wu	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	*2480.00	97.5 PK			1.37 H	175	65.30	32.20		
2	*2480.00	93.0 AV			1.37 H	175	60.80	32.20		
3	2483.50	57.7 PK	74.0	-16.3	1.38 H	177	25.50	32.20		
4	2483.50	45.3 AV	54.0	-8.7	1.38 H	177	13.10	32.20		
5	4960.00	47.0 PK	74.0	-27.0	1.00 H	125	8.10	38.90		
6	4960.00	33.9 AV	54.0	-20.1	1.00 H	125	-5.00	38.90		
		ANTENNA	A POLARIT	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M			
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	*2480.00	90.1 PK			1.00 V	299	57.90	32.20		
2	*2480.00	86.3 AV			1.00 V	299	54.10	32.20		
3	2483.50	57.1 PK	74.0	-16.9	1.00 V	296	24.90	32.20		
4	2483.50	44.9 AV	54.0	-9.1	1.00 V	296	12.70	32.20		
5	4000.00	10.0 511	74.0	07.0	4.00.17	055	7.00	20.00		
5	4960.00	46.2 PK	74.0	-27.8	1.00 V	255	7.30	38.90		

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.



#### **BELOW 1GHz WORST-CASE DATA:**

<b>EUT TEST CONDITION</b>		MEASUREMENT DETAIL			
CHANNEL Channel 39		FREQUENCY RANGE	Below 1000MHz		
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak		
ENVIRONMENTAL CONDITIONS	127deg (* 71%RH		Cedric Wu		
TEST MODE	Α				

		ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)			
1	99.84	19.4 QP	43.5	-24.1	1.00 H	183	38.20	-18.80			
2	140.58	25.1 QP	43.5	-18.4	1.25 H	163	40.00	-14.90			
3	433.52	22.7 QP	46.0	-23.3	1.75 H	52	32.30	-9.60			
4	544.10	26.3 QP	46.0	-19.7	1.25 H	85	34.20	-7.90			
5	637.22	26.2 QP	46.0	-19.8	1.00 H	64	31.90	-5.70			
6	774.96	28.6 QP	46.0	-17.4	1.00 H	207	31.60	-3.00			
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M				
NO	FREQ.	EMISSION	LINAIT	MARGIN ANTENNA TABLE RAW (dB) HEIGHT ANGLE VALUE				CORRECTION			
NO.	(MHz)	LEVEL (dBuV/m)	LIMIT (dBuV/m)		HEIGHT (m)	ANGLE (Degree)	VALUE (dBuV)	FACTOR (dB/m)			
<b>NO.</b>											
	(MHz)	(dBuV/m)	(dBuV/m)	(dB)	(m)	(Degree)	(dBuV)	(dB/m)			
1	(MHz) 35.82	(dBuV/m) 26.3 QP	(dBuV/m)	(dB) -13.7	(m) 1.25 V	<b>(Degree)</b> 125	(dBuV) 41.30	(dB/m) -15.00			
1 2	(MHz) 35.82 105.66	(dBuV/m) 26.3 QP 19.0 QP	(dBuV/m) 40.0 43.5	(dB) -13.7 -24.5	(m) 1.25 V 1.00 V	(Degree) 125 177	(dBuV) 41.30 37.00	(dB/m) -15.00 -18.00			
1 2 3	(MHz) 35.82 105.66 427.70	(dBuV/m) 26.3 QP 19.0 QP 23.2 QP	(dBuV/m) 40.0 43.5 46.0	-13.7 -24.5 -22.8	(m) 1.25 V 1.00 V 1.50 V	(Degree) 125 177 3	(dBuV) 41.30 37.00 32.80	(dB/m) -15.00 -18.00 -9.60			

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value



EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL Channel 39		FREQUENCY RANGE	Below 1000MHz		
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak		
ENVIRONMENTAL CONDITIONS	27deg. C, 71%RH	TESTED BY	Cedric Wu		
TEST MODE	В				

		ANTENNA	POLARITY	& TEST DIS	TANCE: HO	RIZONTAL	AT 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	159.98	18.0 QP	43.5	-25.5	1.00 H	242	31.90	-13.90
2	322.94	19.7 QP	46.0	-26.3	1.49 H	50	31.60	-11.90
3	526.64	23.7 QP	46.0	-22.3	1.25 H	235	31.70	-8.00
4	679.90	26.9 QP	46.0	-19.1	1.25 H	249	31.90	-5.00
5	885.54	29.2 QP	46.0	-16.8	1.49 H	295	30.70	-1.50
6	928.22	30.0 QP	46.0	-16.0	1.00 H	157	30.50	-0.50
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	62.98	20.8 QP	40.0	-19.2	1.25 V	26	35.60	-14.80
2	322.94	19.2 QP	46.0	-26.8	1.50 V	180	31.10	-11.90
3	549.92	24.4 QP	46.0	-21.6	1.75 V	311	32.00	-7.60
4	687.66	26.4 QP	46.0	-19.6	1.50 V	17	31.40	-5.00
5	800.18	28.8 QP	46.0	-17.2	1.00 V	327	31.60	-2.80
6	889.42	30.1 QP	46.0	-15.9	1.00 V	8	31.60	-1.50

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value



#### 4.2 CONDUCTED EMISSION MEASUREMENT

#### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)			
	Quasi-peak	Average		
0.15 ~ 0.5	66 to 56	56 to 46		
0.5 ~ 5	56	46		
5 ~ 30	60	50		

**NOTE**: 1. The lower limit shall apply at the transition frequencies.

- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.2.2 TEST INSTRUMENTS

Tested date: May 28, 2013

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Nov. 09, 2012	Nov. 08, 2013
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 28, 2012	Dec. 27, 2013
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 21, 2012	Dec. 20, 2013
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 06, 2012	Jul. 05, 2013
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 2.
- 3. The VCCI Site Registration No. is C-2047.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) was not recorded.


**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.



#### 4.2.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.




#### 4.2.7 TEST RESULTS

#### **CONDUCTED WORST CASE DATA:**

PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq.	Corr.	Readin	g Value	Emis Le	ssion vel	Lir	nit	Mar	gin
NO	Factor	[dB	(uV)]	[dB	(uV)]	[dB	(uV)]	(d	B)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.20721	0.20	28.43	19.60	28.63	19.80	63.32	53.32	-34.69	-33.52
2	0.46620	0.23	25.36	20.24	25.59	20.47	56.58	46.58	-30.99	-26.11
3	1.20936	0.30	20.32	9.42	20.62	9.72	56.00	46.00	-35.38	-36.28
4	3.51942	0.38	23.97	14.59	24.35	14.97	56.00	46.00	-31.65	-31.03
5	8.19921	0.46	27.81	21.79	28.27	22.25	60.00	50.00	-31.73	-27.75
6	9.76954	0.49	26.82	21.11	27.31	21.60	60.00	50.00	-32.69	-28.40

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq.	Corr.	Corr. Reading Value Emission Level		Limit		Margin			
NO		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.46183	0.27	43.93	39.23	44.20	39.50	56.66	46.66	-12.46	-7.16
2	0.68654	0.27	33.62	28.05	33.89	28.32	56.00	46.00	-22.11	-17.68
3	1.28650	0.28	35.23	28.03	35.51	28.31	56.00	46.00	-20.49	-17.69
4	2.75144	0.37	28.25	22.46	28.62	22.83	56.00	46.00	-27.38	-23.17
5	3.56092	0.42	29.08	24.32	29.50	24.74	56.00	46.00	-26.50	-21.26
6	6.88534	0.51	32.81	28.05	33.32	28.56	60.00	50.00	-26.68	-21.44

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	В		

No	Freq. Corr. Factor		Reading Value			Emission Level		Limit		Margin	
NO			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)		
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.24220	0.20	34.76	27.46	34.96	27.66	62.02	52.02	-27.06	-24.36	
2	1.47656	0.30	31.27	21.46	31.57	21.76	56.00	46.00	-24.43	-24.24	
3	2.49609	0.34	31.86	20.74	32.20	21.08	56.00	46.00	-23.80	-24.92	
4	4.20169	0.40	35.71	23.02	36.11	23.42	56.00	46.00	-19.89	-22.58	
5	6.26172	0.43	31.89	26.10	32.32	26.53	60.00	50.00	-27.68	-23.47	
6	9.36200	0.48	31.12	25.55	31.60	26.03	60.00	50.00	-28.40	-23.97	

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	В		

Na	Freq.	Corr. Factor	Readin	g Value		ssion vel	Lir	nit	Mar	gin	
No	Factor		[dB	dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.44034	0.27	38.77	34.08	39.04	34.35	57.06	47.06	-18.02	-12.71	
2	0.68186	0.27	34.59	29.19	34.86	29.46	56.00	46.00	-21.14	-16.54	
3	0.95597	0.26	32.00	25.69	32.26	25.95	56.00	46.00	-23.74	-20.05	
4	2.25788	0.34	32.38	25.41	32.72	25.75	56.00	46.00	-23.28	-20.25	
5	4.10294	0.45	32.58	24.79	33.03	25.24	56.00	46.00	-22.97	-20.76	
6	7.08069	0.51	35.84	30.83	36.35	31.34	60.00	50.00	-23.65	-18.66	

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.





#### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST SETUP



#### 4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 TEST PROCEDURE

- 1. Set resolution bandwidth (RBW) = 100kHz
- 2. Set the video bandwidth (VBW)  $\geq$  3 x RBW, Detector = Peak.
- 3. Trace mode = max hold.
- 4. Sweep = auto couple.
- 5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



# 4.3.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL	
0	2402	0.67	0.5	PASS	
19	2440	0.68	0.5	PASS	
39	2480	0.68	0.5	PASS	




#### 4.4 CONDUCTED OUTPUT POWER

#### 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz: 1 Watt (30dBm)

#### 4.4.2 TEST SETUP



#### 4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

#### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

#### 4.4.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
0	2402	0.925	-0.34	30	PASS
19	2440	0.966	-0.15	30	PASS
39	2480	0.798	-0.98	30	PASS




#### 4.5 POWER SPECTRAL DENSITY MEASUREMENT

#### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

#### 4.5.2 TEST SETUP



#### 4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 4.5.4 TEST PROCEDURE

- a. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
- b. Set the video bandwidth (VBW)  $\geq$  3 x RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

#### 4.5.7 TEST RESULTS

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-15.62	8	PASS
19	2440	-15.63	8	PASS
39	2480	-16.46	8	PASS



#### 4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

#### 4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

#### 4.6.2 TEST SETUP



#### 4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 4.6.4 TEST PROCEDURE

#### **MEASUREMENT PROCEDURE REF**

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



#### **MEASUREMENT PROCEDURE OOBE**

- 1. Set RBW = 100 kHz.
- 2. Set VBW ≥ 300 kHz.
- 3. Set span to encompass the spectrum to be examined
- 4. Detector = peak.
- 5. Trace Mode = max hold.
- 6. Sweep = auto couple.

#### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6


#### 4.6.7 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

34 of 38



#### 4.6.8 TEST RESULTS





## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

5. THOTOGRAPHS OF THE TEST CONFIGURATION
Please refer to the attached file (Test Setup Photo).



# 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:Hsin Chu EMC/RF Lab:Tel: 886-2-26052180Tel: 886-3-5935343Fax: 886-2-26051924Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

37 of 38



# 7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---