



A D T

RF EXPOSURE REPORT (FOR WLAN & BLUETOOTH)

REPORT NO.: SA120327C08-1

MODEL NO.: F-10D

FCC ID: VQK-F10D

RECEIVED: Mar 27, 2012

TESTED: Apr. 27 ~ May 09, 2012

ISSUED: May 17, 2012

APPLICANT: FUJITSU LIMITED

ADDRESS: 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki
211-8588, Japan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New
Taipei City, Taiwan (R.O.C.)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 4 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product, certification, approval, or endorsement by any government agency. The test results in the report only apply to the tested sample.



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA120327C08-1	Original release	May 17, 2012



A D T

1. CERTIFICATION

PRODUCT: Mobile Phone

MODEL: F-10D

BRAND: Xi

APPLICANT: FUJITSU LIMITED

TESTED: Apr. 27 ~ May 09, 2012

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 2 (Section 2.1093)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment (model: F-10D) have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : , **DATE:** May 17, 2012
Polly Chien / Specialist

APPROVED BY : , **DATE:** May 17, 2012
Gary Chang / Technical Manager

2. REDUCED CONDITION FOR SAR

When output power is $\leq 60/f(\text{GHz})$ mW, SAR evaluation is not required.

3. MAXIMUM MEASURED POWER OF EUT

Maximum measured transmitter power:

Mode	Frequency band (MHz)	Conducted power (dBm)	Conducted power (mW)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)
WiFi	2412~2462	12.63	18.323	-9.6	3.03	2.00
	5180~5240	9.28	8.472	-6.9	2.38	1.73
	5260~5320	9.48	8.872	-7.0	2.48	1.77
	5500~5700	9.49	8.892	-6.5	2.99	1.99
BT EDR	2402~2480	8.27	6.714	-9.6	-1.33	0.74
BT LE	2402~2480	7.63	5.79	-9.6	-1.97	0.64

4. CONCLUSION

No SAR evaluation is required since output power of EUT is less than threshold of SAR.