

TEST REPORT

No. 2009TAR014

for

Shenzhen Sang Fei Consumer Communications Co.,Ltd.

850/900/1800/1900 GSM/GPRS Mobile Phone

Type: Xenium X810

with

Hardware Version: PR1

Software Version: XFLAT2_M6229X_081205_V10

Issued Date: Apr 1st, 2009

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DAT-P-114/01-01

FCC 2.948 Listed: No.733176
IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Information Industry

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100083.

Tel:+86(0)10-62303288-2105, Fax:+86(0)10-62304793 Email:welcome@emcite.com. www.emcite.com
©Copyright. All rights reserved by TMC Beijing.



CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION	4
2.1. APPLICANT INFORMATION	4
2.2. MANUFACTURER INFORMATION	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. GENERAL DESCRIPTION	6
4. REFERENCE DOCUMENTS	6
4.1. REFERENCE DOCUMENTS FOR TESTING	
5. LABORATORY ENVIRONMENT	
6. SUMMARY OF TEST RESULTS	
7. TEST EQUIPMENTS UTILIZED	
ANNEX A: MEASUREMENT RESULTS	
A.1 OUTPUT POWER (§22.913(A)/§24.232(B))	
A.2 EMISSION LIMT (§2.1051/§24.238)	
A.3 CONDUCTED EMISSION	
A.4 FREQUENCY STABILITY (§2.1055/§24.235)	
A.5 OCCUPIED BANDWIDTH (§2.1049(H)(I))	29
A.6 EMISSION BANDWIDTH (§22.917(B)/§24.238(B))	37
A.7 BAND EDGE COMPLIANCE	
A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)	49



1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MII Address: No 52, Huayuan beilu, Haidian District, Beijing, P.R.China

Postal Code: 100083

Telephone: 00861062303288 Fax: 00861062304793

1.2. <u>Testing Environment</u>

Normal Temperature: $15-35^{\circ}$ C Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: Jan 5,2009
Testing End Date: Mar 31,2009

1.4. Signature

登略刚

Zi Xiaogang

(Prepared this test report)

Sun Xiangqian

(Reviewed this test report)

Lu Bingsong

附城村

Deputy Director of the laboratory

(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: Shenzhen Sang Fei Consumer Communications Co.,Ltd.

Address /Post:

11 Science & Technology Rd., Shenzhen Hi-tech Industrial Park,

Nanshan District, Shenzhen 518057

City: Shenzhen
Postal Code: 518057
Country: China

Telephone: 0755-26633217 Fax: 0755-26635272

2.2. Manufacturer Information

Company Name: Shenzhen Sang Fei Consumer Communications Co.,Ltd.

11 Science & Technology Rd., Shenzhen Hi-tech Industrial Park,

Address /Post:

Nanshan District, Shenzhen 518057

City: Shenzhen
Postal Code: 518057
Country: China

Telephone: 0755-26633217 Fax: 0755-26635272



3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description 850/900/1800/1900 GSM/GPRS Mobile Phone

Model Xenium X810 FCC ID VQRCTX810

Frequency GSM 850MHz; PCS 1900MHz

Antenna Internal

Power supply Battery or Charger (AC Adaptor)

Output power 25.0 dBm maximum EIRP measured for PCS1900

Extreme vol. Limits 3.5VDC to 4.2VDC (nominal: 3.7 VDC)

Extreme temp. Tolerance -30°C to +50°C

Note: Photographs of EUT are shown in ANNEX A of this test report. Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MII of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID* SN or IMEI HW Version SW Version

N06 351675039999960 PR1 XFLAT2_M6229X_081205_V10

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	GY100000216
AE2	Travel Adapter	1
AE3	Headset	1

AE1

Model AB1050DWM

Manufacturer Haerbin Coslight power CO.,LTD

Capacitance 1050mAh Nominal Voltage 3.7V

AE2

Model DSA-5W-05 FUS 050065 Manufacturer DeeVan Enterprise Co.,Ltd

Length of DC line 120cm

AE3

Model ED-D867

Manufacturer Shenzhen Sang Fei Consumer Communications Co.,Ltd.

Length of line 160cm

^{*}EUT ID: is used to identify the test sample in the lab internally.

^{*}AE ID: is used to identify the test sample in the lab internally.



3.4. General Description

The Equipment Under Test (EUT) is a model of 850/900/1800/1900 GSM/GPRS Mobile Phone with integrated antenna. It consists of Hand Telephone Set and normal options: lithium battery, charger and headset.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.06
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.06
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment	2004
	Measurement and Performance Standards	
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from	2003
	Low-Voltage Electrical and Electronic Equipment in the	
	Range of 9 kHz to 40 GHz	

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters × 17meters × 10meters) did not exceed following limits along the EMC testing:

_ 3	
Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C	
Relative humidity Min. =30 %, Max. = 60 %		
Shielding effectiveness	> 110 dB	
Electrical insulation	> 10 kΩ	
Ground system resistance	< 0.5 Ω	



Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 $^{\circ}$ C, Max. = 30 $^{\circ}$ C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters × 3.08 meters × 3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C	
Relative humidity Min. = 30 %, Max. = 60 %		
Shielding effectiveness	rectiveness > 110 dB	
Electrical insulation $> 10 \text{ k}\Omega$		
Ground system resistance	< 0.5 Ω	
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz	

6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(b)	Р
2	Emission Limit	2.1051/22.917/24.238	Р
3	Conducted Emission	15.107/207	Р
4	Frequency Stability	2.1055/24.235	Р
5	Occupied Bandwidth	2.1049(h)(i)	Р
6	Emission Bandwidth	22.917(b)/24.238(b)	Р
7	Band Edge Compliance	22.917(b)/24.238(b)	Р
8	Conducted Spurious Emission	2.1057/22.917/24.238	Р

7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESS	847151/015	R&S	2009-10-30
2	Test Receiver	ESI40	831564/002	R&S	2010-2-11
3	BiLog Antenna	3142B	9908-1403	EMCO	2010-1-16
4	BiLog Antenna	3142B	9908-1405	EMCO	2009-9-19
5	Signal Generator	SMT06	831285/005	R&S	2009-12-26
6	Signal Generator	SMP04	100070	R&S	2009-4-20
7	LISN	ESH2-Z5	829991/012	R&S	2009-8
8	Spectrum Analyzer	FSU26	200030	R&S	2009-6-18



9	Universal Radio Communication Tester	CMU200	100680	R&S	2009-8-23
10	Dual-Ridge Waveguide Horn Antenna	3115	9906-5827	EMCO	2010-3
11	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2010-3
12	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2010-3
13	Climatic chamber	PL-2G	343074	ESPEC	2009-5-15



ANNEX A: MEASUREMENT RESULTS

<u>A.1 OUTPUT POWER</u> (§22.913(a)/§24.232(b))

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT.

In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak)

These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band;824.4MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

GSM850

Limit

	Power step	Nominal Peak output power (dBm)	Tolerance (dB)
GSM	5	33dBm(2W)	± 2
GPRS	3	33dBm(2W)	± 2
EGPRS	6	27dBm(0.5W)	± 2

Measurement result

GSM

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	5	31.20
836.6	5	31.32
848.8	5	31.29

GPRS

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	3	30.76
836.6	3	30.78
848.8	3	30.77



EGPRS

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	6	25.94
836.6	6	26.14
848.8	6	25.95

PCS1900

Limit

	Power step Nominal Peak output power (dBm)		Tolerance (dB)
GSM	0	30dBm(1W)	± 2
GPRS	3	30dBm(1W)	±2
EGPRS	5	26 dBm(0.4W)	±2

Measurement result

GSM

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	0	27.70
1880.0	0	27.75
1909.8	0	27.63

GPRS

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	3	27.43
1880.0	3	27.48
1909.8	3	27.30

EGPRS

Frequency(MHz)	Power Step Peak output power(d	
1850.2	5	24.84
1880.0	5	24.79
1909.8	5	24.60

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."



A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

- 1. In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to the input of the dipole, and the power received (P_r) at the chamber's probe antenna is recorded.
- 2. The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as A_{Rpl} =Pin + 2.15 Pr. The A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss.

The measurement results are obtained as described below:

Power=P_{Mea}+A_{Rpl}

- 3. The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
- 4. From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
- 5. The EUT is then put into continuously transmitting mode at its maximum power level.
- 6. Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.
- 7. This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (Pin).
- 8. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi..

GSM 850-ERP 22.913(a)

Limits

	Power Step Burst Peak ERP (dBm	
GSM	5	≤38.45dBm (7W)
GPRS	3	≤38.45dBm (7W)
EGPRS	6	≤38.45dBm (7W)

Measurement result

GSM

Frequency(MHz)	Power Step	Peak ERP(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Polarization
824.2	5	24.02	45.95	-21.93	Horizontal
836.6	5	24.39	45.98	-21.59	Horizontal
848.8	5	24.66	45.82	-21.16	Horizontal

GPRS

Frequency(MHz)	Power Step	Peak ERP(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Polarization
824.2	3	24.26	45.95	-21.69	Horizontal
836.6	3	24.57	45.98	-21.41	Horizontal
848.8	3	24.83	45.82	-20.99	Horizontal

©Copyright. All rights reserved by TMC Beijing.



EGPRS

Frequency(MHz)	Power Step	Peak ERP(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Polarization
824.2	6	19.96	45.95	-25.99	Horizontal
836.6	6	20.69	45.98	-25.29	Horizontal
848.8	6	20.76	45.82	-25.06	Horizontal

ANALYZER SETTINGS: RBW = VBW = 3MHz

PCS1900-EIRP 24.232(b)

Limits

	Power Step Burst Peak EIRP (dBm)	
GSM	0	≤33dBm (2W)
GPRS	3	≤33dBm (2W)
EGPRS	5	≤33dBm (2W)

Measurement result

GSM

Frequency(MHz)	Power Step	Peak EIRP(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Polarization
1850.2	0	24.26	47.11	-22.85	Horizontal
1880.0	0	24.57	47.37	-22.80	Horizontal
1909.8	0	24.83	47.54	-22.71	Horizontal

GPRS

Frequency(MHz)	Power Step	Peak EIRP(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Polarization
1850.2	3	24.79	47.11	-22.32	Horizontal
1880.0	3	25.00	47.37	-22.37	Horizontal
1909.8	3	24.82	47.54	-22.72	Horizontal

EGPRS

Frequency(MHz)	Power Step	Peak EIRP(dBm)	A _{Rpl} (dBm)	$P_{Mea}(dBm)$	Polarization
1850.2	5	23.02	47.11	-24.09	Horizontal
1880.0	5	22.55	47.92	-25.37	Vertical
1909.8	5	22.96	47.54	-24.58	Horizontal

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.2 EMISSION LIMT (§2.1051/§24.238)

A.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the




PCS1900 band, GSM850 band.

The procedure of radiated spurious emissions is as follows:


a) Pre-calibration

With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, RSE=Rx (dBuV) +CL (dB) +SA (dB) +Gain (dBi) -107 (dBuV to dBm) The SA is calibrated using following setup.



b) EUT test

EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



A.2.2 Measurement Limit

Sec. 24.238 Emission Limits.

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is



13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz) ,GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss.

The measurement results are obtained as described below:

Power=P_{Mea}+A_{Rpl}

GSM Mode Channel 128/824.2MHz

Frequency(GHz)	Power(dBm)	A _{Rpl} (dBm)	$P_{Mea}(dBm)$	Limit (dBm)	Polarity
1.6480	-43.97	-2.65	-41.32	-13	Horizontal
2.4725	-40.23	0.65	-40.88	-13	Vertical
3.2970	-47.22	0.45	-47.67	-13	Vertical
4.9450	-40.12	1.95	-42.07	-13	Horizontal

GSM Mode Channel 190/836.6MHz

Frequency(GHz)	Power(dBm)	A _{Rpl} (dBm)	$P_{Mea}(dBm)$	Limit (dBm)	Polarity
1.6735	-45.52	-2.85	-42.67	-13	Horizontal
2.5095	-41.74	-0.25	-41.49	-13	Horizontal
3.3465	-46.95	0.55	-47.5	-13	Vertical
4.1830	-46.95	2.45	-49.4	-13	Vertical

GSM Mode Channel 251/848.8MHz

Frequency(GHz)	Power(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
1.6975	-46.936	-2.85	-44.086	-13	Horizontal
2.5460	-45.145	0.35	-45.495	-13	Vertical
3.3945	-45.732	0.25	-45.982	-13	Vertical
5.0925	-43.723	1.75	-45.473	-13	Horizontal



GSM Mode Channel 512/1850.2MHz

Frequency(GHz)	Power(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
5.5505	-45.27	5.0	-50.27	-13	Vertical
9.2510	-43.56	10.5	-54.06	-13	Vertical
12.9510	-41.40	12.3	-53.7	-13	Vertical
14.8020	-26.00	15.2	-41.2	-13	Vertical

GSM Mode Channel 661/1880.0MHz

Frequency(GHz)	Power(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
5.6400	-48.10	5.2	-53.3	-13	Vertical
9.4005	-45.54	11.8	-57.34	-13	Vertical
13.1598	-39.38	14.3	-53.68	-13	Vertical
15.0420	-38.84	14.9	-53.74	-13	Horizontal

GSM Mode Channel 810/1909.8MHz

Frequency(GHz)	Power(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
7.6390	-47.45	8.8	-56.25	-13	Vertical
13.3686	-36.66	12.4	-49.06	-13	Horizontal




GSM 850

A.2.3.1 RADIATED SPURIOUS EMISSIONS-Channel 128: 30MHz -1GHz

Radiated spurious emission limit :-13dBm.


NOTE: peak above the limit line is the Carrier frequency @ ch-128



A.2.3.2 RADIATED SPURIOUS EMISSIONS-Channel 190: 30MHz - 1GHz

Radiated spurious emission limit :-13dBm.

NOTE: peak above the limit line is the Carrier frequency @ ch-190







A.2.3.3 RADIATED SPURIOUS EMISSIONS-Channel 251: 30MHz - 1GHz

Radiated spurious emission limit :-13dBm.

NOTE: peak above the limit line is the Carrier frequency @ ch-251




A.2.3.4 RADIATED SPURIOUS EMISSIONS-Channel 128: 1GHz – 10GHz Radiated spurious emission limit :-13dBm.






A.2.3.5 RADIATED SPURIOUS EMISSIONS-Channel 190: 1GHz – 10GHz Radiated spurious emission limit :-13dBm.




A.2.3.6 RADIATED SPURIOUS EMISSIONS-Channel 251: 1GHz – 10GHz Radiated spurious emission limit :-13dBm.






A.2.3.7 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 30MHz – 1GHz Radiated spurious emission limit:-13dBm.



A.2.3.8 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 1GHz – 10GHz Radiated spurious emission limit:-13dBm.






PCS 1900

A.2.3.9 RADIATED SPURIOUS EMISSIONS-Channel 512: 30MHz - 2GHz

Radiated spurious emission limit :-13dBm.


NOTE: peak above the limit line is the Carrier frequency @ ch-512



A.2.3.10 RADIATED SPURIOUS EMISSIONS-Channel 661: 30MHz - 2GHz

Radiated spurious emission limit :-13dBm.

NOTE: peak above the limit line is the Carrier frequency @ ch-661







A.2.3.11 RADIATED SPURIOUS EMISSIONS-Channel 810: 30MHz - 2GHz

Radiated spurious emission limit :-13dBm.

NOTE: peak above the limit line is the Carrier frequency @ ch-810




A.2.3.12 RADIATED SPURIOUS EMISSIONS-Channel 512: 2GHz – 18GHz Radiated spurious emission limit :-13dBm.






A.2.3.13 RADIATED SPURIOUS EMISSIONS-Channel 661: 2GHz – 18GHz Radiated spurious emission limit :-13dBm.



A.2.3.14 RADIATED SPURIOUS EMISSIONS-Channel 810: 2GHz – 18GHz Radiated spurious emission limit :-13dBm.







A.2.3.15 Radiated spurious emission (18GHz-20GHz)

Radiated spurious emission limit :-13dBm.

Note: This plot is valid for low, mid & high channels. It is same as the floor noise.




A.2.3.16 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 30MHz – 2GHz Radiated spurious emission limit :-13dBm.






A.2.3.17 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 2GHz – 18GHz Radiated spurious emission limit:-13dBm.



A.2.3.18 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 18GHz – 20GHz Radiated spurious emission limit :-13dBm.

Note: It is same as the floor noise.






<u>A.3 CONDUCTED EMISSION</u> (§15.107§15.207)

The measurement procedure in ANSI C63.4-1003 is used. Conducted Emission is measured with travel charger.

A.3.1 Limit


Frequency of Emission (MHz)	Conducted Limit (dBµV)			
	Quasi -Peak	Average		
0.15 – 0.5	66 to 56*	56 to 46*		
0.5 – 5	56	46		
5 – 30	60	50		
* Decreases with logarithm of the frequency				

A.3.2 Measurement result GSM850MHz






PCS 1900MHz



MP3





A.4 FREQUENCY STABILITY (§2.1055/§24.235)

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -30°C.
- 3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900, channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10℃ increments from -30℃ to +50℃. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at +50°C.
- 7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

A.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the



fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.4.3 Measurement results

GSM 850

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	22	0.024
3.7	14	0.017
4.2	17	0.020

Frequency Error vs Temperature

Troquency = 11 or to rempera	141.0	
$temperature(^{\circ}\!$	Frequency error(Hz)	Frequency error(ppm)
-30	29	0.035
-20	26	0.031
-10	22	0.026
0	22	0.026
10	21	0.024
20	18	0.021
30	17	0.020
40	24	0.029
50	30	0.036

PCS 1900

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	35	0.019
3.7	28	0.015
4.2	26	0.014

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	45	0.024
-20	41	0.022
-10	35	0.018
0	31	0.016
10	27	0.014
20	25	0.013
30	30	0.016
40	36	0.019
50	42	0.022



A.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))


A.5.1 Occupied Bandwidth Results

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the USPCS frequency band. The table below lists the measured -20dBc BW (99%). Spectrum analyzer plots are included on the following pages.

GSM 850(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
824.2	245.192
836.6	251.603
848.8	241.987


GSM 850 Channel 128-Occupied Bandwidth (99%)



Date: 21.JAN.2009 07:25:50




Channel 190-Occupied Bandwidth (99%)



Date: 21.JAN.2009 07:26:22

Channel 251-Occupied Bandwidth (99%)



Date: 21.JAN.2009 07:27:00




GPRS 850(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
824.2	243.590
836.6	245.192
848.8	245.192

GPRS 850


Channel 128-Occupied Bandwidth (99%)



Date: 21.JAN.2009 08:09:55




Channel 190-Occupied Bandwidth (99%)



Date: 21.JAN.2009 08:09:17

Channel 251-Occupied Bandwidth (99%)




Date: 21.JAN.2009 08:08:46



PCS 1900(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	245.192
1880.0	243.590
1909.8	245.192


PCS 1900 Channel 512-Occupied Bandwidth (99%)



Date: 21.JAN.2009 07:23:38




Channel 661-Occupied Bandwidth (99%)



Date: 21.JAN.2009 07:24:19

Channel 810-Occupied Bandwidth (99%)




Date: 21.JAN.2009 07:24:58



GPRS 1900(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	241.987
1880.0	245.192
1909.8	246.795


GPRS 1900 Channel 512-Occupied Bandwidth (99%)



Date: 21.JAN.2009 08:10:54




Channel 661-Occupied Bandwidth (99%)



Date: 21.JAN.2009 08:11:42

Channel 810-Occupied Bandwidth (99%)



Date: 21.JAN.2009 08:12:22



A.6 EMISSION BANDWIDTH (§22.917(b)/§24.238(b))


A.6.1Emission Bandwidth Results

Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the PCS1900 band and GSM850 band. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

GSM 850(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)		
824.2	309.295		
836.6	307.692		
848.8	306.090		


GSM 850 Channel 128-Occupied Bandwidth (-26dBc BW)



Date: 21.JAN.2009 07:29:07




Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 21.JAN.2009 07:28:22

Channel 251-Occupied Bandwidth (-26dBc BW)



Date: 21.JAN.2009 07:27:40




GPRS 850(-26dBc)

Frequency(MHz)	Occupied Bandwidth (–26dBc BW)(kHz)		
824.2	309.295		
836.6	306.090		
848.8	307.692		

GPRS 850


Channel 128-Occupied Bandwidth (-26dBc BW)



Date: 21.JAN.2009 08:14:54




Channel 190-Occupied Bandwidth (-26dBc BW)



Date: 21.JAN.2009 08:15:28

Channel 251-Occupied Bandwidth (-26dBc BW)




Date: 21.JAN.2009 08:16:05



PCS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)		
1850.2	307.692		
1880.0	306.090		
1909.8	304.487		


PCS 1900 Channel 512-Occupied Bandwidth (-26dBc BW)



Date: 21.JAN.2009 07:29:42




Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 21.JAN.2009 07:30:29

Channel 810-Occupied Bandwidth (-26dBc BW)



Date: 21.JAN.2009 07:31:18




GPRS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)		
1850.2	310.897		
1880.0	309.294		
1909.8	307.692		

GPRS 1900


Channel 512-Occupied Bandwidth (-26dBc BW)



Date: 21.JAN.2009 08:14:14




Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 21.JAN.2009 08:13:34

Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 21.JAN.2009 08:13:01




A.7 BAND EDGE COMPLIANCE (§22.917(b)/§24.238(b))

GSM850 LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 21.JAN.2009 07:41:04


HIGH BAND EDGE BLOCK-C (GSM850) -Channel 251



Date: 21.JAN.2009 07:40:26




GPRS 850 LOW BAND EDGE BLOCK-A (GPRS 850)-Channel 128



Date: 21.JAN.2009 07:55:46


HIGH BAND EDGE BLOCK-C (GPRS 850) -Channel 251



Date: 21.JAN.2009 07:57:04




PCS 1900 LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 21.JAN.2009 07:41:58


HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810



Date: 21.JAN.2009 07:42:52




GPRS 1900 LOW BAND EDGE BLOCK-A (GPRS-1900)-Channel 512



Date: 21.JAN.2009 07:57:52

HIGH BAND EDGE BLOCK-C (GPRS-1900) -Channel 810



Date: 21.JAN.2009 07:58:32



<u>A.8 CONDUCTED SPURIOUS EMISSION</u> (§2.1057/§22.917/§24.238)

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.
- 2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

GSM850 Transmitter

Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

PCS1900 Transmitter

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

A. 8.2 Measurement Limit

Sec. 24.238 Emission Limits.

(a) On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.




A. 8.3 Measurement result GSM850

Harmonic	Tx ch. 128 Freq. (MHz)	Level (dBm)	Tx ch. 190 Freq. (MHz)	Level (dBm)	Tx ch. Freq. (MHz) 251	Level (dBm)
2	1648.4	nf	1673.2	nf	1697.6	nf
3	2472.6	nf	2509.8	nf	2546.4	nf
4	3296.8	nf	3346.4	nf	3395.2	nf
5	4121	nf	4183	nf	4244	nf
6	4945.2	nf	5019.6	nf	5092.8	nf
7	5769.4	nf	5856.2	nf	5941.6	nf
8	6593.6	nf	6692.8	nf	6790.4	nf
9	7417.8	nf	7529.4	nf	7639.2	nf
10	8242	nf	8366	nf	8488	nf
nf: Noise floor						

A.8.3.1 Channel 128: 30MHz - 4GHz

Spurious emission limit -13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 21.JAN.2009 07:48:00



A.8.3.2 Channel 128: 4GHz - 10GHz

Spurious emission limit -13dBm.




Date: 21.JAN.2009 07:48:21

A.8.3.3 Channel 190: 30MHz - 4GHz

Spurious emission limit -13dBm

NOTE: peak above the limit line is the carrier frequency.




Date: 21.JAN.2009 07:49:22



A.8.3.4 Channel 190: 4GHz -10GHz

Spurious emission limit -13dBm




Date: 21.JAN.2009 07:48:55

A.8.3.5 Channel 251: 30MHz - 4GHz

Spurious emission limit -13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 21.JAN.2009 07:49:54



A.8.3.6 Channel 251: 4GHz - 10GHz


Spurious emission limit -13dBm.



Date: 21.JAN.2009 07:50:16

A.8.3.7 Idle mode: 30MHz - 4GHz

Spurious emission limit -13dBm.




Date: 21.JAN.2009 07:51:09



A.8.3.8 Idle mode: 4GHz - 10GHz

Spurious emission limit -13dBm.



Date: 21.JAN.2009 07:50:45




PCS1900

Harmonic	Tx ch. 512 Freq. (MHz)	Level (dBm)	Tx ch. 661 Freq. (MHz)	Level (dBm)	Tx ch. 810 Freq. (MHz)	Level (dBm)
2	3700.4	nf	3760	nf	3819.6	nf
3	5550.6	nf	5640	nf	5729.4	nf
4	7400.8	nf	7520	nf	7639.2	nf
5	9251.0	nf	9400	nf	9549.0	nf
6	11101.2	nf	11280	nf	11458.8	nf
7	12951.4	nf	13160	nf	13368.6	nf
8	14801.6	nf	15040	nf	15278.4	nf
9	16651.8	nf	16920	nf	17188.2	nf
10	18502.0	nf	18800	nf	19098.0	nf
nf: Noise floor						

A. 8.3.9 Channel 512: 30MHz - 4GHz

Spurious emission limit -13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 21.JAN.2009 07:46:43



A. 8.3.10 Channel 512: 4GHz - 20GHz

Spurious emission limit -13dBm.




Date: 21.JAN.2009 07:47:02

A. 8.3.11 Channel 661: 30MHz - 4GHz

Spurious emission limit -13dBm

NOTE: peak above the limit line is the carrier frequency.




Date: 21.JAN.2009 07:46:02



A. 8.3.12 Channel 661: 4GHz -20GHz

Spurious emission limit -13dBm




Date: 21.JAN.2009 07:45:30

A. 8.3.13 Channel 810: 30MHz - 4GHz

Spurious emission limit -13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 21.JAN.2009 07:44:18



A. 8.3.14 Channel 810: 4GHz - 20GHz


Spurious emission limit -13dBm.



Date: 21.JAN.2009 07:44:48

A. 8.3.15 Idle mode: 30MHz - 4GHz

Spurious emission limit -13dBm.




Date: 21.JAN.2009 07:52:04



A. 8.3.16 Idle mode: 4GHz - 20GHz

Spurious emission limit -13dBm.



Date: 21.JAN.2009 07:52:27

END OF REPORT