

Report No.:

**31551027.001**

Page 1 of 32

# Electromagnetic Compatibility

## Test Report

Tested To: FCC Part 15C

On

## BLE Device

## Model: nIO-BT



**900 Northrop Rd.  
Wallingford, CT 06492 USA**

Prepared by:

## TUV Rheinland of North America, Inc.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

**31551027.001**

Page 2 of 32

## Manufacturer's statement - attestation

The manufacturer; Sensor Switch, as the responsible party for the equipment tested, hereby affirms:

- a) That he has reviewed and concurs that the test shown in this report are reflective of the operational characteristics of the device for which certification is sought;
- b) That the device in this test report will be representative of production units;
- c) That all changes (in hardware and software/firmware) to the subject device will be reviewed.
- d) That any changes impacting the attributes, functionality or operational characteristics documented in this report will be communicated to the body responsible for approving (certifying) the subject equipment.

---

**Frank Pelliccio**

Printed name of official



---

Signature of official

---

900 Northrop Road  
Wallingford, CT 06492 USA  
Address

---

13 August 2015

Date

---

(203) 303-5447  
Telephone number

---

Frank.Pelliccio@acuitybrands.com  
Email address of official

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

**31551027.001**

Page 3 of 32

<b>Client:</b>	 An Acuity Brands Company 900 Northrop Rd. Wallingford, CT 06492 USA			Frank Pelliccio Ph: (203) 303-5447 Fax: Email: Frank.Pelliccio@acuitybrands.com
<b>Identification:</b>	BLE Device	<b>Serial No.:</b>	PRODUCTION PROTOTYPE	
<b>Test item:</b>	Model: nIO-BT	<b>Date tested:</b>	05 August 2015	
<b>Testing location:</b>	TUV Rheinland of North America 762 Park Avenue Youngsville, NC 27596-9470 U.S.A.		Tel: (919) 554-3668 Fax: (919) 554-3542	
<b>Test specification:</b>	<b>Emissions:</b> FCC Part 15, Subpart C; FCC Parts 15.207(a), FCC Parts 15.249(d), 15.209 and 15.215(c) FCC Part 15.249, FCC Parts 15.249(a) and 15.249(c), FCC Part 2.1093,			
<b>Test Result</b>	The above product was found to be <b>Compliant</b> to the above test standard(s)			
<i>tested by:</i> Mark Ryan	<i>reviewed by:</i> Michael Moranha			
<u>18 September 2015</u>	<u>Date</u>	<u>Signature</u>	<u>18 September 2015</u>	<u>Date</u>
<b>Other Aspects:</b>	None			
Abbreviations: OK, Pass, Compliant, Complies = passed Fail, Not Compliant, Does Not Comply = failed N/A = not applicable				
<b>FC</b>		<b>Industry Canada</b>		
<b>90552 and 100881</b>	<b>Testing Cert #3331.05</b>		<b>2932H-1 and 2932H-2</b>	

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

**TABLE OF CONTENTS**

<b>1 GENERAL INFORMATION .....</b>	<b>5</b>
1.1 SCOPE .....	5
1.2 PURPOSE .....	5
1.3 REVISION HISTORY.....	5
1.4 SUMMARY OF TEST RESULTS .....	6
<b>2 LABORATORY INFORMATION .....</b>	<b>7</b>
2.1 ACCREDITATIONS .....	7
2.2 MEASUREMENT UNCERTAINTY EMISSIONS .....	8
2.3 CALIBRATION TRACEABILITY .....	8
2.4 MEASUREMENT EQUIPMENT USED .....	9
<b>3 PRODUCT INFORMATION .....</b>	<b>9</b>
3.1 PRODUCT DESCRIPTION.....	9
3.2 EQUIPMENT MODIFICATIONS .....	9
3.3 TEST PLAN.....	9
<b>4 RADIATED EMISSIONS IN TRANSMIT MODE .....</b>	<b>10</b>
4.1 RADIATED EMISSIONS - FCC PARTS 15.249.....	10
4.2 CONDUCTED EMISSIONS ON AC MAINS – FCC 207(A).....	19
4.3 BAND EDGE REQUIREMENTS - FCC PART 15.249(D) .....	22
<b>5 RF EXPOSURE.....</b>	<b>27</b>
5.1 CLASSIFICATION.....	27
5.2 TEST RESULTS .....	27
<b>APPENDIX A .....</b>	<b>29</b>
<b>6 TEST PLAN.....</b>	<b>29</b>
6.1 GENERAL INFORMATION .....	29
6.2 EQUIPMENT UNDER TEST (EUT) DESCRIPTION .....	29
6.3 GENERAL PRODUCT INFORMATION.....	30
6.4 EUT TEST PROGRAM.....	31
6.5 MONITORING OF EUT DURING TESTING .....	31

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

## 1 General Information

### 1.1 Scope

This report is intended to document the status of conformance with the requirements of the required standards, based on the results of testing performed on 05 August 2015 on the BLE Device, Model No. nIO-BT, manufactured by Sensor Switch. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

### 1.2 Purpose

Testing was performed to evaluate the EMC performance of the EUT (Equipment Under Test) in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report.

### 1.3 Revision History

Revision	Date	Description of Revision
--	24 August 2015	Initial Release
A	18 September 2015	Corrected typos and added Test Setup Block Diagrams.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

31551027.001

Page 6 of 32

**1.4 Summary of Test Results**

<b>Applicant</b>	Sensor Switch 900 Northrop Rd. Wallingford, CT 06492 USA	<b>Tel</b>	(203) 303-5447	<b>Contac</b> <b>t</b>	Frank Pelliccio	
		<b>Fax</b>		<b>e-mail</b>	Frank.Pelliccio@acuitybrands.com	
<b>Description</b>		<b>Model</b>		nIO-BT		
<b>Serial Number</b>		<b>Test Voltage/Freq.</b>		5.0 VDC		
<b>Test Date Completed:</b>		<b>Test Engineer</b>		Mark Ryan		
Standards	Description	Severity Level or Limit			Worst-case Values	Test Result
FCC Part 15, Subpart C Standard	Radio Frequency Devices-Subpart C: Intentional Radiators	See called out parts below			See Below	Complies
FCC Part 15.249	Operation within the band 2400 to 2483.5 MHz	See called out parts below			See Below	Complies
FCC Parts 15.249(a) and 15.249(c)	Radiated Output Power for Fundamental and Harmonic Frequencies	Fund: Shall not exceed 50 mV/m at 3m Harmonics: Shall not exceed 500 $\mu$ V/m (0.5 mV/m) at 3m, (unrestricted bands)			90.89 dB $\mu$ V/m	Complies
FCC Parts 15.249(d), 15.209 and 15.215(c)	Out-of-Band Spurious Emissions and Band Edges (EUT in Transmit Mode)	Below the applicable limits			50.09 dB $\mu$ V	Complies
FCC Parts 15.207(a)	Conducted Emissions on AC Mains	150kHz - 30MHz			21.25 dB $\mu$ V	Complies
FCC Part 2.1093	RF Exposure and Antenna Gain Calculation	SAR or MPE Requirements			0.00007 mW/cm <sup>2</sup>	Complies

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

## 2 Laboratory Information

### 2.1 Accreditations

#### 2.1.1 US Federal Communications Commission

TUV Rheinland of North America located at 762 Park Avenue, Youngsville, NC 27596-9470 is accredited by the commission for performing testing services for the general public on a fee basis. This laboratory test facilities have been fully described in reports submitted to and accepted by the FCC (Registration No 90552 and 100881). The laboratory scope of accreditation includes: Title 47 CFR Part 15, and 18. The accreditation is updated every 3 years.

#### 2.1.2 ILAC / A2LA

The laboratory has been assessed and accredited by A2LA in accordance with ISO Standard 17025:2005 (Certificate Number: 3331.05, Master Code: 134288). The scope of laboratory accreditation includes emission and immunity testing. The accreditation is updated annually.

#### 2.1.3 Industry Canada

Registration No.: 2932H-1 The OATS has been accepted by Industry Canada to perform testing to 3 and to 10 meters, based on the test procedures described in ANSI C63.4-2009.

Registration No.: 2932H-2 The 5 meter chamber has been accepted by Industry Canada to perform testing to 3 meters, based on the test procedures described in ANSI C63.4-2009.

#### 2.1.4 Japan – VCCI

The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) is a group that consists of Information Technology Equipment (ITE) manufacturers and EMC test laboratories. The purpose of the Council is to take voluntary control measures against electromagnetic interference from Information Technology Equipment, and thereby contribute to the development of a socially beneficial and responsible state of affairs in the realm of Information Technology Equipment in Japan. TUV Rheinland at the 762 Park Ave. Youngsville, N.C 27596 address has been assessed and approved in accordance with the Regulations for Voluntary Control Measures. (Laboratory Registration No: A-0034).

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

### 2.1.5 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\text{Field Strength (dB}\mu\text{V/m)} = \text{RAW} - \text{AMP} + \text{CBL} + \text{ACF}$$

Where: RAW = Measured level before correction (dB $\mu$ V)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu\text{V/m} = 10^{\frac{\text{dB}\mu\text{V/m}}{20}}$$

#### Sample radiated emissions calculation @ 30 MHz

**Measurement +Antenna Factor–Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)**

$$25 \text{ dBuV/m} + 17.5 \text{ dB} - 20 \text{ dB} + 1.0 \text{ dB} = 23.5 \text{ dBuV/m}$$

### 2.2 Measurement Uncertainty Emissions

	$U_{\text{lab}}$	$U_{\text{cispr}}$
<b>Radiated Disturbance @ 10m</b>		
30 MHz – 1,000 MHz	3.3 dB	5.2 dB
<b>Conducted Disturbance @ Mains Terminals</b>		
150 kHz – 30 MHz	1.18 dB	3.6 dB
<b>Disturbance Power</b>		
30 MHz – 300 MHz	3.88 dB	4.5 dB

### 2.3 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Standard 17025:2005. Equipment calibration records are kept on file at the test facility.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

**Report No.:**
**31551027.001**
**Page 9 of 32**

## 2.4 Measurement Equipment Used

Equipment	Manufacturer	Model #	Serial/Inst #	Last Cal dd/mm/yy	Next Cal dd/mm/yy
Radiated Emissions (5 Meter Chamber)					
Receiver, EMI	Rohde & Schwarz	ESIB40	100043	19-Aug-14	19-Aug-15
Spectrum Analyzer	Agilent Tec.	E7405A	US39440161	20-Aug-14	20-Aug-15
Amplifier, preamp	Agilent Technologies	8449B	3008A01480	14-Aug-13	14-Aug-15
Ant. BiconiLog	Chase	CBL6140A	1108	16-Sep-13	16-Sep-15
Antenna Horn 1-18 GHz	EMCO	3115	5770	30-Dec-14	30-Dec-15
Antenna Horn 18-26.5 GHz	ATM	42-442-6/cal	G181104-01	31-Dec-14	31-Dec-15
Cable, Coax	MicroCaox	MKR300C-0-0-1200-500500	002	22-Aug-14	22-Aug-15
Cable, Coax	MicroCaox	MKR300C-0-1968-500310	005	22-Aug-14	22-Aug-15
Cable, Coax	MicroCaox	UFB29C-1-5905-50U-50U	009	22-Aug-14	22-Aug-15
3.0 GHz High Pass Filter	Bonn Electronik	BHF 3000	025155	14-Aug-13	14-Aug-15
Notch Filter	Micro-tronics	BRM50702	049	14-Aug-13	14-Aug-15
Conducted Emissions (AC/DC)					
Receiver, EMI	Rohde & Schwarz	ESCI 7	100917	19-Aug-14	19-Aug-15
Cable, Coax	Pasternack	RG-223	051	22-Aug-14	22-Aug-15
LISN 15-18 (NSLK 8126)	Schwarzbeck Mess-Electronik	NSLK 8126	003885	13-Aug-13	13-Aug-15
Transient Limiter	Schaffner	CFL-9206	1649	13-Aug-13	13-Aug-15
General Laboratory Equipment					
Meter, Multi & Thermocouple	Fluke	179	90580752	19-Aug-14	19-Aug-15
Meter, Temp/Humid/Barom	ExTech	SD700	Q677933	06-May-13	06-May-16
Meter, Temp/Humid/Barom	ExTech	SD700	Q677942	06-May-13	06-May-16

## 3 Product Information

### 3.1 Product Description

See Section Appendix A.

### 3.2 Equipment Modifications

No modifications were needed to bring product into compliance.

### 3.3 Test Plan

The EUT product information, test configuration, mode of operation, test types, test procedures, test levels, pass/failure criteria, in this report were carried out per the product test plan located in appendix A of this report

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

## 4 Radiated Emissions in Transmit mode

### 4.1 Radiated emissions - FCC Parts 15.249

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limits:

Fundamental Frequency: 2400 to 2483.5 MHz – 50 mV/m (94 dB  $\mu$ V/m) at 3m.

Harmonic Frequencies: 500  $\mu$ V/m (54 dB  $\mu$ V/m) at 3m.

Spurious Emissions: To the limits of FCC Part 15.209.

#### 4.1.1 Over View of Test

<b>Results</b>	<b>Complies</b> (as tested per this report)			<b>Date</b>	3 – 4 August 2015		
<b>Standard</b>	FCC Parts 15.205, 15.209, 15.215(c), 15.249(a), 15.249(c), 15.249(d)						
<b>Product Model</b>	nIO-BT			<b>Serial#</b>	Production Prototype		
<b>Test Set-up</b>	Tested in a 5m Semi Anechoic chamber, placed on a 1.0m x 1.5m non-conductive table 80cm above the ground plane on a turn-table.						
<b>EUT Powered By</b>	5.0 VDC	<b>Temp</b>	75° F	<b>Humidity</b>	43%	<b>Pressure</b>	1003 mbar
<b>Perf. Criteria</b>	(Below Limit)		<b>Perf. Verification</b>	Readings Under Limit			
<b>Mod. to EUT</b>	None		<b>Test Performed By</b>	Mark Ryan			

#### 4.1.2 Test Procedure

Testing was performed in accordance with 47 CFR Part 15 and ANSI C63.10:2009. These test methods are listed under the laboratory's A2LA Scope of Accreditation. This test measures the levels emanating from the EUT, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices.

#### 4.1.3 Deviations


Since all emissions outside the band are within the limits of FCC Part 15.209. The emissions shown below are also compliant with FCC Parts 15.205, 15.209, 15.215(c), 15.249(d).

#### 4.1.4 Final Test

All final radiated spurious emissions measurements were below (in compliance) the limits.

The worst –case emissions are shown below. All other emissions are on file at TUV Rheinland.

#### 4.1.5 Test Setup Block Diagram



The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

31551027.001

Page 11 of 32

#### 4.1.5.1 Final Graphs and Tabulated Data

Orientations:

Emission Freq (MHz)	ANT Polar	ANT Pos (m)	Table Pos (deg)	FIM Value (dB $\mu$ V)	Amp Gain (dB)	Cable Loss (dB)	ANT Factor (dB/m)	E-Field Value (dB $\mu$ V / m)	Spec Limit (dB $\mu$ V / m)	Spec Margin (dB)
<b>2440.00:</b>										
Orientation A										
<b>2440.00</b>	<b>H</b>	<b>2</b>	<b>199</b>	<b>63.38</b>	<b>0.00</b>	<b>5.95</b>	<b>28.56</b>	<b>97.89</b>		
<b>2440.00</b>	<b>V</b>	<b>2</b>	<b>74</b>	<b>58.12</b>	<b>0.00</b>	<b>5.95</b>	<b>28.56</b>	<b>92.63</b>		
Orientation B										
<b>2440.00</b>	<b>H</b>	<b>2</b>	<b>181</b>	<b>60.63</b>	<b>0.00</b>	<b>5.95</b>	<b>28.56</b>	<b>95.14</b>		
<b>2440.00</b>	<b>V</b>	<b>1.5</b>	<b>240</b>	<b>64.20</b>	<b>0.00</b>	<b>5.95</b>	<b>28.56</b>	<b>98.71</b>		
Orientation C										
<b>2440.00</b>	<b>H</b>	<b>2</b>	<b>325</b>	<b>61.22</b>	<b>0.00</b>	<b>5.95</b>	<b>28.56</b>	<b>95.73</b>		
<b>2440.00</b>	<b>V</b>	<b>1.6</b>	<b>218</b>	<b>64.80</b>	<b>0.00</b>	<b>5.95</b>	<b>28.56</b>	<b>99.31</b>		
Orientation B										
<b>2402.00</b>	<b>H</b>	<b>1.6</b>	<b>305</b>	<b>59.65</b>	<b>0.00</b>	<b>5.89</b>	<b>28.54</b>	<b>94.08</b>		
<b>2402.00</b>	<b>V</b>	<b>1.6</b>	<b>240</b>	<b>64.40</b>	<b>0.00</b>	<b>5.89</b>	<b>28.54</b>	<b>98.83</b>		
Orientation B										
<b>2480.00</b>	<b>H</b>	<b>1.4</b>	<b>248</b>	<b>65.64</b>	<b>0.00</b>	<b>5.98</b>	<b>28.68</b>	<b>100.30</b>	<b>114.00</b>	<b>-13.70</b>
<b>2480.00</b>	<b>V</b>	<b>1.3</b>	<b>247</b>	<b>66.14</b>	<b>0.00</b>	<b>5.98</b>	<b>28.68</b>	<b>100.80</b>	<b>114.00</b>	<b>-13.20</b>
<b>2480.00</b>	<b>V</b>	<b>1.3</b>	<b>247</b>	<b>56.23</b>	<b>0.00</b>	<b>5.98</b>	<b>28.68</b>	<b>90.89</b>	<b>94.00</b>	<b>-3.11</b>

Spec Margin = E-Field Value - Limit, E-Field Value = FIM Value - Amp Gain + Cable Loss + ANT Factor

 Notes: **Red = Peak Detector, Blue = Average Detector**

 The **Peak** and **Average** measurements were made **WITH MODULATION** using specified RBW.

 The Limit is 50 mV/m which is equivalent to 94 dB $\mu$ V/m (at 3m distance).

 The Limit using the Peak Detector is 20dB higher than the Average Detector limit.  
 EUT in Orientation B is worst case as shown. All other data is on file at TUV Rheinland.

 This **highlighted** frequency and orientation was worst case (2480 MHz, Orientation B).

 The maximum average Field Value of 90.89 dB $\mu$ V/m (35 mV/m) is below the limit value of FCC Part 15.249 which is 94 dB $\mu$ V/m (50 mV/m).

Therefore, this report is testing to the requirements of FCC Part 15.249

#### 4.1.5.2 Maximum Time-weighted Emission:


The EUT was modified to transmit continuously.

The maximum measured Duty Cycle of the signal is 40.76%

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

#### 4.1.5.3 Emissions Outside the Frequency Band:

##### Radiated Emissions – 30 MHz to 1 GHz Horizontal



01:19:44 PM, Tuesday, August 04, 2015

Emission Freq (MHz)	ANT Polar	ANT Pos (m)	Table Pos (deg)	FIM Value (dBuV)	Amp Gain (dB)	Cable Loss (dB)	ANT Factor (dB/m)	E-Field Value (dBuV/m)	Spec Limit (dBuV/m)	Spec Margin (dB)

Spec Margin = E-Field Value - Limit, E-Field Value = FIM Value - Amp Gain + Cable Loss + ANT Factor


Notes: Transmitting Mode-Low, mid and high Channels

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

31551027.001

Page 13 of 32

**Radiated Emissions – 30 MHz to 1 GHz**
**Vertical**


01:22:22 PM, Tuesday, August 04, 2015


Emission Freq (MHz)	ANT Polar (H/V)	ANT Pos (m)	Table Pos (deg)	FIM Value (dBuV)	Amp Gain (dB)	Cable Loss (dB)	ANT Factor (dB/m)	E-Field Value (dBuV/m)	Spec Limit (dBuV/m)	Spec Margin (dB)
66.80	V	1.2	0	8.36	0.00	0.94	9.72	19.02	40.00	-20.98

Spec Margin = E-Field Value - Limit, E-Field Value = FIM Value - Amp Gain + Cable Loss + ANT Factor

Notes: Transmitting Mode-Low, mid and high Channels

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

## Radiated Emissions – 1 to 10 GHz



10:31:06 AM, Monday, August 03, 2015

Spec Margin = E-Field Value - Limit, E-Field Value = FIM Value - Amp Gain + Cable Loss + ANT Factor

Notes: Transmitting Mode-Low, Mid and High Channels

A 2.4GHz band-notch filter was used at the input of the preamp for the 1 GHz to 10 GHz range.

A 2.4 GHz band-notch filter was used at the input of the preamp for the 1 GHz to 10.2 GHz band. The emissions shown in **GREEN** are using the average detector and average limits

The emissions shown in **GREEN** are using the average detector and average  
The emissions shown in **BLUE** are using the peak detector and peak limits


The **HIGHLIGHTED** cells indicate frequencies that do NOT fall within a Restricted band (-20dBc Limit).

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

**31551027.001**

Page 15 of 32

**Radiated Emissions – 1 to 10 GHz**
**Vertical**


10:41:06 AM, Monday, August 03, 2015

Emission Freq (MHz)	ANT Polar (H/V)	ANT Pos (m)	Table Pos (deg)	FIM Value (dBuV)	Amp Gain (dB)	Cable Loss (dB)	ANT Factor (dB/m)	E-Field Value (dBuV/m)	Spec Limit (dBuV/m)	Spec Margin (dB)
4960.40	V	1.3	346	29.04	33.66	11.81	33.19	40.39	54.00	-13.61
4960.40	V	1.3	346	43.27	33.66	11.81	33.19	54.62	74.00	-19.38
7206.80	V	1.0	216	24.56	33.61	14.51	36.07	41.53	54.00	-12.47
7206.80	V	1.0	215	40.01	33.61	14.51	36.07	56.98	74.00	-17.02
9607.21	V	1.4	7	25.13	34.18	16.88	37.93	45.76	54.00	-8.24
9607.21	V	1.4	7	39.12	34.18	16.88	37.93	59.75	74.00	-14.25

Spec Margin = E-Field Value - Limit, E-Field Value = FIM Value - Amp Gain + Cable Loss + ANT Factor

Notes: Transmitting Mode-Low, Mid and High Channels

A 2.4GHz band-notch filter was used at the input of the preamp for the 1 GHz to 10 GHz range.

 The emissions shown in **GREEN** are using the average detector and average limits

 The emissions shown in **BLUE** are using the peak detector and peak limits.


 The **HIGHLIGHTED** cells indicate frequencies that do NOT fall within a Restricted band (-20dBc Limit).

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

31551027.001

Page 16 of 32

**Radiated Emissions – 10 to 18 GHz**  
**Horizontal**


Emission Freq (MHz)	ANT Polar (H/V)	ANT Pos (m)	Table Pos (deg)	FIM Value (dBuV)	Amp Gain (dB)	Cable Loss (dB)	ANT Factor (dB/m)	E-Field Value (dBuV/m)	Spec Limit (dBuV/m)	Spec Margin (dB)

Spec Margin = E-Field Value - Limit, E-Field Value = FIM Value - Amp Gain + Cable Loss + ANT Factor

Notes: Transmitting Mode-Low, Mid and High Channels


A 3 GHz high-pass filter was used at the input of the preamp for the 10 GHz to 18 GHz range.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

31551027.001

Page 17 of 32

 Radiated Emissions – 10 to 18 GHz  
 Vertical


02:40:07 PM, Monday, August 03, 2015

Emission Freq (MHz)	ANT Polar (H/V)	ANT Pos (m)	Table Pos (deg)	FIM Value (dBuV)	Amp Gain (dB)	Cable Loss (dB)	ANT Factor (dB/m)	E-Field Value (dBuV/m)	Spec Limit (dBuV/m)	Spec Margin (dB)
12398.80	V	1.6	0	24.01	32.95	20.00	39.02	50.09	54.00	-3.91
12398.80	V	1.6	0	40.59	32.95	20.00	39.02	66.67	74.00	-7.33

Spec Margin = E-Field Value - Limit, E-Field Value = FIM Value - Amp Gain + Cable Loss + ANT Factor

Notes: Transmitting Mode-Low, Mid and High Channels

A 3 GHz high-pass filter was used at the input of the preamp for the 10 GHz to 18 GHz range.

 The **HIGHLIGHTED** cells show the worst-case harmonic emission.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

**31551027.001**

Page 18 of 32



**Radiated Emissions – 18 GHz to 25 GHz**

## Notes:

No measureable emissions found outside the band.

Plots utilizing a Peak detector shown below.

Remaining plots for the other frequencies are on file at TUV Rheinland.

**Radiated Emissions – 18 GHz to 24 GHz – Horizontal:****Radiated Emissions – 18 GHz to 24 GHz – Vertical:**

Note: Base-line scan, no correction factors were applied.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

## 4.2 Conducted Emissions on AC Mains – FCC 207(a)

This test measures the electromagnetic levels of spurious signals generated by the EUT on the AC power line that may affect the performance of other nearby electronic equipment.

### 4.2.1 Over View of Test

<b>Results</b>	<b>Complies</b> (as tested per this report)			<b>Date</b>	5 August 2015		
<b>Standard</b>	FCC Parts 15.207(a)						
<b>Product Model</b>	nIO-BT		<b>Serial#</b>	Production Prototype			
<b>Test Set-up</b>	Tested in shielded room. EUT placed on table, see test plans for details						
<b>EUT Powered By</b>	5.0 VDC	<b>Temp</b>	72° F	<b>Humidity</b>	56%	<b>Pressure</b>	1001 mbar
<b>Frequency Range</b>	150 kHz – 30 MHz						
<b>Perf. Criteria</b>	(Below Limit )	<b>Perf. Verification</b>		Readings Under Limit for L1 & Neutral			
<b>Mod. to EUT</b>	None	<b>Test Performed By</b>					

### 4.2.2 Test Procedure

Conducted and FCC emissions tests were performed using the procedures of ANSI C63.10:2009 including methods for signal maximizations and EUT configuration. The photos included with the report show the EUT in its maximized configuration.

The frequency range from 150kHz – 30MHz was investigated for conducted emissions.

Conducted Emissions measurements were performed in either the shielded room or ground plane location (with attached vertical ground plane) using procedures specified in the test plan and standard.

The EUT was powered by a 5 VDC Power Module. The emissions were made on the AC Mains side of the Module.

There were no deviations from the test methodology listed in the test plan for the conducted emission test.


### 4.2.3 Deviations

There were no deviations from the test methodology listed in the test plan for the conducted emission test.

### 4.2.4 Final Test

All final conducted emissions measurements were below (in compliance) the limits.

### 4.2.5 Test Setup Block Diagram




The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

31551027.001

Page 20 of 32

## 4.2.6 Final data and Graphs

 Conducted Emissions @ 120V/60Hz  
 Line 1


Freq (MHz)	ID (1,2,3,N)	Quasi FIM (dBµV)	Ave FIM (dBµV)	Cable Loss (dB)	TL/LISN (dB)	Limit QP (dBµV)	Limit AVE (dBµV)	Margin QP (dB)	Margin AVE (dB)
0.15	1	18.31	2.91	0.03	9.97	65.78	55.78	-37.48	-42.88
0.24	1	8.71	0.02	0.03	9.97	62.03	52.03	-43.32	-42.01
16.22	1	3.38	0.01	0.27	10.74	60.00	50.00	-45.62	-38.99

Quasi Spec Margin = Quasi FIM + Cable Loss + TL/LISN - QP Limit

Ave Spec Margin = Ave FIM + Cable Loss + TL/LISN CF - Ave Limit


Notes: The highlighted average cells show the worst-case emission (21.25 dBµV)

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

31551027.001

Page 21 of 32

 Conducted Emissions @ 120V/60Hz  
 Neutral


Freq (MHz)	ID (1,2,3,N)	Quasi FIM (dBµV)	Ave FIM (dBµV)	Cable Loss (dB)	TL/LISN (dB)	Limit QP (dBµV)	Limit AVE (dBµV)	Margin QP (dB)	Margin AVE (dB)
0.15	N	17.91	1.98	0.03	9.97	65.78	55.78	-37.88	-43.81
0.25	N	8.13	0.01	0.03	9.96	61.89	51.89	-43.77	-41.89
16.23	N	4.61	0.02	0.27	10.37	60.00	50.00	-44.76	-39.35

Quasi Spec Margin = Quasi FIM + Cable Loss + TL/LISN - QP Limit

Ave Spec Margin = Ave FIM + Cable Loss + TL/LISN CF - Ave Limit

Notes:

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

### 4.3 Band Edge requirements - FCC Part 15.249(d)

#### 4.3.1 Test Over View

<b>Results</b>	<b>Complies</b> (as tested per this report)				<b>Date</b>	6 July 2015			
<b>Standard</b>	FCC Part 15.249(d)								
<b>Product Model</b>	nIO-BT			<b>Serial#</b>	Production Prototype				
<b>Test Set-up</b>	Radiated Measurement								
<b>EUT Powered By</b>	5.0 VDC	<b>Temp</b>	78° F	<b>Humidity</b>	43%	<b>Pressure</b>	1003 mbar		
<b>Perf. Criteria</b>	(Below Limit)		<b>Perf. Verification</b>	Readings Under Limit					
<b>Mod. to EUT</b>	None		<b>Test Performed By</b>	Mark Ryan					

#### 4.3.2 Test Procedure

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Sec. 15.209, whichever is the lesser attenuation.

#### 4.3.3 Deviations

The Marker-delta method for band-edge measurements (section 6.9.3 of ANSI C63.10:2009) was used, as emissions up to 2 MHz removed from the band edge will also be measured.

The total span of band-edge measurements were approximately 4.8 MHz.

RBW of 100 kHz was chosen as it is within 1% to 5% of the total span. (4.8%)


The VBW of 300 kHz was chosen as it is 3 times the 100 kHz RBW.

The Sweep time was set to Auto.

#### 4.3.4 Final Test

The EUT met the performance criteria requirement as specified in the standards.

#### 4.3.1 Test Setup Block Diagram



The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.


Report No.:

**31551027.001**

Page 23 of 32



Marker 1 [T1]	RBW	100 kHz	RF Att	0 dB
Ref Lvl	VBW	300 kHz		
110 dB <sub>AV</sub>	SWT	500 ms	Unit	dB <sub>AV</sub>
2.40175170 GHz				



Date: 3.AUG.2015 16:25:27

Notes: Plot includes Correction Factors. Measured using the Average Detector, Line F1 is the Band Edge is at 2.4 GHz. Line D1 is the Restricted Band Peak limit.

The nearest restricted band (2390MHz) is 10 MHz below the band edge

The Highest frequency outside the band is at 47.30 dB<sub>AV</sub> (using the Average Detector) which is 6.7 dB below the average Limit for a restricted band.


Figure 1: Lower Band Edge Measurement (Radiated Emission-Average)

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

Report No.:

31551027.001

Page 24 of 32



Date: 3.AUG.2015 16:21:54

Notes: Plot includes Correction Factors. Measured using the Peak Detector, Line F1 is the Band Edge is at 2.4 GHz. Line D1 is the Restricted Band Peak limit.

The nearest restricted band (2390MHz) is 10 MHz below the band edge

The Highest frequency outside the band is at 60.44 dB $\mu$ V (using the Peak Detector) which is 13.56 dB below the peak Limit for a restricted band.

The -20dBc value was not shown, as it can be clearly seen that that point is well within the band and would be very close the 15.209 limit line.

Figure 2: Lower Band Edge Measurement (Radiated Emission-Peak)

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.


Report No.:

**31551027.001**

Page 25 of 32



Marker 2 [T1] RBW 100 kHz RF Att 0 dB  
 Ref Lvl 49.40 dB $\mu$ V  
 110 dB $\mu$ V 2.48355160 GHz SWI 500 ms Unit dB $\mu$ V



Date: 3.AUG.2015 16:35:15

Note: Measured using the Average detector. Band Edge is at 2.483.5 MHz (Line F1), line D1 is the average restricted band limit.

The Band edge (Line F1) at 2483.5 MHz is also the start of a restricted band, so the restricted band rules apply.

The Highest frequency outside the band is at 49.40 dB $\mu$ V (using the Average Detector) which is 4.6 dB below the Average restricted-band limits)

Figure 3: Upper Band Edge Measurement (Radiated Emission-Average)

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.


Report No.:

**31551027.001**

Page 26 of 32



Marker 1 [T1] RBW 100 kHz RF Att 0 dB  
 Ref Lvl 100.68 dB $\mu$ V  
 110 dB $\mu$ V 2.47974238 GHz SWF 500 ms Unit dB $\mu$ V



Date: 3.AUG.2015 16:33:32

Note: Measured using the Peak detector. Band Edge is at 2.483.5 MHz (Line F1), line D1 is the peak restricted band limit.

The Band edge (Line F1) at 2483.5 MHz is also the start of a restricted band, so the restricted band rules apply.

The Highest frequency outside the band is at 62.05 dB $\mu$ V (using the Peak Detector) which is 11.95 dB below the Peak restricted-band limits)

Figure 4: Upper Band Edge Measurement (Radiated Emission-Peak)

The EUT is compliant with the rules.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

## 5 RF Exposure

### 5.1 Classification

The antenna of the product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in user's manual. Therefore, this device is classified as a **Mobile Device**.

### 5.2 Test Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

#### 5.2.1 Antenna Gain

The maximum published Gain of the antenna is +3 dBi peak or 2.0 (numeric).

#### 5.2.2 Output Power into Antenna & RF Exposure value at distance 20cm:

Calculations for this report are based on highest power calculation and the highest gain of the antenna.

Limit for MPE (from FCC part 1.1310 table 1) which is 1.0 mW/cm<sup>2</sup> for the 2400MHz band.

Assuming a duty cycle of 100% will give a worst case value. Actual value, including the Duty Cycle, will be much lower than that shown below.

Highest Pout is 0.185 mW or 0.000184W\*

The maximum published gain of the antenna is +3 dBi. Linear gain =  $10^{(\text{dBi Gain} / 10)} = 2.0$

and R is 20cm or 0.2m.

		FCC:							
Controlled Exposures - Limit (mW/cm <sup>2</sup> ) =		5							
Uncontrolled Exposures - Limit (mW/cm <sup>2</sup> ) =		1							
		Pd = 0.0007175 mW/cm <sup>2</sup>				Pd = (Pout*G) / (4*π*R <sup>2</sup> )			
Controlled Margin to Limit =		4.9993 mW/cm <sup>2</sup>							
<b>Uncontrolled Margin to Limit =</b>		<b>0.9993 mW/cm<sup>2</sup></b>							

\*Note: The Pout value was taken from the 100.8 dB $\mu$ V/m value from section 4.1.4.1 of this report.

This value was applied to the  $P = (E^*D)^2 / (30^*G)$  equation, factoring in the published gain of the antenna. Where:

“E” is the field strength in V/m ( $(10^{(\text{dB}\mu\text{V/m value} / 20)}) / 10^6 = \text{V/m} = 0.035 \text{ V/m}$ )

“G” is the numeric gain of the transmitting antenna over an isotropic radiator. (2)

“d” is the distance at which the measurement is being executed. (3m)

“P” is the transmitter power in Watts. (0.0001845 W or 0.184 mW)

All calculations are on file at TUV Rheinland.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

### 5.2.3 Sample Calculation

The Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where;

$P_d$  = power density in  $\text{mW/cm}^2$

$P_{out}$  = output power to antenna in  $\text{mW}$  (0.018  $\text{mW}$ ).

$G$  = gain of antenna in linear scale (we are assuming a numeric gain of 2 as a worst-case scenario).

$\pi \approx 3.1416$

$R$  = distance between observation point and center of the radiator in  $\text{cm}$  (20cm)

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition, Page 640, Eq. (11-133).

$$P_d = (0.184 \cdot 2) / (4 \cdot \pi \cdot 20^2) = .368 / 5026.55 = 0.000073 \text{ mW/cm}^2$$

### 5.2.4 Results

Calculated PD ( $\text{mW/cm}^2$ )	Uncontrolled Exposure Limit ( $\text{mW/cm}^2$ )	Uncontrolled Margin to Limit ( $\text{mW/cm}^2$ )
0.000073	1	-0.9993

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

## Appendix A

### 6 Test Plan

This test report is intended to follow this test plan outlined here in unless otherwise stated in this report. The following test plan will give details on product information, standards to be used, test set ups and refer to TUV test procedures. The test procedures will give the steps to be taken when performing the stated test. The product information below came via client, product manual, product itself and or the internet.

#### 6.1 General Information

<b>Client</b>	SENSOR SWITCH
<b>Address 1</b>	900 Northrop Rd.
<b>Address 2</b>	Wallingford, CT 06492 USA
<b>Contact Person</b>	Frank Pelliccio
<b>Telephone</b>	(203) 303-5447
<b>e-mail</b>	Frank.Pelliccio@acuitybrands.com

##### 6.1.1 Product Name

nIO-BT - Tel Job # 129566 (21532486)

##### 6.1.2 Type of Product

BLE Device (Bluetooth-Low Energy)

#### 6.2 Equipment Under Test (EUT) Description

The Sensor Switch nIO-BT device is a Bluetooth Low Energy (now known as Bluetooth Smart) device that facilitates wireless communications with Sensor Switch's proprietary wired nLight RS-485 network. The nIO-BT unit derives its power from 16-28VDC provided by the nLight bus via CAT5e cable. The nIO-BT has a dedicated microcontroller and a specialized *BlueNRG-QTR* monolithic BLE coprocessor from ST Microelectronics. The nIO-BT EUT is expected to communicate within the specifications for the BLE protocol, which are intentional radiated emissions from 2402MHz to 2480MHz.

##### 6.2.1 Testing Preparation

Connect the provided 10' CAT5e cable between the nIO-BT EUT and the nPS-80 power supply to provide the EUT power. If necessary, the 10' cable may be replaced by any CAT5e-compliant cable that is terminated with RJ-45 connectors. The nPS-80 can be powered directly from 60Hz 100VAC-120VAC U.S. mains power.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

### 6.3 General Product Information

Size	H	2.54cm	W	5.03cm	L	6.45cm
Weight	0.04Kg	Fork-Lift Needed			No	
Notes						

#### Product environmental operating conditions:

-10° to 71° C Operating temperature range.

20 to 90% non-condensing Operating humidity range.

N/A Operating pressure range.

#### 6.3.1 EUT Electrical Powered Information

##### 6.3.1.1 Electrical Power Type

<input type="checkbox"/>	AC	<input type="checkbox"/>	DC	<input type="checkbox"/>	Batteries	<input checked="" type="checkbox"/>	Host – 120VAC mains-powered nLight nPS-80 Power Supply
--------------------------	----	--------------------------	----	--------------------------	-----------	-------------------------------------	---

##### 6.3.1.2 Electrical Power Information

Name	Type	Voltage		Frequency	Current	Notes
		min	max			
nLight nPS-80	AC-DC converter	100VAC	120VAC	60Hz	0.015A	
Notes	nPS-80 device powers nIO-BT EUT via CAT5e cable					

#### 6.3.2 EUT Modes of Operation

nIO-BT EUT must be connected to nLight nPS-80 via CAT5e cable via either port on the EUT and either port on the nPS-80 power supply. Once powered, the nIO-BT LED will rapidly flash briefly. At this point, the BLE radio is broadcasting advertising packets. By pressing then releasing the button on the device a certain number of times, different test modes can be entered. The EUT must be power-cycled before entering a new test mode, by either removing then re-inserting the CAT5e cable from the EUT, or by power cycling the nPS-80 power supply.

- One button press – Carrier Wave Tone Mode : The nIO-BT EUT will enter tone mode by pressing the button once. The unit will round-robin cycle the tone frequency in 2MHz increments between 2.401750GHz and 2479.75MHz for BLE channels 0-39 ( $f = 2402 + \text{channel} * 2 - 0.250$  MHz, with channel = 0 to 39). Each frequency will emit the tone for a duration of 2 seconds before switching to the next frequency.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

**Report No.:**
**31551027.001**

Page 31 of 32

- Two button presses – Data Transmit Mode : The nIO-BT EUT will enter a constant data transmit mode by pressing the button twice. The unit will round-robin between BLE channels @ 2402MHz, 2442MHz, 2480MHz, transmitting a continuous stream of BLE-modulated data on each channel for a duration of 2 seconds per channel before switching to the next channel.
- Three button presses – The radio will be placed into Receive Mode.
- Four button presses – 2442 MHz Carrier Wave Tone Mode: The nIO-BT EUT will transmit a constant 2442MHz carrier tone.

### 6.3.3 EUT Clock/Oscillator Frequencies

<input type="checkbox"/>	<b>Less than 108MHz</b>	<b>FCC – scan up to 1GHz</b>
<input type="checkbox"/>	<b>Less than 500MHz</b>	<b>FCC – scan up to 2GHz</b>
<input type="checkbox"/>	<b>Less than 1000MHz</b>	<b>FCC – scan up to 5GHz</b>
<input checked="" type="checkbox"/>	<b>Greater than 1000MHz</b>	<b>FCC – scan up to 5<sup>th</sup> Harmonic or 40GHz</b>

### 6.3.4 Electrical Support Equipment

Type	Manufacture	Model	Connected To
Power Supply	nLight	nPS-80	120VAC mains power, then to nIO-BT EUT via CAT5e cable.

### 6.3.5 EUT Equipment/Cabling Information

EUT Port	Connected To	Location	Cable Type		
			Length	Shielded	Bead
RJ-45	nPS-80		10' Cat5e		

## 6.4 EUT Test Program


See: “6.3.2 EUT Modes of Operation”

## 6.5 Monitoring of EUT during Testing

No external monitoring required during testing. nIO-BT EUT will output a constant RF signal during any of the test modes outlined in section 1.7.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.

### 6.5.1 Block Diagram



Note: the nPS80 is a power module used to simulate a typical host device providing power to the EUT.

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.