

Page: 1 of 178

# SAR TEST REPORT

<b>Equipment Under Test</b>	Mobile Internet Device		
Model Name	M01M		
Company Name	Qisda Corporation		
Company Address	157 Shan-Yang Road, Gueishan Taoyuan 333, Taiwan		
Date of Receipt	2009.08.29		
Date of Test(s)	2009.09.19~2009.09.21,2009.10.14		
Date of Issue	2009.10.27		

Standards:

### FCC OET Bulletin 65 supplement C, ANSI/IEEE C95.1, C95.3, IEEE 1528

In the configuration tested, the EUT complied with the standards specified above. Remarks:

This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS Taiwan Electronic & Communication Laboratory or testing done by SGS Taiwan Electronic & Communication Laboratory in connection with distribution or use of the product described in this report must be approved by SGS Taiwan Electronic & Communication Laboratory in writing.

Tested by : Antony Wu **Engineer** 

**Date** 

2009.10.27

Approved by : Robert Chang Tech Manager

Date

2009.10.27

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms\_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

Andany Win



Page: 2 of 178

# **Contents**

1. General Information	3
1.1 Testing Laboratory	3
1.2 Details of Applicant	3
1.3 Description of EUT	3
1.4 Test Environment	6
1.5 Operation description	6
1.6 Positioning Procedure	8
1.7 EVALUATION PROCEDURES	9
1.8 The SAR Measurement System	
1.9 System Components	12
1.10 SAR System Verification	13
1.11 issue Simulant Fluid for the Frequency Band	15
1.12 Test Standards and Limits	
2. Summary of Results	19
3. Instruments List	
4. Measurements	28
5. System Verification	122
5. DAE & Probe Calibration certificate	
7. Uncertainty Analysis	
3. Phantom description	
9. System Validation from Original equipment supplier	141

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 3 of 178

### 1. General Information

### 1.1 Testing Laboratory

SGS Taiwan Ltd. Electronics & Communication Laboratory				
134, Wu Kung Road, Wuku industrial zone				
Taipei county, Taiwan, R.O.C.				
Telephone	+886-2-2299-3279			
Fax	+886-2-2298-0488			
Internet	http://www.tw.sgs.com/			

### 1.2 Details of Applicant

Company Name	Qisda Corporation
Company Address	157 Shan-Ying Road, Gueishan Taoyuan 333, Taiwan
Contact Person	Kun Han Liu
TEL	+886-3-359-8800
Fax	+886-3-359-3395
E-mail	Kun.han.liu@qisda.com

### 1.3 Description of EUT

EUT Name	Mobile Internet Device			
Model Name	M01M			
Brand Name	DELL			
IMEI Code	011954000001490			
FCC ID	VRSM01M001			
Mode of Operation	GSM /GPRS/EDGE/WCDMA/HSDPA/HSUPA/802.11b+g			
Definition	Production unit			

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 4 of 178

Modulation Mode		GSM/GMSK/8PSK/QPSK/16QAM			
Duty Cycle	GSM	GPRS (4multi-slot)	WCDMA B2	WCDMA B5	
	1/8	1/2	1	1 ,	
Maximum RF	GSM 850	GSM1900	WCDMA B2	WCDMA B5	
Conducted Power (Average)	32.78dbm	29.88dbm	23.11dbm	23.14dbm	
TX Frequency Range	GSM 850	GSM1900	WCDMA B2	WCDMA B5	
(MHz)	824.2-	1850.2-	1852.4-	826.4-	
(IVII IZ)	848.8	1909.8	1907.6	846.6	
Channel Number	GSM 850	GSM1900	WCDMA B2	WCDMA B5	
(ARFCN)	128-251	512-810	9262-9538	4132-4233	
VOIP Function		N	No		
Battery Type		3.7 V Lit	hium-Ion		
Antenna Type	Internal Antenna				
31	GSM850				
	ŀ	lead	В	ody	
	O.431 mW/g  (At GSM 850 Right Head  _Cheek Position_ 128 channel)		(At GSM 8	<b>0.956 mW/g</b> (At GSM 850 Body _ 190 channel)	
		GSN	11900		
Max. SAR Measured	Head		Body		
(1 g)	0.385 mW/g (At GSM 1900 Left Head _Cheek Position_ 512 channel)		0.644 mW/g (At GSM 1900 Body _ 810 channel		
	WCDMA B2				
	ŀ	lead	E	Body	
	O.725 mW/g (At WCDMA B2 Left Head _Cheek Position_ 9262 channel)		(At WC	0.506 mW/g (At WCDMA B2 Body _ 9400 channel	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 5 of 178

	WCDMA B5		
	Head	Body	
	O.296 mW/g (At WCDMA B5 Right Head _Cheek Position_ 4233 channel)	<b>0.407 mW/g</b> (At WCDMA B5 Body _ 4132 channel	
Max. SAR Measured	WLAN 802.11 b		
(1 g)	Body		
	0.156 mW/g		
	(At WLAN 802.11b Body_ channel 11)		
	WLAN 802.11 g		
	Body		
	0.104 mW/g		
	(At WLAN 802.11	lg Body_ channel 11)	

### 1. WCDMA B2 & B5 HSDPA & HSUPA conducted power:

Mada Sub ta	Sub-test	Band	WCDMA B2		
Mode	Sub-test	Channel	9262	9400	9538
	1	$\beta_c/\beta_d$ (2/15)	23.11	22.67	22.34
HSDPA	2	$\beta_c/\beta_d(12/15)$	22.7	22.27	21.92
HSDFA	3	$\beta_c/\beta_d(15/8)$	22.63	22.22	21.81
	4	$\beta_c/\beta_d(15/4)$	22.7	22.23	21.93

Mode Sub-test	Band	WCDMA B2			
Wiode	Sub-test	Channel	9262	9400	9538
	1	$\beta_c/\beta_d(11/15)$	22.74	22.39	22.01
	2	$\beta_c/\beta_d(6/15)$	20.79	20.46	20.05
HSUPA	3	$\beta_c/\beta_d(15/9)$	21.80	21.41	21.09
	4	$\beta_c/\beta_d(2/15)$	20.92	20.51	20.09
	5	$\beta_c/\beta_d(15/15)$	22.63	22.25	21.92

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 6 of 178

Mode Sub-test	Band		WCDMA B5		
Mode	Sub-test	Channel	4132	4183	4233
	1	$\beta_c/\beta_d$ (2/15)	23.14	23.11	23.08
HSDPA	2	$\beta_c/\beta_d(12/15)$	22.85	22.75	22.76
ПЗДРА	3	$\beta_c/\beta_d(15/8)$	22.68	22.63	22.59
	4	$\beta_c/\beta_d(15/4)$	22.73	22.67	22.65

Mode Sub-test	Band	WCDMA B5			
Mode	Sub-test	Channel	4132	4183	4233
	1	$\beta_c/\beta_d(11/15)$	22.88	22.79	22.81
	2	$\beta_c/\beta_d(6/15)$	20.94	20.87	20.85
<b>HSUPA</b>	3	$\beta_c/\beta_d(15/9)$	21.92	21.85	21.89
	4	$\beta_c/\beta_d(2/15)$	20.99	20.93	20.93
	5	$\beta_{c}/\beta_{d}(15/15)$	22.74	22.62	22.70

#### 1.4 Test Environment

Ambient Temperature: 22±2° C Tissue Simulating Liquid: 22±2° C

### 1.5 Operation description

#### **General:**

- 1. The EUT is controlled by using a Radio Communication Tester (Agilent 8960), and the communication between the EUT and the tester is established by air link.
- 2. Measurements are performed respectively on the lowest, middle and highest channels of the operating band(s). The EUT is set to maximum power level during all tests, and at the beginning of each test the battery is fully charged.
- 3. The WLAN transmitter is controlled by chip-specific software installed in this PDA phone, to make the EUT transmit at max power.
- 4. During the SAR testing, the DASY5 system checks power drift by comparing the e-field strength of one specific location measured at the beginning with that measured at the end of the SAR testing.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 7 of 178

5. Testing Head SAR at lowest, middle and highest channel for all bands with LET/LEC/RET/REC conditions.

6. Testing body-worn SAR by separating 1.5cm between the back of the EUT and the flat phantom in GPRS mode.

### Additional configuration(Head):

7. For highest SAR configuration in this band repeated with external Memory card inside.

### Additional configuration(Body):

SAR evaluation is necessary.

- 8. Testing body-worn SAR with Handset and with Bluetooth transmitter OFF by separating **1.5cm** between the front of the EUT and the flat phantom in GPRS mode.
- 9. For highest SAR configuration in this band repeated with external Memory card inside.

### SAR evaluation considerations for handsets with multiple transmitters:

10. Since the WLAN function of this device does NOT support VoIP function. Users will not use it close to head. SAR evaluation of head adjacent is unnecessary, only Body condition will be considered for WLAN stand-alone situation. The maximum SAR value for licensed transmitter happens on GSM 850 band, Body worn , channel 190. the value is 0.956W/kg(1g). And the max SAR value for un-licensed transmitter WLAN 802.11b happens on Body worn, channel 11 The SAR value is 0.156W/kg (1g). The summation of the 1g SAR is 0.956+0.156 = 1.11W/kg, which lower than the limit 1.6W/kg. NO simultaneous transmission

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sqs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 t (886-2) 2299-3279 www.tw.sgs.com




Page: 8 of 178

### 1.6 Positioning Procedure



Phone position 1, "cheek" or "touch" position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning



Phone position 2, "tilted position." The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning Cheek/Touch Position:

the handset was brought toward the mouth of the head phantom by pivoting against the ear reference point until any point of the mouthpiece or keypad touched the phantom. Ear/Tilt Position:

With the phone aligned in the Cheek/Touch position, the handset was tilted away from the mouth with respect to the test device reference point by 15 degrees.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 9 of 178

#### 1.7 EVALUATION PROCEDURES

The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- 1. The extraction of the measured data (grid and values) from the Zoom Scan.
- 2. The calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- 3. The generation of a high-resolution mesh within the measured volume
- 4. The interpolation of all measured values from the measurement grid to the high-resolution grid
- 5. The extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- 6. The calculation of the averaged SAR within masses of 1g and 10g. The probe is calibrated at the center of the dipole sensors that is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated. The angle between the probe axis and the surface normal line is less than 30 degree.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extreme of the SAR distribution. The uncertainty on the locations of the extreme is less than 1/20 of the grid size. Only local maximum within -2 dB of the global maximum are searched and passed for the Cube Scan measurement. In the Cube Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5mm.

The maximum search is automatically performed after each area scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 10 of 178

for most SAR distributions even with relatively large grid spacing. After the area scanning measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations. The 1g and 10g peak evaluations are only available for the predefined cube 7x7x7 scans.

The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 30x30x30mm contains about 30g of tissue. The first procedure is an extrapolation (incl. Boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume. In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is the moved around until the highest averaged SAR is found.

If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.

### 1.8 The SAR Measurement System

A photograph of the SAR measurement System is given in Fig. a. This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY 5 professional system ). A Model EX3DV3 field probe is used to determine the internal electric fields. The SAR can be obtained from the equation SAR=  $\sigma$  ( $|Ei|^2$ )/  $\rho$  where  $\sigma$  and ρ are the conductivity and mass density of the tissue-simulant.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 11 of 178




Fig.a The block diagram of SAR system

The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Staubli RX family) with controller, teach pendant and software. An arm extension is for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 12 of 178

### positioning.

- A computer operating Windows 2000 or Windows XP.
- · DASY5 software.
- · Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
  - The SAM twin phantom enabling testing left-hand and right-hand usage.
  - The device holder for handheld mobile phones.
  - Tissue simulating liquid mixed according to the given recipes.
  - Validation dipole kits allowing to validate the proper functioning of the system.

### 1.9 System Components

#### FX3DV3 F-Field Probe

EX3DV3 E-FIEIO	Plube			
Construction:  Calibration:	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE) Basic Broad Band Calibration in air Conversion Factors (CF) for HSL850/1900/2450			
	Additional CF for other liquids and frequencies upon request	EX3DV3 E-Field Probe		
Frequency:	10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30	MHz to 6 GHz)		
Directivity:	<ul><li>± 0.3 dB in HSL (rotation around probe axis)</li><li>± 0.5 dB in tissue material (rotation normal to probe axis)</li></ul>			
Dynamic Range:				
Dimensions:	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm			
Application:	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.			

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms\_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 t (886-2) 2299-3279 www.tw.sgs.com



Page: 13 of 178

#### **SAM PHANTOM V4.0C**

SAM FITAIN OM	V 4.00					
Construction:	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.					
Shell Thickness:	2 ± 0.2 mm					
Filling Volume:	Approx. 25 liters	( TUTAL TO THE PARTY OF THE PAR				
Dimensions:	Height: 251mm; Length: 1000 mm; Width: 500 mm					

#### **DEVICE HOLDER**

	In combination with the Twin SAM Phantom	
Construction	V4.0/V4.0C or Twin SAM, the Mounting	-
	Device (made from POM) enables the rotation	
	of the mounted transmitter in spherical	
	coordinates, whereby the rotation point is the	
	ear opening. The devices can be easily and	
	accurately positioned according to IEC, IEEE,	
	CENELEC, FCC or other specifications. The	
	device holder can be locked at different	
	phantom locations (left head, right head, flat	
	phantom).	Device Holder

### 1.10 SAR System Verification

The microwave circuit arrangement for system verification is sketched in Fig. b. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd. No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 www.tw.sgs.com

台灣檢驗科技股份有限公司

t (886-2) 2299-3279 f (886-2) 2298-0488



Page: 14 of 178

measurement was performed to see if the measured SAR was within +/- 5% from the target SAR values. These tests were done at 850/1900/2450 MHz. The tests were conducted on the same days as the measurement of the DUT. The obtained results from the system accuracy verification are displayed in the table 1. During the tests, the ambient temperature of the laboratory was in the range 22.1°C, the relative humidity was in the range 62% and the liquid depth above the ear reference points was above 15 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.




Fig.b The block diagram of SAR system verification

- A. Agilent Model 8648D Signal Generator
- B. Mini circuits Model ZHL-42 Amplifier
- C. Agilent Model U2001B Power Sensor
- D. Agilent Model 778D & 777D Dual directional coupling
- E. Reference dipole antenna



Photograph of the dipole Antenna

Validation k	Frequency (MHz)	Target SAR (1g) (Pin=250mW)	Measured SAR (1g)	Measured Date
D835V2 S/N: 4d06	835 MHz 3 (Head)	2.38 mW/g	2.29 mW/g	2009/09/19
D835V2 S/N: 4d06	835 MHz 3 (Body)	2.55 mW/g	2.51 mW/g	2009/09/20
D1900V2 S/N: 5d02	1900 MHz 7 (Head)	10.5 mW/g	10.3 mW/g	2009/09/19
D1900V2 S/N: 5d02	1900 MHz 7 (Body)	10.6 mW/g	11 mW/g	2009/09/20
D2450V2 S/N: 727	2450 MHz (Body)	13.2 mW/g	13.4 mW/g	2009/09/20

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 t (886-2) 2299-3279 www.tw.sgs.com



Page: 15 of 178

D835V2 S/N: 4d063	835 MHz (Body)	2.55 mW/g	2.49 mW/g	2009/10/14
D2450V2 S/N: 727	2450 MHz (Body)	13.2 mW/g	13.1 mW/g	2009/10/14

Table 1. System validation (follow manufacture target value)

### 1.11 issue Simulant Fluid for the Frequency Band

The dielectric properties for this Head-simulant fluid were measured by using the HP Model 85070D Dielectric Probe (rates frequency band 200 MHz to 20 GHz) in conjuncation with HP 8753D Network Analyzer (30 KHz-6000MHz) by using a procedure detailed in Section V.

All dielectric parameters of tissue simulates were measured within 24 hours of SAR measurements. The depth of the tissue simulant in the ear reference point of the phantom was 15cm±5mm during all tests. (Appendix Fig. 2)

Fraguency		Measurement date/	Die	electric Pa	rameters
Frequency (MHz)	Tissue type	Measurement date/ Limits	ρ	σ (S/m)	Simulated Tissue Temperature(° C)
050	Hood	Measured, 2009. 09.19	40.4	0.878	21.7
850	Head	Recommended Limits	38.76-42.84	0.85-0.93	20-24
850	Pody	Measured, 2009. 09.20	52.6	0.978	21.7
630	Body	Recommended Limits	51.11-56.49	0.96-1.06	20-24
1900	Hood	Measured, 2009. 09.19	38.2	1.46	21.7
1900	Head	Recommended Limits	36.67-40.53	1.4-1.54	20-24
1900	Pody	Measured, 2009. 09.20	55.7	1.55	21.7
1900	Body	Recommended Limits	52.16-57.65	1.48-1.64	20-24
2450	Pody	Measured, 2009. 09.20	54.2	1.99	21.7
2430	Body	Recommended Limits	51.68-57.12	1.88-2.08	20-24
050	Pody	Measured, 2009. 10.14	52.5	0.975	21.7
850	Body	Recommended Limits	51.11-56.49	0.96-1.06	20-24
1000	Hoad	Measured, 2009. 10.14	54	1.97	21.7
1900	Head	Recommended Limits	51.68-57.12	1.88-2.08	20-24

Table 2. Dielectric Parameters of Tissue Simulant Fluid

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 16 of 178

The composition of the brain tissue simulating liquid for 850 & 1900 & 2450 band:

Ingredient	850MHz (Head)	850MHz (Body)	1900MHz (Head)	1900MHz (Body)	2450Mhz (Body)
DGMBE	X	X	444.52 g	300.67 g	301.7 ml
Water	532.98 g	631.68 g	552.42 g	716.56 g	698.3 ml
Salt	18.3 g	11.72 g	3.06 g	4.0 g	X
Preventol D-7	2.4 g	1.2 g	Х	Х	X
Cellulose	3.2 g	X	Χ	Χ	Χ
Sugar	766.0 g	600 g	X	Χ	Χ
Total	1 L	1 L	) 1 L	1 L	1 L
amount	(1.0kg)	(1.0kg)	(1.0kg)	(1.0kg)	(1.0kg)

Table 3. Recipes for tissue simulating liquid

### 1.12 Test Standards and Limits

According to FCC 47CFR §2.1093(d) The limits to be used for evaluation are based generally on criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate ("SAR") in Section 4.2 of "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," ANSI/IEEE C95.1–1992, Copyright 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017. These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86, Section 17.4.5. Copyright NCRP, 1986, Bethesda, Maryland 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards. The criteria to be used are specified in paragraphs (d)(1) and (d)(2) of this section and shall apply for portable devices transmitting in the frequency range from 100 kHz to 6 GHz. Portable devices that transmit at frequencies above 6 GHz are to be evaluated in terms of the MPE limits specified in § 1.1310 of this chapter.

Measurements and calculations to demonstrate compliance with MPE field strength or

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 17 of 178

power density limits for devices operating above 6 GHz should be made at a minimum distance of 5 cm from the radiating source.

- (1) Limits for Occupational/Controlled exposure: 0.4 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 8 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 20 W/kg, as averaged over an 10 grams of tissue (defined as a tissue volume in the shape of a cube). Occupational/Controlled limits apply when persons are exposed as a consequence of their employment provided these persons are fully aware of and exercise control over their exposure. Awareness of exposure can be accomplished by use of warning labels or by specific training or education through appropriate means, such as an RF safety program in a work environment.
- (2) Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube).

General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section. (Table .6)

Human Exposure	Uncontrolled Environment	Controlled Environment
	General Population	Occupational
Spatial Peak SAR	1.60 m W/g	8.00 m W/g
(Brain)		
Spatial Average SAR	0.08 m W/g	0.40 m W/g
(Whole Body)		
Spatial Peak SAR	4.00 m W/g	20.00 m W/g
(Hands/Feet/Ankle/Wrist)		

Table 4. RF exposure limits

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 18 of 178

#### Notes:

1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.

2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan/台北縣五股工業區五工路 134 號 t (886-2) 2299-3279 www.tw.sgs.com



Page: 19 of 178

# 2. Summary of Results

### **GSM 850 MHZ**

Dight Hood						
Right Head	· · · · · · · · · · · · · · · · · · ·			100/11		
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	rempt C
	128	824.2	32.77dbm	0.431	22.1	21.7
850 MHz	190	836.6	32.78dbm	0.428	22.1	21.7
	251	848.8	32.76dbm	0.43	22.1	21.7
Left Head (	Cheek Pos	ition)				
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
	128	824.2	32.77dbm	0.39	22.1	21.7
850 MHz	190	836.6	32.78dbm	0.384	22.1	21.7
	251	848.8	32.76dbm	0.371	22.1	21.7
Right Head	(15° Tilt I	Position	1)			
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
	128	824.2	32.77dbm	0.268	22.1	21.7
850 MHz	190	836.6	32.78dbm	0.26	22.1	21.7
	251	848.8	32.76dbm	0.233	22.1	21.7
Left Head (	15° Tilt Po	sition)				
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C
	128	824.2	32.77dbm	0.28	22.1	21.7
850 MHz	190	836.6	32.78dbm	0.277	22.1	21.7
	251	848.8	32.76dbm	0.257	22.1	21.7
Body worn	testing ir	GPRS	mode)			
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C
	128	824.2	29.51dbm	0.89	22.1	21.7
850 MHz	190	836.6	29.53dbm	0.956	22.1	21.7
	251	848.8	29.51dbm	0.936	22.1	21.7

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路 134 號 t (886-2) 2299-3279



Page: 20 of 178

Body worn (	Body worn (testing in GPRS mode)_repeated for EUT front to phantom							
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid		
			Power (Average)	1g	Temp[°C]	Temp[°C]		
850 MHz	190	836.6	29.53dbm	0.249	22.1	21.7		
Body worn (	(testing ir	GPRS	mode)_repeated \	with Memory car	d			
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid		
			Power (Average)	1g	Temp[°C]	Temp[°C]		
850 MHz	190	836.6	29.53dbm	0.873	22.1	21.7		
Body worn (	Body worn (testing in GPRS mode)_repeated with headset							
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid		
			Power (Average)	1g	Temp[°C]	Temp[°C]		
850 MHz	190	836.6	29.53dbm	0.758	22.1	21.7		
Body worn (	(testing ir	EGPR	S mode)					
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid		
			Power (Average)	1g	Temp[°C]	Temp[°C]		
	128	824.2	25.58dbm	0.296	22.1	21.7		
850 MHz	190	836.6	25.94dbm	0.366	22.1	21.7		
	251	848.8	25.87dbm	0.379	22.1	21.7		

### **PCS 1900 MHZ**

Right Head	Right Head (Cheek Position)								
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid			
			Power (Average)	1g	Temp[°C]	Temp[°C]			
	512	1850.2	29.75dbm	0.21	22.1	21.7			
1900 MHz	661	1880	29.85dbm	0.235	22.1	21.7			
	810	1909.8	29.88dbm	0.243	22.1	21.7			
Left Head (0	Cheek Pos	sition)							
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid			
			Power (Average)	1g	Temp[°C]	Temp[°C]			
	512	1850.2	29.75dbm	0.385	22.1	21.7			
1900 MHz	661	1880	29.85dbm	0.379	22.1	21.7			
	810	1909.8	29.88dbm	0.347	22.1	21.7			

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 21 of 178

Right Head	(15° Tilt I	Position	1)			
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
\	512	1850.2	29.75dbm	0.127	22.1	21.7
1900 MHz	661	1880	29.85dbm	0.13	22.1	21.7
	810	1909.8	29.88dbm	0.13	22.1	21.7
Left Head (	15° Tilt Po	osition)				
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
	512	1850.2	29.75dbm	0.156	22.1	21.7
1900 MHz	661	1880	29.85dbm	0.157	22.1	21.7
	810	1909.8	29.88dbm	0.15	22.1	21.7
Body worn	(testing ir	GPRS	mode)			
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
	512	1850.2	27.14dbm	0.592	22.1	21.7
1900 MHz	661	1880	27.27dbm	0.592	22.1	21.7
	810	1909.8	27.22dbm	0.644	22.1	21.7
Body worn	(testing ir	n EGPRS	S mode)			
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
	512	1850.2	24.28dbm	0.291	22.1	21.7
1900 MHz	661	1880	24.52dbm	0.326	22.1	21.7
\	810	1909.8	24.11dbm	0.359	22.1	21.7

## **WCDMA BAND 2**

Right Head (Cheek Position)								
Frequency	Channel	MHz	Conducted Output Power (Average)	Measured(W/kg) 1g	Amb. Temp[°C]	Liquid Temp[°C]		
	9262	1852.4	22.82dbm	0.415	22.1	21.7		
WCDMA B2	9400	1880	22.41dbm	0.379	22.1	21.7		
	9538	1907.6	22.07dbm	0.335	22.1	21.7		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 22 of 178

Left Head (0	Cheek Pos	ition)				
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
\	9262	1852.4	22.82dbm	0.725	22.1	21.7
WCDMA B2	9400	1880	22.41dbm	0.658	22.1	21.7
	9538	1907.6	22.07dbm	0.516	22.1	21.7
Left Head (0	Cheek Pos	ition) _	repeated with Me	mory card		
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
WCDMA B2	9262	1852.4	22.82dbm	0.69	22.1	21.7
Right Head	(15° Tilt I	Position	1)			
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
	9262	1852.4	22.82dbm	0.247	22.1	21.7
WCDMA B2	9400	1880	22.41dbm	0.231	22.1	21.7
	9538	1907.6	22.07dbm	0.177	22.1	21.7
Left Head (*	15° Tilt Po	sition)				
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
	9262	1852.4	22.82dbm	0.288	22.1	21.7
WCDMA B2	9400	1880	22.41dbm	0.254	22.1	21.7
	9538	1907.6	22.07dbm	0.207	22.1	21.7
Body worn	1					•
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
	9262	1852.4	22.82dbm	0.502	22.1	21.7
WCDMA B2	9400	1880	22.41dbm	0.506	22.1	21.7
	9538	1907.6	22.07dbm	0.445	22.1	21.7

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 23 of 178

# WCDMA BAND 2 HSDPA mode(Sub-test 1)

				•		
Body worn						
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
			Power (Average)	1g	Temp[°C]	Temp[°C]
	9262	1852.4	23.11dbm	0.386	22.1	21.7
WCDMA B2	9400	1880	22.67dbm	0.395	22.1	21.7
	9538	1907.6	22.34dbm	0.345	22.1	21.7

WCDMA BAND 2 HSUPA mode(Sub-test 1)

Body worn								
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid		
			Power (Average)	1g	Temp[°C]	Temp[°C]		
	9262	1852.4	22.74dbm	0.383	22.1	21.7		
WCDMA B2	9400	1880	22.39dbm	0.418	22.1	21.7		
	9538	1907.6	21.01dbm	0.339	22.1	21.7		

### WCDMA BAND 5

WODIVIA BAILE S										
Right Head	Right Head (Cheek Position)									
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid				
			Power (Average)	1g	Temp[°C]	Temp[°C]				
	4132	826.4	22.92dbm	0.276	22.1	21.7				
WCDMA B5	4183	836.6	22.86dbm	2.86dbm 0.283		21.7				
	4233	846.6	22.89dbm	0.296	22.1	21.7				
Left Head (0	Cheek Pos	ition)								
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid				
465	1		Power (Average)	1g	Temp[°C]	Temp[°C]				
	4132	826.4	22.92dbm	0.269	22.1	21.7				
WCDMA B5	4183	836.6	22.86dbm	0.264	22.1	21.7				
	4233	846.6	22.89dbm	0.279	22.1	21.7				

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 24 of 178

Right Head	(15° Tilt F	Position	1)			
Frequency	Channel	MHz	Conducted Output Power (Average)			Liquid Temp[°C]
,	4132	826.4	22.92dbm	0.165	22.1	21.7
WCDMA B5	4183	836.6	22.86dbm	0.15	22.1	21.7
	4233	846.6	22.89dbm	0.188	22.1	21.7
Left Head (1	15° Tilt Po	sition)			46	
Frequency	Channel	MHz	Conducted Output Power (Average)	Measured(W/kg) 1g	Amb. Temp[°C]	Liquid Temp[°C]
	4132	826.4	22.92dbm	0.183	22.1	21.7
WCDMA B5	4183	836.6	22.86dbm	0.191	22.1	21.7
	4233	846.6	22.89dbm	0.216	22.1	21.7
Body worn		ľ				·
Frequency	Channel	MHz	Conducted Output Power (Average)	Measured(W/kg) 1g	Amb. Temp[°C]	Liquid Temp[°C]
	4132	826.4	22.92dbm	0.407 22.1		21.7
WCDMA B5	4183	836.6	22.86dbm	0.369	22.1	21.7
	4233	846.6	22.89dbm	0.392 22.1		21.7

# WCDMA BAND 5 HSDPA mode(Sub-test 1)

Body worn						
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	(W/kg) Amb.	
			Power (Average)	1g	Temp[°C]	Temp[°C]
	4132	826.4	23.14dbm	0.389	22.1	21.7
WCDMA B5	4183	836.6	23.11dbm	0.359	22.1	21.7
	4233	846.6	23.08dbm	0.318	22.1	21.7

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 25 of 178

# WCDMA BAND 5 HSUPA mode(Sub-test 1)

Body worn								
Frequency	Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid		
			Power (Average)	1g	Temp[°C]	Temp[°C]		
	4132	826.4	22.88dbm	0.346	22.1	21.7		
WCDMA B5	4183	836.6	22.79dbm	0.332	22.1	21.7		
	4233	846.6	22.81dbm	0.357	22.1	21.7		

### WI ANRO2 11 h

VVLAIV	<u>02. i i</u>	D						
Body worn								
Frequency	Channel	MHz	Conducted Output Power (Average)	Measured(W/kg) 1g	Amb. Temp[°C]	Liquid Temp[°C]		
	1	2412	17.12dbm	0.101	22.1	21.7		
WLAN 802.11 b	6	2437	17.68dbm	0.143	22.1	21.7		
802.11 b	11	2462	17.67dbm	0.156	22.1	21.7		
Body worn-	repeated	for EU	T front to phanton	1				
Frequency	Channel	MHz	Conducted Output Power (Average)	Measured(W/kg) 1g	Amb. Temp[°C]	Liquid Temp[°C]		
WLAN 802.11 b	11	2462	17.67dbm	0.075	22.1	21.7		
Body worn-	Body worn-repeated with Memory card							
Frequency	Channel	MHz	Conducted Output Power (Average)	Measured(W/kg) 1g	Amb. Temp[°C]	Liquid Temp[°C]		
WLAN 802.11 b	11	2462	17.67dbm	0.146	22.1	21.7		
Body worn-	repeated	with Bl	uetooth active					
Frequency	Channel	MHz	Conducted Output Power (Average)	Measured(W/kg) 1g	Amb. Temp[°C]	Liquid Temp[°C]		
WLAN 802.11 b	11	2462	17.67dbm	0.142	22.1	21.7		
Body worn-	Body worn-repeated with headset							
Frequency	Channel	MHz	Conducted Output Power (Average)	Measured(W/kg) 1g	Amb. Temp[°C]	Liquid Temp[°C]		
WLAN 802.11 b	11	2462	17.67dbm	0.148	22.1	21.7		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 26 of 178

# WLAN 802.11 a

Channel	MHz	Conducted Output	Measured(W/kg)	Amb.	Liquid
		Power (Average)	1g	Temp[°C]	Temp[°C]
1	2412	18.31dbm	0.076	22.1	21.7
6	2437	18.63dbm	0.101	22.1	21.7
11	2462	18.31dbm	0.104	22.1	21.7
	1 6	1 2412 6 2437	Power (Average)  1 2412 18.31dbm  6 2437 18.63dbm	Power (Average) 1g  1 2412 18.31dbm 0.076  6 2437 18.63dbm 0.101	Power (Average)         1g         Temp[°C]           1         2412         18.31dbm         0.076         22.1           6         2437         18.63dbm         0.101         22.1

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms\_and\_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 t (886-2) 2299-3279 www.tw.sgs.com



Page: 27 of 178

## 3. Instruments List

Manufacturer	Device	Туре	Serial number	Date of last calibration
Schmid & Partner Engineering AG	Dosimetric E-FieldProbe	EX3DV3	3526	Aug.26.2009
	850/1900/2450MHz	D835V2	4d063	May.25.2009
Schmid & Partner Engineering AG	System Validation	D1900V2	5d027	Apr.27.2009
Linging Ad	Dipole	D2450V2	727	Apr.27.2009
Schmid & Partner Engineering AG	Data acquisition Electronics	DAE4	856	May.26.2009
Schmid & Partner Engineering AG	Software	DASY 5 V5.0 Build125	N/A	Calibration not required
Schmid & Partner Engineering AG	Phantom	SAM	N/A	Calibration not required
Agilent	Network Analyzer	8753D	3410A05547	Mar.31.2009
Agilent	Dielectric Probe Kit	85070D	US01440168	Calibration not required
A - 11 1	Dual-directional	778D	50313	Aug.26.2009
Agilent	coupler	777D	50014	Aug.27.2009
Agilent	RF Signal Generator	8648D	3847M00432	May.25.2009
Agilent	Power Sensor	U2001B	MY48100169	Apr.23.2009
Agilent	Radio Communication Test	E5515c	GB44051912	Nov.05 .2008

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 28 of 178

### 4. Measurements

Date/Time: 09/19/2009 01:56:45

### RE Cheek\_CH128

DUT: MO1M;

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used (interpolated): f = 824.2 MHz;  $\sigma = 0.87$  mho/m;

 $\epsilon_r = 40.6$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**RE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.453 mW/g

RE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 8.4 V/m; Power Drift = 0.00297 dB

Peak SAR (extrapolated) = 0.536 W/kg

### SAR(1 g) = 0.431 mW/g; SAR(10 g) = 0.332 mW/g

Maximum value of SAR (measured) = 0.449 mW/g



0 dB = 0.449 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路 134 號



Page: 29 of 178

Date/Time: 09/19/2009 02:23:28

### RE Cheek\_CH190

DUT: MO1M;

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used: f = 837 MHz;  $\sigma = 0.88$  mho/m;  $\epsilon_r = 40.4$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Right Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

RE Cheek/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.449 mW/g

RE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 8.13 V/m; Power Drift = 0.125 dB

Peak SAR (extrapolated) = 0.535 W/kg

SAR(1 g) = 0.428 mW/g; SAR(10 g) = 0.329 mW/g

Maximum value of SAR (measured) = 0.447 mW/g



0 dB = 0.447 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 t (886-2) 2299-3279



Page: 30 of 178

Date/Time: 09/19/2009 02:48:34

### RE Cheek\_CH251

DUT: MO1M;

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used: f = 849 MHz;  $\sigma = 0.894$  mho/m;  $\epsilon_r = 40.2$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Right Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**RE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.454 mW/g

RE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 8.13 V/m; Power Drift = 0.034 dB

Peak SAR (extrapolated) = 0.535 W/kg

SAR(1 g) = 0.430 mW/g; SAR(10 g) = 0.329 mW/g

Maximum value of SAR (measured) = 0.447 mW/g



0 dB = 0.447 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路 134 號



Page: 31 of 178

Date/Time: 09/19/2009 04:41:13

### LE Cheek\_CH128

DUT: MO1M;

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used (interpolated): f = 824.2 MHz;  $\sigma = 0.87 \text{ mho/m}$ ;

 $\varepsilon_{\rm r} = 40.6$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.403 mW/g

**LE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 8.33 V/m; Power Drift = -0.119 dB

Peak SAR (extrapolated) = 0.485 W/kg

SAR(1 g) = 0.390 mW/g; SAR(10 g) = 0.300 mW/g

Maximum value of SAR (measured) = 0.409 mW/g



0 dB = 0.409 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 t (886-2) 2299-3279



Page: 32 of 178

Date/Time: 09/19/2009 05:08:36

### LE Cheek\_CH190

DUT: MO1M;

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used: f = 837 MHz;  $\sigma = 0.88$  mho/m;  $\epsilon_r = 40.4$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Left Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.398 mW/g

### **LE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 7.98 V/m; Power Drift = 0.077 dB

Peak SAR (extrapolated) = 0.476 W/kg

### SAR(1 g) = 0.384 mW/g; SAR(10 g) = 0.294 mW/g

Maximum value of SAR (measured) = 0.407 mW/g



0 dB = 0.407 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 t (886-2) 2299-3279 www.tw.sgs.com



Page: 33 of 178

Date/Time: 09/19/2009 05:36:26

### LE Cheek\_CH251

DUT: MO1M;

Communication System: GSM 850; Frequency: 846.6 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used: f = 837 MHz;  $\sigma = 0.894$  mho/m;  $\epsilon_r = 40.2$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Left Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.385 mW/g

### LE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 7.88 V/m; Power Drift = -0.016 dB

Peak SAR (extrapolated) = 0.462 W/kg

### SAR(1 g) = 0.371 mW/g; SAR(10 g) = 0.284 mW/g

Maximum value of SAR (measured) = 0.391 mW/g



0 dB = 0.391 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路 134 號



Page: 34 of 178

Date/Time: 09/19/2009 03:18:03

### RE Tilt\_CH128

DUT: MO1M;

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used (interpolated): f = 824.2 MHz;  $\sigma = 0.87 \text{ mho/m}$ ;

 $\varepsilon_{\rm r} = 40.6$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

RE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.283 mW/g

RE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 13.1 V/m; Power Drift = -0.043 dB

Peak SAR (extrapolated) = 0.332 W/kg

SAR(1 g) = 0.268 mW/g; SAR(10 g) = 0.210 mW/g

Maximum value of SAR (measured) = 0.281 mW/g



0 dB = 0.281 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號 t (886-2) 2299-3279 www.tw.sgs.com



Page: 35 of 178

Date/Time: 09/19/2009 03:44:06

### RE Tilt\_CH190

DUT: MO1M;

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used: f = 837 MHz;  $\sigma = 0.88$  mho/m;  $\epsilon_r = 40.4$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Right Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**RE Tilt/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.275 mW/g

RE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 12.8 V/m; Power Drift = -0.139 dB

Peak SAR (extrapolated) = 0.319 W/kg

### SAR(1 g) = 0.260 mW/g; SAR(10 g) = 0.202 mW/g

Maximum value of SAR (measured) = 0.272 mW/g



0 dB = 0.272 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路 134 號



Page: 36 of 178

Date/Time: 09/19/2009 04:12:35

### RE Tilt\_CH251

DUT: MO1M;

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used: f = 849 MHz;  $\sigma = 0.894$  mho/m;  $\epsilon_r = 40.2$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Right Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**RE Tilt/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.246 mW/g

RE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 12.4 V/m; Power Drift = -0.00653 dB

Peak SAR (extrapolated) = 0.288 W/kg

SAR(1 g) = 0.233 mW/g; SAR(10 g) = 0.181 mW/g

Maximum value of SAR (measured) = 0.244 mW/g



0 dB = 0.244 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路 134 號



Page: 37 of 178

Date/Time: 09/19/2009 06:05:09

## LE Tilt\_CH128

DUT: MO1M;

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used (interpolated): f = 824.2 MHz;  $\sigma = 0.87 \text{ mho/m}$ ;

 $\varepsilon_r = 40.6$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Tilt/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.294 mW/g

### LE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 13.3 V/m; Power Drift = -0.100 dB

Peak SAR (extrapolated) = 0.344 W/kg

## SAR(1 g) = 0.280 mW/g; SAR(10 g) = 0.217 mW/g

Maximum value of SAR (measured) = 0.291 mW/g



0 dB = 0.291 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan /台北縣五股工業區五工路 134 號

台灣檢驗科技股份有限公司

f (886-2) 2298-0488

www.tw.sgs.com



Page: 38 of 178

Date/Time: 09/19/2009 06:33:41

## LE Tilt\_CH190

DUT: MO1M;

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used: f = 837 MHz;  $\sigma = 0.88$  mho/m;  $\epsilon_r = 40.4$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Left Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

LE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.290 mW/g

### **LE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 13 V/m; Power Drift = -0.010 dB

Peak SAR (extrapolated) = 0.344 W/kg

#### SAR(1 g) = 0.277 mW/g; SAR(10 g) = 0.215 mW/g

Maximum value of SAR (measured) = 0.289 mW/g



0 dB = 0.289 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 39 of 178

Date/Time: 09/19/2009 06:59:51

## LE Tilt\_CH251

DUT: MO1M;

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: HEAD900 Medium parameters used: f = 849 MHz;  $\sigma = 0.894$  mho/m;  $\varepsilon_r = 40.2$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Left Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(11.06, 11.06, 11.06); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

LE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.270 mW/g

### **LE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 12.3 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 0.316 W/kg

## SAR(1 g) = 0.257 mW/g; SAR(10 g) = 0.198 mW/g

Maximum value of SAR (measured) = 0.268 mW/g



0 dB = 0.268 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 40 of 178

Date/Time: 09/20/2009 12:49:16

# Body\_CH128

DUT: MO1M;

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:2

Medium: BODY900 Medium parameters used (interpolated): f = 824.2 MHz;  $\sigma = 0.973$ 

mho/m;  $\varepsilon_r = 52.8$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section

Probe: EX3DV3 - SN3526; ConvF(10.88, 10.88, 10.88); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.27 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,

dv=8mm, dz=5mm

Reference Value = 9.45 V/m; Power Drift = -0.130 dB

Peak SAR (extrapolated) = 1.61 W/kg

SAR(1 g) = 0.890 mW/g; SAR(10 g) = 0.669 mW/g

Maximum value of SAR (measured) = 0.933 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 1: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 9.45 V/m; Power Drift = -0.130 dB

Peak SAR (extrapolated) = 1.08 W/kg

SAR(1 g) = 0.818 mW/g; SAR(10 g) = 0.565 mW/g

Maximum value of SAR (measured) = 0.896 mW/g



0 dB = 0.896 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路 134 號 t (886-2) 2299-3279 www.tw.sgs.com

台灣檢驗科技股份有限公司

f (886-2) 2298-0488



Page: 41 of 178

Date/Time: 09/20/2009 13:16:47

## Body\_CH190

DUT: MO1M;

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2

Medium: BODY900 Medium parameters used: f = 837 MHz;  $\sigma = 0.979$  mho/m;  $\varepsilon_r = 52.5$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Probe: EX3DV3 - SN3526; ConvF(10.88, 10.88, 10.88); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.03 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,

dv=8mm, dz=5mm

Reference Value = 9.66 V/m; Power Drift = -0.042 dB

Peak SAR (extrapolated) = 1.21 W/kg

SAR(1 g) = 0.956 mW/g; SAR(10 g) = 0.734 mW/g

Maximum value of SAR (measured) = 0.994 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 1: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 9.66 V/m; Power Drift = -0.042 dB

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.891 mW/g; SAR(10 g) = 0.631 mW/g

Maximum value of SAR (measured) = 0.960 mW/g



0 dB = 0.960 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms\_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.

No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan / 台北縣五股工業區五工路 134 號 t (886-2) 2299-3279 www.tw.sgs.com

台灣檢驗科技股份有限公司

f (886-2) 2298-0488



Page: 42 of 178



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 43 of 178

Date/Time: 09/20/2009 13:44:27

# Body\_CH251

DUT: MO1M;

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:2

Medium: BODY900 Medium parameters used: f = 849 MHz;  $\sigma = 0.981$  mho/m;  $\varepsilon_r = 52.4$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Probe: EX3DV3 - SN3526; ConvF(10.88, 10.88, 10.88); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Body/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 1.02 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,

dy=8mm, dz=5mm

Reference Value = 9.75 V/m; Power Drift = -0.158 dB

Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.936 mW/g; SAR(10 g) = 0.718 mW/g

Maximum value of SAR (measured) = 0.976 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 1: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 9.75 V/m; Power Drift = -0.158 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.769 mW/g; SAR(10 g) = 0.536 mW/g

Maximum value of SAR (measured) = 0.866 mW/g



0 dB = 0.866 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 44 of 178

Date/Time: 09/20/2009 19:49:00

# Body\_CH190\_repeated for EUT front to phantom

DUT: MO1M;

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2

Medium: BODY900 Medium parameters used: f = 837 MHz;  $\sigma = 0.979$  mho/m;  $\varepsilon_r = 52.5$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Flat Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(10.88, 10.88, 10.88); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.266 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 4.88 V/m; Power Drift = -0.022 dB

Peak SAR (extrapolated) = 0.316 W/kg

## SAR(1 g) = 0.249 mW/g; SAR(10 g) = 0.190 mW/g

Maximum value of SAR (measured) = 0.259 mW/g



0 dB = 0.259 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 45 of 178

Date/Time: 09/20/2009 20:16:40

# Body\_CH190\_repeated with Memory card

DUT: MO1M;

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2

Medium: BODY900 Medium parameters used: f = 837 MHz;  $\sigma = 0.979$  mho/m;  $\varepsilon_r = 52.5$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Flat Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(10.88, 10.88, 10.88); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.956 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 9.27 V/m; Power Drift = -0.181 dB

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.873 mW/g; SAR(10 g) = 0.676 mW/g

Maximum value of SAR (measured) = 0.909 mW/g



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 46 of 178

Date/Time: 10/14/2009 14:18:00

# BODY\_CH190\_repeated with headset

DUT: MO1M;

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2

Medium: BODY900 Medium parameters used: f = 837 MHz;  $\sigma = 0.979$  mho/m;  $\varepsilon_r = 52.5$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Flat Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(10.88, 10.88, 10.88); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.785 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 7.51 V/m; Power Drift = 0.150 dB

Peak SAR (extrapolated) = 0.965 W/kg

## SAR(1 g) = 0.758 mW/g; SAR(10 g) = 0.563 mW/g

Maximum value of SAR (measured) = 0.802 mW/g



0 dB = 0.802 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 47 of 178

Date/Time: 09/20/2009 14:10:11

# Body\_CH128\_repeated with EGPRS mode

DUT: MO1M;

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:2

Medium: BODY900 Medium parameters used (interpolated): f = 824.2 MHz;  $\sigma = 0.973$ 

mho/m;  $\varepsilon_r = 52.8$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(10.88, 10.88, 10.88); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Body/Area Scan (71x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.309 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 4.87 V/m; Power Drift = 0.186 dB

Peak SAR (extrapolated) = 0.376 W/kg

#### SAR(1 g) = 0.296 mW/g; SAR(10 g) = 0.228 mW/g

Maximum value of SAR (measured) = 0.310 mW/g



0 dB = 0.310 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 48 of 178

Date/Time: 09/20/2009 14:38:50

# Body\_CH190\_repeated with EGPRS mode

DUT: MO1M;

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2

Medium: BODY900 Medium parameters used: f = 837 MHz;  $\sigma = 0.979$  mho/m;  $\varepsilon_r = 52.5$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Flat Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(10.88, 10.88, 10.88); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (71x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.375 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 5.65 V/m; Power Drift = -0.068 dB

Peak SAR (extrapolated) = 0.479 W/kg

SAR(1 g) = 0.366 mW/g; SAR(10 g) = 0.272 mW/g

Maximum value of SAR (measured) = 0.374 mW/g



0 dB = 0.374 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 49 of 178

Date/Time: 09/20/2009 15:06:03

# Body\_CH251\_repeated with EGPRS mode

DUT: MO1M;

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:2

Medium: BODY900 Medium parameters used: f = 849 MHz;  $\sigma = 0.981$  mho/m;  $\epsilon_r = 52.4$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Flat Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(10.88, 10.88, 10.88); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Body/Area Scan (71x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.375 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 5.74 V/m; Power Drift = 0.033 dB

Peak SAR (extrapolated) = 0.501 W/kg

SAR(1 g) = 0.379 mW/g; SAR(10 g) = 0.278 mW/g

Maximum value of SAR (measured) = 0.377 mW/g



0 dB = 0.377 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 50 of 178

Date/Time: 09/19/2009 14:36:27

## RE Cheek\_CH512

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used (interpolated): f = 1850.2 MHz;  $\sigma = 1.51$ 

mho/m;  $\varepsilon_r = 39.1$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

RE Cheek/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.227 mW/g

RE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 5.7 V/m; Power Drift = -0.089 dB

Peak SAR (extrapolated) = 0.298 W/kg

SAR(1 g) = 0.210 mW/g; SAR(10 g) = 0.141 mW/g

Maximum value of SAR (measured) = 0.226 mW/g



0 dB = 0.226 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 51 of 178

Date/Time: 09/19/2009 15:04:18

## RE Cheek\_CH661

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Right Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**RE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.251 mW/g

RE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 5.45 V/m; Power Drift = -0.00726 dB

Peak SAR (extrapolated) = 0.341 W/kg

SAR(1 g) = 0.235 mW/g; SAR(10 g) = 0.154 mW/g

Maximum value of SAR (measured) = 0.249 mW/g



0 dB = 0.249 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 52 of 178

Date/Time: 09/19/2009 15:30:32

## RE Cheek\_CH810

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used: f = 1910 MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 39$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Right Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**RE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.262 mW/g

### RE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 5.53 V/m; Power Drift = 0.199 dB

Peak SAR (extrapolated) = 0.359 W/kg

## SAR(1 g) = 0.243 mW/g; SAR(10 g) = 0.156 mW/g

Maximum value of SAR (measured) = 0.261 mW/g



0 dB = 0.261 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 53 of 178

Date/Time: 09/19/2009 17:22:03

# LE Cheek\_CH512

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used (interpolated): f = 1850.2 MHz;  $\sigma = 1.51$ 

mho/m;  $\varepsilon_r = 39.1$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.435 mW/g

### LE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 6.45 V/m; Power Drift = 0.101 dB

Peak SAR (extrapolated) = 0.568 W/kg

## SAR(1 g) = 0.385 mW/g; SAR(10 g) = 0.247 mW/g

Maximum value of SAR (measured) = 0.410 mW/g



0 dB = 0.410 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 54 of 178

Date/Time: 09/19/2009 17:49:14

## LE Cheek\_CH661

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Left Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.434 mW/g

## LE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 6.28 V/m; Power Drift = 0.013 dB

Peak SAR (extrapolated) = 0.570 W/kg

## SAR(1 g) = 0.379 mW/g; SAR(10 g) = 0.243 mW/g

Maximum value of SAR (measured) = 0.405 mW/g



0 dB = 0.405 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 55 of 178

Date/Time: 09/19/2009 18:18:13

## LE Cheek\_CH810

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used: f = 1910 MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 39$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Left Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.399 mW/g

### LE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 6.23 V/m; Power Drift = -0.028 dB

Peak SAR (extrapolated) = 0.526 W/kg

# SAR(1 g) = 0.347 mW/g; SAR(10 g) = 0.221 mW/g

Maximum value of SAR (measured) = 0.371 mW/g



0 dB = 0.371 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 56 of 178

Date/Time: 09/19/2009 15:58:04

## RE Tilt\_CH512

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used (interpolated): f = 1850.2 MHz;  $\sigma = 1.51$ 

mho/m;  $\varepsilon_r = 39.1$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

RE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.142 mW/g

RE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 9.19 V/m; Power Drift = -0.073 dB

Peak SAR (extrapolated) = 0.207 W/kg

SAR(1 g) = 0.127 mW/g; SAR(10 g) = 0.075 mW/g

Maximum value of SAR (measured) = 0.134 mW/g



0 dB = 0.134 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 57 of 178

Date/Time: 09/19/2009 16:24:51

## RE Tilt\_CH661

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Right Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

RE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.152 mW/g

### RE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 9.18 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 0.209 W/kg

### SAR(1 g) = 0.130 mW/g; SAR(10 g) = 0.077 mW/g

Maximum value of SAR (measured) = 0.139 mW/g



0 dB = 0.139 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 58 of 178

Date/Time: 09/19/2009 16:53:39

## RE Tilt\_CH810

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used: f = 1910 MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 39$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Right Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

RE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.150 mW/g

### RE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 9.32 V/m; Power Drift = -0.013 dB

Peak SAR (extrapolated) = 0.212 W/kg

### SAR(1 g) = 0.130 mW/g; SAR(10 g) = 0.075 mW/g

Maximum value of SAR (measured) = 0.141 mW/g



0 dB = 0.141 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 59 of 178

Date/Time: 09/19/2009 18:45:14

## LE Tilt\_CH512

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used (interpolated): f = 1850.2 MHz;  $\sigma = 1.51$ 

mho/m;  $\varepsilon_r = 39.1$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

LE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.167 mW/g

### **LE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 10.3 V/m; Power Drift = 0.069 dB

Peak SAR (extrapolated) = 0.248 W/kg

## SAR(1 g) = 0.156 mW/g; SAR(10 g) = 0.096 mW/g

Maximum value of SAR (measured) = 0.165 mW/g



0 dB = 0.165 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 60 of 178

Date/Time: 09/19/2009 19:11:52

# LE Tilt\_CH661

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Left Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

LE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.177 mW/g

### **LE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 10.3 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 0.248 W/kg

## SAR(1 g) = 0.157 mW/g; SAR(10 g) = 0.096 mW/g

Maximum value of SAR (measured) = 0.168 mW/g



0 dB = 0.168 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 61 of 178

Date/Time: 09/19/2009 19:39:37

## LE Tilt\_CH810

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: HEAD1900 Medium parameters used: f = 1910 MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 39$ ;  $\rho =$ 

1000 kg/m<sup>3</sup>

Phantom section: Left Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

LE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.167 mW/g

### **LE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 10.1 V/m; Power Drift = -0.00224 dB

Peak SAR (extrapolated) = 0.242 W/kg

# SAR(1 g) = 0.150 mW/g; SAR(10 g) = 0.091 mW/g

Maximum value of SAR (measured) = 0.156 mW/g



0 dB = 0.156 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 62 of 178

Date/Time: 09/20/2009 03:42:39

# Body\_CH512

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:2

Medium: BODY1900 Medium parameters used (interpolated): f = 1850.2 MHz;  $\sigma = 1.51$ 

mho/m;  $ε_r = 55.8$ ;  $ρ = 1000 \text{ kg/m}^3$ Phantom section: Flat Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(8.89, 8.89, 8.89); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (71x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.652 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 8.44 V/m; Power Drift = -0.054 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.592 mW/g; SAR(10 g) = 0.320 mW/g

Maximum value of SAR (measured) = 0.658 mW/g



0 dB = 0.658 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 63 of 178

Date/Time: 09/20/2009 04:11:31

# Body\_CH661

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2

Medium: BODY1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.54$  mho/m;  $\varepsilon_r = 55.8$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(8.89, 8.89, 8.89); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (71x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.722 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 8.75 V/m; Power Drift = 0.187 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.592 mW/g; SAR(10 g) = 0.322 mW/g

Maximum value of SAR (measured) = 0.661 mW/g



0 dB = 0.661 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 64 of 178

Date/Time: 09/20/2009 04:38:44

# Body\_CH810

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:2

Medium: BODY1900 Medium parameters used: f = 1910 MHz;  $\sigma = 1.56$  mho/m;  $\varepsilon_r = 55.7$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(8.89, 8.89, 8.89); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Body/Area Scan (71x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.732 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 9.15 V/m; Power Drift = -0.043 dB

Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.644 mW/g; SAR(10 g) = 0.350 mW/g

Maximum value of SAR (measured) = 0.703 mW/g



0 dB = 0.703 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 65 of 178

Date/Time: 09/20/2009 05:07:23

# Body\_CH512\_repeated with EGPRS mode

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:2

Medium: BODY1900 Medium parameters used (interpolated): f = 1850.2 MHz;  $\sigma = 1.51$ 

mho/m;  $ε_r = 55.8$ ;  $ρ = 1000 \text{ kg/m}^3$ Phantom section: Flat Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(8.89, 8.89, 8.89); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (71x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.326 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 4.59 V/m; Power Drift = 0.167 dB

Peak SAR (extrapolated) = 0.474 W/kg

SAR(1 g) = 0.291 mW/g; SAR(10 g) = 0.162 mW/g

Maximum value of SAR (measured) = 0.323 mW/g



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 66 of 178

Date/Time: 09/20/2009 05:34:51

# Body\_CH661\_repeated with EGPRS mode

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2

Medium: BODY1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.54$  mho/m;  $\varepsilon_r = 55.8$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(8.89, 8.89, 8.89); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (71x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.366 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 4.73 V/m; Power Drift = -0.066 dB

Peak SAR (extrapolated) = 0.562 W/kg

### SAR(1 g) = 0.326 mW/g; SAR(10 g) = 0.181 mW/g

Maximum value of SAR (measured) = 0.360 mW/g



0 dB = 0.360 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 67 of 178

Date/Time: 09/20/2009 06:03:59

# Body\_CH810\_repeated with EGPRS mode

DUT: MO1M;

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:2

Medium: BODY1900 Medium parameters used: f = 1910 MHz;  $\sigma = 1.56$  mho/m;  $\varepsilon_r = 55.7$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(8.89, 8.89, 8.89); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (71x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.428 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 4.67 V/m; Power Drift = -0.163 dB

Peak SAR (extrapolated) = 0.821 W/kg

## SAR(1 g) = 0.359 mW/g; SAR(10 g) = 0.192 mW/g

Maximum value of SAR (measured) = 0.412 mW/g



0 dB = 0.412 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 68 of 178

Date/Time: 09/19/2009 20:05:15

## RE Cheek\_CH9262

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used (interpolated): f = 1852.4 MHz;  $\sigma = 1.5$ 

mho/m;  $\varepsilon_r = 39$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section

### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**RE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.444 mW/g

RE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 7.91 V/m; Power Drift = -0.051 dB

Peak SAR (extrapolated) = 0.597 W/kg

SAR(1 g) = 0.415 mW/g; SAR(10 g) = 0.276 mW/g

Maximum value of SAR (measured) = 0.447 mW/g



0 dB = 0.447 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 69 of 178

Date/Time: 09/19/2009 20:33:33

## RE Cheek\_CH9400

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Right Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**RE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.410 mW/g

RE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 7.18 V/m; Power Drift = -0.114 dB

Peak SAR (extrapolated) = 0.554 W/kg

SAR(1 g) = 0.379 mW/g; SAR(10 g) = 0.249 mW/g

Maximum value of SAR (measured) = 0.401 mW/g



0 dB = 0.401 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 70 of 178

Date/Time: 09/19/2009 21:00:11

## RE Cheek\_CH9538

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used: f = 1908 MHz;  $\sigma = 1.53$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Right Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**RE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.354 mW/g

RE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 6.5 V/m; Power Drift = 0.105 dB

Peak SAR (extrapolated) = 0.499 W/kg

SAR(1 g) = 0.335 mW/g; SAR(10 g) = 0.214 mW/g

Maximum value of SAR (measured) = 0.363 mW/g



0 dB = 0.363 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 71 of 178

Date/Time: 09/19/2009 22:53:23

## LE Cheek\_CH9262

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used (interpolated): f = 1852.4 MHz;  $\sigma = 1.5$ 

mho/m;  $\varepsilon_r = 39$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section

#### **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.829 mW/g

## LE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 8 V/m; Power Drift = -0.135 dB

Peak SAR (extrapolated) = 1.11 W/kg

### SAR(1 g) = 0.725 mW/g; SAR(10 g) = 0.461 mW/g

Maximum value of SAR (measured) = 0.782 mW/g



0 dB = 0.782 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 72 of 178



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 73 of 178

Date/Time: 09/19/2009 23:20:14

# LE Cheek\_CH9400

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Left Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.757 mW/g

## **LE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 7.24 V/m; Power Drift = -0.013 dB

Peak SAR (extrapolated) = 1.02 W/kg

## SAR(1 g) = 0.658 mW/g; SAR(10 g) = 0.416 mW/g

Maximum value of SAR (measured) = 0.709 mW/g



0 dB = 0.709 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 74 of 178

Date/Time: 09/19/2009 23:48:44

# LE Cheek\_CH9538

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used: f = 1908 MHz;  $\sigma = 1.53$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Left Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.595 mW/g

## LE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 6.59 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.808 W/kg

# SAR(1 g) = 0.516 mW/g; SAR(10 g) = 0.324 mW/g

Maximum value of SAR (measured) = 0.556 mW/g



0 dB = 0.556 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 75 of 178

Date/Time: 09/20/2009 01:40:21

# LE Cheek\_CH9262\_repeated with Memory card

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used (interpolated): f = 1852.4 MHz;  $\sigma = 1.5$ 

mho/m; ε<sub>r</sub> = 39; ρ = 1000 kg/m<sup>3</sup> Phantom section: Left Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Cheek/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.797 mW/g

## **LE Cheek/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 8.46 V/m; Power Drift = -0.098 dB

Peak SAR (extrapolated) = 1.03 W/kg

# SAR(1 g) = 0.690 mW/g; SAR(10 g) = 0.442 mW/g

Maximum value of SAR (measured) = 0.730 mW/g



0 dB = 0.730 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 76 of 178

Date/Time: 09/19/2009 21:29:23

# RE Tilt\_CH9262

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used (interpolated): f = 1852.4 MHz;  $\sigma = 1.5$ 

mho/m; ε<sub>r</sub> = 39; ρ = 1000 kg/m<sup>3</sup> Phantom section: Right Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

RE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.289 mW/g

RE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 12.8 V/m; Power Drift = -0.107 dB

Peak SAR (extrapolated) = 0.399 W/kg

## SAR(1 g) = 0.247 mW/g; SAR(10 g) = 0.145 mW/g

Maximum value of SAR (measured) = 0.264 mW/g



0 dB = 0.264 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 77 of 178

Date/Time: 09/19/2009 21:56:12

# RE Tilt\_CH9400

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Right Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

RE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.263 mW/g

RE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 12.1 V/m; Power Drift = 0.047 dB

Peak SAR (extrapolated) = 0.377 W/kg

## SAR(1 g) = 0.231 mW/g; SAR(10 g) = 0.134 mW/g

Maximum value of SAR (measured) = 0.245 mW/g



0 dB = 0.245 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 78 of 178

Date/Time: 09/19/2009 22:24:45

# RE Tilt\_CH9538

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used: f = 1908 MHz;  $\sigma = 1.53$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Right Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**RE Tilt/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.205 mW/g

### RE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 10.7 V/m; Power Drift = 0.013 dB

Peak SAR (extrapolated) = 0.292 W/kg

## SAR(1 g) = 0.177 mW/g; SAR(10 g) = 0.102 mW/g

Maximum value of SAR (measured) = 0.189 mW/g



0 dB = 0.189 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 79 of 178

Date/Time: 09/20/2009 00:16:15

# LE Tilt\_CH9262

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used (interpolated): f = 1852.4 MHz;  $\sigma = 1.5$ 

mho/m;  $\varepsilon_r = 39$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**LE Tilt/Area Scan (81x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.326 mW/g

## LE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 13.6 V/m; Power Drift = -0.052 dB

Peak SAR (extrapolated) = 0.458 W/kg

# SAR(1 g) = 0.288 mW/g; SAR(10 g) = 0.178 mW/g

Maximum value of SAR (measured) = 0.306 mW/g



0 dB = 0.306 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 80 of 178

Date/Time: 09/20/2009 00:45:38

# LE Tilt\_CH9400

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Left Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

LE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.289 mW/g

## **LE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 12.6 V/m; Power Drift = 0.016 dB

Peak SAR (extrapolated) = 0.414 W/kg

## SAR(1 g) = 0.254 mW/g; SAR(10 g) = 0.154 mW/g

Maximum value of SAR (measured) = 0.265 mW/g



0 dB = 0.265 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 81 of 178

Date/Time: 09/20/2009 01:12:51

# LE Tilt\_CH9538

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: HEAD1900 Medium parameters used: f = 1908 MHz;  $\sigma = 1.53$  mho/m;  $\epsilon_r = 39.1$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Left Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(9.38, 9.38, 9.38); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

LE Tilt/Area Scan (81x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.238 mW/g

## **LE Tilt/Zoom Scan (7x7x7) (5x5x7)/Cube 0:** Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = -0.045 dB

Peak SAR (extrapolated) = 0.333 W/kg

# SAR(1 g) = 0.207 mW/g; SAR(10 g) = 0.126 mW/g

Maximum value of SAR (measured) = 0.226 mW/g



0 dB = 0.226 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 82 of 178

Date/Time: 09/20/2009 06:36:27

# Body\_CH9262

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: BODY1900 Medium parameters used (interpolated): f = 1852.4 MHz;  $\sigma = 1.51$ 

mho/m;  $\varepsilon_r = 55.9$ ;  $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(8.89, 8.89, 8.89); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (71x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.543 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 8.33 V/m; Power Drift = 0.077 dB

Peak SAR (extrapolated) = 0.898 W/kg

SAR(1 g) = 0.502 mW/g; SAR(10 g) = 0.274 mW/g

Maximum value of SAR (measured) = 0.562 mW/g



0 dB = 0.562 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.



Page: 83 of 178

Date/Time: 09/20/2009 07:03:16

# Body\_CH9400

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: BODY1900 Medium parameters used: f = 1880 MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 55.8$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(8.89, 8.89, 8.89); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Body/Area Scan (71x121x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.553 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 8.25 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.918 W/kg

## SAR(1 g) = 0.506 mW/g; SAR(10 g) = 0.273 mW/g

Maximum value of SAR (measured) = 0.565 mW/g



0 dB = 0.565 mW/g

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 84 of 178

Date/Time: 09/20/2009 07:32:12

# Body\_CH9538

DUT: MO1M;

Communication System: WCDMA B2; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: BODY1900 Medium parameters used: f = 1908 MHz;  $\sigma = 1.56$  mho/m;  $\varepsilon_r = 55.7$ ;  $\rho$ 

 $= 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

## **DASY5** Configuration:

Probe: EX3DV3 - SN3526; ConvF(8.89, 8.89, 8.89); Calibrated: 8/26/2009

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn856; Calibrated: 5/26/2009

Phantom: SAM1; Type: SAM;

Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

Body/Area Scan (71x121x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.478 mW/g

Body/Zoom Scan (7x7x7) (5x5x7)/Cube 0: Measurement grid: dx=8mm,


dy=8mm, dz=5mm

Reference Value = 7.06 V/m; Power Drift = -0.00747 dB

Peak SAR (extrapolated) = 0.816 W/kg

SAR(1 g) = 0.445 mW/g; SAR(10 g) = 0.240 mW/g

Maximum value of SAR (measured) = 0.495 mW/g



0 dB = 0.495 mW/q

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="www.sgs.com/terms\_and\_conditions.htm">www.sgs.com/terms\_and\_conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be

SGS Taiwan Ltd.