



FCC RADIO TEST REPORT

Applicant's company	Qisda Corporation
Applicant Address	157, Shan-Ying Road, Gueishan, Taoyuan 333, Taiwan
FCC ID	VRSQT11A
Manufacturer's company	1.Qisda Corporation 2.Qisda (Suzhou) Co., Ltd. 3.Qisda Optronics (Suzhou) Co., Ltd. 4.Qisda Mexicana S.A. De C.V.
Manufacturer Address	1.157 & 159, Shan-Ying Road, Gueishan, Taoyuan , Taiwan 2.169, Zhujiang Road, New District, Suzhou, Jiangsu Province, P.R. China 3.169, Zhujiang Road, New District, Suzhou, Jiangsu 215129, P.R. China 4.Calzada Venustiano Carranza, No. 88 Col. Plutarco Elias Calles, Mexocali B.C. Mexico C.P 21376 Mexico

Product Name	Tablet Computer
Brand Name	Qisda
Model Name	QT11A
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Mar. 11, 2013
Final Test Date	Apr. 01, 2013
Submission Type	Original Equipment

Statement

Test result included is only for the Bluetooth 1.0/2.0/2.1+EDR part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION.....	3
3.1. Product Details	3
3.2. Accessories	3
3.3. Table for Filed Antenna	4
3.4. Table for Carrier Frequencies	4
3.5. Table for Test Modes	5
3.6. Table for Testing Locations.....	6
3.7. Table for Supporting Units	7
3.8. Table for Parameters of Test Software Setting.....	7
3.9. EUT Operation during Test.....	7
3.10. Test Configurations.....	8
4. TEST RESULT.....	10
4.1. AC Power Line Conducted Emissions Measurement	10
4.2. Maximum Conducted Output Power Measurement.....	14
4.3. Hopping Channel Separation Measurement.....	16
4.4. Number of Hopping Frequency Measurement.....	27
4.5. Dwell Time Measurement.....	29
4.6. Radiated Emissions Measurement.....	36
4.7. Emissions Measurement.....	48
4.8. Antenna Requirements	60
5. LIST OF MEASURING EQUIPMENTS	61
6. TEST LOCATION.....	63
APPENDIX A. TEST PHOTOS.....	A1 ~ A5
APPENDIX B. CO-LOCATION REPORT.....	B1 ~ B3



History of This Test Report



Report No.: FR331615AB

Certificate No.: CB10204103

1. CERTIFICATE OF COMPLIANCE

Product Name : Tablet Computer
Brand Name : Qisda
Model No. : QT11A
Applicant : Qisda Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sportun International as requested by the applicant to evaluate the EMC performance of the product sample received on Mar. 11, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	5.93 dB
4.2	15.247(b)(1)	Maximum Conducted Output Power	Complies	27.03 dB
4.3	15.247(a)(1)	Hopping Channel Separation	Complies	-
4.4	15.247(b)(1)	Number of Hopping Frequency	Complies	-
4.5	15.247(a)(1)	Dwell Time	Complies	-
4.6	15.247(d)	Radiated Emissions	Complies	0.13 dB
4.7	15.247(d)	Band Edge Emissions	Complies	5.40 dB
4.8	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Hopping Channel Separation	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Power Type	From Power Adapter and Battery
Modulation	FHSS (GFSK / π/4-DQPSK / 8DPSK)
Data Rate (Mbps)	GFSK: 1 ; π/4-DQPSK: 2 ; 8DPSK: 3
Reference Number	TL-14857
Frequency Range	2400 ~ 2483.5MHz
Channel Number	79
Channel Band Width (99%)	For Bluetooth 1.0 : 0.9080 MHz For Bluetooth 2.0 : 1.2000 MHz For Bluetooth 2.1 + EDR : 1.2000 MHz
Maximum Conducted Output Power	For Bluetooth 1.0 : 2.97 dBm For Bluetooth 2.0 : 0.81 dBm For Bluetooth 2.1 + EDR : -0.69 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

3.2. Accessories

Power	Brand Holder	Model	Rating
LI-ION RECHARGEABLE BATTERY	T-GEE Electronic Co., Ltd.	QIC3000	10.8Vdc, 5833mAh, 63Wh
Adapter	SINPRO ELECTRONICS CO., LTD.	HPU101-107	INPUT: 100-240V, 47-63 Hz, 1.2-0.5A OUTPUT: 19V, 5.26A max
Other			
Docking Station - Brand Name: Qisda / Model Name: QD11A			
Power Cable			

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
1	Magic	AWPD01A-016A0013	PCB Antenna	I-PEX	2.56	TX/RX
2	Magic	AWPD01B-016A0013	PCB Antenna	I-PEX	-0.1	TX/RX


Note: The EUT has two antennas.

For Bluetooth mode (1TX/1RX):

The EUT supports the antenna with TX/RX diversity function

Both of Ant. 1 and Ant. 2 can be used as transmitting/receiving antennas, but only one antenna can be used as transmitting/receiving antenna at the same time.

Ant. 2 generated the worst case than Ant. 1, so it tested and recorded in the report.



3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	0	2402 MHz	40	2442 MHz
	1	2403 MHz	:	:
	:	:	77	2479 MHz
	38	2440 MHz	78	2480 MHz
	39	2441 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

For Bluetooth 1.0 :

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	GFSK	1 Mbps	0/39/78	2
Hopping Channel Separation	GFSK	1 Mbps	0~1/39~40/77~78	2
Number of Hopping Frequency	GFSK	1 Mbps	0~78	2
Dwell Time	1DH1/1DH3/1DH5	1 Mbps	0/39/78	2
Radiated Emissions Below 1GHz	CTX	-	-	-
Radiated Emissions Above 1GHz	GFSK	1 Mbps	0/39/78	2
Band Edge Emissions	GFSK	1 Mbps	0/78	2

For Bluetooth 2.0 :

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	4-DQPSK	2 Mbps	0/39/78	2
Hopping Channel Separation	4-DQPSK	2 Mbps	0~1/39~40/77~78	2
Number of Hopping Frequency	4-DQPSK	2 Mbps	0~78	2
Dwell Time	2DH1/2DH3/2DH5	2 Mbps	0/39/78	2
Radiated Emissions Below 1GHz	CTX	-	-	-
Radiated Emissions Above 1GHz	4-DQPSK	2 Mbps	0/39/78	2
Band Edge Emissions	4-DQPSK	2 Mbps	0/78	2

For Bluetooth 2.1+EDR :

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	8DPSK	3 Mbps	0/39/78	2
Hopping Channel Separation	8DPSK	3 Mbps	0~1/39~40/77~78	2
Number of Hopping Frequency	8DPSK	3 Mbps	0~78	2
Dwell Time	3DH1/3DH3/3DH5	-	-	2
Radiated Emissions Below 1GHz	CTX	-	-	-
Radiated Emissions Above 1GHz	8DPSK	3 Mbps	0/39/78	2
Band Edge Emissions	8DPSK	3 Mbps	0/78	2

The following test modes were performed for all tests:

For Conducted Emission test:

The EUT was performed at Horizontal and Vertical and the worst-case was found at Vertical for Radiated emission below 1GHz test.

So Conducted Emission test will follow this same test mode.

Mode 1. : EUT (CTX) with Docking Station.

For Radiated Emission below 1GHz test:

Mode 1. : EUT (CTX) with WLAN and BT function Docking Station.

Mode 2. : EUT (CTX) with WLAN and BT function Lying.

Due to Mode 1 generated the worst test result, it was recorded in this report.

<For Co-location Test>:

The EUT could be applied with 2.4GHz WLAN function and Bluetooth function; therefore Co-location (please refer to Appendix B) tests are added for simultaneously transmit between 2.4GHz WLAN function and Bluetooth function.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

N/A

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For Bluetooth 1.0 :

Test Software Version	Blut Test 3		
Frequency	2402 MHz	2441 MHz	2480 MHz
Power Parameters	63	63	63

For Bluetooth 2.0 :

Test Software Version	Blut Test 3		
Frequency	2402 MHz	2441 MHz	2480 MHz
Power Parameters	105	105	105

For Bluetooth 2.1+EDR :


Test Software Version	Blut Test 3		
Frequency	2402 MHz	2441 MHz	2480 MHz
Power Parameters	105	105	105

3.9. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


3.10. Test Configurations

3.10.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shield	Length
1	Power cable	No	3.4m

3.10.2. Radiation Emissions Test Configuration



Item	Connection	Shield	Length
1	Power cable	No	3.4m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For a Low-power Radio-frequency Device which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	49%
Test Engineer	Sin Chang	Phase	Line
Configuration	CTX		



Freq	Over		Limit	Read	LISN	Cable	Remark
	Line	Level					
	MHz	dBuV	dB	dBuV	dB	dB	
1	0.19344	52.98	-10.91	63.89	52.63	0.15	0.20 QP
2	0.19344	43.94	-9.95	53.89	43.59	0.15	0.20 AVERAGE
3	0.20396	53.04	-10.41	63.45	52.69	0.15	0.20 QP
4 @	0.20396	46.75	-6.70	53.45	46.40	0.15	0.20 AVERAGE
5	0.21392	52.57	-10.48	63.05	52.22	0.15	0.20 QP
6	0.21392	45.21	-7.84	53.05	44.86	0.15	0.20 AVERAGE
7	0.35388	43.02	-15.85	58.87	42.67	0.15	0.20 QP
8	0.35388	33.96	-14.91	48.87	33.61	0.15	0.20 AVERAGE
9	11.683	23.40	-26.60	50.00	22.64	0.36	0.39 AVERAGE
10	11.683	34.89	-25.11	60.00	34.13	0.36	0.39 QP
11	15.552	27.83	-32.17	60.00	27.01	0.42	0.40 QP
12	15.552	22.47	-27.53	50.00	21.65	0.42	0.40 AVERAGE

Temperature	25°C	Humidity	49%
Test Engineer	Sin Chang	Phase	Neutral
Configuration	CTX		



Freq	Over Limit		Read Line Level	LISN Factor	Cable Loss	Remark
	Level	Limit				
MHz	dBuV	dB	dBuV	dB	dB	
1	0.19344	54.69	-9.20	63.89	54.41	0.08 0.20 QP
2	0.19344	46.03	-7.86	53.89	45.75	0.08 0.20 AVERAGE
3	0.19969	55.13	-8.49	63.62	54.85	0.08 0.20 QP
4 @	0.19969	47.69	-5.93	53.62	47.41	0.08 0.20 AVERAGE
5 @	0.20723	46.68	-6.64	53.32	46.40	0.08 0.20 AVERAGE
6	0.20723	53.45	-9.87	63.32	53.17	0.08 0.20 QP
7	0.21506	52.40	-10.61	63.01	52.12	0.08 0.20 QP
8	0.21506	43.68	-9.33	53.01	43.40	0.08 0.20 AVERAGE
9	0.22437	51.12	-11.54	62.66	50.84	0.08 0.20 QP
10	0.22437	32.24	-20.42	52.66	31.96	0.08 0.20 AVERAGE
11	0.35201	42.45	-16.46	58.91	42.17	0.08 0.20 QP
12	0.35201	33.74	-15.17	48.91	33.46	0.08 0.20 AVERAGE
13	0.38724	44.22	-13.90	58.12	43.94	0.08 0.20 QP
14	0.38724	29.08	-19.04	48.12	28.80	0.08 0.20 AVERAGE
15	0.46861	28.60	-17.94	46.54	28.32	0.08 0.20 AVERAGE
16	0.46861	45.79	-10.75	56.54	45.51	0.08 0.20 QP
17	0.47865	45.45	-10.91	56.36	45.17	0.08 0.20 QP
18	0.47865	28.07	-18.29	46.36	27.79	0.08 0.20 AVERAGE
19	0.56709	26.56	-19.44	46.00	26.28	0.08 0.20 AVERAGE
20	0.56709	43.24	-12.76	56.00	42.96	0.08 0.20 QP
21	0.59794	24.23	-21.77	46.00	23.95	0.08 0.20 AVERAGE
22	0.59794	39.68	-16.32	56.00	39.40	0.08 0.20 QP
23	15.552	46.08	-13.92	60.00	45.35	0.32 0.40 QP
24	15.552	35.54	-14.46	50.00	34.81	0.32 0.40 AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, the limit for peak output power is 1Watt (30dBm). For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts (21dBm). The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	GFSK/DQPSK/8DPSK
Test Date	Apr. 01, 2013		

For Bluetooth 1.0 :

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
0	2402 MHz	2.86	30.00	Complies
39	2441 MHz	2.97	30.00	Complies
78	2480 MHz	2.52	30.00	Complies

For Bluetooth 2.0 :

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
0	2402 MHz	0.65	30.00	Complies
39	2441 MHz	0.81	30.00	Complies
78	2480 MHz	0.21	30.00	Complies

For Bluetooth 2.1+EDR :

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
0	2402 MHz	-1.08	30.00	Complies
39	2441 MHz	-0.69	30.00	Complies
78	2480 MHz	-1.18	30.00	Complies

4.3. Hopping Channel Separation Measurement

4.3.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilized for 20 dB bandwidth measurement.
3. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were utilized for channel separation measurement.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Hopping Channel Separation

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	GFSK/DQPSK/8DPSK

For Bluetooth 1.0 :

Frequency	Ch. Separation (MHz)	20dB Bandwidth (MHz)	Two-Thirds of 20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Result
2402 MHz	1.00	0.8880	0.592	0.8840	Complies
2441 MHz	1.00	0.9440	0.629	0.9080	Complies
2480 MHz	1.00	0.9800	0.653	0.9000	Complies

Ch. Separation Limits: >20dB bandwidth or > Two-Thirds of 20dB bandwidth

For Bluetooth 2.0 :

Frequency	Ch. Separation (MHz)	20dB Bandwidth (MHz)	Two-Thirds of 20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Result
2402 MHz	1.00	1.3120	0.875	1.2000	Complies
2441 MHz	1.00	1.2600	0.840	1.1960	Complies
2480 MHz	1.00	1.2200	0.813	1.1840	Complies

Ch. Separation Limits: >20dB bandwidth or > Two-Thirds of 20dB bandwidth


For Bluetooth 2.1+EDR :

Frequency	Ch. Separation (MHz)	20dB Bandwidth (MHz)	Two-Thirds of 20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Result
2402 MHz	1.00	1.2720	0.848	1.2000	Complies
2441 MHz	1.00	1.2720	0.848	1.2000	Complies
2480 MHz	1.00	1.2760	0.851	1.1960	Complies

Ch. Separation Limits: >20dB bandwidth or > Two-Thirds of 20dB bandwidth


For Bluetooth 1.0 :

20 dB Bandwidth Plot on Channel 0 / 2402 MHz




Date: 1.APR.2013 11:58:21

20 dB Bandwidth Plot on Channel 39 / 2441 MHz




Date: 1.APR.2013 11:59:01

20 dB Bandwidth Plot on Channel 78 / 2480 MHz




Date: 1.APR.2013 11:59:32

Channel Separation Plot on Channel 0~1 / 2402 MHz ~ 2403 MHz




Date: 1.APR.2013 12:27:41

Channel Separation Plot on Channel 39~40 / 2441 MHz ~ 2442 MHz



Date: 1.APR.2013 12:28:53


Channel Separation Plot on Channel 77~78 / 2479 MHz ~ 2480 MHz



Date: 1.APR.2013 12:30:06


For Bluetooth 2.0 :

20 dB Bandwidth Plot on Channel 0 / 2402 MHz




Date: 1.APR.2013 11:57:25

20 dB Bandwidth Plot on Channel 39 / 2441 MHz




Date: 1.APR.2013 11:56:48

20 dB Bandwidth Plot on Channel 78 / 2480 MHz




Date: 1.APR.2013 11:55:29

Channel Separation Plot on Channel 0~1 / 2402 MHz ~ 2403 MHz




Date: 1.APR.2013 12:26:32

Channel Separation Plot on Channel 39~40 / 2441 MHz ~ 2442 MHz



Date: 1.APR.2013 12:24:24


Channel Separation Plot on Channel 77~78 / 2479 MHz ~ 2480 MHz



Date: 1.APR.2013 12:22:45


For Bluetooth 2.1+EDR :

20 dB Bandwidth Plot on Channel 0 / 2402 MHz




Date: 1.APR.2013 11:53:27

20 dB Bandwidth Plot on Channel 39 / 2441 MHz




Date: 1.APR.2013 11:54:02

20 dB Bandwidth Plot on Channel 78 / 2480 MHz




Date: 1.APR.2013 11:54:33

Channel Separation Plot on Channel 0~1 / 2402 MHz ~ 2403 MHz




Date: 1.APR.2013 12:17:24

Channel Separation Plot on Channel 39~40 / 2441 MHz ~ 2442 MHz



Date: 1.APR.2013 12:19:07

Channel Separation Plot on Channel 77~78 / 2479 MHz ~ 2480 MHz



Date: 1.APR.2013 12:20:37

4.4. Number of Hopping Frequency Measurement

4.4.1. Limit

At least 15 hopping frequencies, and should be equally spaced.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	1000 kHz
VB	1 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 1000 kHz and the video bandwidth of 1 kHz were utilized.
3. Observe frequency hopping in 2400MHz~2483.5MHz, there are at least 75 non-overlapping channels.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Number of Hopping Frequency


Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	GFSK/DQPSK/8DPSK

For Bluetooth 1.0 / Bluetooth 2.0 / Bluetooth 2.1+EDR :

Modulation Type	Channel No.	Frequency (MHz)	Hopping Ch. (Channels)	Min. Limit (Channels)	Test Result
GFSK/DQPSK/8DPSK	0 ~ 78	2402 ~ 2480	79	15	Complies

For Bluetooth 1.0 / Bluetooth 2.0 / Bluetooth 2.1+EDR :

Number of Hopping Channel Plot on Channel 0~78 / 2402 MHz ~ 2480 MHz



Date: 1.APR.2013 12:13:07

4.5. Dwell Time Measurement

4.5.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.5.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	0 MHz
RB	1000 kHz
VB	1000 kHz
Detector	Peak
Trace	Single Trigger

4.5.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer
2. Set RBW of spectrum analyzer to 1000kHz and VBW to 1000kHz.
3. Use a video trigger with the trigger level set to enable triggering only on full pulses.
4. Sweep Time is more than once pulse time.
5. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
6. Measure the maximum time duration of one single pulse.
7. Set the EUT for 3DH5, 3DH3 and 3DH1 packet transmitting.
8. Measure the maximum time duration of one single pulse.

4.5.4. Test Setup Layout



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Test Result of Dwell Time

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	GFSK / 1DH1, 1DH3, 1DH5

Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402 MHz	2.9200	0.3115	0.4000	Complies
DH3	2402 MHz	1.6700	0.2672	0.4000	Complies
DH1	2402 MHz	0.4100	0.1312	0.4000	Complies
DH5	2441 MHz	2.9200	0.3115	0.4000	Complies
DH3	2441 MHz	1.6700	0.2672	0.4000	Complies
DH1	2441 MHz	0.4100	0.1312	0.4000	Complies
DH5	2480 MHz	2.9200	0.3115	0.4000	Complies
DH3	2480 MHz	1.6700	0.2672	0.4000	Complies
DH1	2480 MHz	0.4100	0.1312	0.4000	Complies

Note: Pulse Duration * Number of Pulses*(Dwell time / measure time)


Remark:

Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time (us)

79 channels come from the Hopping Channel number.


Average Hopping Channel = hops / sweep time

Dwell Time Plot on Channel 0 / DH1 / 2402 MHz




Date: 1.APR.2013 12:35:50

Dwell Time Plot on Channel 39 / DH1 / 2441 MHz




Date: 1.APR.2013 12:36:39

Dwell Time Plot on Channel 78 / DH1 / 2480 MHz




Date: 1.APR.2013 12:41:08


Dwell Time Plot on Channel 0 / DH3 / 2402 MHz



Date: 1.APR.2013 12:34:44


Dwell Time Plot on Channel 39 / DH3 / 2441 MHz


Date: 1.APR.2013 12:37:40

Dwell Time Plot on Channel 78 / DH3 / 2480 MHz



Date: 1.APR.2013 12:40:21

Dwell Time Plot on Channel 0 / DH5 / 2402 MHz




Date: 1.APR.2013 12:33:08

Dwell Time Plot on Channel 39 / DH5 / 2441 MHz



Date: 1.APR.2013 12:38:42

Dwell Time Plot on Channel 78 / DH5 / 2480 MHz



Date: 1.APR.2013 12:39:30

4.6. Radiated Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.6.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.6.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Test Date	Mar. 27, 2013
Configurations	CTX		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


4.6.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Configurations	CTX

Horizontal



Freq	Level	Limit	Over	Read	Cable			A/Pos	T/Pos	Pol/Phase	Remark
					Line	Limit	Level				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	261.83	37.99	46.00	-8.01	54.83	1.95	12.75	31.54	125	190	HORIZONTAL Peak
2	332.64	37.99	46.00	-8.01	53.32	2.26	13.81	31.40	100	180	HORIZONTAL Peak
3 pk	514.03	42.10	46.00	-3.90	53.37	2.85	17.29	31.41	200	54	HORIZONTAL Peak
4 pp	600.00	43.08	46.00	-2.92	52.75	3.12	18.45	31.24	143	42	HORIZONTAL QP
5	771.08	38.65	46.00	-7.35	46.74	3.61	19.66	31.36	100	47	HORIZONTAL Peak
6 !	857.41	42.71	46.00	-3.29	49.78	3.84	20.28	31.19	100	257	HORIZONTAL QP

Vertical


Freq	Limit		Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m								
1	36.79	29.38	40.00	-10.62	46.35	0.71	14.20	31.88	100	250	VERTICAL Peak
2	142.52	28.92	43.50	-14.58	48.37	1.42	10.66	31.53	100	8	VERTICAL Peak
3	514.03	39.36	46.00	-6.64	50.63	2.85	17.29	31.41	100	124	VERTICAL Peak
4 pk	600.36	39.45	46.00	-6.55	49.12	3.12	18.45	31.24	100	87	VERTICAL Peak
5	771.08	36.84	46.00	-9.16	44.93	3.61	19.66	31.36	150	316	VERTICAL Peak
6 pp	857.15	42.80	46.00	-3.20	49.87	3.84	20.28	31.19	137	311	VERTICAL QP

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6.9. Results for Radiated Emissions (1GHz~10th Harmonic)

For Bluetooth 1.0 :

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Configurations	Channel 0
Test Date	Mar. 27, 2013		

Horizontal

Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
		Line	Limit	Level	Loss	Factor	Factor		cm	deg	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			
1	4803.97	53.87	54.00	-0.13	52.60	3.29	33.02	35.04	Average	101	313 HORIZONTAL
2	4803.97	57.98	74.00	-16.02	56.71	3.29	33.02	35.04	Peak	101	313 HORIZONTAL

Vertical

Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
		Line	Limit	Level	Loss	Factor	Factor		cm	deg	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			
1	4804.00	53.26	54.00	-0.74	51.99	3.29	33.02	35.04	Average	101	292 VERTICAL
2	4804.00	59.51	74.00	-14.49	58.24	3.29	33.02	35.04	Peak	101	292 VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Configurations	Channel 39
Test Date	Mar. 27, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dB	dB/m	dB						
1	4881.96	53.80	54.00	-0.20	52.34	3.33	33.16	35.03	Average	100	248	HORIZONTAL		
2	4881.96	59.55	74.00	-14.45	58.09	3.33	33.16	35.03	Peak	100	248	HORIZONTAL		
3	7323.00	35.31	54.00	-18.69	30.69	4.06	35.96	35.40	Average	100	108	HORIZONTAL		
4	7323.00	46.35	74.00	-27.65	41.73	4.06	35.96	35.40	Peak	100	108	HORIZONTAL		

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dB	dB/m	dB						
1	4881.96	52.56	54.00	-1.44	51.10	3.33	33.16	35.03	Average	102	243	VERTICAL		
2	4881.96	58.49	74.00	-15.51	57.03	3.33	33.16	35.03	Peak	102	243	VERTICAL		
3	7322.90	43.46	54.00	-10.54	38.84	4.06	35.96	35.40	Average	136	170	VERTICAL		
4	7322.90	49.68	74.00	-24.32	45.06	4.06	35.96	35.40	Peak	136	170	VERTICAL		

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Configurations	Channel 78
Test Date	Mar. 27, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
1	4959.93	53.61	54.00	-0.39	51.92	3.37	33.33	35.01	Average	101	240	HORIZONTAL		
2	4959.93	59.27	74.00	-14.73	57.58	3.37	33.33	35.01	Peak	101	240	HORIZONTAL		
3	7440.00	36.21	54.00	-17.79	31.34	4.07	36.20	35.40	Average	101	154	HORIZONTAL		
4	7440.00	45.50	74.00	-28.50	40.63	4.07	36.20	35.40	Peak	101	154	HORIZONTAL		

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable			Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m						
1	4959.94	53.25	54.00	-0.75	51.56	3.37	33.33	35.01	Average	101	180	VERTICAL		
2	4959.94	62.78	74.00	-11.22	61.09	3.37	33.33	35.01	Peak	101	180	VERTICAL		
3	7439.99	35.50	54.00	-18.50	30.63	4.07	36.20	35.40	Average	101	229	VERTICAL		
4	7439.99	45.53	74.00	-28.47	40.66	4.07	36.20	35.40	Peak	101	229	VERTICAL		

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Bluetooth 2.1+EDR :

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Configurations	Channel 0
Test Date	Mar. 27, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
1	4803.96	50.44	54.00	-3.56	49.17	3.29	33.02	35.04	Average	100	184 HORIZONTAL
2	4803.96	62.06	74.00	-11.94	60.79	3.29	33.02	35.04	Peak	100	184 HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
1	4803.97	52.53	54.00	-1.47	51.26	3.29	33.02	35.04	Average	106	185 VERTICAL
2	4803.97	59.69	74.00	-14.31	58.42	3.29	33.02	35.04	Peak	106	185 VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Configurations	Channel 39
Test Date	Mar. 27, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
1	4881.94	45.23	54.00	-8.77	43.77	3.33	33.16	35.03	Average	100	146 HORIZONTAL
2	4881.94	50.44	74.00	-23.56	48.98	3.33	33.16	35.03	Peak	100	146 HORIZONTAL
3	7323.00	32.64	54.00	-21.36	28.02	4.06	35.96	35.40	Average	100	119 HORIZONTAL
4	7323.00	43.87	74.00	-30.13	39.25	4.06	35.96	35.40	Peak	100	119 HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	Cable Antenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
1	4881.90	47.78	54.00	-6.22	46.32	3.33	33.16	35.03	Average	100	185 VERTICAL
2	4881.90	53.56	74.00	-20.44	52.10	3.33	33.16	35.03	Peak	100	185 VERTICAL
3	7323.00	32.67	54.00	-21.33	28.05	4.06	35.96	35.40	Average	100	304 VERTICAL
4	7323.00	42.46	74.00	-31.54	37.84	4.06	35.96	35.40	Peak	100	304 VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Configurations	Channel 78
Test Date	Mar. 26, 2013		

Horizontal

Freq	Level	Limit		Over Limit	Read Level	CableAntenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
1	4959.97	43.39	54.00	-10.61	41.70	3.37	33.33	35.01	Average	100	148 HORIZONTAL
2	4960.02	53.87	74.00	-20.13	52.18	3.37	33.33	35.01	Peak	100	148 HORIZONTAL
3	7440.01	32.78	54.00	-21.22	27.91	4.07	36.20	35.40	Average	100	193 HORIZONTAL
4	7440.01	43.18	74.00	-30.82	38.31	4.07	36.20	35.40	Peak	100	193 HORIZONTAL

Vertical

Freq	Level	Limit		Over Limit	Read Level	CableAntenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
1	4959.93	50.39	54.00	-3.61	48.70	3.37	33.33	35.01	Average	100	194 VERTICAL
2	4959.93	56.31	74.00	-17.69	54.62	3.37	33.33	35.01	Peak	100	194 VERTICAL
3	7440.00	33.00	54.00	-21.00	28.13	4.07	36.20	35.40	Average	100	99 VERTICAL
4	7440.00	43.30	74.00	-30.70	38.43	4.07	36.20	35.40	Peak	100	99 VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.7. Emissions Measurement

4.7.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.7.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 kHz /100 kHz for Peak

4.7.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.6.3, only the frequency range investigated is limited to 100MHz around band edges.

For Conducted Out of Band Emission Measurement:

1. The conducted emission test is performed on each TX port of operating mode without summing or adding $10\log (N)$ since the limit is relative emission limit. Only worst data of each operating mode is presented.

4.7.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.6.4.

For Conducted Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.7.7. Test Result of Band Edge and Fundamental Emissions

For Bluetooth 1.0 :

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Configurations	Channel 0, 39, 78
Test Date	Mar. 26, 2013		

Channel 0

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
			Line	Limit	Level	Loss	Factor	Factor		cm	deg	
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB	dB/m	dB			
1	2390.00	45.73	54.00	-8.27	15.34	2.22	28.17	0.00	Average	100	351	VERTICAL
2	2390.00	54.24	74.00	-19.76	23.85	2.22	28.17	0.00	Peak	100	351	VERTICAL
3	2401.84	98.45			68.02	2.22	28.21	0.00	Peak	100	351	VERTICAL
4	2402.00	94.40			63.97	2.22	28.21	0.00	Average	100	351	VERTICAL

Item 3, 4 are the fundamental frequency at 2402 MHz.

Channel 39

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
			Line	Limit	Level	Loss	Factor	Factor		cm	deg	
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB	dB/m	dB			
1	2390.00	45.73	54.00	-8.27	15.34	2.22	28.17	0.00	Average	100	134	HORIZONTAL
2	2390.00	54.53	74.00	-19.47	24.14	2.22	28.17	0.00	Peak	100	134	HORIZONTAL
3	2441.00	87.80			57.27	2.24	28.29	0.00	Average	100	134	HORIZONTAL
4	2441.00	91.98			61.45	2.24	28.29	0.00	Peak	100	134	HORIZONTAL
5	2483.50	46.17	54.00	-7.83	15.53	2.26	28.38	0.00	Average	100	134	HORIZONTAL
6	2483.50	55.06	74.00	-18.94	24.42	2.26	28.38	0.00	Peak	100	134	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2441 MHz.

Channel 78

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
			Line	Limit	Level	Loss	Factor	Factor		cm	deg	
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB	dB/m	dB			
1	2479.84	95.58			64.95	2.26	28.37	0.00	Peak	100	171	VERTICAL
2	2480.00	94.70			64.07	2.26	28.37	0.00	Average	100	171	VERTICAL
3	2483.50	48.27	54.00	-5.73	17.64	2.26	28.37	0.00	Average	100	171	VERTICAL
4	2484.62	58.43	74.00	-15.57	27.80	2.26	28.37	0.00	Peak	100	171	VERTICAL

Item 1, 2 are the fundamental frequency at 2480 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Bluetooth 2.1+EDR :

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Configurations	Channel 0, 39, 78
Test Date	Mar. 26, 2013		

Channel 0

Freq	Level	Limit		Over Limit	Read Level	CableAntenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
1	2390.00	45.61	54.00	-8.39	15.22	2.22	28.17	0.00	Average	100	351 VERTICAL
2	2390.00	54.86	74.00	-19.14	24.47	2.22	28.17	0.00	Peak	100	351 VERTICAL
3	2401.84	98.55			68.12	2.22	28.21	0.00	Peak	100	351 VERTICAL
4	2402.00	94.46			64.03	2.22	28.21	0.00	Average	100	351 VERTICAL

Item 3, 4 are the fundamental frequency at 2402 MHz.

Channel 39

Freq	Level	Limit		Over Limit	Read Level	CableAntenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
1	2390.00	45.62	54.00	-8.38	15.23	2.22	28.17	0.00	Average	100	196 VERTICAL
2	2390.00	55.86	74.00	-18.14	25.47	2.22	28.17	0.00	Peak	100	196 VERTICAL
3	2441.00	91.92			61.39	2.24	28.29	0.00	Average	100	196 VERTICAL
4	2441.00	95.85			65.32	2.24	28.29	0.00	Peak	100	196 VERTICAL
5	2483.50	45.92	54.00	-8.08	15.29	2.26	28.37	0.00	Average	100	196 VERTICAL
6	2483.50	54.46	74.00	-19.54	23.83	2.26	28.37	0.00	Peak	100	196 VERTICAL

Item 3, 4 are the fundamental frequency at 2441 MHz.

Channel 78

Freq	Level	Limit		Over Limit	Read Level	CableAntenna Preamp			A/Pos	T/Pos	Pol/Phase
		Line	dB			dBuV	dB	dB/m			
1	2479.84	93.46			62.83	2.26	28.37	0.00	Peak	100	170 VERTICAL
2	2480.00	88.01			57.38	2.26	28.37	0.00	Average	100	170 VERTICAL
3	2483.50	48.60	54.00	-5.40	17.97	2.26	28.37	0.00	Average	100	170 VERTICAL
4	2483.50	59.39	74.00	-14.61	28.76	2.26	28.37	0.00	Peak	100	170 VERTICAL

Item 1, 2 are the fundamental frequency at 2480 MHz.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


For Bluetooth 1.0 :

Plot on Configuration For Bluetooth 1.0 / Channel 0 / Reference Level




Date: 1.APR.2013 13:47:14

Plot on Configuration For Bluetooth 1.0 / Channel 0 / 30MHz~2400MHz (down 30dBc)




Date: 1.APR.2013 14:13:29

Plot on Configuration For Bluetooth 1.0 / Channel 78 / Reference Level




Date: 1.APR.2013 13:48:09

Plot on Configuration For Bluetooth 1.0 / Channel 78 / 2500MHz~26500MHz (down 30dBc)




Date: 1.APR.2013 14:15:43

Plot on Configuration For Bluetooth 1.0 / Hopping / Reference Level




Date: 1.APR.2013 13:39:25

Plot on Configuration For Bluetooth 1.0/ Hopping / 30MHz~2400MHz (down 30dBc)



Date: 1.APR.2013 14:14:22


Plot on Configuration For Bluetooth 1.0 / Hopping / 2500MHz~26500MHz (down 30dBc)



Date: 1.APR.2013 14:16:18


For Bluetooth 2.1+EDR :

Plot on Configuration For Bluetooth 2.1+EDR / Channel 0 / Reference Level




Date: 1.APR.2013 13:06:50

Plot on Configuration For Bluetooth 2.1+EDR / Channel 0 / 30MHz~2400MHz (down 30dBc)




Date: 1.APR.2013 14:07:01

Plot on Configuration For Bluetooth 2.1+EDR / Channel 78 / Reference Level




Date: 1.APR.2013 13:26:36

Plot on Configuration For Bluetooth 2.1+EDR / Channel 78 / 2500MHz~2650MHz (down 30dBc)




Date: 1.APR.2013 14:08:35

Plot on Configuration For Bluetooth 2.1+EDR / Hopping / Reference Level




Date: 1.APR.2013 13:28:44

Plot on Configuration For Bluetooth 2.1+EDR / Hopping / 30MHz~2400MHz (down 30dBc)



Date: 1.APR.2013 14:11:24

Plot on Configuration For Bluetooth 2.1+EDR / Hopping / 2500MHz~26500MHz (down 30dBc)



Date: 1.APR.2013 14:10:48

4.8. Antenna Requirements

4.8.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

4.8.2. Antenna Connector Construction

Please refer to section 3.3 in this test report, antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 21, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 04, 2012	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 16, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

*** Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

Appendix A. Test Photos

1. Photographs of Conducted Emissions Test Configuration

FRONT VIEW



REAR VIEW



2. Photographs of Radiated Emissions Test Configuration

Test Configuration: 9kHz ~30MHz

FRONT VIEW



REAR VIEW



Test Mode: Mode 1

Test Configuration: 30MHz~1GHz

FRONT VIEW




REAR VIEW



Test Configuration: Above 1GHz

FRONT VIEW



REAR VIEW




Appendix B. Co-location


1. Results of Radiated Emissions for Co-located

Temperature	24°C	Humidity	60%
Test Engineer	David Tseng	Configurations	Wi-Fi + Bluetooth

Horizontal



Freq	Level	Limit		Over Limit	Read Level	Cable		Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
		Line	dBuV/m			dB	dBuV			cm	deg		
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB	dB	dB/m	dB	cm	deg		
1	1627.33	46.41	74.00	-27.59	54.56	3.01	25.65	36.81	103	117	HORIZONTAL	Peak	
2	1627.36	40.75	54.00	-13.25	48.90	3.01	25.65	36.81	103	117	HORIZONTAL	Average	
3 pp	4824.00	48.87	54.00	-5.13	45.72	5.69	32.76	35.30	143	210	HORIZONTAL	Average	
4	4824.13	53.92	74.00	-20.08	50.77	5.69	32.76	35.30	143	210	HORIZONTAL	Peak	
5	4882.13	46.41	54.00	-7.59	43.16	5.76	32.81	35.32	100	36	HORIZONTAL	Average	
6	4882.13	51.76	74.00	-22.24	48.51	5.76	32.81	35.32	100	36	HORIZONTAL	Peak	
7 pk	7322.76	54.43	74.00	-19.57	45.59	7.06	37.13	35.35	100	351	HORIZONTAL	Peak	
8	7322.95	42.91	54.00	-11.09	34.07	7.06	37.13	35.35	100	351	HORIZONTAL	Average	

Vertical


Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
		Line	Limit	Level	Loss	Factor	Factor	cm	deg		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	1627.22	43.08	74.00	-30.92	51.23	3.01	25.65	36.81	100	300	VERTICAL Peak
2	1627.41	33.67	54.00	-20.33	41.82	3.01	25.65	36.81	100	300	VERTICAL Average
3 pk	4823.93	56.61	74.00	-17.39	53.46	5.69	32.76	35.30	104	195	VERTICAL Peak
4 pp	4824.00	52.64	54.00	-1.36	49.49	5.69	32.76	35.30	104	195	VERTICAL Average
5 !	4882.00	52.19	54.00	-1.81	48.94	5.76	32.81	35.32	100	274	VERTICAL Average
6	4882.06	55.80	74.00	-18.20	52.55	5.76	32.81	35.32	100	274	VERTICAL Peak
7	7322.77	54.06	74.00	-19.94	45.22	7.06	37.13	35.35	100	112	VERTICAL Peak
8	7322.90	43.81	54.00	-10.19	34.97	7.06	37.13	35.35	100	112	VERTICAL Average