Maximum Permissive Exposure

Brand : DELL

Product Name : Flat Panel Monitor

Model Name : S2317HWib FCC ID : VRSS2317HWIB


1. Tested Supporting System List

| No. | Product | Brand | Model No. | Serial No. | FCC ID |
|-----|--------------|---------|----------------------------|-------------|------------|
| 1. | Mobile Phone | SAMSUNG | SM-G9208/SS (Galaxy S6) | R28G40LGHGJ | A3LSMG920T |

2. Radiated Emission Measurement

| Item | Туре | Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Interval |
|------|-----------------------------------|--------------|-----------|------------|--------------|---------------|
| 1. | Broadband Field Meter | NARDA | NBM-550 | B-0959 | 2014. 11. 18 | 2 Year |
| 2. | Magnetic Field Meter (1Hz-400kHz) | NARDA | ELT-400 | M-0291 | 2014. 12. 04 | 2 Year |
| 3. | B-Field Probe (100kHz-3GHz) | NARDA | EF0391 | A-1034 | 2014. 11. 19 | 2 Year |

3. Setup Configuration



4. Operating Condition of EUT

Mobile phone S6 was at 0% power and in contact directly with EUT for charging.

5. MPE Calculation

Qisda Corporation declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm2) | Averaging Time (minutes) |
|-----------------------------|---|---|----------------------------------|--------------------------------|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f ²)* | 30 |
| 30-300 | 27.5 | 0.73 | 2 | 30 |
| 300-1500 | | | f/150 | 30 |
| 1500-100,000 | | | 1 | 30 |

Qisda Corporation declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

WPC:

| Separation | Probe from EUT side | E-filed strength (V/m) | H-field strength (A/m) |
|-------------------|---------------------|---------------------------|---------------------------|
| 10cm | Left | 0.06 | 0.02 |
| 10cm | Right | 0.50 | 0.08 |
| 10cm | Тор | 0.23 | 0.03 |
| 10cm | Bottom | 0.19 | 0.05 |
| 10cm | Back | 0.19 | 0.02 |
| 10cm | Front | 0.11 | 0.05 |
| Aggregation Level | | 1.28 | 0.28 |
| Limit | | 614 | 1.63 |

Simultaneous MPE Calculation:

S2317HWib is embedded with certified Wi-Fi Combo card FCC ID: PPD-QCNFA324, the total MPE is calculate as following.

| <u> </u> | | | |
|----------|-----------------------------|-----------------------------|-------|
| WPC MPE | Wi-Fi MPE ^{note 1} | Total MPE ^{note 2} | Limit |
| 0.28 | 0.16321 | 0.3349 | < 1 |

Note 1: The max MPE of FCC ID: PPD-QCNFA324 is 0.16321mW/cm² in 802.11g mode(reference from original filing).

Note 2: The total MPE was calculated from (MPE 1/Limit 1)+ (MPE 2/Limit 2)

Sincerely Yours,

Mr. Ben Cheng

Manager

AUDIX Technology Corporation