



**M. Flom Associates, Inc. - Global Compliance Center**  
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176  
www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Date: November 22, 1999

Federal Communications Commission  
Via: Electronic Filing

Attention: Authorization & Evaluation Division

FCC Rules: 90

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

William H. Graff, Director  
of Engineering

enclosure(s)  
cc: Applicant  
WHG/cvr

LIST OF EXHIBITS  
(FCC **CERTIFICATION** (TRANSMITTERS) - REVISED 9/28/98)

BY APPLICANT:

1. LETTER OF AUTHORIZATION
2. IDENTIFICATION DRAWINGS, 2.1033(c) (11)
  - LABEL
  - LOCATION OF LABEL
  - COMPLIANCE STATEMENT
  - LOCATION OF COMPLIANCE STATEMENT
3. PHOTOGRAPHS, 2.1033(c) (12)
4. DOCUMENTATION: 2.1033(c)
  - (3) USER MANUAL
  - (9) TUNE UP INFO
  - (10) SCHEMATIC DIAGRAM
  - (10) CIRCUIT DESCRIPTION
5. PART 90.203(e) & (g) ATTESTATION

BY M.F.A. INC.

- A. TESTIMONIAL & STATEMENT OF CERTIFICATION
- B. STATEMENT OF QUALIFICATIONS



**M. Flom Associates, Inc. - Global Compliance Center**  
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176  
www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

---

Sub-part  
2.1033(c) :

NAMEPLATE DRAWING

ATTACHED, EXHIBIT 1.

LOCATION

AS PER LABEL DRAWING(S)

DATE OF REPORT

November 22, 1999

SUPERVISED BY:



William H. Graff, Director  
of Engineering

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	5
	Standard Test Conditions and Engineering Practices	6
2.1046(a)	Carrier Output Power (Conducted)	7
2.1051	Unwanted Emissions (Transmitter Conducted)	9
2.1053(a)	Field Strength of Spurious Radiation	13
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	17
2.1047(a)	Audio Low Pass Filter (Voice Input)	22
2.1047(a)	Audio Frequency Response	25
2.1047(b)	Modulation Limiting	27
2.1055(a)(1)	Frequency Stability (Temperature Variation)	29
2.1055(b)(1)	Frequency Stability (Voltage Variation)	32
2.202(g)	Necessary Bandwidth and Emission Bandwidth	33

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)

TEST REPORT

b) Laboratory: M. Flom Associates, Inc.  
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107  
(Canada: IC 2044) Chandler, AZ 85224

c) Report Number: d99b0081

e)

Description: VHF FM Handheld Transceiver

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: November 22, 1999  
EUT Received: October 9, 1999

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:



William H. Graff, Director  
of Engineering

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATION

IN ACCORDANCE WITH FCC RULES AND REGULATIONS,  
VOLUME II, PART 2 AND TO

90

Sub-part 2.1033

(c) (3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c) (4): TYPE OF EMISSION: 16K0F3E

(c) (5): FREQUENCY RANGE, MHz: 35 to 50

(c) (6): POWER RATING, Watts: 1 to 6  
\_\_\_\_ Switchable  Variable  N/A

(c) (7): MAXIMUM POWER RATING, Watts: 300

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below.



THE AMERICAN  
ASSOCIATION  
FOR LABORATORY  
ACCREDITATION

### ACCREDITED LABORATORY

A2LA has accredited

**M. FLOM ASSOCIATES, INC.**

**Chandler, AZ**

for technical competence in the field of

#### Electrical (EMC) Testing

The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC Guide 25-1990 "General Requirements for the Competence of Calibration and Testing Laboratories" (equivalent to relevant requirements of the ISO 9000 series of standards) and any additional program requirements in the identified field of testing.

Presented this 24<sup>th</sup> day of November, 1998.



*Pete Flom*  
President  
For the Accreditation Council  
Certificate Number 1008.01  
Valid to December 31, 2000

For tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical (EMC) Scope of Accreditation



American Association for Laboratory Accreditation

#### SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 25-1990 AND EN 45001

M. FLOM ASSOCIATES, INC.  
Electronic Testing Laboratory  
3356 North San Marcos Place, Suite 107  
Chandler, AZ 85224-1571  
Morton Flom Phone: 602 926 3100

#### ELECTRICAL (EMC)

Valid to: December 31, 2000

Certificate Number: 1008-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following electromagnetic compatibility tests:

Tests	Standard(s)
RF Emissions	FCC Part 15 (Subparts B and C) using ANSI C63.4-1992; CISPR 11; CISPR 13; CISPR 14; CISPR 22; EN 55011; EN 55013; EN 55014; EN 55022; EN 50081-1; EN 50081-2; FCC Part 18; ICES-003; AS/NZS 1044; AS/NZS 1053; AS/NZS 3548; AS/NZS 4251.1
RF Immunity	EN 50082-1; EN 50082-2; AS/NZS 4251.1
Radiated Susceptibility	EN 61000-4-3; ENV 50140; ENV 50204; IEC 1000-4-3; IEC 801-3
ESD	EN 61000-4-2; IEC 1000-4-2; IEC 801-2
EFT	EN 61000-4-4; IEC 1000-4-4; IEC 801-4
Surge	EN 61000-4-5; ENV 50142; IEC 1000-4-5; IEC 801-5
47 CFR (FCC)	2, 21, 22, 23, 24, 74, 80, 87, 90, 95, 97

*Pete Flom*

5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8307 • Phone: 301 644 3200 • Fax: 301 662 2974



"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not be covered by this laboratory's A2LA accreditation.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE,  
INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual  
COLLECTOR VOLTAGE, Vdc = per manual  
SUPPLY VOLTAGE, Vdc = 7.5

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

       ATTACHED EXHIBITS  
x N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

Sub-part

2.1033(c)(14):

TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- \_\_\_\_ 21 - Domestic Public Fixed Radio Services
- \_\_\_\_ 22 - Public Mobile Services
- \_\_\_\_ 22 Subpart H - Cellular Radiotelephone Service
- \_\_\_\_ 22.901(d) - Alternative technologies and auxiliary services
- \_\_\_\_ 23 - International Fixed Public Radiocommunication services
- \_\_\_\_ 24 - Personal Communications Services
- \_\_\_\_ 74 Subpart H - Low Power Auxiliary Stations
- \_\_\_\_ 80 - Stations in the Maritime Services
- \_\_\_\_ 80 Subpart E - General Technical Standards
- \_\_\_\_ 80 Subpart F - Equipment Authorization for Compulsory Ships
- \_\_\_\_ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- \_\_\_\_ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- \_\_\_\_ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- \_\_\_\_ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- \_\_\_\_ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- \_\_\_\_ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- \_\_\_\_ 80 Subpart X - Voluntary Radio Installations
- \_\_\_\_ 87 - Aviation Services
- 90 - Private Land Mobile Radio Services
- \_\_\_\_ 94 - Private Operational-Fixed Microwave Service
- \_\_\_\_ 95 Subpart A - General Mobile Radio Service (GMRS)
- \_\_\_\_ 95 Subpart C - Radio Control (R/C) Radio Service
- \_\_\_\_ 95 Subpart D - Citizens Band (CB) Radio Service
- \_\_\_\_ 95 Subpart E - Family Radio Service
- \_\_\_\_ 95 Subpart F - Interactive Video and Data Service (IVDS)
- \_\_\_\_ 97 - Amateur Radio Service
- \_\_\_\_ 101 - Fixed Microwave Services

STANDARD TEST CONDITIONS  
and  
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 7 of 33.

NAME OF TEST: Carrier Output Power (Conducted)

SPECIFICATION: 47 CFR 2.1046(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is  $\pm 3\%$ .

MEASUREMENT RESULTS  
(Worst case)

FREQUENCY OF CARRIER, MHz = 42.6, 35.1, 49.9

POWER SETTING	R. F. POWER, WATTS
Low	1
High	6


SUPERVISED BY:



William H. Graff, Director  
of Engineering

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT  
TEST 2: FREQUENCY STABILITY



Asset Description (as applicable)	s/n
(1) COAXIAL ATTENUATOR	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(2) POWER METERS	
i00014 HP 435A	1733A05836
i00039 HP 436A	2709A26776
i00020 HP 8901A POWER MODE	2105A01087
(3) FREQUENCY COUNTER	
i00042 HP 5383A	1628A00959
i00019 HP 5334B	2704A00347
i00020 HP 8901A FREQUENCY MODE	2105A01087

PAGE NO.

9 of 33.

NAME OF TEST:

Unwanted Emissions (Transmitter Conducted)

SPECIFICATION:

47 CFR 2.1051

GUIDE:

ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

TEST EQUIPMENT:

As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
  - (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
  - (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.
3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE

FREQUENCY OF CARRIER, MHz = 42.6, 35.1, 49.9

SPECTRUM SEARCHED, GHz = 0 to 10 x  $F_c$

MAXIMUM RESPONSE, Hz = 3160

ALL OTHER EMISSIONS = = 20 dB BELOW LIMIT

LIMIT(S), dBc

$-(50+10\log P)$  = -50 (1 Watt)

$-(50+10\log P)$  = -57.8 (6 Watts)


SUPERVISED BY:



William H. Graff, Director  
of Engineering

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)  
 TEST B. OUT-OF-BAND SPURIOUS



Asset Description (as applicable)	s/n
(1) <u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00012 HP 3312A	1432A11250
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(3) <u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126 Eagle TNF-1	100-250
i00125 Eagle TNF-1	50-60
i00124 Eagle TNF-1	250-850
(4) <u>SPECTRUM ANALYZER</u>	
i00048 HP 8566B	2511A01467
i00029 HP 8563E	3213A00104

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)  
 g99b0334: 1999-Nov-17 Wed 11:37:00  
 STATE: 1:Low Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
35.100000	70.207000	-42.3	-72.3	-22.3
42.600000	85.196000	-37.8	-67.8	-17.8
49.900000	99.814000	-52.3	-82.3	-32.3
35.100000	105.315000	-35.2	-65.2	-15.2
42.600000	127.788000	-37.5	-67.5	-17.5
35.100000	140.253000	-54.7	-84.7	-34.7
49.900000	149.712000	-38.8	-68.8	-18.8
42.600000	170.403000	-49.9	-79.9	-29.9
35.100000	175.875000	-54.6	-84.6	-34.6
49.900000	199.966000	-54.6	-84.6	-34.6
35.100000	210.276000	-54.9	-84.9	-34.9
42.600000	213.006000	-50.9	-80.9	-30.9
35.100000	245.428000	-54.8	-84.8	-34.8
49.900000	249.973000	-55.2	-85.2	-35.2
42.600000	255.486000	-54.7	-84.7	-34.7
35.100000	280.685000	-53.6	-83.6	-33.6
42.600000	297.866000	-54.2	-84.2	-34.2
49.900000	299.054000	-54.9	-84.9	-34.9
35.100000	316.102000	-53.7	-83.7	-33.7
42.600000	340.774000	-53.8	-83.8	-33.8
49.900000	349.201000	-54.3	-84.3	-34.3
35.100000	350.538000	-55.1	-85.1	-35.1
42.600000	383.707000	-55	-85	-35
35.100000	386.046000	-55	-85	-35
49.900000	399.333000	-53.7	-83.7	-33.7
35.100000	420.973000	-55.5	-85.5	-35.5
42.600000	426.174000	-55.4	-85.4	-35.4
49.900000	448.758000	-54.7	-84.7	-34.7
35.100000	456.473000	-54.8	-84.8	-34.8
42.600000	469.097000	-54.7	-84.7	-34.7
35.100000	491.579000	-55	-85	-35
49.900000	499.219000	-54.5	-84.5	-34.5
42.600000	511.622000	-54.2	-84.2	-34.2
35.100000	526.041000	-54.4	-84.4	-34.4
49.900000	548.779000	-54.4	-84.4	-34.4
42.600000	554.295000	-54.2	-84.2	-34.2
42.600000	595.973000	-53.4	-83.4	-33.4
49.900000	598.994000	-55.6	-85.6	-35.6
42.600000	638.847000	-54.3	-84.3	-34.3
49.900000	648.477000	-54.8	-84.8	-34.8
49.900000	698.692000	-55	-85	-35
49.900000	748.407000	-54	-84	-34

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)  
 g99b0333: 1999-Nov-17 Wed 11:24:00  
 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
35.100000	70.210000	-43.1	-80.8	-23.1
42.600000	84.995000	-43.7	-81.4	-23.7
49.900000	99.814000	-36.6	-74.3	-16.6
35.100000	105.312000	-25.5	-63.2	-5.5
42.600000	127.785000	-43.1	-80.8	-23.1
35.100000	140.829000	-44.3	-82	-24.3
49.900000	149.713000	-35.3	-73	-15.3
42.600000	170.797000	-43.4	-81.1	-23.4
35.100000	175.132000	-44.3	-82	-24.3
49.900000	199.926000	-45	-82.7	-25
35.100000	210.999000	-44.1	-81.8	-24.1
42.600000	212.835000	-44.7	-82.4	-24.7
35.100000	245.729000	-44.4	-82.1	-24.4
49.900000	249.541000	-44.1	-81.8	-24.1
42.600000	255.204000	-44.9	-82.6	-24.9
35.100000	280.690000	-43.7	-81.4	-23.7
42.600000	297.850000	-44.8	-82.5	-24.8
49.900000	299.158000	-45	-82.7	-25
35.100000	315.936000	-45.2	-82.9	-25.2
42.600000	340.517000	-43.6	-81.3	-23.6
49.900000	349.642000	-44.7	-82.4	-24.7
35.100000	350.843000	-43.7	-81.4	-23.7
42.600000	383.496000	-44.5	-82.2	-24.5
35.100000	386.361000	-44.2	-81.9	-24.2
49.900000	399.576000	-45.1	-82.8	-25.1
35.100000	421.700000	-45.7	-83.4	-25.7
42.600000	425.791000	-44.6	-82.3	-24.6
49.900000	448.758000	-43.8	-81.5	-23.8
35.100000	456.043000	-44.9	-82.6	-24.9
42.600000	468.984000	-44.3	-82	-24.3
35.100000	491.780000	-44.5	-82.2	-24.5
49.900000	498.611000	-45.1	-82.8	-25.1
42.600000	511.032000	-44.9	-82.6	-24.9
35.100000	526.193000	-44	-81.7	-24
49.900000	549.064000	-45.6	-83.3	-25.6
42.600000	554.190000	-43.6	-81.3	-23.6
42.600000	596.279000	-44.9	-82.6	-24.9
49.900000	598.839000	-44.9	-82.6	-24.9
42.600000	639.331000	-44.9	-82.6	-24.9
49.900000	649.169000	-45.1	-82.8	-25.1
49.900000	698.384000	-45.3	-83	-25.3
49.900000	748.659000	-44.3	-82	-24.3

PAGE NO. 13 of 33.

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: 47 CFR 2.1053(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.12


TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. A description of the measurement facilities was filed with the FCC and was found to be in compliance with the requirements of Section 2.948, by letter from the FCC dated March 3, 1997, FILE 31040/SIT. All pertinent changes will be reported to the Commission by up-date prior to March 2000.
2. At first, in order to locate all spurious frequencies and approximate amplitudes, and to determine proper equipment functioning, the test sample was set up at a distance of three meters from the test instrument. Valid spurious signals were determined by switching the power on and off.
3. In the field, the test sample was placed on a wooden turntable above ground at three (or thirty) meters away from the search antenna. Excess power leads were coiled near the power supply.

The cables were oriented in order to obtain the maximum response. At each emission frequency, the turntable was rotated and the search antennas were raised and lowered vertically.

4. The emission was observed with both a vertically polarized and a horizontally polarized search antenna and the worst case was used.
5. The field strength of each emission within 20 dB of the limit was recorded and corrected with the appropriate cable and transducer factors.
6. The worst case for all channels is shown.
7. Measurement results: ATTACHED FOR WORST CASE

RADIATED TEST SETUP

## NOTES:

- (a) Search Antenna - Rotatable on boom
- (b) Non-metallic boom
- (c) Non-metallic mast
- (d) Adjustable horizontally
- (e) Equipment Under Test
- (f) Turntable
- (g) Boom adjustable in height.
- (h) External control cables routed horizontally at least one wavelength.
- (i) Rotatable
- (j) Cables routed through hollow turntable center
- (k) 30 cm or less
- (l) External power source
- (m) 10 cm diameter coil of excess cable
- (n) 25 cm (V), 1 m-7 m (V, H)
- (o) 25 cm from bottom end of 'V', 1m normally
- (p) Calibrated Cable at least 10m in length
- (q) Amplifier (optional)
- (r) Spectrum Analyzer

Asset	Description (as applicable)	s/n	Cycle	Last Cal
per ANSI C63.4-1992, 10.1.4				
<u>TRANSDUCER</u>				
i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-99
i00065	EMCO 3301-B Active Monopole	2635	12 mo.	Sep-99
i00089	Aprél 2001 200MHz-1GHz	001500	12 mo.	Sep-99
i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-99
<u>AMPLIFIER</u>				
i00028	HP 8449A	2749A00121	12 mo.	Mar-99
<u>SPECTRUM ANALYZER</u>				
i00029	HP 8563E	3213A00104	12 mo.	Aug-99
i00033	HP 85462A	3625A00357	12 mo.	May-99
i00048	HP 8566B	2511AD1467	6 mo.	May-99

PAGE NO. 15 of 33.

NAME OF TEST: Field Strength of Spurious Radiation

ALL OTHER EMISSIONS = = 20 dB BELOW LIMIT

EMISSION, MHz/HARMONIC	SPURIOUS LEVEL, dBc	
	Low	High
2nd to 10th	<-65	<-60

SUPERVISED BY:



William H. Graff, Director  
of Engineering

NAME OF TEST: Field Strength of Spurious Radiation

g99b0326: 1999-Nov-10 Wed 08:45:00

STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	METER, dBuV	CF, dB	ERP, dBm	MARGIN, dB
42.600000	85.218000	48.26	9.94	-28.7	-8.7
42.600000	127.825000	51.17	14.73	-21	-1
42.600000	170.400000	23.44	15.73	-47.8	-27.7
42.600000	212.999880	19.99	18.18	-48.8	-28.7
42.600000	255.599880	1.36	20.98	-64.6	-44.6
42.600000	298.199880	5.28	30.05	-51.6	-31.6
42.600000	340.799880	4.6	20.69	-61.6	-41.6
42.600000	383.399880	11.24	22.99	-52.7	-32.7
42.600000	425.999880	4.83	23.78	-58.3	-38.3

PAGE NO. 17 of 33.

NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECIFICATION: 47 CFR 2.1049(c)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11

TEST EQUIPMENT: As per previous page


#### MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for  $\pm 2.5$  kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

18 of 33.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
g99b0330: 1999-Nov-17 Wed 11:17:00  
STATE: 1:Low Power



POWER: LOW  
MODULATION: NONE


SUPERVISED BY:

  
William H. Graff, Director  
of Engineering

PAGE NO.

19 of 33.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
g99b0331: 1999-Nov-17 Wed 11:19:00  
STATE: 1:Low Power



POWER:  
MODULATION:

LOW  
VOICE: 2500 Hz SINE WAVE  
MASK: B, VHF/UHF 25kHz,  
w/LPF


SUPERVISED BY:

  
William H. Graff, Director  
of Engineering

PAGE NO.

20 of 33.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
g99b0329: 1999-Nov-17 Wed 11:12:00  
STATE: 2:High Power



POWER: HIGH  
MODULATION: NONE


SUPERVISED BY:

  
William H. Graff, Director  
of Engineering

PAGE NO.

21 of 33.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
g99b0332: 1999-Nov-17 Wed 11:21:00  
STATE: 2:High Power



POWER:  
MODULATION:

HIGH  
VOICE: 2500 Hz SINE WAVE  
MASK: B, VHF/UHF 25kHz,  
w/LPF

SUPERVISED BY:

  
William H. Graff, Director  
of Engineering

PAGE NO. 22 of 33.

NAME OF TEST: Audio Low Pass Filter (Voice Input)

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15


TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP

TEST A. MODULATION CAPABILITY/DISTORTION  
 TEST B. AUDIO FREQUENCY RESPONSE  
 TEST C. HUM AND NOISE LEVEL  
 TEST D. RESPONSE OF LOW PASS FILTER  
 TEST E. MODULATION LIMITING




Asset	Description (as applicable)	s/n
(1) <u>Audio Oscillator</u>		
i00010	HP 204D	1105A04683
i00017	HP 8903A	2216A01753
i00118	HP 33120A	US36002064
(2) <u>COAXIAL ATTENUATOR</u>		
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3) <u>MODULATION ANALYZER</u>		
i00020	HP 8901A	2105A01087
(4) <u>AUDIO ANALYZER</u>		
i00017	HP 8903A	2216A01753

PAGE NO.

24 of 33.

NAME OF TEST: Audio Low Pass Filter (Voice Input)  
g99b0296: 1999-Nov-16 Tue 08:32:00  
STATE: 0:General



SUPERVISED BY:

William H. Graff, Director  
of Engineering

PAGE NO. 25 of 33.  
NAME OF TEST: Audio Frequency Response  
SPECIFICATION: 47 CFR 2.1047(a)  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6  
TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

26 of 33.

NAME OF TEST: Audio Frequency Response  
g99b0294: 1999-Nov-16 Tue 08:27:00  
STATE: 0:General



Frequency of Maximum Audio Response, Hz = 3160

Additional points:

FREQUENCY, Hz	LEVEL, dB
300	-12.74
20000	-36.34
30000	-36.28
50000	-36.50

SUPERVISED BY:

  
William H. Graff, Director  
of Engineering

PAGE NO. 27 of 33.

NAME OF TEST: Modulation Limiting

SPECIFICATION: 47 CFR 2.1047(b)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation ( $\pm 1.5$  kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.


5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.


28 of 33.

NAME OF TEST: Modulation Limiting  
g99b0297: 1999-Nov-16 Tue 08:43:00  
STATE: 0:General

Positive  
Peaks:



Negative  
Peaks:



SUPERVISED BY:

William H. Graff, Director  
of Engineering

PAGE NO. 29 of 33.

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: 47 CFR 2.1055(a)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST CONDITIONS: As Indicated


TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP

TEST A. OPERATIONAL STABILITY  
 TEST B. CARRIER FREQUENCY STABILITY  
 TEST C. OPERATIONAL PERFORMANCE STABILITY  
 TEST D. HUMIDITY  
 TEST E. VIBRATION  
 TEST F. ENVIRONMENTAL TEMPERATURE  
 TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION  
 TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION




Transmitter Test Set-Up

Asset Description (as applicable)		s/n
(1) TEMPERATURE, HUMIDITY, VIBRATION		
i00027 Tenny Temp. Chamber	9083-765-234	
i00 Weber Humidity Chamber		
i00 L.A.B. RVH 18-100		
(2) COAXIAL ATTENUATOR		
i00122 NARDA 766-10	7802	
i00123 NARDA 766-10	7802A	
i00113 SIERRA 661A-3D	1059	
i00069 BIRD 8329 (30 dB)	10066	
(3) R.F. POWER		
i00014 HP 435A POWER METER	1733A05839	
i00039 HP 436A POWER METER	2709A26776	
i00020 HP 8901A POWER MODE	2105A01087	
(4) FREQUENCY COUNTER		
i00042 HP 5383A	1628A00959	
i00019 HP 5334B	2704A00347	
i00020 HP 8901A	2105A01087	

PAGE NO.

31 of 33.

NAME OF TEST: Frequency Stability (Temperature Variation)  
g99b0325: 1999-Nov-17 Wed 16:21:00  
STATE: 0:General



SUPERVISED BY:

  
William H. Graff, Director  
of Engineering

PAGE NO. 32 of 33.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(b)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at  $25\pm5^{\circ}\text{C}$  and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)

g99b0335: 1999-Nov-17 Wed 12:08:22

STATE: 0:General

LIMIT, ppm = 5  
LIMIT, Hz = 213  
BATTERY END POINT (Voltage) = 7.5

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	6.37	42.600000	0	0.00
100	7.5	42.600000	0	0.00
115	8.62	42.600000	0	0.00
100	7.5	42.600010	10	0.23

SUPERVISED BY:



William H. Graff, Director  
of Engineering

PAGE NO. 33 of 33.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 16K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B <sub>N</sub> ), kHz	= (2 x M) + (2 x D x K)
	= 16.0

SUPERVISED BY:



William H. Graff, Director  
of Engineering

TESTIMONIAL  
AND  
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:



William H. Graff, Director  
of Engineering