



M. Flom Associates, Inc. - Global Compliance Center
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176
www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Transmitter Certification

of

to

Federal Communications Commission

Rule Parts 22, 74, 90, 90.210, Confidentiality

Date of report: May 3, 2004

On the Behalf of the Applicant:

At the Request of:

P.O. JB-F-006

Attention of:

Supervised by:

A handwritten signature in black ink, appearing to read 'M. Flom, P. Eng.' with a long horizontal line underneath.

Morton Flom, P. Eng.

List of Exhibits

(FCC **Certification** (Transmitters) - Revised 9/28/98)

Applicant:

FCC ID:

By Applicant:

1. Letter of Authorization	x
2. Confidentiality Request: 0.457 And 0.459	x
3. Part 90.203(e) & (g) Attestation	x
4. Identification Drawings, 2.1033(c)(11)	
<u>x</u> Label	
<u>x</u> Location of Label	
<u>x</u> Compliance Statement	
<u>x</u> Location of Compliance Statement	
5. Photographs, 2.1033(c)(12)	x
6. Documentation: 2.1033(c)	
(3) User Manual	x
(9) Tune Up Info	x
(10) Schematic Diagram	x
(10) Circuit Description	x
Block Diagram	x
Active Devices	x

By M.F.A. Inc.:

A. Testimonial & Statement of Certification

The Applicant has been cautioned as to the following:

15.21 Information to the User.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) Special Accessories.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

Table of Contents

<u>Rule</u>	<u>Description</u>	<u>Page</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	6
	Standard Test Conditions and Engineering Practices	7
2.1046(a)	Carrier Output Power (Conducted)	8
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	10
2.1046(a)	ERP Carrier Power (Radiated)	29
2.1053(a)	Field Strength of Spurious Radiation	30
90.214	Transient Frequency Behavior	34
2.1047(a)	Audio Low Pass Filter (Voice Input)	40
2.1047(a)	Audio Frequency Response	43
2.1047(b)	Modulation Limiting	45
2.1055(a)(1)	Frequency Stability (Temperature Variation)	48
2.1055(b)(1)	Frequency Stability (Voltage Variation)	51
2.202(g)	Necessary Bandwidth and Emission Bandwidth	52

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)

Test Report

b) Laboratory:
(FCC: 31040/SIT)
(Canada: IC 2044) M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, AZ 85225

c) Report Number: d0450002

d) Client:

e) Identification:

FCC ID:

EUT Description: VHF / FM Transceiver

f) EUT Condition:

Not required unless specified in individual tests.

g) Report Date:

May 3, 2004

EUT Received:

March 9, 2004

h, j, k):

As indicated in individual tests.

i) Sampling method:

No sampling procedure used.

l) Uncertainty:

In accordance with MFA internal quality manual.

m) Supervised by:



Morton Flom, P. Eng.

n) Results:

The results presented in this report relate only to the item tested.

o) Reproduction:

This report must not be reproduced, except in full, without written permission from this laboratory.

List of General Information Required for Certification

In Accordance with FCC Rules and Regulations,
Volume II, Part 2 and to

22, 74, 90, 90.210, Confidentiality

Sub-part 2.1033

(c)(1): Name and Address of Applicant:

Manufacturer:

(c)(2): FCC ID:

Model Numbers:

(c)(3): Instruction Manual(s):

Please see attached exhibits

(c)(4): Type of Emission: 16K0F3E, 11K0F3E

(c)(5): Frequency Range, MHz: 136 to 174

(c)(6): Power Rating, Watts: Switchable Variable N/A 5

FCC Grant Note:

BE - The output power is continuously variable from the value listed in the entry to 15%-20% of the value listed.

(c)(7): Maximum Power Rating, Watts: 300

DUT Results:

Passes Fails

Information for Push-To-Talk Devices

Type and number of antenna to be used for this device:
Whip antenna series

Maximum antenna gain for antenna indicated above:
0dBi nominal

Can this device sustain continuous operation with respect to its hardware capabilities and allowable operating functions?
No

Other hardware or operating restrictions that could limit a person's RF Exposure:
Time Out Timer

Source-based time-averaging (see 2.1093 of rules) applicable to reduce the average output power:
No

If device has headset and belt-clip accessories that would allow body-worn operations, what is the minimum separation distance between the antenna and the user's body in this operating configuration?

2.5cm

Can device access wire-line services to make phone calls, either directly or through an operator?

No

Can specific operating instructions be given to users to eliminate any potential RF Exposure concerns for both front-of-the-face and body-worn operating configurations?

Yes, in manual

Other applicable information the applicant may provide that can serve as effective means for ensuring RF Exposure compliance:

See manual

Industry Canada

 <p>Certification and Engineering Bureau</p> <p>M. Flom Associates Inc.</p>  <p>is recognized as an approved testing facility, in accordance with the provisions of the Industry Canada Terminal Attachment Programme, subject to any exclusions specified in their letter of approval.</p> <p><i>[Signature]</i> Director, Certification and Engineering Bureau</p> <p>Canada</p>	<p>Industrie Canada Industry Canada 1241 Clyde Avenue Ottawa, Ontario K2C 1Y3</p> <p>February 24, 1998</p> <p>Mr. M. Flom M. Flom Associates, Inc. 3356 North San Marcos Place, Suite 107 Chandler, Arizona 85224-1571</p> <p>Dear Mr. Flom,</p> <p>The Bureau has received your test report for the Open Area Test Site located at Chandler, Arizona, dated January 30, 1998 and the supplemental information received February 24, 1998. I have reviewed the report and find it complies with RSP 100, Issue 7, section 3.3 Description of Open Area Test Site.</p> <p>The site is acceptable to Industry Canada for the performance of radiated measurements. Please reference the file number "IC 2044" in the body of all test reports containing measurements made on this site. This reference number is the indication of Industry Canada's acceptance of your site. Your company has been added to our published list of qualified sites on the Bureau's web page. It is located at: http://spectrum.ic.gc.ca/cert/ Please keep the contact information current by notifying us if it changes or is in error.</p> <p>Keep informed of the latest Industry Canada regulations by visiting the Bureau's site on the World Wide Web;</p> <p style="text-align: center;">http://spectrum.ic.gc.ca/cert/ or the Industry Canada main site at; http://strategis.ic.gc.ca</p> <p>Whenever major construction or repairs to the site are completed, a re-submission of the site attenuation characteristics will be required.</p> <p style="text-align: right;">Yours sincerely,</p> <p><i>Brian Kasper</i></p> <p>Brian Kasper Head, EMC and Standards Certification and Engineering Bureau</p> <p>Canada</p>
--	---

NIST

 <p>UNITED STATES DEPARTMENT OF COMMERCE National Institute of Standards and Technology Gaithersburg, Maryland 20889</p> <p>September 15, 1999</p> <p>Mr. Morton Flom M. Flom Associates Inc. 3356 N. San Marcos Place, Suite 107 Chandler, AZ 85224</p> <p>Dear Mr. Flom:</p> <p>I am pleased to inform you that your laboratory has been validated by the Chinese Taipei Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation Mutual Recognition Arrangement (APEC MRA). Your laboratory is now formally designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC MRA between the American Institute in Taiwan (AIT) and the Taipei Economic and Cultural Representative Office (TECRO) in the United States, covering equipment subject to Electro-Magnetic Compatibility (EMC) requirements. The names of all validated and nominated laboratories will be posted on the NIST website at http://ts.nist.gov/mra under the "Asia" category.</p> <p>As of August 1, 1999, you may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable EMC requirements. Your assigned BSMI number is SL2-1N-E-041R; you must use this number when sending test reports to BSMI. Your designation will remain in force as long as your NVLAP and/or A2LA and/or BSMI accreditation remains valid for the CNS 13438.</p> <p>Please note that BSMI requires that the entity making application for the approval of regulated equipment must make such application in person at their Taipei office. <u>BSMI also requests the name of the authorized signatories who are authorized to sign the test reports.</u> You can send this information via fax to C-Taipei CAB Response Manager at 301-973-5414. I am also enclosing a copy of the cover sheet that, according to BSMI requirements, must accompany every test report.</p> <p style="text-align: center;">NIST</p>	<p>If you have any questions, please contact Robert Gladhill at 301-975-4273 or Joe Dhillon at 301-975-5521. We appreciate your continued interest in our international conformity assessment activities.</p> <p>Sincerely,</p> <p><i>Belinda L. Collins</i> Belinda L. Collins, Ph.D. Director, Office of Standards Services</p> <p>Enclosure</p>
--	--

Subpart 2.1033 (continued)

(c)(8): Voltages & currents in all elements in final RF stage, including final transistor or solid-state device:

Collector Current, A	= per manual
Collector Voltage, Vdc	= per manual
Supply Voltage, Vdc	= 7.5

(c)(9): **Tune-Up Procedure:**

Please see attached exhibits

(c)(10): **Circuit Diagram/Circuit Description:**

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

Please see attached exhibits

(c)(11): **Label Information:**

Please see attached exhibits

(c)(12): **Photographs:**

Please see attached exhibits

(c)(13): **Digital Modulation Description:**

Attached Exhibits
 N/A

(c)(14): **Test and Measurement Data:**

Follows

Sub-part

2.1033(c)(14):**Test and Measurement Data**

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- _____ 21 – Domestic Public Fixed Radio Services
- 22 – Public Mobile Services
- _____ 22 Subpart H - Cellular Radiotelephone Service
- _____ 22.901(d) - Alternative technologies and auxiliary services
- _____ 23 – International Fixed Public Radiocommunication services
- _____ 24 – Personal Communications Services
- 74 Subpart H - Low Power Auxiliary Stations
- _____ 80 – Stations in the Maritime Services
- _____ 80 Subpart E - General Technical Standards
- _____ 80 Subpart F - Equipment Authorization for Compulsory Ships
- _____ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- _____ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- _____ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- _____ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- _____ 80 Subpart V - Emergency Position Indicating Radio Beacons (EPIRB'S)
- _____ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- _____ 80 Subpart X - Voluntary Radio Installations
- _____ 87 – Aviation Services
- 90 – Private Land Mobile Radio Services
- _____ 94 – Private Operational-Fixed Microwave Service
- _____ 95 Subpart A - General Mobile Radio Service (GMRS)
- _____ 95 Subpart C - Radio Control (R/C) Radio Service
- _____ 95 Subpart D - Citizens Band (CB) Radio Service
- _____ 95 Subpart E - Family Radio Service
- _____ 95 Subpart F - Interactive Video and Data Service (IVDS)
- _____ 97 - Amateur Radio Service
- _____ 101 – Fixed Microwave Services

**Standard Test Conditions
and
Engineering Practices**

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000 Draft, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

Page Number 8 of 52.

Name of Test: Carrier Output Power (Conducted)


Specification: 47 CFR 2.1046(a)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1

Test Equipment: As per attached page

Measurement Procedure

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an RF Power Meter.
2. Measurement accuracy is $\pm 3\%$.



Asset	Description	s/n
(1) Coaxial Attenuator		
X i00231/2	PASTERNACK PE7021-30 (30 dB)	231 or 232
i00122/3	NARDA 766 (10 dB)	7802 or 7802A
(2) Power Meters		
X i00020	HP 8901A Power Mode	2105A01087
(3) Frequency Counter		
X i00020	HP 8901A Frequency Mode	2105A01087

Measurement Results
(Worst case)

Frequency of Carrier, MHz = 136.050, 155.050, 173.950
Ambient Temperature = $23^{\circ}\text{C} \pm 3^{\circ}\text{C}$

Power Setting	RF Power, Watts
High	5.02, 5.28, 5.12




Performed by:

David E. Lee, Lab Manager

Name of Test: Emission Masks (Occupied Bandwidth)**Specification:** 47 CFR 2.1049(c)(1)**Guide:** ANSI/TIA/EIA-603-1992, Paragraph 2.2.11**Measurement Procedure**

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for $\pm 2.5/\pm 1.25$ kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.



Asset	Description	s/n
-------	-------------	-----

(1) Audio Oscillator/Generator

X	i00017	HP 8903A Audio Analyzer	2216A01753
	i00002	HP 3336B Synthesizer / Level Gen.	1931A01465

(2) Coaxial Attenuator

X	i00231/2	PASTERNACK PE7021-30 (30 dB)	231 or 232
	i0012/3	NARDA 766 (10 dB)	7802 or 7802A

(3) Spectrum Analyzer

X	i00048	HP 8566B Spectrum Analyzer	2511A01467
	i00029	HP 8563E Spectrum Analyzer	3213A00104


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430136: 2004-Mar-30 Tue 10:04:00

State: 1:Low Power

Ambient Temperature: 23°C ± 3°C



Power:

LOW

Modulation:

NONE

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430137: 2004-Mar-30 Tue 10:05:00

State: 1:Low Power

Ambient Temperature: 23°C ± 3°C



Power:

LOW

Modulation:

NONE

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430138: 2004-Mar-30 Tue 10:07:00

State: 1:Low Power

Ambient Temperature: 23°C ± 3°C



Power:

LOW

Modulation:

NONE

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430127: 2004-Mar-30 Tue 09:42:00

State: 1:Low Power

Ambient Temperature: 23°C ± 3°C



Power:

Modulation:

LOW

VOICE: 2500 Hz SINE WAVE

MASK: B, VHF/UHF 25kHz, w/LPF

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430128: 2004-Mar-30 Tue 09:43:00

State: 1:Low Power

Ambient Temperature: 23°C ± 3°C



Power:
Modulation:

LOW
VOICE: 2500 Hz SINE WAVE
MASK: B, VHF/UHF 25kHz, w/LPF

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430129: 2004-Mar-30 Tue 09:44:00

State: 1:Low Power

Ambient Temperature: 23°C ± 3°C



Power:

Modulation:

LOW

VOICE: 2500 Hz SINE WAVE

MASK: B, VHF/UHF 25kHz, w/LPF

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430133: 2004-Mar-30 Tue 09:58:00

State: 1:Low Power

Ambient Temperature: 23°C ± 3°C



Power:

LOW

Modulation:

VOICE: 2500 Hz SINE WAVE

MASK: D, VHF/UHF 12.5kHz BW

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430134: 2004-Mar-30 Tue 10:00:00

State: 1:Low Power

Ambient Temperature: 23°C ± 3°C



Power:

Modulation:

LOW

VOICE: 2500 Hz SINE WAVE

MASK: D, VHF/UHF 12.5kHz BW

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430135: 2004-Mar-30 Tue 10:01:00

State: 1:Low Power

Ambient Temperature: 23°C ± 3°C



Power:

LOW

Modulation:

VOICE: 2500 Hz SINE WAVE

MASK: D, VHF/UHF 12.5kHz BW

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430121: 2004-Mar-30 Tue 09:17:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:

HIGH

Modulation:

NONE

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430122: 2004-Mar-30 Tue 09:23:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:

HIGH

Modulation:

NONE

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430123: 2004-Mar-30 Tue 09:24:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:

HIGH

Modulation:

NONE

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430139: 2004-Mar-31 Wed 00:56:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:
Modulation:

HIGH
VOICE: 2500 Hz SINE WAVE
MASK: B, VHF/UHF 25kHz, w/LPF

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430125: 2004-Mar-30 Tue 09:39:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:

HIGH

Modulation:

VOICE: 2500 Hz SINE WAVE

MASK: B, VHF/UHF 25kHz, w/LPF

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430126: 2004-Mar-30 Tue 09:40:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:

HIGH

Modulation:

VOICE: 2500 Hz SINE WAVE

MASK: B, VHF/UHF 25kHz, w/LPF

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430130: 2004-Mar-30 Tue 09:52:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:

HIGH

Modulation:

VOICE: 2500 Hz SINE WAVE

MASK: D, VHF/UHF 12.5kHz BW

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430131: 2004-Mar-30 Tue 09:54:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:

HIGH

Modulation:

VOICE: 2500 Hz SINE WAVE

MASK: D, VHF/UHF 12.5kHz BW

Performed by:

David E. Lee, Lab Manager


Name of Test:

Emission Masks (Occupied Bandwidth)

g0430132: 2004-Mar-30 Tue 09:56:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:

HIGH

Modulation:

VOICE: 2500 Hz SINE WAVE

MASK: D, VHF/UHF 12.5kHz BW

Performed by:

David E. Lee, Lab Manager


Name of Test: ERP Carrier Power (Radiated)

Specification: TIA/EIA 603A (Substitution Method) Paragraph 2.2.17

Definition: The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

Method of Measurement:

a) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



- b) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.
- c) Repeat step b) for seven additional readings at 45° interval positions of the turntable.
- d) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.
- e) Calculate the average radiated output power from the readings in step c) and d) by the following:

$$\text{average radiated power} = 10 \log_{10} \Sigma 10(\text{LVL} - \text{LOSS})/10 \text{ (dBm)}$$

Results

	136.05 MHz		155.05 MHz		173.95 MHz	
	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db
0°	20.3	+0.3	31.4	+3.3	31.7	+1.3
45°	20.3	+0.3	31.4	+3.3	31.8	+1.3
90°	20.2	+0.3	31.3	+3.3	32.0	+1.3
135°	20.1	+0.3	31.5	+3.3	32.0	+1.3
180°	20.3	+0.3	31.3	+3.3	31.7	+1.3
225°	20.2	+0.3	31.4	+3.3	31.8	+1.3
270°	20.5	+0.3	31.3	+3.3	31.9	+1.3
315°	20.2	+0.3	31.4	+3.3	32.0	+1.3
Av. Radiated Power:		20.6dbm	34.7dbm	33.2dbm		

Name of Test: Field Strength of Spurious Radiation

Specification: 47 CFR 2.1053(a)

Guide: ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917


Measurement Procedure

Definition:

Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

Method of Measurement

- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHZ), 1 MHZ (> 1GHz).
 - 2) Video Bandwidth \geq 3 times Resolution Bandwidth, or 30 kHz (22.917)
 - 3) Sweep Speed \leq 2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.




Name of Test: Field Strength of Spurious Radiation (Cont.)

D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to \pm the test bandwidth (see section 1.3.4.4).

E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.

F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



G) Reconnect the equipment as illustrated.

H) Keep the spectrum analyzer adjusted as in step B).

I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

Name of Test: Field Strength of Spurious Radiation (Cont.)

J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.

K) Repeat step J) with both antennas vertically polarized for each spurious frequency.

L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.

M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

$$\text{Radiated spurious emissions dB} = 10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step I})$$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:

Asset	Description	s/n	Cycle	Last Cal
<small>Per ANSI C63.4-1992/2000 Draft, 10.1.4</small>				
Transducer				
	i00088 EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-03
X	i00089 Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-03
X	i00103 EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Jan-03
Amplifier				
X	i00028 HP 8449A	2749A00121	12 mo.	May-03
Spectrum Analyzer				
X	i00029 HP 8563E	3213A00104	12 mo.	May-03
X	i00033 HP 85462A	3625A00357	12 mo.	Aug-03
Substitution Generator				
X	i00067 HP 8920A Communication TS	3345U01242	12 mo.	Oct-03
	i00207 HP 8753D Network Analyzer	3410A08514	12 mo.	Jul-03
Microphone, Antenna Port, and Cabling				
Microphone	Yes	Cable Length	N/A	Meters
Antenna Port Terminated	Yes	Load	No	Antenna Gain
All Ports Terminated by Load	No	Peripheral	N/A	0dBi

Name of Test: Field Strength of Spurious Radiation

g0430113: 2004-Mar-16 Tue 12:39:00

STATE: 2:High Power

Ambient Temperature: 23°C ± 3°C

Frequency Tuned, MHz	Frequency Emission, MHz	ERP, dBm	ERP, dBc
136.050	272.102500	-26.8	≤ -88.6
136.050	408.168300	-48.0	≤ -88.6
136.050	544.297000	-68.1	≤ -88.6
136.050	680.295000	-53.4	≤ -88.6
136.050	816.299000	-52.2	≤ -88.6
136.050	952.351000	-48.9	≤ -88.6
136.050	1088.400800	-54.0	≤ -88.6
136.050	1224.450800	-58.0	≤ -88.6
136.050	1360.500800	-51.9	≤ -88.6

Performed by:



David E. Lee, Lab Manager

Name of Test:

Transient Frequency Behavior

Specification:

47 CFR 90.214

Guide:

ANSI/TIA/EIA-603-1992, Paragraph 2.2.19

Test Equipment:

As per attached page

Measurement Procedure


- A) The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.
- B) The transmitter was turned on.
- C) Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded.
- D) The transmitter was turned off.
- E) An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step C) above, measured at the output of the combiner. This level was then fixed for the remainder of the test.
- F) The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).
- G) The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded.
- H) The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

Performed by:



David E. Lee, Lab Manager

Transient Frequency Behavior



Transient Frequency Behavior

Asset	Description	s/n
(1) Attenuator (Removed after 1st step) X i00231/2	PASTERNACK PE7021-30 (30 dB)	231 or 232
(2) Attenuator X i00231/2 i00122/3	PASTERNACK PE7021-30 (30 dB) NARDA 766 (10 dB)	231 or 232 7802 or 7802A
(3) Combiner X i00154	4 x 25 Ω Combiner	154
(4) Crystal Decoder X i00159	HP 8470B Crystal Detector	1822A10054
(5) RF Signal Generator X i00067	HP 8920A Communication TS	3345U01242
(6) Modulation Analyzer X i00020	HP 8901A Modulation Meter	2105A01087
(7) Oscilloscope X i00030	HP 54502A Digital Oscilloscope	2927A00209

Page Number


36 of 52.

Name of Test:

Transient Frequency Behavior

2004-MAR-31, 03:49, Wed

Ambient Temperature: 23°C ± 3°C



Power:

High

Modulation:

25 kHz Deviation

Description:

Carrier On

Performed by:

David E. Lee, Lab Manager



Page Number


37 of 52.

Name of Test:

Transient Frequency Behavior

2004-MAR-31, 03:51, Wed

Ambient Temperature: 23°C ± 3°C



Power:
Modulation:
Description:

High
12.5 kHz Deviation
Carrier On

Performed by:

David E. Lee, Lab Manager

MFA p0430004, d0450002

Page Number


38 of 52.

Name of Test:

Transient Frequency Behavior

2004-MAR-31, 03:56, Wed

Ambient Temperature: 23°C ± 3°C



Power:

High

Modulation:

12.5 kHz Deviation

Description:

Carrier Off

Performed by:


David E. Lee, Lab Manager

Name of Test:

Transient Frequency Behavior

2004-MAR-31, 03:58, Wed

Ambient Temperature: 23°C ± 3°C

**Power:**

High

Modulation:

25 kHz Deviation

Description:

Carrier Off

Performed by:

David E. Lee, Lab Manager



Page Number 40 of 52.

Name of Test: Audio Low Pass Filter (Voice Input)

Specification: 47 CFR 2.1047(a)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15

Test Equipment: As per attached page

Measurement Procedure

1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. Measurement Results: Attached

Transmitter Test Set-Up


Test A. Modulation Capability/Distortion

Test B. Audio Frequency Response

Test C. Hum and Noise Level

Test D. Response of Low Pass Filter

Test E. Modulation Limiting



Asset	Description	s/n
(1) Audio Oscillator		
X i00002	HP 3336B Synthesizer / Level Gen.	1931A01465
(2) Coaxial Attenuator		
i00122/3	NARDA 766 (10dB)10	7802 or 7802A
X i00231/2	PASTERNACK PE7021-30 (30 dB)	231 or 232
(3) Modulation Analyzer		
X i00020	HP 8901A Modulation Meter	2105A01087
(4) Audio Analyzer		
X i00001	HP 3586B Selective Level Meter	1928A01360


Name of Test:

Audio Low Pass Filter (Voice Input)

2004-MAR-31, 15:58, Wed

State: General

Ambient Temperature: $23^{\circ}\text{C} \pm 3^{\circ}\text{C}$



Performed by:

David E. Lee, Lab Manager

Page Number

43 of 52.

Name of Test:

Audio Frequency Response

Specification:

47 CFR 2.1047(a)

Guide:

ANSI/TIA/EIA-603-1992, Paragraph 2.2.6

Test Equipment:

As per previous page

Measurement Procedure


1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. Measurement Results: Attached

Name of Test:

Audio Frequency Response

2004-MAR-31, 16:04, Wed

State: General

Ambient Temperature: $23^{\circ}\text{C} \pm 3^{\circ}\text{C}$ 

Frequency of Maximum Audio Response, Hz = 2820

Additional points:

	Frequency, Hz	Level, dB
300		-10.82
20000		-27.64
30000		-27.52
50000		-27.19

Performed by:

David E. Lee, Lab Manager

Page Number 45 of 52.
Name of Test: Modulation Limiting
Specification: 47 CFR 2.1047(b)
Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3
Test Equipment: As per previous page

Measurement Procedure

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation (± 1.5 kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.
5. Measurement Results: Attached

Name of Test:


Modulation Limiting

2004-MAR-31, 15:10, Wed


State: General – 25kHz Channel

Ambient Temperature: $23^{\circ}\text{C} \pm 3^{\circ}\text{C}$

Positive
Peaks:



Negative
Peaks:



Performed by:

David E. Lee, Lab Manager

Name of Test:


Modulation Limiting

2004-MAR-31, 15:14, Wed


State: General - 12.5kHz Channel

Ambient Temperature: 23°C ± 3°C

Positive
Peaks:



Negative
Peaks:



Performed by:

David E. Lee, Lab Manager

Page Number 48 of 52.

Name of Test: Frequency Stability (Temperature Variation)

Specification: 47 CFR 2.1055(a)(1)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

Test Conditions: As Indicated


Test Equipment: As per previous page

Measurement Procedure

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. Measurement Results: Attached

Transmitter Test Set-Up

Frequency Stability: Temperature Variation
 Frequency Stability: Voltage Variation




Asset	Description	s/n
(1) Temperature, Humidity, Vibration		
X i00027	Tenney Temp. Chamber	9083-765-234
(2) Coaxial Attenuator		
X i00231/2	PASTERNACK PE7021-30 (30 dB)	231 or 232
i00122/3	NARDA 766 (10 dB)	7802 or 7802A
(3) RF Power		
X i00067	HP 8920A Communications TS	3345U01242
(4) Frequency Counter		
X i00067	HP 8920A Communications TS	3345U01242

Name of Test:

2004-MAR-31, 16:38, Wed

State: General

Frequency Stability (Temperature Variation)

Ambient Temperature: $23^{\circ}\text{C} \pm 3^{\circ}\text{C}$ 

Performed by:

David E. Lee, Lab Manager

Page Number 51 of 52.

Name of Test: Frequency Stability (Voltage Variation)

Specification: 47 CFR 2.1055(d)(1)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

Test Equipment: As per previous page

Measurement Procedure

1. The EUT was placed in a temperature chamber at $25 \pm 5^{\circ}\text{C}$ and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

Results: Frequency Stability (Voltage Variation)

State: General

Ambient Temperature: $23^{\circ}\text{C} \pm 3^{\circ}\text{C}$

Limit, ppm	= 2.5
Limit, Hz	= 387
Battery End Point (Voltage)	= 6.2

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	6.37	155.049910	-90	-0.58
100	7.5	155.049890	-110	-0.71
115	8.62	155.049890	-110	-0.71
84	6.3	155.049900	-100	-0.65



Performed by:

David E. Lee, Lab Manager

Page Number 52 of 52.

Name of Test: Necessary Bandwidth and Emission Bandwidth

Specification: 47 CFR 2.202(g)

Modulation = 16K0F3E

Necessary Bandwidth Calculation:

Maximum Modulation (M), kHz	3
Maximum Deviation (D), kHz	= 5
Constant Factor (K)	= 1
Necessary Bandwidth (B _N), kHz	= $(2 \times M) + (2 \times D \times K)$
	= 16.0

Modulation = 11K0F3E

Necessary Bandwidth Calculation:

Maximum Modulation (M), kHz	3
Maximum Deviation (D), kHz	= 2.5
Constant Factor (K)	= 1
Necessary Bandwidth (B _N), kHz	= $(2 \times M) + (2 \times D \times K)$
	= 11.0

Performed by:



David E. Lee, Lab Manager

END OF TEST REPORT

MFA p0430004, d0450002

**Testimonial
and
Statement of Certification**

This is to Certify:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:



Morton Flom, P. Eng.