



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / [www.sporton.com.tw](http://www.sporton.com.tw)

## FCC RADIO TEST REPORT

Applicant's company	<b>MetaLink Ltd.</b>
Applicant Address	Yakum Business Park Yakum 60972 Israel
FCC ID	<b>VT6-237VB</b>
Manufacturer's company	<b>MetaLink Ltd.</b>
Manufacturer Address	Yakum Business Park Yakum 60972 Israel

Product Name	MtW_RGPlus_5.0_VB_001 802.11n/a video bridge
Brand Name	MetaLink
Model Name	MtW_RGPlus_5.0_VB_001
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	5725 ~ 5850MHz
Received Date	Jun. 4, 2008
Final Test Date	Jul. 4, 2008
Submission Type	Original Equipment



### Statement

**Test result included is only for the 802.11a (5725 ~ 5850MHz) of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	4
3.4. Table for Carrier Frequencies .....	5
3.5. Table for Test Modes.....	5
3.6. Table for Testing Locations.....	6
3.7. Table for Supporting Units .....	6
3.8. Table for Parameters of Test Software Setting .....	6
3.9. Test Configurations .....	7
<b>4. TEST RESULT .....</b>	<b>9</b>
4.1. AC Power Line Conducted Emissions Measurement.....	9
4.2. Maximum Conducted Output Power Measurement.....	15
4.3. Power Spectral Density Measurement .....	20
4.4. 6dB Spectrum Bandwidth Measurement .....	24
4.5. Radiated Emissions Measurement .....	28
4.6. Band Edge Emissions Measurement .....	40
4.7. Antenna Requirements .....	42
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>43</b>
<b>6. TEST LOCATION.....</b>	<b>44</b>
<b>7. TAF CERTIFICATE OF ACCREDITATION .....</b>	<b>45</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT.....</b>	<b>A1 ~ A16</b>
<b>APPENDIX B. TEST PHOTOS.....</b>	<b>B1 ~ B5</b>
<b>APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>C1 ~C3</b>



## History of This Test Report

Original Issue Date: Jun. 30, 2008

Report No.: FR860613AD

- No additional attachment.
- Additional attachment were issued as following record:



Report No.: FR860613AD

Certificate No.: CB9706099

## 1. CERTIFICATE OF COMPLIANCE

Product Name : MtW\_RGPlus\_5.0\_VB\_001 802.11n/a video bridge  
Brand Name : MetaLink  
Model Name : MtW\_RGPlus\_5.0\_VB\_001  
Applicant : MetaLink Ltd.  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jun. 4, 2008 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that appears to read "Wayne Hsu 9.7.08".

Wayne Hsu

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	2.77 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	7.45 dB
4.3	15.247(e)	Power Spectral Density	Complies	16.47 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	4.90 dB
4.6	15.247(d)	Band Edge Emissions	Complies	25.41 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	$\pm 8.5 \times 10^{-8}$	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

Items	Description
Power Type	Power Adapter
Modulation	OFDM for IEEE 802.11a
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1 / 2 / 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	5725 ~ 5850MHz
Channel Number	11a: 5
Channel Band Width (99%)	11a: 17.36 MHz
Conducted Output Power	11a: 22.55 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

#### 3.2. Accessories

Power	Brand	Model	Rating
Adapter	LEI	MT12-4120100-A1	Input: 120V, 50/60Hz, 0.3A Output: 12V, 1A
<b>Others</b>			
Cradle			

### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
A	WHA YU	C1264-510006-A	Dipole Antenna	MHF	2
B	WHA YU	C1264-510006-A	Dipole Antenna	MHF	2
C	WHA YU	C1264-510006-A	Dipole Antenna	MHF	2

Note:

The EUT has three antennas(2TX, 3RX).


The EUT has three antenna connectors, the Connector 1 and the Connector 3 have both TX/RX function , Connector 2 have only RX function.

Connector 1 : Ant. A

Connector 2 : Ant. B

Connector 3 : Ant. C

Ant. A & Ant. C could transmit/receive simultaneously.



### 3.4. Table for Carrier Frequencies

Frequency Allocation for 802.11a

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz	149	5745 MHz	161	5805 MHz
	153	5765 MHz	165	5825 MHz
	157	5785 MHz		

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Max. Peak Conducted Output Power Power Spectral Density 6dB Spectrum Bandwidth	11a/BPSK	6 Mbps	149/157/165	A / C / A+C A+C A+C
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	11a/BPSK	6 Mbps	149/157/165	A+C
Band Edge Emissions	11a/BPSK	6 Mbps	149/165	A+C

Note:

Test Mode:

Mode 1 : EUT is put in Horizontal way

Mode 2: EUT is put in Vertical way

<For Conducted Emission>:

Due to Mode 2 generated the worst test result, so it was recorded in this report.

<For Radiated Emission>:

Due to Mode 1 generated the worst test result, so it was recorded in this report.

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No.
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	-	-	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	1200	E2K4965AGNM
Notebook	DELL	D400	E2K24GBRL

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11a

Test Software Version	DUT		
	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a Ant. A	18	16	19
IEEE 802.11a Ant. C	18	16	18

During the test, "Ping.exe" under WIN XP was executed to link with the remote workstation to receive and transmit signal by LAN and WLAN.


During testing, the remote wire network ancillary were connected by EUT.

Executed " DUT " to control the EUT continuously transmit RF signal.

### 3.9. Test Configurations


#### 3.9.1. Radiation Emissions Test Configuration

Test Configuration: 9KHz~1GHz




Test Configuration: above 1GHz

Test Mode: Mode 1



### 3.9.2. AC Power Line Conduction Emissions Test Configuration



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



##### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in  $50 \Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


## 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	54%
Test Engineer	Johnson Chang	Phase	Line
Configuration	Normal Link / Mode 2		



Freq	Level	Over Limit	Limit Line	Read	LISN	Cable	Remark
				Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.30230	49.46	-10.72	60.18	49.22	0.04	0.20 QP
2	0.30230	32.37	-17.81	50.18	32.13	0.04	0.20 AVERAGE
3	0.35983	46.05	-12.68	58.73	45.82	0.03	0.20 QP
4	0.35983	26.04	-22.69	48.73	25.81	0.03	0.20 AVERAGE
5	0.41903	46.85	-10.62	57.47	46.62	0.03	0.20 QP
6	0.41903	26.30	-21.17	47.47	26.07	0.03	0.20 AVERAGE
7	0.47838	43.52	-12.85	56.37	43.36	0.03	0.13 QP
8	0.47838	22.74	-23.63	46.37	22.58	0.03	0.13 AVERAGE
9	0.55054	17.51	-28.49	46.00	17.28	0.03	0.20 AVERAGE
10	0.55054	37.71	-18.29	56.00	37.48	0.03	0.20 QP
11	0.59873	24.44	-21.56	46.00	24.21	0.03	0.20 AVERAGE
12	0.59873	41.70	-14.30	56.00	41.47	0.03	0.20 QP
13	0.68090	40.59	-15.41	56.00	40.36	0.03	0.20 QP
14	0.68090	27.21	-18.79	46.00	26.98	0.03	0.20 AVERAGE
15	0.78345	37.57	-18.43	56.00	37.34	0.03	0.20 QP
16	0.78345	19.56	-26.44	46.00	19.33	0.03	0.20 AVERAGE
17	0.88969	19.27	-26.73	46.00	19.04	0.03	0.20 AVERAGE
18	0.88969	35.36	-20.64	56.00	35.13	0.03	0.20 QP
19	1.080	21.40	-24.60	46.00	21.19	0.03	0.18 AVERAGE
20	1.080	39.80	-16.20	56.00	39.59	0.03	0.18 QP
21	1.314	40.00	-16.00	56.00	39.83	0.04	0.13 QP
22	1.314	22.05	-23.95	46.00	21.88	0.04	0.13 AVERAGE

Temperature	23°C	Humidity	54%
Test Engineer	Johnson Chang	Phase	Neutral
Configuration	Normal Link / Mode 2		



Freq	Level	Over	Limit	Read	LISN	Cable	Remark
		Limit	Line	Level	Factor	Loss	
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15000	56.46	-9.54	66.00	56.15	0.11	0.20 QP
2 @	0.15000	53.23	-2.77	56.00	52.92	0.11	0.20 AVERAGE
3	0.24814	52.38	-9.44	61.82	52.10	0.08	0.20 QP
4	0.24814	30.11	-21.71	51.82	29.83	0.08	0.20 AVERAGE
5	0.30751	52.01	-8.02	60.04	51.74	0.07	0.20 QP
6	0.30751	39.39	-10.64	50.04	39.12	0.07	0.20 AVERAGE
7	0.36920	46.66	-11.86	58.52	46.39	0.07	0.20 QP
8	0.36920	33.81	-14.71	48.52	33.54	0.07	0.20 AVERAGE
9	0.42825	47.15	-10.14	57.29	46.88	0.07	0.20 QP
10	0.42825	28.80	-18.49	47.29	28.53	0.07	0.20 AVERAGE
11	0.47865	46.83	-9.54	56.36	46.63	0.07	0.13 QP
12	0.47865	26.52	-19.85	46.36	26.32	0.07	0.13 AVERAGE
13	0.56111	44.59	-11.41	56.00	44.32	0.07	0.20 QP
14	0.56111	24.25	-21.75	46.00	23.98	0.07	0.20 AVERAGE
15	0.68263	46.51	-9.49	56.00	46.24	0.07	0.20 QP
16	0.68263	38.31	-7.69	46.00	38.04	0.07	0.20 AVERAGE
17	0.75702	44.13	-11.87	56.00	43.86	0.07	0.20 QP
18	0.75702	38.42	-7.58	46.00	38.15	0.07	0.20 AVERAGE
19	0.83143	44.65	-11.35	56.00	44.38	0.07	0.20 QP
20	0.83143	35.90	-10.10	46.00	35.63	0.07	0.20 AVERAGE
21	0.86643	42.59	-13.41	56.00	42.32	0.07	0.20 QP
22	0.86643	23.10	-22.90	46.00	22.83	0.07	0.20 AVERAGE
23	1.021	43.32	-12.68	56.00	43.05	0.07	0.19 QP

	Freq	Level	Over	Limit	Read	LISN	Cable
			Limit	Line	Level	Factor	Loss Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB
24		<b>1.021</b>	<b>26.11</b>	<b>-19.89</b>	<b>46.00</b>	<b>25.84</b>	<b>0.07</b> <b>0.19</b> AVERAGE
25		<b>1.289</b>	<b>39.19</b>	<b>-16.81</b>	<b>56.00</b>	<b>38.97</b>	<b>0.08</b> <b>0.14</b> QP
26		<b>1.289</b>	<b>31.78</b>	<b>-14.22</b>	<b>46.00</b>	<b>31.56</b>	<b>0.08</b> <b>0.14</b> AVERAGE
27		<b>1.619</b>	<b>41.98</b>	<b>-14.02</b>	<b>56.00</b>	<b>41.77</b>	<b>0.08</b> <b>0.13</b> QP
28		<b>1.619</b>	<b>24.31</b>	<b>-21.69</b>	<b>46.00</b>	<b>24.10</b>	<b>0.08</b> <b>0.13</b> AVERAGE
29		<b>2.334</b>	<b>42.27</b>	<b>-13.73</b>	<b>56.00</b>	<b>41.97</b>	<b>0.10</b> <b>0.20</b> QP
30		<b>2.334</b>	<b>25.70</b>	<b>-20.30</b>	<b>46.00</b>	<b>25.40</b>	<b>0.10</b> <b>0.20</b> AVERAGE
31		<b>2.993</b>	<b>39.63</b>	<b>-16.37</b>	<b>56.00</b>	<b>39.31</b>	<b>0.12</b> <b>0.20</b> QP
32		<b>2.993</b>	<b>23.69</b>	<b>-22.31</b>	<b>46.00</b>	<b>23.37</b>	<b>0.12</b> <b>0.20</b> AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	PEAK
Trace	Max Hold
Sweep Time	AUTO

### 4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

#### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

Temperature	26°C	Humidity	56%
Test Engineer	Sam Chen	Configurations	802.11a

##### Configuration IEEE 802.11a Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	19.45	30.00	Complies
157	5785 MHz	19.56	30.00	Complies
165	5825 MHz	19.52	30.00	Complies


##### Configuration IEEE 802.11a Ant. C

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	19.35	30.00	Complies
157	5785 MHz	19.51	30.00	Complies
165	5825 MHz	19.17	30.00	Complies

##### Configuration IEEE 802.11a Ant. A + Ant. C


Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	22.41	30.00	Complies
157	5785 MHz	22.55	30.00	Complies
165	5825 MHz	22.36	30.00	Complies

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5745 MHz



Date: 25.JUN.2008 19:57:35

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. C / 5745 MHz



Date: 25.JUN.2008 19:54:33

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5785 MHz




Date: 3.JUN.2008 16:35:48

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. C / 5785 MHz




Date: 3.JUN.2008 16:34:45

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5825 MHz



Date: 25.JUN.2008 20:03:05

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. C / 5825 MHz



Date: 3.JUN.2008 16:39:17

### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

#### 4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.
5. Measuring multiple antennas, the connector is required to link with spectrum analyser through a combiner.

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


#### 4.3.7. Test Result of Power Spectral Density

<b>Temperature</b>	26°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Sam Chen	<b>Configurations</b>	802.11a

##### Configuration IEEE 802.11a Ant. A + Ant. C


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	-8.47	8.00	Complies
157	5785 MHz	-9.85	8.00	Complies
165	5825 MHz	-10.57	8.00	Complies

### Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. C / 5745 MHz




Date: 7.JUN.2008 08:33:43

### Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. C / 5785 MHz



Date: 7.JUN.2008 08:40:05

**Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. C / 5825 MHz**



Date: 7.JUN.2008 08:43:41

## 4.4. 6dB Spectrum Bandwidth Measurement

### 4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.
4. Measuring multiple antennas, the connector is required to link with spectrum analyzer through a combiner.

### 4.4.4. Test Setup Layout



### 4.4.5. Test Deviation

There is no deviation with the original standard.

### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	26°C	Humidity	56%
Test Engineer	Sam Chen	Configurations	802.11a

##### Configuration IEEE 802.11a Ant. A + Ant. C


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	13.20	17.32	500	Complies
157	5785 MHz	13.16	17.36	500	Complies
165	5825 MHz	13.20	17.36	500	Complies

### 6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. C / 5745 MHz




Date: 7.JUN.2008 08:33:18

### 6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. C / 5785 MHz



Date: 7.JUN.2008 08:39:40

## 6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. C / 5825 MHz



Date: 7.JUN.2008 08:43:16

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100KHz / 100KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	23°C	Humidity	54%
Test Engineer	Aric Li		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


#### 4.5.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	23°C	Humidity	54%
Test Engineer	Aric Li	Configurations	Normal Link

##### Horizontal



Freq	Level	Over Limit	Limit	Read		Antenna	Preamp	Cable	Table	Ant	
				Line	Factor						
MHz		dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	deg	cm	
1 @	30.000	28.92	-11.08	40.00	38.22	18.00	27.80	0.50	Peak	0	100 HORIZONTAL
2 @	141.550	29.14	-14.36	43.50	44.81	10.32	27.39	1.41	Peak	0	100 HORIZONTAL
3 @	229.820	31.15	-14.85	46.00	46.77	9.60	27.04	1.82	Peak	0	100 HORIZONTAL
4 @	319.060	30.59	-15.41	46.00	41.92	13.57	27.03	2.14	Peak	0	100 HORIZONTAL
5 @	374.350	32.10	-13.90	46.00	42.49	14.79	27.42	2.25	Peak	0	100 HORIZONTAL
6 @	479.110	32.82	-13.18	46.00	41.09	17.07	27.99	2.66	Peak	0	100 HORIZONTAL

**Vertical**


Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable	Table	Ant		
		Limit	Line	Level	Factor	Factor	Loss			Pos	Pol/Phase
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB			deg	cm
1 @	44.000	35.10	-4.90	40.00	52.45	9.75	27.80	0.70 QP	248	100	VERTICAL
2 @	105.660	37.27	-6.23	43.50	52.71	10.94	27.57	1.20 Peak	0	400	VERTICAL
3 @	141.550	29.63	-13.87	43.50	45.30	10.32	27.39	1.41 Peak	0	400	VERTICAL
4 @	374.350	30.76	-15.24	46.00	41.14	14.79	27.42	2.25 Peak	0	400	VERTICAL
5 @	479.110	31.61	-14.39	46.00	39.87	17.07	27.99	2.66 Peak	0	400	VERTICAL
6 @	749.740	34.63	-11.37	46.00	38.86	20.07	27.80	3.50 Peak	0	400	VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


#### 4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

Temperature	23°C	Humidity	54%
Test Engineer	Aric Li	Configurations	802.11a CH 149 Ant. A + Ant. C / Mode 1

##### Horizontal




Freq	Level	Over Limit	Limit	Read		Ant Pos	Table Pos	Table Pol/Phase	
				Antenna Line	Antenna Factor				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @	11490.040	41.99	-18.01	60.00	32.30	39.50	5.14	34.95	AVERAGE
2	11490.220	54.55	-25.45	80.00	44.87	39.50	5.14	34.95	PEAK


**Vertical**


Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant Pos	Table Pos	Table Pos	
		Limit	Line	Level	Factor	Loss	Factor				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		
1 @	11489.860	43.37	-16.63	60.00	33.68	39.50	5.14	34.95	AVERAGE	100	323 VERTICAL
2	11494.740	56.39	-23.61	80.00	46.70	39.50	5.15	34.96	PEAK	100	323 VERTICAL

Temperature	23°C	Humidity	54%
Test Engineer	Aric Li	Configurations	802.11a CH 157 Ant. A + Ant. C / Mode 1

**Horizontal**



Freq	Level	Over Limit	Limit Line	ReadAntenna		Cable Preamp			Ant Pos	Table Pos	Table Pol/Phase
				Level	Factor	dBuV	dB/m	dB			
1 @	11570.000	41.33	-18.67	60.00	31.64	39.47	5.18	34.96	AVERAGE	100	100 HORIZONTAL
2	11570.000	53.60	-26.40	80.00	43.91	39.47	5.18	34.96	PEAK	100	100 HORIZONTAL

**Vertical**



Freq	Level	Over Limit		Read		Ant Pos	Table Pos	Table Pol/Phase	
		Line	Limit	Antenna Level	Factor				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	11569.560	54.42	-25.58	80.00	44.75	39.47	5.17	34.96	PEAK
2 @	11570.020	43.10	-16.90	60.00	33.41	39.47	5.18	34.96	AVERAGE

Temperature	23°C	Humidity	54%
Test Engineer	Aric Li	Configurations	802.11a CH 165 Ant. A + Ant. C / Mode 1

## Horizontal



Freq	Level	Over Limit	Line	ReadAntenna		Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
				Level	Factor						
1	11649.000	54.13	-25.87	80.00	44.45	39.44	5.20	34.97 PEAK	100	99	HORIZONTAL
2 @	11649.740	40.73	-19.27	60.00	31.05	39.44	5.20	34.97 AVERAGE	100	99	HORIZONTAL

*Vertical*


Freq	Level	Over Limit	Line	ReadAntenna		Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
				MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	11648.440	54.76	-25.24	80.00	45.08	39.44	5.20	34.97	PEAK	100	320 VERTICAL
2 @	11649.860	42.36	-17.64	60.00	32.68	39.44	5.20	34.97	AVERAGE	100	320 VERTICAL

## Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Band Edge Emissions Measurement

### 4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

### 4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

### 4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

### 4.6.5. Test Deviation

There is no deviation with the original standard.

### 4.6.6. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	23°C	Humidity	54%
Test Engineer	Aric Li	Configurations	802.11a CH 149, 165
Test Date	Jun. 7, 2008		


For Emission not in Restricted Band

##### Low Band Edge Plot on Configuration IEEE 802.11a / 5745 MHz



Date: 7.JUN.2008 08:33:51

##### High Band Edge Plot on Configuration IEEE 802.11a / 5825 MHz



Date: 7.JUN.2008 08:43:49

## 4.7. Antenna Requirements

### 4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Mar. 03, 2008	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2008	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2008	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2008	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz – 30MHz	Mar. 27, 2008	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2008	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 14, 2008	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jun. 07, 2008	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100305	9 kHz - 40 GHz	Sep. 27, 2007	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2007*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 21, 2007	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Mar. 04, 2008	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan. 18, 2008	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 10, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jun. 27, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jun. 27, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 27, 2008	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 04, 2007*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2008	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2007	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2007	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2007	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 14, 2007	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 10, 2008	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

\* Calibration Interval of instruments listed above is two year.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 728, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-070110

財團法人全國認證基金會  
Taiwan Accreditation Foundation

### Certificate of Accreditation

This is to certify that

**Sportun International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	:	ISO/IEC 17025:2005
Accreditation Number	:	1190
Originally Accredited	:	December 15, 2003
Effective Period	:	January 10, 2007 to January 09, 2010
Accredited Scope	:	Testing Field, see described in the Appendix
Specific Accreditation Program	:	Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory



Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : January 10, 2007

PI, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.