FCC PART 15B MEASUREMENT AND TEST REPORT FOR

FULL RIVER (HONGKONG) LIMITED

Room 0708, QiuRui Building, MinKang Rd., MinZhi DaDao, LongHua Town,

BaoAn District, ShenZhen, China

FCC ID: VTIS24PED

Report Concerns:	Equipment Type:		
Original Report	24 Port Fast Ethernet PoE Switch		
Model:	<u>SW1024P</u>		
Report No.:	STR10118120I		
Test Date:	2010-11-11 to 2010-12-25		
Issue Date:	2011-01-07		
Tested By:	Breeze Jiang / Engineer	re fiance	
Reviewed By:	Lahm Peng / EMC Manager	ne jane	
Approved & Authorized By:	Jandy so / PSQ Manager	mlyso	
Prepared By:			
SEM.Test Compliance Service Co., Ltd 3/F, Jinbao Commerce Building, Xin'an Fanshen Road,			

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd.

Bao'an District, Shenzhen, P.R.C. (518101)
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 1.2 TEST STANDARDS 1.3 TEST METHODOLOGY 1.4 TEST FACILITY 1.5 EUT EXERCISE SOFTWARE 1.6 ACCESSORIES EQUIPMENT LIST AND DETAILS 1.7 EUT CABLE LIST AND DETAILS	
2. SUMMARY OF TEST RESULTS	5
3. §15.107 (A)- CONDUCTED EMISSION	6
3.1 MEASUREMENT UNCERTAINTY 3.2 TEST EQUIPMENT LIST AND DETAILS 3.3 TEST PROCEDURE 3.4 BASIC TEST SETUP BLOCK DIAGRAM 3.5 ENVIRONMENTAL CONDITIONS 3.6 TEST RECEIVER SETUP 3.7 SUMMARY OF TEST RESULTS/PLOTS 3.8 CONDUCTED EMISSIONS TEST DATA	
4. §15.109(A)- RADIATED EMISSION	10
4.1 Measurement Uncertainty 4.2 Test Equipment List and Details 4.3 Test Procedure 4.4 Test Receiver Setup 4.5 Corrected Amplitude & Margin Calculation 4.6 Environmental Conditions	
4.7 SUMMARY OF TEST RESULTS/PLOTS	11

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: FULL RIVER (HONGKONG) LIMITED

Address of applicant: Room 0708, QiuRui Building, MinKang Rd., MinZhi DaDao,

LongHua Town, BaoAn District, ShenZhen, China

Manufacturer: FULL RIVER (HONGKONG) LIMITED

Address of manufacturer: FullRiver Industrial Ceramics Estate Garden Area LiLing

City HuNan Province China

General Description of E.U.T

Items	Description	
EUT Description:	24 Port Fast Ethernet PoE Switch	
Trade Name:	FullRiver	
Model No.:	SW1024P, POEFE24T	
Rated Voltage:	AC 100-240V	
Rated Current:	/	
Packaging Size: 44.2X20.7X4.3 cm		
For more information refer to the circuit diagram form and the user's manual.		

The test data is gathered from a production sample, provided by the manufacturer. The other model listed in the report has different appearance only of SW1024P without circuit and electronic construction changed, declared by the manufacturer.

1.2 Test Standards

The following report is prepared on behalf of the FULL RIVER (HONGKONG) LIMITED in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15.107, and 15.109 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

Model: SW1024P

The equipment under test (EUT) was configured to measure its highest possible susceptibility against the tested phenomena. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

• FCC – Registration No.: 994117

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

• Industry Canada (IC) Registration No.: 7673A

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

• CNAS Registration No.: L4062

Shenzhen SEM. Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Exercise Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the system components. The test software, provided by the customer, is started while the EUT is on to simulate the normal work, under the Windows XP terminal.

1.6 Accessories Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	ASUS	X50R	N/A

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
Network Cable	1	Unshielded	Without Core

1.7 EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
AC Cable	1.5	Unshielded	Without Core

2. SUMMARY OF TEST RESULTS

Description of Test	Result
§15.107 (a) Conducted Emission	Compliant
§15.109 (a) Radiated Emission	Compliant

3. §15.107 (a)- CONDUCTED EMISSION

3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

3.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2010-08-12	2011-08-11
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2010-08-12	2011-08-11
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2010-08-12	2011-08-11

3.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.107 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

3.4 Basic Test Setup Block Diagram



REPORT NO.: STR10118120I PAGE 6 OF 13 FCC PART 15B

3.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

3.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	. 150 kHz
Stop Frequency	. 30 MHz
Sweep Speed	. Auto
IF Bandwidth	. 10 kHz
Quasi-Peak Adapter Bandwidth	.9 kHz
Quasi-Peak Adapter Mode	. Normal

3.7 Summary of Test Results/Plots

According to the data in section 3.8, the EUT <u>complied with the FCC 15B</u> Conducted margin for a Class B device, with the *worst* margin reading of:

-2.32 dB μV at 18.534 MHz in the Neutral mode, Average detector, 0.15-30MHz

3.8 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


Conducted Disturbance

EUT: 24 Port Fast Ethernet PoE Switch

M/N: SW1024P

Operating Condition: Running

Test Specification: N
Comment: AC 120V/60Hz



Plot of Conducted Emissions Test Data


Conducted Disturbance

EUT: 24 Port Fast Ethernet PoE Switch

M/N: SW1024P

Operating Condition: Running

Test Specification: L Comment: AC 120V/60Hz



4. §15.109(a)- RADIATED EMISSION

4.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is \pm 5.10 dB.


4.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2010-04-16	2011-04-15
EMI Test Receiver	R&S	ESVB	825471/005	2010-08-12	2011-08-11
Positioning Controller	C&C	CC-C-1F	N/A	2010-08-12	2011-08-11
RF Switch	EM	EMSW18	SW060023	2010-08-12	2011-08-11
Pre-amplifier	Agilent	8447F	3113A06717	2010-08-12	2011-08-11
Pre-amplifier	Compliance Direction	PAP-0118	24002	2010-08-12	2011-08-11
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2010-07-21	2011-07-20
Horn Antenna	ETS	3117	00086197	2010-07-21	2011-07-20

4.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 and FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.



4.4 Test Receiver Setup

During the radiated emission test, the test receiver was set with the following configurations:

Start Frequency	30 MHz
Stop Frequency	1000 MHz
Sweep Speed	Auto
IF Bandwidth	100 kHz
Quasi-Peak Adapter Bandwidth	120 kHz
Quasi-Peak Adapter Mode	Normal

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-6dB\mu V$ means the emission is $6dB\mu V$ below the maximum limit for Class B. The equation for margin calculation is as follows:

4.6 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

4.7 Summary of Test Results/Plots

According to the data, the <u>EUT complied with the FCC 15B Class B</u> standards, and had the worst margin of:

-2.99 dBµV at 81.2117MHz in the Vertical polarization, 30 MHz to 1 GHz, 3Meters

Plot of Radiation Emissions Test Data

Radiated Disturbance

EUT: 24 Port Fast Ethernet PoE Switch

M/N: SW1024P

Operating Condition: Running

Test Specification: Horizontal & Vertical


Comment: AC 120V/60Hz

Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	106.7587	26.73	7.86	34.59	43.50	-8.91	360	100	peak
2	149.4857	30.68	4.08	34.76	43.50	-8.74	360	100	peak
3	175.6516	31.44	5.32	36.76	43.50	-6.74	360	100	peak
4	200.6881	31.29	6.60	37.89	43.50	-5.61	360	100	peak
5	249.4250	34.32	8.68	43.00	46.00	-3.00	360	100	peak

Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	81.2117	32.94	4.07	37.01	40.00	-2.99	360	100	peak
2	106.7587	29.73	7.86	37.59	43.50	-5.91	360	100	peak
3	124.5690	30.20	5.32	35.52	43.50	-7.98	360	100	peak
4	175.6516	31.14	5.32	36.46	43.50	-7.04	360	100	peak

***** END OF REPORT *****