


SK TECH CO., LTD.

Page 1 of 28

Certificate of Compliance

Test Report No.:	SKTTRT-071203-032		
KOLAS No.:	KT191		
Applicant:	Entra Health Systems, Ltd.		
Applicant Address:	Round Foundry Media Centre, Foundry Street, Leeds LS11 5QP, UK		
Manufacturer:	Infopia Co., Ltd		
Manufacturer Address:	#1603 Dongil Technotown A Bldg., 889-3Kwanyang2-Dong, Dongan-Gu, Anyang, Kyunggi, 431-716 South Korea		
Device Under Test:	myglucohealth™ Bluetooth Glucose Meter		
FCC ID:	VUG-EHS-MGEU00001	Model Name:	MGH-BT1
Brand/Trade Name:	myglucohealth™		
Receipt No.:	SKTEU07-1085	Date of receipt:	November 7, 2007
Date of Issue:	December 03, 2007		
Location of Testing:	SK TECH CO., LTD. 820-2, Wolmoon-Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea		
Test Procedure:	ANSI C63.4, FCC Public Notice DA 00-705 (March 2000)		
Test Specification:	47CFR, Part 15 Rules		
FCC Equipment Class: IC Equipment Category:	DSS - Part 15 Spread Spectrum Transmitter		
Test Result:	The above-mentioned device has been tested and passed.		
Tested & Reported by: : Yong-Duk, Kwon	Tested & Reported by: Jong-Soo, Yoon		
	2007. 12. 03		2007. 12. 03
Signature	Date	Signature	Date
Other Aspects:	-		
Abbreviations:	· OK, Pass = passed · Fail = failed · N/A = not applicable		

- This test report is not permitted to copy partly and entirely without our permission.
- This test result is dependent on only equipment to be used.
- This test result is based on a single evaluation of submitted samples of the above mentioned.
- This test report is the accredited testing items by Korea Laboratory Accreditation Scheme, which signed the ILAC-MRA.



>> CONTENTS <<

1. GENERAL	4
2. TEST SITE	4
2.1 Location	4
2.2 List of Test and Measurement Instruments	5
2.3 Test Date	5
2.4 Test Environment	5
3. DESCRIPTION OF THE EQUIPMENT UNDER TEST	6
3.1 Rating and Physical Characteristics	6
3.2 Equipment Modifications	6
3.3 Submitted Documents	6
4. MEASUREMENT CONDITIONS	7
4.1 Description of test configuration	7
4.2 List of Peripherals	7
4.3 Type of Used Cables	7
4.4 Uncertainty	7
5. TEST AND MEASUREMENTS	8
5.1 ANTENNA REQUIREMENT	8
5.1.1 Regulation	8
5.1.2 Result	8
5.2 MAXIMUM PEAK OUTPUT POWER	9
5.2.1 Regulation	9
5.2.2 Test Procedure	9
5.2.3 Test Results	9
Table 1: Measured values of the Maximum Peak Output Power (Conducted)	9
Figure 1: Plot of the Maximum Peak Output Power (Conducted)	10
5.3 CARRIER FREQUENCY SEPARATION	11
5.3.1 Regulation	11
5.3.2 Test Procedure	11
5.3.3 Test Results	11
Table 2: Measured values of the Carrier Frequency Separation (Conducted)	11
Figure 2: Plot of the Carrier Frequency Separation (Conducted)	12
5.4 20dB CHANNEL BANDWIDTH	13
5.4.1 Regulation	13
5.4.2 Test Procedure	13
5.4.3 Test Results	13
Table 3: Measured values of the 20dB Channel Bandwidth (Conducted)	13
Figure 3: Plot of the 20dB Channel Bandwidth (Conducted)	14



5.5 NUMBER OF HOPPING CHANNELS	15
5.5.1 Regulation	15
5.5.2 Test Procedure	15
5.5.3 Test Results	15
Table 4: Measured values of the Number of Hopping Channels (Conducted).....	15
Figure 4: Plot of the Number of Hopping Channels (Conducted)	16
5.6 TIME OF OCCUPANCY (DWELL TIME)	17
5.6.1 Regulation	17
5.6.2 Test Procedure	17
5.6.3 Test Results	17
Table 5: Measured values of the Time of Occupancy (Conducted).....	17
Figure 5: Plot of the Time of Occupancy (Conducted)	18
5.7 SPURIOUS EMISSION, BAND EDGE, AND RESTRICTED BANDS	19
5.7.1 Regulation	19
5.7.2 Test Procedure	20
5.7.3 Test Results	22
Table 6: Measured values of the field strength of spurious emission (Radiated).....	22
Figure 6: Plot of the Band Edge (Conducted).....	23
Figure 7: Plot of the Band Edge (Radiated)	24
Figure 8: Plot of the Spurious RF conducted emission	25
5.8 PEAK POWER SPECTRAL DENSITY	26
5.8.1 Regulation	26
5.8.2 Test Procedure	26
5.8.3 Test Results	26
Table 7: Measured values of the Peak Power Spectral Density (Conducted)	26
Figure 9: Plot of the Peak Power Spectral Density (Conducted)	27
5.9 RF EXPOSURE	28
5.9.1 Regulation	28
5.9.2 RF Exposure Compliance Issue	28

**SK TECH CO., LTD.***Page 4 of 28*

1. GENERAL

These tests were performed using the test procedure outlined in ANSI C63.4, 2003 for intentional radiators, and in accordance with the limits set forth in FCC Part 15.247 for Spread Spectrum Transmitter. The EUT (Equipment Under Test) has been shown to be capable of compliance with the applicable technical standards.

We attest to the accuracy of data. All measurements reported herein were performed by SK TECH Co., Ltd. and were made under Chief Engineer's supervision.

We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

2. TEST SITE

SK TECH Co., Ltd.



2.1 Location

820-2, Wolmoon-Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea

(FCC Registered Test Site Number: 90752)

This test site is in compliance with ISO/IEC 17025 for general requirements for the competence of testing and calibration laboratories.

This laboratory is recognized as a Conformity Assessment Body (CAB) for CAB's Designation Number:

KR0007 by FCC, is accredited by NVLAP for NVLAP Lab. Code: **200220-0**, DATech for DAR-Registration No.: **DAT-P-076/97-01** and KOLAS for Accreditation No.: **KT191**.



2.2 List of Test and Measurement Instruments

No.	Description	Manufacturer	Model #	Serial #	Calibrated until	Used
1	Spectrum Analyzer	Agilent	E4405B	US40520856	2008.07.23	<input type="checkbox"/>
2	EMC Spectrum Analyzer	Agilent	E7405A	US40240203	2008.02.02	<input checked="" type="checkbox"/>
3	EMI Test Receiver	Rohde&Schwarz	ESIB40	100277	2008.07.23	<input checked="" type="checkbox"/>
4	EMI Test Receiver	Rohde&Schwarz	ESVS10	825120/008	2008.07.24	<input type="checkbox"/>
5	EMI Test Receiver	Rohde&Schwarz	ESHS10	862970/019	2008.07.24	<input type="checkbox"/>
6	Artificial Mains Network	Rohde&Schwarz	ESH2-Z5	834549/011	2008.07.25	<input type="checkbox"/>
7	Pre-amplifier	HP	8447F	3113A05153	2008.02.23	<input checked="" type="checkbox"/>
8	Pre-amplifier	MITEQ	AFS44	1116321	2008.03.07	<input checked="" type="checkbox"/>
9	Pre-amplifier	MITEQ	AFS44	1116322	2008.02.06	<input checked="" type="checkbox"/>
10	Power Meter	Agilent	E4417A	MY45100426	2008.07.24	<input type="checkbox"/>
11	Power Sensor	Agilent	E9327A	MY44420696	2008.07.24	<input type="checkbox"/>
12	Attenuator (10dB)	HP	8491B	38067	2008.07.25	<input type="checkbox"/>
13	Oscilloscope	Agilent	54820A	US40240160	2008.03.06	<input type="checkbox"/>
14	Diode detector	Agilent	8473C	1882A03173	2008.02.06	<input type="checkbox"/>
15	High Pass Filter	Wainwright	WHKX3.0/18G	8	2008.07.25	<input checked="" type="checkbox"/>
16	VHF Precision Dipole Antenna (TX/RX)	Schwarzbeck	VHAP	1014 / 1015	2008.11.27	<input type="checkbox"/>
17	UHF Precision Dipole Antenna (TX/RX)	Schwarzbeck	UHAP	989 / 990	2008.11.27	<input type="checkbox"/>
18	Loop Antenna	Schwarzbeck	HFH2-Z2	863048/019	2008.12.01	<input type="checkbox"/>
19	TRILOG Broadband Antenna	Schwarzbeck	VULB9160	3141	2008.05.29	<input checked="" type="checkbox"/>
20	Horn Antenna	AH Systems	SAS-200/571	304	N/A	<input type="checkbox"/>
21	Horn Antenna	EMCO	3115	00040723	2008.03.15	<input checked="" type="checkbox"/>
22	Horn Antenna	EMCO	3115	00056768	2008.07.24	<input checked="" type="checkbox"/>
23	Vector Signal Generator	Agilent	E4438C	MY42080359	2008.07.25	<input type="checkbox"/>
24	PSG analog signal generator	Agilent	E8257D-520	MY45141255	2008.07.25	<input type="checkbox"/>
25	DC Power Supply	HP	6622A	3448A03950	2008.07.23	<input type="checkbox"/>
26	DC Power Supply	HP	6268B	2542A-07856	2008.07.23	<input checked="" type="checkbox"/>
27	Digital Multimeter	HP	HP3458A	2328A14389	2008.03.07	<input checked="" type="checkbox"/>
28	PCS Interface	HP	83236B	3711J00881	2008.03.09	<input type="checkbox"/>
29	CDMA Mobile Test Set	HP	8924C	US35360253	2008.03.09	<input type="checkbox"/>
30	Hygro/Thermo Graph	SATO	PC-5000TRH-II	-	2008.04.09	<input checked="" type="checkbox"/>
31	Temperature/Humidity Chamber	All Three	ATM-50M	20030425	2008.03.06	<input type="checkbox"/>
32	Temperature/Humidity Chamber	DAEJIN	DJ-THC02	06071	2008.03.07	<input type="checkbox"/>

2.3 Test Date

Date of Test: November 20, 2007 ~ December 1, 2007

2.4 Test Environment

See each test item's description.



3. DESCRIPTION OF THE EQUIPMENT UNDER TEST

The product specification described herein was obtained from the product data sheet or user's manual.


3.1 Rating and Physical Characteristics

Power source	3V (Alkaline Battery, 1.5V AAA Size × 2EA)
Transmit Frequency	2402 ~ 2480 MHz (1 MHz step, 79 channels)
Antenna Type	Integral (chip antenna, Gain: 2.92 dBi)
Type of Modulation	FHSS (GFSK)
RF Output power	4 dBm
External Ports	Test strip port for the Test Strip USB ** DATA communication; transmits the stored information in it to personal computer (equipped with serial to USB converter chip)

** Equipment authorization as a Class B digital device was processed under Declaration of Conformity (DoC) with other EMI test report.

3.2 Equipment Modifications

None



3.3 Submitted Documents

Block diagram

Schematic diagram

Antenna Specification

Part List


User manual



4. MEASUREMENT CONDITIONS

4.1 Description of test configuration

The measurements were taken in continuous transmitting mode using the TEST MODE. For controlling the EUT as TEST MODE, the test program and the test jig were provided by the applicant.



[System Block Diagram of Test Configuration]

4.2 List of Peripherals

Equipment Type	Manufacturer	Model	S/N
PC **	DELL INC.	DCNE	7XH86BX
AC/DC Adaptor **	Seung Bo Elecom Co., Ltd.	SP1013A	SB0611000679
TEST JIG **	MOVON	-	-

** For control of the RF module via SPI interface in the EUT.

4.3 Type of Used Cables

#	START		END		CABLE	
	NAME	I/O PORT	NAME	I/O PORT	LENGTH(m)	SHIELDED
1	EUT	SPI	TEST JIG	SPI	0.2	NO
2	TEST JIG	SPI	PC	LPT1	1.0	NO
3	TEST JIG	DC power IN	AC/DC Adaptor	DC Output	1.8	NO
4	AC/DC adaptor	AC Power IN	AC mains	-	-	NO

4.4 Uncertainty

Measurement Item	Combined Standard Uncertainty U _c	Expanded Uncertainty U = KU _c (K = 2)
Conducted RF power	± 1.49 dB	± 2.98dB
Radiated disturbance	± 2.30 dB	± 4.60 dB
Conducted disturbance	± 1.96 dB	± 3.92 dB



5. TEST AND MEASUREMENTS

Summary of Test Results

Requirement	CFR 47 Section	Report Section	Test Result
Antenna Requirement	15.203, 15.247(b)(4)	5.1	PASS
Maximum Peak Output Power	15.247(b)(1), (4)	5.2	PASS
Carrier Frequency Separation	15.247(a)(1)	5.3	PASS
20dB Channel Bandwidth	15.247(a)(1)	5.4	PASS
Number of Hopping Channels	15.247(a)(iii), 15.247(b)(1)	5.5	PASS
Time of Occupancy (Dwell Time)	15.247(a)(iii)	5.6	PASS
Spurious Emission, Band Edge, and Restricted bands	15.247(d), 15.205(a), 15.209(a)	5.7	PASS
Peak Power Spectral Density	15.247(e)	5.8	PASS
Conducted Emissions	15.207(a)	N/A	N/A **
RF Exposure	15.247(i), 1.1307(b)(1)	5.9	PASS

* Not required, the EUT is only battery powered (3V Alkaline Battery).

5.1 ANTENNA REQUIREMENT

5.1.1 Regulation

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.1.2 Result:

PASS

The transmitter has an integral chip antenna. The directional gain of the antenna is 2.92 dBi.



5.2 MAXIMUM PEAK OUTPUT POWER

5.2.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2.2 Test Procedure

1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via SPI interface and make sure the spectrum analyzer is operated in its linear range.
4. Set the spectrum analyzer as follows:
 - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 - RBW > the 20 dB bandwidth of the emission being measured
 - VBW \geq RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold
5. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
6. Repeat above procedures until all frequencies measured were complete.

5.2.3 Test Results:

PASS

Table 1: Measured values of the Maximum Peak Output Power (Conducted)




Operating Frequency	Resolution Bandwidth	Actual	Limit
2402 MHz	3 MHz	2.50 mW(3.98 dBm)	1 W (30 dBm)
2441 MHz	3 MHz	2.56 mW(4.09 dBm)	1 W (30 dBm)
2480 MHz	3 MHz	2.29 mW(3.59 dBm)	1 W (30 dBm)

NOTE:

1. Since the directional gain of the integral antenna declared by the manufacturer ($G_{ANT} = 2.92$ dBi) does not exceed 6.0 dBi, there was no need to reduce the output power.
2. We took the insertion loss of the cable loss into consideration within the measuring instrument.


SK TECH CO., LTD.

Page 10 of 28

Figure 1. Plot of the Maximum Peak Output Power (Conducted)
**Lowest Channel
(2402 MHz)**

**Middle Channel
(2441 MHz)**

**Highest Channel
(2480 MHz)**




5.3 CARRIER FREQUENCY SEPARATION

5.3.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.3.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via SPI interface.
4. Set the spectrum analyzer as follows:
 - Span = wide enough to capture the peaks of two adjacent channels
 - Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span
 - Video (or Average) Bandwidth (VBW) \geq RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold
5. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
6. Repeat above procedures until all frequencies measured were complete.

5.3.3 Test Results:

PASS




Table 2: Measured values of the Carrier Frequency Separation (Conducted)

Operating frequency	Carrier frequency separation	Limit
2402 MHz	1004 kHz	≥ 25 kHz or 20 dB bandwidth
2441 MHz	1004 kHz	≥ 25 kHz or 20 dB bandwidth
2480 MHz	1004 kHz	≥ 25 kHz or 20 dB bandwidth

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.


SK TECH CO., LTD.

Page 12 of 28

Figure 2. Plot of the Carrier Frequency Separation (Conducted)
**Lowest Channel
(2402 MHz)**

**Middle Channel
(2441 MHz)**

**Highest Channel
(2480 MHz)**




5.4 20 dB CHANNEL BANDWIDTH

5.4.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.4.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via SPI interface and make sure the spectrum analyzer is operated in its linear range.
4. Set the spectrum analyzer as follows:
 - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
 - RBW \geq 1% of the 20 dB bandwidth
 - VBW \geq RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold
5. Set a reference level on it equal to the highest peak value.
6. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
7. Repeat above procedures until all frequencies measured were complete.

5.4.3 Test Results:

PASS


Table 3: Measured values of the 20dB Channel Bandwidth (Conducted)

Operating frequency	20dB Channel bandwidth	Limit	Carrier frequency separation
2402 MHz	732 kHz	< Carrier frequency separation	1004 kHz
2441 MHz	738 kHz	< Carrier frequency separation	1004 kHz
2480 MHz	738 kHz	< Carrier frequency separation	1004 kHz


NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.


SK TECH CO., LTD.


Page 14 of 28

Figure 3. Plot of the 20dB Channel Bandwidth (Conducted)
**Lowest Channel
(2402 MHz)**


Date: 20.NOV.2007 10:59:23

**Middle Channel
(2441 MHz)**


Date: 20.NOV.2007 11:01:19

**Highest Channel
(2480 MHz)**


Date: 20.NOV.2007 11:03:06



5.5 NUMBER OF HOPPING CHANNELS

5.5.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

5.5.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set the hopping function enabled by controlling it via SPI interface.
4. Set the spectrum analyzer as follows:
 - Span = the frequency band of operation
 - RBW \geq 1% of the span
 - VBW \geq RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold
5. Record the number of hopping channels.

5.5.3 Test Results:

PASS


Table 4: Measured values of the Number of Hopping Channels (Conducted)

Operating frequency	Number of hopping channels	Limit
2402 - 2480 MHz	79	≥ 15

NOTE: We took the insertion loss of the attenuator and cable loss into consideration within the measuring instrument.

**SK TECH CO., LTD.**

Page 16 of 28

Figure 4. Plot of the Number of Hopping Channels (Conducted)



5.6 TIME OF OCCUPANCY (DWELL TIME)

5.6.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.6.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via SPI interface.
4. Set the spectrum analyzer as follows:
 - Span = zero span, centered on a hopping channel
 - RBW = 1 MHz
 - VBW \geq RBW
 - Sweep = as necessary to capture the entire dwell time per hopping channel
 - Detector function = peak
 - Trace = max hold
5. Measure the dwell time using the marker-delta function.
6. Repeat above procedures until all frequencies measured were complete.
7. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

5.6.3 Test Results:

PASS

Table 5: Measured values of the Time of Occupancy (Conducted)

Operating frequency	Reading	Hopping rate	Number of Channels	Actual	Limit
2402 MHz	3.05 ms	266.667 hops/s	79	0.33 seconds	0.4 seconds
2441 MHz	3.05 ms	266.667 hops/s	79	0.33 seconds	0.4 seconds
2480 MHz	3.05 ms	266.667 hops/s	79	0.33 seconds	0.4 seconds

Actual = Reading \times (Hopping rate / Number of channels) \times Test period




Test period = 0.4 [seconds / channel] \times 79 [channel] = 31.6 [seconds]

NOTE:

1. The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625 μ s with 79 channels. A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.
2. We took the insertion loss of the cable loss into consideration within the measuring instrument.


SK TECH CO., LTD.

Page 18 of 28

Figure 5. Plot of the Time of Occupancy (Conducted)
**Lowest Channel
(2402 MHz)**

**Middle Channel
(2441 MHz)**

**Highest Channel
(2480 MHz)**




5.7 SPURIOUS EMISSIONS, BAND EDGE, AND RESTRICTED BANDS

5.7.1 Regulation

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to §15.209(a), for an intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Field strength (μ V/m @ 3m)	Field strength (dB μ V/m @ 3m)
30–88	100	40.0
88–216	150	43.5
216–960	200	46.0
Above 960	500	54.0

According to §15.109(a), for an unintentional device, except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the above table.

** The emission limits shown in the above table are based on measurement instrumentation employing a CISPR quasi-peak detector and above 1000 MHz are based on the average value of measured emissions.



5.7.2 Test Procedure

1) Band-edge Compliance of RF Conducted Emissions

1. Set the spectrum analyzer as follows:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation

RBW \geq 1% of the span

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

2. Allow the trace to stabilize. Set the marker on the emission at the band-edge, or on the highest modulation product outside of the band, if this level is greater than that at the band-edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.
3. Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

2) Spurious RF Conducted Emissions:

1. Set the spectrum analyzer as follows:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.

3) Spurious Radiated Emissions:

1. The preliminary radiated measurements were performed to determine the frequency producing the maximum emissions in an anechoic chamber at a distance of 3 meters.
2. The EUT was placed on the top of the 0.8-meter height, 1 \times 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360°.
3. The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 30 to 1000 MHz using the TRILOG broadband antenna, and from 1000 MHz to 18000 MHz using the horn antenna.
4. To obtain the final measurement data, the EUT was arranged on a turntable situated on a 4 \times 4 meter at the Open Area Test Site. The EUT was tested at a distance 3 meters.
5. Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.



6. The presence of ambient signals was verified by turning the EUT off. In case an ambient signal was detected, the measurement bandwidth was reduced temporarily and verification was made that an additional adjacent peak did not exist. This ensures that the ambient signal does not hide any emissions from the EUT.
7. If the emission on which a radiated measurement must be made is located at the edge of the authorized band of operation, then the alternative "marker-delta" method may be employed.

4) Marker-Delta Method at the edge of the authorized band of operation:

1. Perform an in-band field strength measurement of the fundamental emission using the RBW and detector function as the above Spurious Radiated Emissions test procedure.
2. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 1% of the total span (but never less than 30 kHz) with a video bandwidth equal to or greater than the RBW. Record the peak levels of the fundamental emission and the relevant band-edge emission (i.e., run several sweeps in peak hold mode). Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band-edge relative to the highest fundamental emission level.
3. Subtract the delta measured in step (2) from the field strengths measured in step (1). The resultant field strengths (CISPR QP, average, or peak, as appropriate) are then used to determine band-edge compliance as required by Section 15.205.
4. The above "delta" measurement technique may be used for measuring emissions that are up to two "standard" bandwidths away from the band-edge, where a "standard" bandwidth is the bandwidth specified by C63.4 for the frequency being measured. For example, for band-edge measurements in the restricted band that begins at 2483.5 MHz, C63.4 specifies a measurement bandwidth of at least 1 MHz. Therefore you may use the "delta" technique for measuring emissions up to 2 MHz removed from the band-edge. Radiated emissions that are removed by more than two "standard" bandwidths must be measured as the above Spurious Radiated Emissions test procedure.

**5.7.3 Test Results:****PASS**

Band-edge compliance of RF conducted/radiated emissions was shown in the Figure 6 and 7.
 Spurious RF conducted emissions were shown in the Figure 8.

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.

Table 6: Measured values of the Field strength of spurious emission (Radiated)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Antenna Height [m]	Turn Table [degree]	Reading [dB(μV)]	Amp Gain [dB]	ATT [dB]	AF [dB(1/m)]	CL [dB]	Actual [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Quasi-peak data, emissions below 1000 MHz												
No Spurious Radiated Emissions Found												
AVERAGE data, emissions above 1000 MHz												
2402.00	1000	H	1.98	15	99.60	43.7	10.1	28.3	4.9	99.2	-	-
1602.00	1000	H	2.24	208	60.67	43.3	0.0	25.9	4.0	47.3	54.0	6.7
4804.00	1000	H	1.68	214	47.70	44.6	0.8	32.6	7.2	43.7	54.0	10.3
2441.00	1000	H	1.93	13	99.04	43.7	10.1	28.3	4.9	98.6	-	-
1628.00*	1000	V	2.05	119	61.29	43.3	0.0	25.9	4.0	47.9	54.0	6.1
4882.00	1000	H	1.61	218	42.99	44.6	0.8	32.5	7.3	39.0	54.0	15.0
2480.00	1000	H	1.98	13	98.50	43.8	10.1	28.6	5.0	98.4	-	-
1654.00*	1000	V	1.93	108	63.85	43.3	0.0	26.2	4.1	50.9	54.0	3.2**
4960.00	1000	V	2.53	207	38.44	44.6	0.8	32.5	7.3	34.4	54.0	19.6
PEAK data, emissions above 1000 MHz												
2402.00	1000	H	1.98	15	102.04	43.7	10.1	28.3	4.9	101.6	-	-
1602.00	1000	H	2.24	208	62.58	43.3	0.0	25.9	4.0	49.2	74.0	24.8
4804.00	1000	H	1.68	214	56.28	44.6	0.8	32.6	7.2	52.3	74.0	21.7
2441.00	1000	H	1.93	13	101.42	43.7	10.1	28.3	4.9	101.0	-	-
1628.00*	1000	V	2.05	119	62.96	43.3	0.0	25.9	4.0	49.6	74.0	24.4
4882.00	1000	H	1.61	218	54.99	44.6	0.8	32.5	7.3	51.0	74.0	23.0
2480.00	1000	H	1.93	13	100.94	43.8	10.1	28.6	5.0	100.8	-	-
1654.00*	1000	V	1.93	108	65.20	43.3	0.0	26.2	4.1	52.2	74.0	21.8
4960.00	1000	V	2.53	207	54.87	44.6	0.8	32.5	7.3	50.9	74.0	23.1

Margin (dB) = Limit – Actual

[Actual = Reading – Amp Gain + Attenuator + AF + CL]

1. H = Horizontal, V = Vertical Polarization

2. ATT = Attenuation (10dB pad and/or Insertion Loss of HPF), AF/CL = Antenna Factor and Cable Loss

* The spurious emission at the frequency does not fall in the restricted bands.



** The measured result is within the test standard limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95 % level of confidence. However, the result indicates that compliance is more probable than non-compliance.

NOTE: All emissions not reported were more than 20 dB below the specified limit or in the noise floor.


SK TECH CO., LTD.

Page 23 of 28

Figure 6. Plot of the Band Edge (Conducted)

 Lower band-edge
 Hopping disenabled

 Upper band-edge
 Hopping disenabled



SK TECH CO., LTD.

Page 24 of 28





Figure 7. Plot of the Band Edge (Radiated)
Lowest Channel (operating at 2402 MHz): PEAK

Lowest Channel (operating at 2402 MHz): AVERAGE

Highest Channel (operating at 2480 MHz): PEAK

Highest Channel (operating at 2480 MHz): AVERAGE

Figure 8: Spurious RF conducted emissions



SK TECH CO., LTD.

Page 25 of 28


Lowest Channel (2402 MHz): 30 MHz ~ 7 GHz




Lowest Channel (2402 MHz): 7 GHz ~ 25 GHz




Middle Channel (2441 MHz): 30 MHz ~ 7 GHz




Middle Channel (2441 MHz): 7 GHz ~ 25 GHz



Highest Channel (2480 MHz): 30 MHz ~ 7 GHz



Highest Channel (2480 MHz): 7 GHz ~ 25 GHz





5.8 PEAK POWER SPECTRAL DENSITY

5.8.1 Regulation

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

5.8.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via SPI interface and make sure the spectrum analyzer is operated in its linear range.
4. Set the spectrum analyzer to MAX HOLD mode with RBW = 3kHz.
5. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
6. Repeat above procedures until all frequencies measured were complete.

5.8.3 Test Results:

PASS




Table 7: Measured values of the Peak Power Spectral Density (Conducted)

Operating frequency	Actual	Limit
2402 MHz	-1.11 dBm	8.0 dBm
2441 MHz	-1.28 dBm	8.0 dBm
2480 MHz	-1.73 dBm	8.0 dBm

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.


SK TECH CO., LTD.

Page 27 of 28

Figure 9. Plot of the Peak Power Spectral Density (Conducted)
**Lowest Channel
(2402 MHz)**

**Middle Channel
(2441 MHz)**

**Highest Channel
(2480 MHz)**




5.9 RF Exposure

5.9.1 Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population/Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1500	/	/	f/1500	30
1500 ~ 15000	/	/	1.0	30

f = frequency in MHz,

* = Plane-wave equivalent power density

MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

S = power density [mW/cm²]

P = power input to antenna [mW]

$$(\Rightarrow R = \sqrt{PG/4\pi S})$$

G = power gain of the antenna in the direction of interest
relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

EUT: Maximum peak output power =2.56 [mW](= 4.09 dBm) & Antenna gain =1.96 (= 2.92 [dBi])	
100 mW, at 20 cm from an antenna 6 [dBi]	$S = PG/4\pi R^2 = 100 \times 3.98 / (4 \times \pi \times 400) = 0.0792 \text{ [mW/cm}^2\text{]} < 1.0 \text{ [mW/cm}^2\text{]}$
2.56 mW, at 20 cm from the antenna 2.92 [dBi]	$S = PG/4\pi R^2 = 0.0010 \text{ [mW/cm}^2\text{]} < 1.0 \text{ [mW/cm}^2\text{]}$
2.56 mW, at 2.5 cm from the antenna 2.92 [dBi]	$S = PG/4\pi R^2 = 0.0638 \text{ [mW/cm}^2\text{]} < 1.0 \text{ [mW/cm}^2\text{]}$

5.9.2 RF Exposure Compliance Issue

The EUT is categorically excluded from routine environmental because it operates at very low power level. The equipment is deemed to comply with the SAR or MPE limits without testing due to this very low power level. SAR data was not submitted because the output power of the EUT was below the low thresholds in the July 02 TCB Exclusion List: for portable transmitters,

Low threshold [(60/f_{GHZ} ≈ 25) mW, d < 2.5 cm, (120/f_{GHZ} ≈ 50) mW, d ≥ 2.5 cm], and

High threshold [(900/f_{GHZ} ≈ 370) mW, d < 20 cm], where f_{GHZ}: 2.44, d: distance to a person's body