

FCC Part 15C Measurement and Test Report

For

ATID CO., LTD

#1211 Byuksan/Kyungin Digitalvalley II, 184, Gasan digital 2-ro,

Geumcheon-gu, Seoul, Korea

FCC ID: VUJAT870A

FCC Rule(s): FCC Part 15C

Product Description: Industrial PDA

Tested Model: AT870A

Report No.: <u>STR17068505I-5</u>

Sample Receipt Date: 2017-06-30

Tested Date: <u>2017-06-31 to 2018-03-08</u>

Issued Date: <u>2018-03-12</u>

Tested By: <u>Jason Su / Engineer</u>

Reviewed By: Silin Chen / EMC Manager

Approved & Authorized By: <u>Jandy So / PSQ Manager</u>

Prepared By:

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,

Jasan Su Silim chen Jumbuso

Bao'an District, Shenzhen, P.R.C. (518101)


Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.



TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
1.2 Test Standards	
1.3 TEST METHODOLOGY	
1.5 EUT SETUP AND TEST MODE.	
1.6 Measurement Uncertainty	6
1.7 TEST EQUIPMENT LIST AND DETAILS	7
2. SUMMARY OF TEST RESULTS	8
3. RF EXPOSURE	9
3.1 STANDARD APPLICABLE	
4. ANTENNA REQUIREMENT	
4.1 STANDARD APPLICABLE.	
4.2 EVALUATION INFORMATION	
5. FREQUENCY HOPPING SYSTEM REQUIREMENTS	
5.1 STANDARD APPLICABLE	
5.2 Frequency Hopping System	
5.3 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	
6. QUANTITY OF HOPPING CHANNELS AND CHANNEL SEPARATION	
6.1 STANDARD APPLICABLE	
6.2 Test Procedure	
6.4 SUMMARY OF TEST RESULTS/PLOTS	
7. DWELL TIME OF HOPPING CHANNEL	15
7.1 STANDARD APPLICABLE	
7.2 Test Procedure	15
7.3 ENVIRONMENTAL CONDITIONS	
7.4 SUMMARY OF TEST RESULTS/PLOTS	
8. 20DB BANDWIDTH	
8.1 STANDARD APPLICABLE	
8.2 Test Procedure	
8.4 SUMMARY OF TEST RESULTS/PLOTS	
9. RF OUTPUT POWER	24
9.1 STANDARD APPLICABLE	
9.2 Test Procedure	
9.3 Environmental Conditions	
9.4 SUMMARY OF TEST RESULTS/PLOTS	24
10. FIELD STRENGTH OF SPURIOUS EMISSIONS	
10.1 STANDARD APPLICABLE	
10.2 Test Procedure	
10.4 Environmental Conditions	
10.5 SUMMARY OF TEST RESULTS/PLOTS	
11. OUT OF BAND EMISSIONS	
11.1 STANDARD APPLICABLE	
11.2 TEST PROCEDURE	
11.3 Environmental Conditions	
12. CONDUCTED EMISSIONS	
12.1 Test Procedure	





12.2 Basic Test Setup Block Diagram	46
12.3 Environmental Conditions	46
12.4 SUMMARY OF TEST RESULTS/PLOTS	
12.5 CONDUCTED EMISSIONS TEST DATA	



1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: ATID CO., LTD

Address of applicant: #1211 Byuksan/Kyungin Digitalvalley II, 184, Gasan

digital 2-ro, Geumcheon-gu, Seoul, Korea

Manufacturer: ATID CO., LTD

Address of manufacturer: #1211 Byuksan/Kyungin Digitalvalley II, 184, Gasan

digital 2-ro, Geumcheon-gu, Seoul, Korea

General Description of EUT	
Product Name:	Industrial PDA
Brand Name:	Atid
Model No.:	AT870A
Adding Model(s):	/
Rated Voltage:	Battery DC 3.7V
Internal Battery:	Rechargeable Li-Ion(2970mAh)
Trigger Battery:	Rechargeable Li-Ion(5200mAh)
	BPI020S05N03
Adapter Model:	Input: AC100-240V 50/60Hz 0.5A;
	Output: DC5V 3.0A
Software Version:	STD870AP70MNGCSZ
Hardware Version:	Rev 1.1
Note: The test data is gathered from a produc	ction sample provided by the manufacturer.

Technical Characteristics of EUT	
Frequency Range:	902.75-927.25MHz
RF Output Power:	27.67dBm (Conducted)
Modulation:	ASK
Quantity of Channels:	50
Channel Separation:	500KHz
Antenna Type:	Circularly Polarized Antenna
Antenna Gain:	1.82dBi
Lowest Internal Frequency of EUT:	32.768kHz

Report No.: STR17068505I-5 Page 4 of 48 FCC PART 15.247



1.2 Test Standards

The following report is prepared on behalf of the ATID CO., LTD in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC - Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

Report No.: STR17068505I-5 Page 5 of 48 FCC PART 15.247



1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	902.75MHz
TM2	Middle Channel	914.75 MHz
TM3	High Channel	927.25 MHz

Accessories Equipment List and Details						
Description	Description Manufacturer Model No. Serial Nun					
/	/	/	/			
Accessories Cable List	and Details					
Cable Description	Cable Description Length (m) Shielded/Unshielded With Core/Without Cor					
Earphone	1.2	Unshielded	Without Core			
EUT Cable List and Details						
Cable Description	Cable Description Length (m) Shielded/Unshielded With Core/Without C					
USB Cable	1.0	Shielded	Without Core			
AC Cable	1.8	Unshielded	Without Core			
DC Cable	1.5	Unshielded	Without Core			

1.6 Measurement Uncertainty

Measurement uncertainty			
Parameter	Conditions	Uncertainty	
RF Output Power	Conducted	±0.42dB	
Occupied Bandwidth	Conducted	±1.5%	
Conducted Spurious Emission	Conducted	±2.17dB	
C 1 / IF : :	Conducted	9-150kHz ± 3.74 dB	
Conducted Emissions	Conducted 0.15-30MHz ±3.3		
		$30-200 MHz \pm 4.52 dB$	
Transmitter Spurious Emissions	Radiated	0.2-1GHz ±5.56dB	
	Kaurateu	1-6GHz ±3.84dB	
		6-18GHz ±3.92dB	

Report No.: STR17068505I-5 Page 6 of 48 FCC PART 15.247



1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2017-06-12	2018-06-11
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2017-06-12	2018-06-11
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2017-06-12	2018-06-11
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2017-06-12	2018-06-11
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2017-06-12	2018-06-11
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2018-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2018-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2018-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2018-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2017-06-12	2018-06-11
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2017-06-12	2018-06-11
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2017-06-12	2018-06-11
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2017-08-15	2018-08-14
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2017-08-15	2018-08-14
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2017-06-12	2018-06-11
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2017-03-09	2018-03-08



2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.209(a)	Radiated Spurious Emissions	Compliant
§ 15.247(a)(1)(i)	Quantity of Hopping Channel	Compliant
§ 15.247(a)(1)	Channel Separation	Compliant
§ 15.247(a)(1)(i)	Time of Occupancy (Dwell time)	Compliant
§ 15.247(a)	20dB Bandwidth	Compliant
§ 15.247(b)(1)	RF Power Output	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant
§ 15.247(a)(1)	Frequency Hopping Sequence	Compliant
§ 15.247(g), (h)	Frequency Hopping System	Compliant

N/A: not applicable

Report No.: STR17068505I-5 Page 8 of 48 FCC PART 15.247



3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR Report.

Report No.: STR17068505I-5 Page 9 of 48 FCC PART 15.247



4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a Circularly Polarized Antenna, fulfill the requirement of this section.

Report No.: STR17068505I-5 Page 10 of 48 FCC PART 15.247



5. Frequency Hopping System Requirements

5.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

5.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses RFID radio which operates in 902-928 MHz band. It uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 50 bands (0.5 MHz each; centered from 902.75-927.25MHz) in the range 902-928 MHz.

5.3 EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 27, 26, 2, 49, 48, 4, 50, 36, 34, 14, 33, 31, 6, 5, 46, 39, 25, 9, 23, 40, 18, 19, 3, 13,7, 20, 8, 30, 24, 10, 32, 28, 16, 17, 11, 45, 15, 35, 29, 22, 43, 12, 47, 21, 44, 38, 37, 41, 1, 42

The system receiver has input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

Report No.: STR17068505I-5 Page 11 of 48 FCC PART 15.247



6. Quantity of Hopping Channels and Channel Separation

6.1 Standard Applicable

According to FCC 15.247(a)(1)(i), For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

6.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.3, the number of hopping frequencies test method as follows.

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

According to ANSI C63.10-2013 section 7.8.2, the EUT shall have its hopping function enabled, the Carrier frequency separation test method as follows:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary
- to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

6.3 Environmental Conditions


Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Report No.: STR17068505I-5 Page 12 of 48 FCC PART 15.247




6.4 Summary of Test Results/Plots

No. of Channel = 50




For GFSK mode Channel Spacing Low Channel






Middle Channel



High Channel





7. Dwell Time of Hopping Channel

7.1 Standard Applicable

According to 15.247(a)(1)(i), For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

7.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.4, the dwell time of a hopping channel test method as follows.

a) Span: Zero span, centered on a hopping channel.

- b) RBW shall be \leq channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start
- of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.

d) Detector function: Peak.

e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) =

(number of hops on spectrum analyzer) × (period specified in the requirements / analyzer sweep time)

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation. The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

Report No.: STR17068505I-5 Page 15 of 48 FCC PART 15.247



7.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots

The dwell time within a period in data mode is independent from the packet type (packet length).

The test period: T = 20 s

Dwell time = time slot length* Number of Bursts

Engage ov (MIIz)	Test period	Number of Bursts per	Burst Duration	Dwell time	Limit
Frequency (MHz)	(s)	Hopping Period	(ms)	(ms)	(ms)
902.75	20	1	50	50	<400
914.75	20	1	50	50	<400
927.25	20	1	50	50	<400


Please refer to the test plots as below:

Report No.: STR17068505I-5 Page 16 of 48 FCC PART 15.247




Low Channel

Dwell time, Burst Duration




Dwell Time, Number of Bursts






Middle Channel

Dwell time, Burst Duration




Dwell Time, Number of Bursts






High Channel

Dwell time, Burst Duration



Dwell Time, Number of Bursts





8. 20dB Bandwidth

8.1 Standard Applicable

According to 15.247(a) and 15.215(c). 20dB bandwidth is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.2 Test Procedure

According to ANSI C63.10-2013 section 6.9.2, the 20dB bandwidth test method as follows.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target "-xx dB down" requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the "-xx dB down amplitude" using [(reference value) -xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the "-xx dB down amplitude" determined in step h). If a marker is below this "-xx dB down amplitude" value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the "-xx dB down amplitude" determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Report No.: STR17068505I-5 Page 20 of 48 FCC PART 15.247



8.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


8.4 Summary of Test Results/Plots

Test Channel MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Result
902.75	134.452	116.0416	Pass
914.75	135.378	117.2652	Pass
927.25	137.335	118.1925	Pass


Report No.: STR17068505I-5 Page 21 of 48 FCC PART 15.247



Low Channel:




Middle Channel:





High Channel:





9. RF Output Power

9.1 Standard Applicable

According to 15.247(b)(2). For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

9.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.5, the output power test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW \geq RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

9.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

Frequency	Measured Value	Output Power	Limit	
MHz	dBm	mW	mW	
902.75	27.36	544.50	1000	
914.75	27.60	575.44	1000	
927.25	27.67	584.79	1000	


Note: the antenna gain is less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.

Test Plots please see the following page


Report No.: STR17068505I-5 Page 24 of 48 FCC PART 15.247



Low Channel




Middle Channel





High Channel



10. Field Strength of Spurious Emissions

10.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


10.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.



Report No.: STR17068505I-5 Page 27 of 48 FCC PART 15.247



Frequency :9kHz-30MHz Frequency :30MHz-1GHz Frequency :Above 1GHz

RBW=10KHz, RBW=120KHz, RBW=1MHz,

VBW=30KHz VBW=300KHz VBW=3MHz(Peak), 10Hz(AV)

Detector function = peak, QP Detector function = peak, AV

10.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-6dB\mu V$ means the emission is $6dB\mu V$ below the maximum limit. The equation for margin calculation is as follows:

10.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

Report No.: STR17068505I-5 Page 28 of 48 FCC PART 15.247



10.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes are performed, but only the worst case is recorded in this report.

Plot of Radiated Emissions Test Data (30MHz to 1GHz)


EUT: Industrial PDA

Tested Model: AT870A

Operating Condition: Transmitting Low Channel (902.75MHz)

Comment: DC 3.7V

Test Specification: Horizontal




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	300.3673	42.86	-9.59	33.27	46.00	-12.73	334	100	peak
2	408.9460	41.73	-8.04	33.69	46.00	-12.31	262	100	peak
3	550.9479	42.46	-5.06	37.40	46.00	-8.60	79	100	peak
4	903.3093	109.74	-3.23	106.51	/	/	/	/	peak

Report No.: STR17068505I-5 Page 29 of 48 FCC PART 15.247



Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	150.5378	41.13	-18.74	22.39	43.50	-21.11	56	100	peak
2	200.6880	41.82	-18.05	23.77	43.50	-19.73	279	100	peak
3	216.7828	38.43	-14.54	23.89	46.00	-22.11	61	100	peak
4	301.4223	39.78	-9.59	30.19	46.00	-15.81	291	100	peak
5	903.3093	107.42	-3.23	104.19	/	/	/	/	peak

Operating Condition: Transmitting Middle Channel (914.75MHz)

Comment: DC 3.7V


Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	300.3673	42.93	-9.59	33.34	46.00	-12.66	341	100	peak
2	400.4318	41.13	-7.80	33.33	46.00	-12.67	100	100	peak
3	492.4685	42.27	-6.21	36.06	46.00	-9.94	50	100	peak
4	916.0687	108.54	-4.12	104.42	/	/	/	/	peak



Test Specification: Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	200.6880	40.82	-18.05	22.77	43.50	-20.73	225	100	peak
2	301.4223	38.70	-9.59	29.11	46.00	-16.89	98	100	peak
3	916.0687	110.60	-4.12	106.48	/	/	/	/	peak



Operating Condition: Transmitting High Channel (927.25MHz)

Comment: DC 3.7V


Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	116.1320	50.22	-16.65	33.57	43.50	-9.93	56	100	peak
2	300.3673	42.09	-9.59	32.50	46.00	-13.50	279	100	peak
3	929.0081	109.34	-4.10	105.24	/	/	/	/	peak



Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	251.1803	39.91	-12.09	27.82	46.00	-18.18	62	100	peak
2	301.4223	40.41	-9.59	30.82	46.00	-15.18	189	100	peak
3	422.0577	39.02	-8.25	30.77	46.00	-15.23	89	100	peak
4	501.1789	40.59	-5.78	34.81	46.00	-11.19	116	100	peak
5	929.0081	108.47	-4.10	104.37	/	/	/	/	peak



Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
			Low Channe	1-902.75MHz			
1805.5	68.18	-9.8	58.38	74	-15.62	Н	PK
1805.5	53.57	-9.81	43.76	54	-10.24	Н	AV
2708.25	70.54	-6.95	63.59	74	-10.41	Н	PK
2708.25	52.79	-6.92	45.87	54	-8.13	Н	AV
1805.5	70.39	-9.8	60.59	74	-13.41	V	PK
1805.5	51.74	-9.81	41.93	54	-12.07	V	AV
2708.25	69.84	-6.95	62.89	74	-11.11	V	PK
2708.25	51.92	-6.92	45.00	54	-9.00	V	AV
			Middle Chann	el-914.75MHz			
1829.5	67.21	-9.52	57.69	74	-16.31	Н	PK
1829.5	51.67	-9.54	42.13	54	-11.87	Н	AV
2744.25	67.21	-6.88	60.33	74	-13.67	Н	PK
2744.25	51.43	-6.87	44.56	54	-9.44	Н	AV
1829.5	69.45	-9.52	59.93	74	-14.07	V	PK
1829.5	50.67	-9.59	41.08	54	-12.92	V	AV
2744.25	67.07	-6.88	60.19	74	-13.81	V	PK
2744.25	51.56	-6.88	44.68	54	-9.32	V	AV
			High Channe	1-927.25MHz			
1854.5	69.64	-9.23	60.41	74	-13.59	Н	PK
1854.5	51.81	-9.19	42.62	54	-11.38	Н	AV
2781.75	70.55	-9.19	61.36	74	-12.64	Н	PK
2781.75	52.13	-9.19	42.94	54	-11.06	Н	AV
1854.5	68.52	-9.19	59.33	74	-14.67	V	PK
1854.5	53.91	-9.19	44.72	54	-9.28	V	AV
2781.75	70.71	-9.19	61.52	74	-12.48	V	PK
2781.75	50.75	-9.19	41.56	54	-12.44	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Report No.: STR17068505I-5 Page 35 of 48 FCC PART 15.247



11. Out of Band Emissions

11.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

11.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.6, the Band-edge measurements for RF conducted emissions test method as follows.

- a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e) (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).
- b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
- c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent "normal mode of operation" as specified in 6.10.3.
- d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6, and orient the EUT and measurement antenna positions to produce the highest emission level.
- e) Perform the test as follows:
 - 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
 - 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.
 - 3) Attenuation: Auto (at least 10 dB preferred).
 - 4) Sweep time: Coupled.
 - 5) Resolution bandwidth: 100 kHz.
 - 6) Video bandwidth: 300 kHz.
 - 7) Detector: Peak.8) Trace: Max hold.
- f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.
- g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak

Report No.: STR17068505I-5 Page 36 of 48 FCC PART 15.247



Model: AT870A

function to move the marker to the peak of the in-band emission.

- h) Repeat step c) through step e) for every applicable modulation.
- i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).
- j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Restricted-band band-edge test method please refers to ANSI C63.10-2013 section 6.10.5. The emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated band-edge measurements.

According to ANSI C63.10-2013 section 7.8.8, Conducted spurious emissions shall be measured for the transmit frequency, per 5.5 and 5.6, and at the maximum transmit powers.

Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The instrument shall span 30 MHz to 10 times the operating frequency in GHz, with a resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector. The band 30 MHz to the highest frequency may be split into smaller spans, as long as the entire spectrum is covered.

11.3 Environmental Conditions


Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Report No.: STR17068505I-5 Page 37 of 48 FCC PART 15.247



11.4 Summary of Test Results/Plots

Lowest Bandedge




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	900.0000	35.29	-3.00	32.29	46.00	-13.71	QP
2	902.0000	38.56	-3.13	35.43	46.00	-10.57	QP
3	902.7599	108.45	-3.19	105.26	/	/	QP

Report No.: STR17068505I-5 Page 38 of 48 FCC PART 15.247



Highest Bandedge


Vertical (Worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	927.2500	110.66	-4.16	106.50	/	/	QP
2	928.0000	39.92	-4.14	35.78	46.00	-10.22	QP
3	930.0000	36.08	-4.07	32.01	46.00	-13.99	QP




Out of Bandedge Lowest












Middle














Highest











Lowest Bandedge





Highest Bandedge




Model: AT870A

12. Conducted Emissions

12.1 Test Procedure

Test is conducting under the description of ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

12.2 Basic Test Setup Block Diagram



12.3 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

12.4 Summary of Test Results/Plots

According to the data in section 12.5, the EUT <u>complied with the FCC Part 15.207(a)</u> Conducted margin for a Class B device, with the *worst* margin reading of:

-4.86 dB at 0.1780 MHz in the Line, QP detector, 0.15-30MHz

Report No.: STR17068505I-5 Page 46 of 48 FCC PART 15.247

Model: AT870A

12.5 Conducted Emissions Test Data


Plot of Conducted Emissions Test Data

EUT: Industrial PDA

Tested Model: AT870A

Operating Condition: Transmitting(RFID)
Comment: AC 120V/60Hz

Test Specification: Neutral




No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1*	0.1780	49.30	9.82	59.12	64.58	-5.46	QP
2	0.1980	31.99	9.80	41.79	53.69	-11.90	AVG
3	0.2460	39.01	9.80	48.81	61.89	-13.08	QP
4	0.2460	24.34	9.80	34.14	51.89	-17.75	AVG
5	0.3100	34.33	9.80	44.13	59.97	-15.84	QP
6	0.3100	19.71	9.80	29.51	49.97	-20.46	AVG

Report No.: STR17068505I-5 Page 47 of 48 FCC PART 15.247



Test Specification: Line



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1*	0.1780	49.90	9.82	59.72	64.58	-4.86	QP
2	0.1980	33.90	9.80	43.70	53.69	-9.99	AVG
3	0.2540	39.23	9.80	49.03	61.63	-12.60	QP
4	0.2540	20.28	9.80	30.08	51.63	-21.55	AVG
5	0.3100	34.74	9.80	44.54	59.97	-15.43	QP
6	0.3100	19.23	9.80	29.03	49.97	-20.94	AVG

***** END OF REPORT *****