


GPS_MODEL_32_C

СРИ	Centrality Atlas-III
	AT642D/372MHz
FLASH	64Mbytes
SDRAM	64Mbytes
LCD	4.3inch(16:9) 64K TFT
TSP	Touch Screen Supported
USB	USB Client 2.0, Full speed (12Mbps), Mini Slot With USB Mass Storage Function or ActiveSync
SD	SD / Multimedia Card Slot
FM Transmitter /TMC	Option
Bule Tooth	Hand free with Echo Cancellers(Option)
Audio	Mono 1W@8ohm or 2W@4ohm Speaker
	Stereo 20 mW/32ohm Headphone
Button	1 Buttons
GPS Receiver	Module and Antenna Built In
External Antenna Connector	YES
GPS	Sensitivity:
	Tracking:-161dBm(11dB-Hz)
	Hot Start:-146 dBm(24dB-Hz)
	Warm Start: -146 dBm(24dB-Hz)
	Cold Start: :-146 dBm(24dB-Hz)
	Reacquisition: :-156 dBm(16dB-Hz)





	GPS_MODEL_52_C 1X不多数
Battery	1100~2000mAH/3.7V Li rechargeable battery
24.10.)	Charging current=500~550mA
Charging	5V DC Power Jack
AC Adapter	120/230V universal AC/DC adapter
Car Adapter	12VDC to 5VDC 2A
LED Status	Blue Tooth LED Adapter plug in and Battery Charging (Red LED On, Green LED Off) Adapter plug in and Battery Full(Red LED Off, Green LED On)
Temperature	Operating: 0 °C to 60 °C Storage: -20 °C to 60 °C
Dimensions	TBD(similar to LCD)
O/S	WinCE.Net 5.0 Core
Language	 □ Simplified Chinese Character + English □ Traditional Chinese + English □ Italy、France 、Spanish、Germany、Portugal、Nertherland、Denmark、Sweden、Norway、Greece
Navigation Software	Third Party
Video Player	WMV9, DIVX 5.0, 4.0, 3.11, XVID and MPEG2 up to 480*272 resolutions
Audio Player	WMA9, MP3 up to 320k bps and WAV
Photo Viewer	JPG, GIF, BMP and PNG
Ebook Reader	ТХТ
System Setting	Backlight/Date Time/Volume/Power/Sys Info
OS update	via SD card
AP update	via SD card
Logo update	via SD card