

SGS-CSTC Standards Technical Services Co., Ltd.

No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663

Telephone: +86 (0) 20 8215 5555 Fax: +86 (0) 20 8207 5059

Email: sgs internet operations@sgs.com

Report No.: SZEMO071203569RFA

Page: 1 of 3

RF Exposure Exhibit

Application No.:SZEMO071203569RFApplicant:Vocentrix(HK)Limited

FCC ID VUY1048B Equipment Under Test (EUT):

EUT Name: Baby monitor

Model: 08280

Date of Receipt: 10 December 2007

Date of Test: 11 December 2007

Date of Issue: 14 December 2007

Test Result : PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Robinson Lo Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at https://www.sgs.com/terms_and_conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law." Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of the Company.



SGS-CSTC Standards Technical Services Co., Ltd.

Report No.: SZEMO071203569RFA

Page: 2 of 3

2 RF Exposure Evaluation

Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307 (b)

LIMITS OFR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time		
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm²)	(Minutes)		
(A) Limits for Occupational/Control Exposures						
300-1500			F/300	6		
1500-100,000			5	6		
(B) Limits for General Population/Uncontrolled Exposures						
300-1500			F/1500	6		
1500-100,000			1	30		

F=Frequency in MHz

Friis Formula

Friis transmission formula:Pd= (Pout*G) / (4*pi*r²)

Where

Pd=power density in mW/cm²

Pout=output power to antenna in mW

G=gain of antenna in linear scale

Pi=3.1416

R=distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



SGS-CSTC Standards Technical Services Co., Ltd.

Report No.: SZEMO071203569RFA

Page: 3 of 3

Test Result of RF Exposure Evaluation

Date of Test	2007-12-05	Temperature	25 deg/C
EUT	Broadband Router	Humidity	52%RH

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 0dBi or 1.00 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel No.	Frequency	Output Power to Antenna	Power Density at R = 20 cm
	(MHz)	(mW)	(mW/cm²)
1	2410.00	9.55	0.0019
6	2440.00	5.62	0.0011
11	2470.00	4.17	0.0008

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1mW/cm².