

BABT TCB

Balfour House, Churchfield Road, Walton-on-Thames, Surrey, KT12 2TD

RF exposure for F3307 (FCC ID: VV7-MBMF33072) and F3607gw (FCC ID: VV7-MBMF3607GW2)

The device F3607gw (FCC ID: VV7-MBMF3607GW2) is designed as module to be installed in other devices. This device is to be used only for fixed and mobile applications. If the final product after integration is intended for portable use, a new application and FCC is required.

The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all the persons and must not be co-located or operating in conjunction with any other antenna or transmitter.

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure:

Frequency Range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
300 – 1500	f (MHz) /1500	30
1500 – 100.000	1.0	30

Based on the above table the limits are:

For 850 MHz frequency band device: 0.55 mW/cm² For 1900 MHz frequency band device: 1 mW/cm²

Using the equation from page 19 of OET Bulletin 65, Edition 97-01:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Compliance with MPE limits can be guaranteed as the calculation below shows:

850 MHz frequency band

Maximum output power considerations:

Mode	Maximum conducted output power (dBm)	Maximum conducted output power (mW)		Equivalent conducted output power (Maximum conducted output power x duty cycle) (mW)
GPRS	32.19	1655.77	25%	413.94
EDGE	28.89	774.46	25%	193.62



G _{850 MHz band}	Min (G ₁ , G ₂ , G ₃)	7.74	dBi
G_3	Antenna gain (dBi) to comply with ERP limits:	8.41	dBi
G_3	Antenna gain (numerical) to comply with ERP limits: (ERP = Maximum conducted output power x Antenna gain / 1,64	6.93 I)	
ERP power li	mit according to §22,913 (a):	7	W
G_2	Antenna gain (dBi) to comply with ERP limits:	7.74	dBi
G_2	Antenna gain (numerical) to comply with ERP limits: (ERP = Maximum conducted output power x Antenna gain / 1,64	5.94 l)	
ERP limit to	comply with categorically exclusion of §2.1091(c)	1.50	W
G_1	Antenna gain (dBi) to comply with MPE limits:	8.25	dBi
G_1	Antenna gain (numerical) to comply with MPE limits:	6.68	
R S	Distance: MPE limit for uncontrolled exposure:	20 0.55	cm mW/cm ²
P	Maximum power input to the antenna:	413.94	

Therefore the maximum antenna gain to comply with MPE and ERP limits should not exceed **7.74 dBi**.

1900 MHz frequency band

Maximum output power considerations:

Мо	ode	Maximum conducted output power (dBm)	Maximum conducted output power (mW)	tput Duty power (Maximum cond	
GP	RS	29.37	864.97	25%	216.24
ED	GE	27.84	608.14	25%	152.03

P R	Maximum power input to the antenna: Distance:	216.24 20	mW cm
S	MPE limit for uncontrolled exposure:	1.00	mW/cm
G_4	Antenna gain (numerical) to comply with MPE limits:	23.25	
G_4	Antenna gain (dBi) to comply with MPE limits:	13.66	dBi

EIRP limit to comply with categorically exclusion of §2.1091(c)

4.92 W



G _{1900 MHz band}	Min (G ₄ , G ₅ , G ₆)	9.66	dBi
G ₆	Antenna gain (dBi) to comply with EIRP limits:	9.66	dBi
G_6	Antenna gain (numerical) to comply with EIRP limits: (EIRP = Maximum conducted output power x Antenna gain)	9.25	
EIRP power	limit according to §24,232 (b):	2	W
G_5	Antenna gain (dBi) to comply with EIRP limits:	13.57	dBi
G ₅	Antenna gain (numerical) to comply with EIRP limits: (EIRP = Maximum conducted output power x Antenna gain)	22.75	

Therefore the maximum antenna gain to comply with MPE and EIRP limits should not exceed **9.66 dBi**.

The device F3307 is exactly the same of F3607 gw device except for the following:

- GPS component functionality has been removed.
- FDD II band filters and components have been removed from the PCB. So, it only supports GSM 850 and PCS 1900 MHz.

It can be checked it in the document: "Differences between F3307 and F3607gw". Just as shows the information above, the differences between F3307 and F3607gw do not effect compliance with FCC part 22H and 24E and that test report number EH/2009/40037 demonstrates compliance with FCC part 22H and 24E for the F3307.

PA.

Sabina Ruiz Dept. Laboratories 29-07-2009

